

# **Apollo Scientific**

Part Number: BI01001 Version No: 1.1 Safety Data Sheet (Conforms to Annex II of REACH (1907/2006) - Regulation 2020/878) Chemwatch Hazard Alert Code: 4

Issue Date: **16/09/2022** Print Date: **31/07/2023** S.REACH.GBR.EN

# SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### 1.1. Product Identifier

Product name	chratoxin A from Aspergillus ochraceus	
Chemical Name	ratoxin A	
Synonyms	Available	
Proper shipping name	TOXIC SOLID, ORGANIC, N.O.S.	
Chemical formula	0-H18-CI-N-O6	
Other means of identification	Not Available	
CAS number	303-47-9	
EC number	206-143-7	

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Not Available
Uses advised against	No specific uses advised against are identified.

#### 1.3. Details of the manufacturer or supplier of the safety data sheet

Registered company name	Apollo Scientific	
Address	nitefield Road, Bredbury SK62QR United Kingdom	
Telephone	614060505	
Fax	0161 406 0506	
Website	http://www.apolloscientific.co.uk/	
Email	sales@apolloscientific.co.uk	

#### 1.4. Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	Not Available
Other emergency telephone numbers	Not Available

#### **SECTION 2 Hazards identification**

### 2.1. Classification of the substance or mixture

Classification according to regulation (EC) No

H350 - Carcinogenicity Category 1B, H300 - Acute Toxicity (Oral) Category 1, H310 - Acute Toxicity (Dermal) Category 1, H360D - Reproductive Toxicity Category 1A, H330 - Acute Toxicity (Inhalation) Category 1, H340 - Germ Cell Mutagenicity Category 1B

1272/2008 [CLP] and amendments <sup>[1]</sup>	
Legend:	1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

### 2.2. Label elements

Hazard pictogram(s) Signal word Danger



#### Hazard statement(s)

H350	lay cause cancer.	
H300	l if swallowed.	
H310	Fatal in contact with skin.	
H360D	May damage the unborn child.	
H330	Fatal if inhaled.	
H340	May cause genetic defects.	

# Supplementary statement(s)

Not Applicable

### Precautionary statement(s) Prevention

P201	Obtain special instructions before use.	
P260	Do not breathe dust/fume.	
P262	Do not get in eyes, on skin, or on clothing.	
P264	Wash all exposed external body areas thoroughly after handling.	
P270	Do not eat, drink or smoke when using this product.	
P271	Use only outdoors or in a well-ventilated area.	
P280	Wear protective gloves and protective clothing.	
P284	[In case of inadequate ventilation] wear respiratory protection.	

### Precautionary statement(s) Response

P301+P310	F SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider.	
P304+P340	INHALED: Remove person to fresh air and keep comfortable for breathing.	
P308+P313	F exposed or concerned: Get medical advice/ attention.	
P330	Rinse mouth.	
P361+P364	Take off immediately all contaminated clothing and wash it before reuse.	
P302+P352	IF ON SKIN: Wash with plenty of water.	

### Precautionary statement(s) Storage

P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

# Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

#### 2.3. Other hazards

Inhalation and/or ingestion may produce serious health damage\*.

REACH - Art.57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS print date.

# **SECTION 3 Composition / information on ingredients**

#### 3.1.Substances

1. CAS No 2.EC No 3.Index No 4.REACH No	%[weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	SCL / M-Factor	Nanoform Particle Characteristics
Not Available	100	Ochratoxin A from Aspergillus ochraceus	Not Applicable	Not Applicable	Not Available

Legend: 1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L; \* EU IOELVs available; [e] Substance identified as having endocrine disrupting properties

#### 3.2.Mixtures

See 'Information on ingredients' in section 3.1

# **SECTION 4 First aid measures**

#### 4.1. Description of first aid measures

Eye Contact	<ul> <li>If this product comes in contact with the eyes:</li> <li>Immediately hold eyelids apart and flush the eye continuously with running water.</li> <li>Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.</li> <li>Transport to hospital or doctor without delay.</li> <li>Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
Skin Contact	<ul> <li>If skin or hair contact occurs:</li> <li>Flush skin and hair with running water (and soap if available).</li> <li>Seek medical attention in event of irritation.</li> </ul>
Inhalation	<ul> <li>If fumes or combustion products are inhaled remove from contaminated area.</li> <li>Lay patient down. Keep warm and rested.</li> <li>Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>Transport to hospital, or doctor, without delay.</li> </ul>
Ingestion	<ul> <li>IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY.</li> <li>For advice, contact a Poisons Information Centre or a doctor.</li> <li>Urgent hospital treatment is likely to be needed.</li> <li>In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition.</li> <li>If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the SDS should be provided. Further action will be the responsibility of the medical specialist.</li> <li>If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the SDS.</li> </ul>
	<ul> <li>Where medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:</li> <li>INDUCE vomiting with fingers down the back of the throat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>NOTE: Wear a protective glove when inducing vomiting by mechanical means.</li> </ul>

#### 4.2 Most important symptoms and effects, both acute and delayed

See Section 11

#### 4.3. Indication of any immediate medical attention and special treatment needed

As in all cases of suspected poisoning, follow the ABCDEs of emergency medicine (airway, breathing, circulation, disability, exposure), then the ABCDEs of toxicology (antidotes, basics, change absorption, change distribution, change elimination).

For poisons (where specific treatment regime is absent):

BASIC TREATMENT

\_\_\_\_\_

Establish a patent airway with suction where necessary.

Watch for signs of respiratory insufficiency and assist ventilation as necessary.

- Administer oxygen by non-rebreather mask at 10 to 15 L/min.
- Monitor and treat, where necessary, for pulmonary oedema.
- Monitor and treat, where necessary, for shock.
- Anticipate seizures.
- DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.

#### ADVANCED TREATMENT

-----

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- ▶ Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- + Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- + Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Treat seizures with diazepam.

Proparacaine hydrochloride should be used to assist eye irrigation.

BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

#### **SECTION 5 Firefighting measures**

#### 5.1. Extinguishing media

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

#### 5.2. Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.

#### 5.3. Advice for firefighters

Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves in the event of a fire.</li> <li>Prevent, by any means available, spillage from entering drains or water courses.</li> <li>Use fire fighting procedures suitable for surrounding area.</li> <li>DO NOT approach containers suspected to be hot.</li> <li>Cool fire exposed containers with water spray from a protected location.</li> <li>If safe to do so, remove containers from path of fire.</li> <li>Equipment should be thoroughly decontaminated after use.</li> </ul>
Fire/Explosion Hazard	<ul> <li>Non combustible.</li> <li>Not considered a significant fire risk, however containers may burn.</li> <li>May emit poisonous fumes.</li> </ul>

#### **SECTION 6 Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

See section 8

#### 6.2. Environmental precautions

See section 12

#### 6.3. Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Remove all ignition sources.</li> <li>Clean up all spills immediately.</li> <li>Avoid contact with skin and eyes.</li> <li>Control personal contact with the substance, by using protective equipment.</li> <li>Use dry clean up procedures and avoid generating dust.</li> <li>Place in a suitable, labelled container for waste disposal.</li> </ul>
Major Spills	

#### 6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# **SECTION 7 Handling and storage**

# 7.1. Precautions for safe handling

Safe handling	<ul> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Prevent concentration in hollows and sumps.</li> <li>DO NOT enter confined spaces until atmosphere has been checked.</li> <li>DO NOT allow material to contact humans, exposed food or food utensils.</li> <li>Avoid contact with incompatible materials.</li> <li>When handling, DO NOT eat, drink or smoke.</li> <li>Keep containers securely sealed when not in use.</li> <li>Avoid physical damage to containers.</li> <li>Always wash hands with soap and water after handling.</li> <li>Work clothes should be laundered separately. Launder contaminated clothing before re-use.</li> <li>Use good occupational work practice.</li> <li>Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.</li> </ul>
Fire and explosion protection	See section 5
Other information	<ul> <li>Store in original containers.</li> <li>Keep containers securely sealed.</li> <li>Store in a cool, dry, well-ventilated area.</li> <li>Store away from incompatible materials and foodstuff containers.</li> <li>Protect containers against physical damage and check regularly for leaks.</li> <li>Observe manufacturer's storage and handling recommendations contained within this SDS.</li> </ul>

# 7.2. Conditions for safe storage, including any incompatibilities

	<ul> <li>Lined metal can, lined metal pail/ can.</li> <li>Plastic pail.</li> </ul>
	Polyliner drum.
	<ul> <li>Packing as recommended by manufacturer.</li> </ul>
	<ul> <li>Check all containers are clearly labelled and free from leaks.</li> </ul>
	<ul> <li>For low viscosity materials</li> <li>Drums and jerricans must be of the non-removable head type.</li> </ul>
	<ul> <li>Where a can is to be used as an inner package, the can must have a screwed enclosure.</li> </ul>
	For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.):
	<ul> <li>Removable head packaging;</li> </ul>
	Cans with friction closures and
Suitable container	Iow pressure tubes and cartridges
Suitable container	may be used.
	•
	Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in
	contact with inner and outer packages *.
	In addition, where inner packagings are glass and contain liquids of packing group I and II there must be sufficient inert
	absorbent to absorb any spillage *.
	-
	* unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.
	All inner and sole packagings for substances that have been assigned to Packaging Groups I or II on the basis of inhalation
	toxicity criteria, must be hermetically sealed.
Storage incompatibility	None known
Storage incompatibility	► Store at-20°c
Hazard categories in	
accordance with	H1: Acute Toxic
Regulation (EC) No	
1272/2008	
Qualifying quantity	
(tonnes) of dangerous	
substances as referred to	H1 Lower- / Upper-tier requirements: 5 / 20
in Article 3(10) for the application of	
application of	

# **SECTION 8 Exposure controls / personal protection**

# 8.1. Control parameters

Ingredient	DNELs Exposure Pattern Worker	PNECs Compartment
Not Available	Not Available	Not Available

\* Values for General Population

### Occupational Exposure Limits (OEL)

# INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Not Available						

### Not Applicable

### Emergency Limits

Ingredient	TEEL-1	TEEL-2		TEEL-3
Ochratoxin A from Aspergillus ochraceus	Not Available	Not Available		Not Available
Ingredient	Original IDLH		Revised IDLH	
Ochratoxin A from				

# 8.2. Exposure controls

	Engineering controls are used to remove a hazard or place a engineering controls can be highly effective in protecting wor provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activit Enclosure and/or isolation of emission source which keeps a that strategically "adds" and "removes" air in the work enviro designed properly. The design of a ventilation system must n Employers may need to use multiple types of controls to prev Local exhaust ventilation usually required. If risk of overexpo obtain adequate protection. Supplied-air type respirator may ensure adequate protection. An approved self contained breathing apparatus (SCBA) ma Provide adequate ventilation in warehouse or closed storage "escape" velocities which, in turn, determine the "capture vel contaminant. Type of Contaminant:	rkers and will typically be independent of wo ity or process is done to reduce the risk. a selected hazard "physically" away from the nment. Ventilation can remove or dilute an a natch the particular process and chemical or vent employee overexposure. Issure exists, wear approved respirator. Correct be required in special circumstances. Correct y be required in some situations. a area. Air contaminants generated in the wo	rker interactions to worker and ventilat ir contaminant if r contaminant in use ect fit is essential to ct fit is essential to rkplace possess va
		All Speed.	
			0.25-0.5 m/s
8.2.1. Appropriate	solvent, vapours, degreasing etc., evaporating from tank (i	n still air).	0.25-0.5 m/s (50-100 f/min.)
	solvent, vapours, degreasing etc., evaporating from tank (i aerosols, fumes from pouring operations, intermittent conta welding, spray drift, plating acid fumes, pickling (released a generation)	ainer filling, low speed conveyer transfers,	(50-100 f/min.) 0.5-1 m/s
	aerosols, fumes from pouring operations, intermittent conta welding, spray drift, plating acid fumes, pickling (released a	ainer filling, low speed conveyer transfers, at low velocity into zone of active	(50-100 f/min.) 0.5-1 m/s (100-200 f/min.) 1-2.5 m/s
	aerosols, fumes from pouring operations, intermittent conta welding, spray drift, plating acid fumes, pickling (released a generation) direct spray, spray painting in shallow booths, drum filling,	ainer filling, low speed conveyer transfers, at low velocity into zone of active conveyer loading, crusher dusts, gas	<ul> <li>(50-100 f/min.)</li> <li>0.5-1 m/s</li> <li>(100-200 f/min.)</li> <li>1-2.5 m/s</li> <li>(200-500 f/min.)</li> <li>2.5-10 m/s</li> </ul>
	aerosols, fumes from pouring operations, intermittent conta welding, spray drift, plating acid fumes, pickling (released a generation) direct spray, spray painting in shallow booths, drum filling, discharge (active generation into zone of rapid air motion) grinding, abrasive blasting, tumbling, high speed wheel gen	ainer filling, low speed conveyer transfers, at low velocity into zone of active conveyer loading, crusher dusts, gas	<ul> <li>(50-100 f/min.)</li> <li>0.5-1 m/s</li> <li>(100-200 f/min.)</li> <li>1-2.5 m/s</li> <li>(200-500 f/min.)</li> <li>2.5-10 m/s</li> </ul>
	aerosols, fumes from pouring operations, intermittent conta welding, spray drift, plating acid fumes, pickling (released a generation) direct spray, spray painting in shallow booths, drum filling, discharge (active generation into zone of rapid air motion) grinding, abrasive blasting, tumbling, high speed wheel gen velocity into zone of very high rapid air motion).	ainer filling, low speed conveyer transfers, at low velocity into zone of active conveyer loading, crusher dusts, gas	<ul> <li>(50-100 f/min.)</li> <li>0.5-1 m/s</li> <li>(100-200 f/min.)</li> <li>1-2.5 m/s</li> <li>(200-500 f/min.)</li> <li>2.5-10 m/s</li> </ul>
	aerosols, fumes from pouring operations, intermittent conta welding, spray drift, plating acid fumes, pickling (released a generation) direct spray, spray painting in shallow booths, drum filling, discharge (active generation into zone of rapid air motion) grinding, abrasive blasting, tumbling, high speed wheel gen velocity into zone of very high rapid air motion). Within each range the appropriate value depends on:	ainer filling, low speed conveyer transfers, at low velocity into zone of active conveyer loading, crusher dusts, gas nerated dusts (released at high initial	<ul> <li>(50-100 f/min.)</li> <li>0.5-1 m/s</li> <li>(100-200 f/min.)</li> <li>1-2.5 m/s</li> <li>(200-500 f/min.)</li> <li>2.5-10 m/s</li> </ul>
8.2.1. Appropriate engineering controls	aerosols, fumes from pouring operations, intermittent conta welding, spray drift, plating acid fumes, pickling (released a generation) direct spray, spray painting in shallow booths, drum filling, discharge (active generation into zone of rapid air motion) grinding, abrasive blasting, tumbling, high speed wheel gen velocity into zone of very high rapid air motion). Within each range the appropriate value depends on: Lower end of the range	ainer filling, low speed conveyer transfers, at low velocity into zone of active conveyer loading, crusher dusts, gas nerated dusts (released at high initial Upper end of the range	<ul> <li>(50-100 f/min.)</li> <li>0.5-1 m/s</li> <li>(100-200 f/min.)</li> <li>1-2.5 m/s</li> <li>(200-500 f/min.)</li> <li>2.5-10 m/s</li> </ul>
	aerosols, fumes from pouring operations, intermittent conta welding, spray drift, plating acid fumes, pickling (released a generation) direct spray, spray painting in shallow booths, drum filling, discharge (active generation into zone of rapid air motion) grinding, abrasive blasting, tumbling, high speed wheel gen velocity into zone of very high rapid air motion). Within each range the appropriate value depends on: Lower end of the range 1: Room air currents minimal or favourable to capture	ainer filling, low speed conveyer transfers, at low velocity into zone of active conveyer loading, crusher dusts, gas nerated dusts (released at high initial Upper end of the range 1: Disturbing room air currents	(50-100 f/min.) 0.5-1 m/s (100-200 f/min.) 1-2.5 m/s (200-500 f/min.)

	extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction for for extraction of advante generated in a tank 2.
	extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.
8.2.2. Individual protection measures, such as personal protective equipment	
Eye and face protection	<ul> <li>Safety glasses with side shields</li> <li>Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]</li> <li>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].</li> </ul>
Skin protection	See Hand protection below
Hands/feet protection	manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: • frequency and duration of contact, • chemical resistance of glove material, • glove thickness and • dexterity Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent). • When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. • When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. • Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use. • Contaminated gloves should be replaced. As defined in ASTM F-739-96 in any application, gloves are rated as: • Excellent when breakthrough time > 20 min • Fair when breakthrough time > 2
	Wear safety footwear or safety gumboots, e.g. Rubber
Body protection	See Other protection below
Other protection	<ul> <li>Overalls.</li> <li>Eyewash unit.</li> <li>Barrier cream.</li> <li>Skin cleansing cream.</li> </ul>

### **Respiratory protection**

Type -P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	P1 Air-line*	-	PAPR-P1 -
up to 50 x ES	Air-line**	P2	PAPR-P2
up to 100 x ES	-	P3	-
		Air-line*	-
100+ x ES	-	Air-line**	PAPR-P3

\* - Negative pressure demand \*\* - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

· Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.

• The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).

• Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.

• Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.

• Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)

· Use approved positive flow mask if significant quantities of dust becomes airborne.

· Try to avoid creating dust conditions.

#### 8.2.3. Environmental exposure controls

See section 12

#### **SECTION 9** Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Divided Solid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	105-110	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Not Available	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available
Nanoform Solubility	Not Available	Nanoform Particle Characteristics	Not Available
Particle Size	Not Available		

Not Available

# **SECTION 10 Stability and reactivity**

10.1.Reactivity	See section 7.2
10.2. Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
10.3. Possibility of hazardous reactions	See section 7.2
10.4. Conditions to avoid	See section 7.2
10.5. Incompatible materials	See section 7.2
10.6. Hazardous decomposition products	See section 5.3

# **SECTION 11 Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Information on toxicological effects

Inhaled	The material is not thought to produce respiratory irritation (as classified by EC Directives using animal models). Nevertheless inhalation of dusts, or fumes, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress. Inhalation of dusts, generated by the material during the course of normal handling, may produce severe damage to the health of the individual. Relatively small amounts absorbed from the lungs may prove fatal. Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled. If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures.
Ingestion	Accidental ingestion of the material may be seriously damaging to the health of the individual; animal experiments indicate that ingestion of less than 40 gram may be fatal.
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may cause transient discomfort characterised by tearing or conjunctival redness (as with windburn). Slight abrasive damage may also result.
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course. Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis, caused by particles less than 0.5 micron penetrating and remaining in the lung.

Ochratoxin A from	TOXICITY	IRRITATION
Aspergillus ochraceus	Oral (Dog) LD50; 0.2 mg/kg <sup>[2]</sup>	Not Available
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	¥	Aspiration Hazard	×

Legend: X – Data either not available or does not fill the criteria for classification

Data available to make classification

#### 11.2.1. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

#### 11.2.2. Other information

See Section 11.1

### **SECTION 12 Ecological information**

### 12.1. Toxicity

Ochratoxin A from Aspergillus ochraceus	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

#### DO NOT discharge into sewer or waterways.

#### 12.2. Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

#### 12.3. Bioaccumulative potential

Ingredient	Bioaccumulation	
	No Data available for all ingredients	

#### 12.4. Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

### 12.5. Results of PBT and vPvB assessment

	Р	В	т
Relevant available data	Not Available	Not Available	Not Available
PBT	×	×	×
vPvB	×	×	×
PBT Criteria fulfilled?			No
vPvB			No

#### 12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

#### 12.7. Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

#### **SECTION 13 Disposal considerations**

### 13.1. Waste treatment methods

Product / Packaging disposal	Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate: Reduction     Reuse     Recycling     Disposal (if all else fails)

	This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf
	life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use,
	and recycling or reuse may not always be appropriate. In most instances the supplier of the material should be consulted.
	DO NOT allow wash water from cleaning or process equipment to enter drains.
	It may be necessary to collect all wash water for treatment before disposal.
	In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
	Where in doubt contact the responsible authority.
	Recycle wherever possible or consult manufacturer for recycling options.
	Consult State Land Waste Management Authority for disposal.
	Bury residue in an authorised landfill.
	Recycle containers if possible, or dispose of in an authorised landfill.
Waste treatment options	Not Available
Sewage disposal options	Not Available

# **SECTION 14 Transport information**

### Labels Required

	6
Marine Pollutant	NO
HAZCHEM	2X

# Land transport (ADR-RID)

	1				
14.1. UN number or ID number	2811				
14.2. UN proper shipping name	TOXIC SOLID, ORGANIC, N.O.S.				
14.3. Transport hazard	Class	6.1			
class(es)	Subsidiary risk Not Applicable				
14.4. Packing group	П				
14.5. Environmental hazard	Not Applicable				
	Hazard identifica	ation (Kemler)	60		
	Classification co	de	T2		
14.6. Special precautions	Hazard Label		6.1		
for user	Special provisions		274 614		
	Limited quantity		500 g		
	Tunnel Restrictio	on Code	2 (D/E)		

# Air transport (ICAO-IATA / DGR)

14.1. UN number	2811			
14.2. UN proper shipping name	Toxic solid, organic, n.o.s. *			
14.3. Transport hazard class(es)	ICAO/IATA Class	6.1 Not Applicable		
	ERG Code	6L		
14.4. Packing group	Ш			
14.5. Environmental hazard	Not Applicable			
14.6. Special precautions for user	Special provisions		A3 A5	
	Cargo Only Packing Instructions		676	
	Cargo Only Maximum	Qty / Pack	100 kg	

Continued...

Passenger and Cargo Packing Instructions	669
Passenger and Cargo Maximum Qty / Pack	25 kg
Passenger and Cargo Limited Quantity Packing Instructions	Y644
Passenger and Cargo Limited Maximum Qty / Pack	1 kg

#### Sea transport (IMDG-Code / GGVSee)

14.1. UN number	2811	
14.2. UN proper shipping name	TOXIC SOLID, ORC	GANIC, N.O.S.
14.3. Transport hazard	IMDG Class	6.1
class(es)	IMDG Subrisk	Not Applicable
14.4. Packing group	Ш	
14.5. Environmental hazard	Not Applicable	
	EMS Number	F-A, S-A
14.6. Special precautions for user	Special provisions	s 274
	Limited Quantities	500 g

### Inland waterways transport (ADN)

14.1. UN number	2811		
14.2. UN proper shipping name	TOXIC SOLID, ORGANIC, N.O.S.		
14.3. Transport hazard class(es)	6.1 Not Applicable		
14.4. Packing group	II		
14.5. Environmental hazard	Not Applicable		
	Classification code	2	
	Special provisions	74; 614; 802	
14.6. Special precautions for user	Limited quantity	00 g	
	Equipment required	P, EP	
	Fire cones number		

### 14.7. Maritime transport in bulk according to IMO instruments

# 14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

### 14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group

### 14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type

#### **SECTION 15 Regulatory information**

#### 15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable - : Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2020/878; Regulation (EC) No 1272/2008 as updated through ATPs.

### Information according to 2012/18/EU (Seveso III):

Seveso Category H1

#### 15.2. Chemical safety assessment

For further information please look at the Chemical Safety Assessment and Exposure Scenarios prepared by your Supply Chain if available.

#### ECHA SUMMARY

Not Applicable

#### **National Inventory Status**

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Not Available
Canada - DSL	Not Available
Canada - NDSL	Not Available
China - IECSC	Not Available
Europe - EINEC / ELINCS / NLP	Not Available
Japan - ENCS	Not Available
Korea - KECI	Not Available
New Zealand - NZIoC	Not Available
Philippines - PICCS	Not Available
USA - TSCA	Not Available
Taiwan - TCSI	Not Available
Mexico - INSQ	Not Available
Vietnam - NCI	Not Available
Russia - FBEPH	Not Available
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

### **SECTION 16 Other information**

Revision Date	16/09/2022
Initial Date	16/09/2022

#### Full text Risk and Hazard codes

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

- EN 340 Protective clothing
- EN 374 Protective gloves against chemicals and micro-organisms
- EN 13832 Footwear protecting against chemicals
- EN 133 Respiratory protective devices

#### **Definitions and abbreviations**

PC - TWA: Permissible Concentration-Time Weighted Average PC - STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit, IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value **BCF: BioConcentration Factors BEI: Biological Exposure Index** AIIC: Australian Inventory of Industrial Chemicals DSL: Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.