

Apollo Scientific

Part Number: **DE234B** Version No: **1.1** Safety Data Sheet (Conforms to Annex II of REACH (1907/2006) - Regulation 2020/878) Chemwatch Hazard Alert Code: 2

Issue Date: **16/09/2022** Print Date: **31/07/2023** S.REACH.GBR.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

1.1. Product Identifier

Product name	-Dichlorobenzene-D4 98.0 Atom % D	
Chemical Name	dichlorobenzene-D4	
Synonyms	Available	
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	
Chemical formula	C4H6CIN	
Other means of identification	Not Available	
CAS number	3855-82-1	

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Not Available
Uses advised against	No specific uses advised against are identified.

1.3. Details of the manufacturer or supplier of the safety data sheet

Registered company name	Apollo Scientific	
Address	tefield Road, Bredbury SK62QR United Kingdom	
Telephone	14060505	
Fax	161 406 0506	
Website	http://www.apolloscientific.co.uk/	
Email	sales@apolloscientific.co.uk	

1.4. Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	Not Available
Other emergency telephone numbers	Not Available

SECTION 2 Hazards identification

2.1. Classification of the substance or mixture

Classification according to	
regulation (EC) No	H319 - Serious Eye Damage/Eye Irritation Category 2, H410 - Hazardous to the Aquatic Environment Long-Term Hazard
1272/2008 [CLP] and	Category 1, H351 - Carcinogenicity Category 2
amendments [1]	

Legend: 1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

2.2. Label elements

Hazard pictogram(s)	
Signal word	Warning

Hazard statement(s)

H319	Causes serious eye irritation.	
H410	Very toxic to aquatic life with long lasting effects.	
H351	Suspected of causing cancer.	

Supplementary statement(s)

Not Applicable

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.	
P280	Vear protective gloves, protective clothing, eye protection and face protection.	
P273	Avoid release to the environment.	
P264	Wash all exposed external body areas thoroughly after handling.	

Precautionary statement(s) Response

IF exposed or concerned: Get medical advice/ attention.	
F IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
e irritation persists: Get medical advice/attention.	
ect spillage.	
е	

Precautionary statement(s) Storage

P405 Store locked up.

Precautionary statement(s) Disposal

P501

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

2.3. Other hazards

REACH - Art.57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS print date.

SECTION 3 Composition / information on ingredients

3.1.Substances

1. CAS No 2.EC No 3.Index No 4.REACH No	%[weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	SCL / M-Factor	Nanoform Particle Characteristics
Not Available	100	1,4-Dichlorobenzene-D4 98.0 Atom % D	Not Applicable	Not Applicable	Not Available

Legend: 1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L; * EU IOELVs available; [e] Substance identified as having endocrine disrupting properties

3.2.Mixtures

See 'Information on ingredients' in section 3.1

SECTION 4 First aid measures

4.1. Description of first aid measures

Eye Contact	 If this product comes in contact with eyes: Wash out immediately with water. If irritation continues, seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	 If skin or hair contact occurs: Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

5.1. Extinguishing media

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog Large fires only.

5.2. Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.

5.3. Advice for firefighters

Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water courses. Use water delivered as a fine spray to control fire and cool adjacent area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use.
Fire/Explosion Hazard	Combustible. Will burn if ignited.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

See section 8

6.2. Environmental precautions

See section 12

6.3. Methods and material for containment and cleaning up

Minor Spills

Major Spills	 Environmental hazard - contain spillage. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Control personal contact with the substance, by using protective equipment and dust respirator. Prevent spillage from entering drains, sewers or water courses. Avoid generating dust. Sweep, shovel up. Recover product wherever possible.
	 Sweep, shove up, Recover product wherever possible. Put residues in labelled plastic bags or other containers for disposal. If contamination of drains or waterways occurs, advise emergency services.

6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

	 Limit all unnecessary personal contact. Wass protective alothing when rick of exposure accurs 		
	 Wear protective clothing when risk of exposure occurs. 		
	Use in a well-ventilated area.		
	Avoid contact with incompatible materials.		
	When handling, DO NOT eat, drink or smoke.		
	Keep containers securely sealed when not in use.		
Safe handling	Avoid physical damage to containers.		
	Always wash hands with soap and water after handling.		
	Work clothes should be laundered separately.		
	Use good occupational work practice.		
	Observe manufacturer's storage and handling recommendations contained within this SDS.		
	Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are		
	maintained.		
Fire and explosion	See section 5		
protection			
	Store in original containers.		
	Keep containers securely sealed.		
	Store in a cool, dry area protected from environmental extremes.		
	Store away from incompatible materials and foodstuff containers.		
	Protect containers against physical damage and check regularly for leaks.		
Other information	Observe manufacturer's storage and handling recommendations contained within this SDS.		
	For major quantities:		
	Consider storage in bunded areas - ensure storage areas are isolated from sources of community water (including		
	stormwater, ground water, lakes and streams}.		
	stornwater, ground water, lares and streams.		
	 Ensure that accidental discharge to air or water is the subject of a contingency disaster management plan; this may require 		

7.2. Conditions for safe storage, including any incompatibilities

Suitable container	 Lined metal can, lined metal pail/ can. Plastic pail. Polyliner drum. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	Avoid contamination of water, foodstuffs, feed or seed. None known Hygroscopic Store under argon
Hazard categories in accordance with Regulation (EC) No 1272/2008	E1: Hazardous to the Aquatic Environment in Category Acute 1 or Chronic 1
Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of	E1 Lower- / Upper-tier requirements: 100 / 200

7.3. Specific end use(s)

See section 1.2

SECTION 8 Exposure controls / personal protection

8.1. Control parameters

Ingredient	DNELs Exposure Pattern Worker	PNECs Compartment	
Not Available	Not Available	Not Available	

* Values for General Population

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Not Available						

Not Applicable

Emergency Limits

Ingredient	TEEL-1	TEEL-2		TEEL-3
1,4-Dichlorobenzene-D4 98.0 Atom % D	Not Available	Not Available		Not Available
Ingredient	Original IDLH		Revised IDLH	
1,4-Dichlorobenzene-D4 98.0 Atom % D	Not Available		Not Available	

8.2. Exposure controls

8.2.1. Appropriate engineering controls	 Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction. Exhaust ventilation should be designed to prevent accumulation and recirculation of particulates in the workplace. If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of: (a): particle dust respirators, if necessary, combined with an absorption cartridge; (b): filter respirators with absorption cartridge or canister of the right type; (c): fresh-air hoods or masks Build-up of electrostatic charge on the dust particle, may be prevented by bonding and grounding. Powder handling equipment such as dust collectors, dryers and mills may require additional protection measures such as explosion venting. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture				
	velocities" of fresh circulating air required to efficiently remov Type of Contaminant:	Air Speed:			
	direct spray, spray painting in shallow booths, drum filling, discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 ft/min)			
	grinding, abrasive blasting, tumbling, high speed wheel ge	2.5-10 m/s			
	velocity into zone of very high rapid air motion).		(500-2000 ft/min)		
	velocity into zone of very high rapid air motion). Within each range the appropriate value depends on:		(500-2000 ft/min)		
		Upper end of the range	(500-2000 ft/min)		
	Within each range the appropriate value depends on:	Upper end of the range 1: Disturbing room air currents	(500-2000 ft/min)		
	Within each range the appropriate value depends on: Lower end of the range		(500-2000 ft/min)		

Simple heavy shows that air velocity falls rapidly with distance away from the opening of a simple centraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple case). Therefore the air speed at the extraction joint should be a minimum of 4-10 m/s (800-2000 ftmin) for extraction of current the air velocity at extraction of current distance from the extraction optic. There extracts are included as an extraction optic structure are included or used. 82.2.1. Individual protection Imple theory shows that air velocity at investment are included or used. 82.2.1. Individual protection Imple theory shows that air velocity at investment are included or used. 82.2.1. Individual protection Imple theory shows that air velocity at investment are included or used. 82.2.1. Individual protection Imple theory shows that a investment and the investment and the investment and individual protection 82.2.1. Individual protection Imple theory shows that a investment and the investment and the investment and individual protection 82.2.1. Individual protection Imple theory shows that a investment and the intermove and equivalent intermoves and an account of injury sequence. 82.2.1. Individual protection Imple theory shows that a investment and the intermove and a state and protection and the intermove and a state and protection and the intermove and a state and protection and the intermove and an account of injury sequence. 82.2.1. Individual protection Imple theory shows that an intermove and intermove and a state and and account of protection and protectin and the inte		4: Large hood or large air mass in motion 4: Small hood-local control only
messures, such as personal protection quipment Softey glasses with side shelds I - Chinal enses may note a spealed hazard; soft contact lenses may absorb and concentrate initiants. A written policy content, descripting the warding of lenses or relations on use, should be created or each workplace or task. This shou include a role warding of lenses or relations on use, should be created or each workplace or task. This shou include a role warding of lenses or relations on use, should be created or each workplace or task. This shou include a role warding of lenses or relations on use, should be created or each workplace or task. This shou include a role warding of lenses or relations on use, should be created or each workplace or task. This shou include a role warding of lenses or relation in the remove contact lines as soon a pendiculale. Lense should be removed at the first sing of egn of neares or relation on the should be result of lense workplace in the weater of demonshould be transition or relation that is any should be result of each workplace can not be calculated in advance and has therefore to be checked prior to the application. The each break through three or substances that be be thered of not the manufacture or the protective gloves and has to be observed when making a final choice. Personal hryghene is a key spectration of approxemented. Stability and durability of gives pis designed not usage. Important factors in the selection of gloves include: . tenguency and duration of contact. . tenguency and specific barries. . Contaminated gloves should be replaced. . As defined in ASTM. KANZS 2161.1.1 or		Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 4-10 m/s (800-2000 ft/min) for extraction of crusher dusts generated 2 metres distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are
From the properties of the second second second second second second and concentrate initiants. A written policy document, describing the weaking of lenses or restrictions on use, should be created for each workplace or task. This should use a review of lense absorption and adsorption for the describing the weaking of lenses or restrictions on use, should be created for each bear second reliable. In this over of the describing the weaking of lenses or restrictions and suitable equipment should be tradicipation. The describing the weaking and the should be tradicipation international source loss of a periadic second be removed in a dean environment only after worker have weaked hands throughly. [CICO NIOSH Current Intelligurce Bulletin 59]. Skin protection See Hand protection below The selection of suitable gloves does not only depend on the material, but also on further marks of quality which way from manufacturer to marked requirement only atter worker have accent track through the origin the for substances has to be obtained from the manufacturer of the protective gloves and has therefore to be checked prior to the application. Personal hygines is its key element of effective hand care. Cloves must only be worn on clean hands. After using gloves, hand should be waaked and direid throroughly. Application of a non-perfuried molecular least of the display of the prior be ideed on the manufacturer of the protective gloves and a should be prove with a protection class of 5 of higher (foreadthrough time y application. Jee weather abunding to glove pixel advector may occur, a glove with a protection class of 5 of higher (foreadthrough time > 40 minutes according to EN34, ASNZS 2161.10.1 or national equivalent). Period weather abunding the sequence of the protection class of 5 of higher (foreadthrough time > 40 minutes according to the	personal protective	
Hands/feet protection Hands/feet protection <td< th=""><th>Eye and face protection</th><th> Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent] Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers </th></td<>	Eye and face protection	 Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent] Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers
 Hands/feet protection An and acture to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygine is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and died thoroughly. Application of a non-perfumed moisturiser is recommended. Suitability and duration of contact. - chemical resistance of glove material, - glove thickness and - glove thickness and - deutarity Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent) is recommended. - When only brief contact is expected, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.1 or national equivalent) is recommended. - When only brief contact is expected, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.1 or national equivalent) is recommended. - Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use. - Contaminated gloves should be replaced. - Keellent when breakthrough time > 20 min - For when glove material degrades For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended. I should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as permetation, difteres with a strict deathy is me	Skin protection	See Hand protection below
 fluorocaoutchouc. polyvinyl chloride. 	Hands/feet protection	can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: • frequency and duration of contact. • chemical resistance of glove material, glove thickness and • dexterity Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent). • When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.1.0.1 or national equivalent) is recommended. • When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.1.0.1 or national equivalent) is recommended. • Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use. • Contaminated gloves should be replaced. As defined in ASTM F-739-96 in any application, gloves are rated as: • Excellent when breakthrough time < 20 min • Fair when pleakthrough time < 20 min • Fair when pleakthrough time < 20 min • Fair when pleakthrough time a set on in the exact composition of the glove model. Therefore, glove site, the glove model. Therefore, glove site, as the requirements and knowledge of breakthrough. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of th
Body protection See Other protection below		 fluorocaoutchouc. polyvinyl chloride. Gloves should be examined for wear and/ or degradation constantly.

No special equipment needed when handling small quantities.

OTHERWISE:

- Overalls.
 Barrier cream.
- Bamer cream.
 Eyewash unit.

Respiratory protection

Other protection

Type -P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator	
up to 10 x ES	P1 Air-line*	-	PAPR-P1 -	
up to 50 x ES	Air-line**	P2	PAPR-P2	
up to 100 x ES	-	P3	-	
		Air-line*	-	
100+ x ES	-	Air-line**	PAPR-P3	

* - Negative pressure demand ** - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 deqC)

· Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.

• The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).

• Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.

• Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.

• Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)

 \cdot Use approved positive flow mask if significant quantities of dust becomes airborne.

· Try to avoid creating dust conditions.

8.2.3. Environmental exposure controls

See section 12

SECTION 9 Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Solid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	52-54	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	173	Molecular weight (g/mol)	Not Available
Flash point (°C)	66	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Combustible.	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available

Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Not Available	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	1.274	VOC g/L	Not Available
Nanoform Solubility	Not Available	Nanoform Particle Characteristics	Not Available
Particle Size	Not Available		

9.2. Other information

Not Available

SECTION 10 Stability and reactivity

10.1.Reactivity	See section 7.2
10.2. Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
10.3. Possibility of hazardous reactions	See section 7.2
10.4. Conditions to avoid	See section 7.2
10.5. Incompatible materials	See section 7.2
10.6. Hazardous decomposition products	See section 5.3

SECTION 11 Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.
Eye	Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may cause transient discomfort characterised by tearing or conjunctival redness (as with windburn). Slight abrasive damage may also result.
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

1,4-Dichlorobenzene-D4	ΤΟΧΙCITY	IRRITATION	
98.0 Atom % D	Not Available	Not Available	
Legend:	 Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances 		

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	*	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×
Legend: 🔀 – Data either not available or does not fill the criteria for classification			

Data available to make classification

11.2.1. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

11.2.2. Other information

See Section 11.1

SECTION 12 Ecological information

12.1. Toxicity

	Endpoint	Test Duration (hr)	Species	Value	Source
1,4-Dichlorobenzene-D4 98.0 Atom % D	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

12.2. Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

12.3. Bioaccumulative potential

Ingredient E	Bioaccumulation	
١	No Data available for all ingredients	

12.4. Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

12.5. Results of PBT and vPvB assessment

	Р	В	т
Relevant available data	Not Available	Not Available	Not Available
PBT	×	×	×
vPvB	×	×	×
PBT Criteria fulfilled?			No
vPvB			No

12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

12.7. Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

SECTION 13 Disposal considerations

13.1. Waste treatment methods

Product / Packaging disposal	 Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material) Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.
Waste treatment options	Not Available
Sewage disposal options	Not Available

SECTION 14 Transport information

Labels Required	
Marine Pollutant	
HAZCHEM	2Z

Land transport (ADR-RID)

14.1. UN number or ID number	3077					
14.2. UN proper shipping name	ENVIRONMENTA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.				
14.3. Transport hazard	Class	9				
class(es)	Subsidiary risk	Subsidiary risk Not Applicable				
14.4. Packing group	III					
14.5. Environmental hazard	Environmentally hazardous					
14.6. Special precautions for user	Hazard identification (Kemler)		90			
	Classification code		M7			
	Hazard Label		9			
	Special provisions		274 335 375 601			
	Limited quantity		5 kg			
	Tunnel Restriction	on Code	3 (-)			

Air transport (ICAO-IATA / DGR)

14.1. UN number 14.2. UN proper shipping	3077			
14.2 UN proper shipping		3077		
name	Environmentally hazardous substance, solid, n.o.s.			
14.3. Transport hazard	ICAO/IATA Class 9			
	ICAO / IATA Subrisk	AO / IATA Subrisk Not Applicable		
class(es)	ERG Code 9L			
14.4. Packing group	II			
14.5. Environmental hazard	Environmentally hazardous			
	Special provisions	A97 A158 A179 A197 A215		
	Cargo Only Packing Ir	956		
	Cargo Only Maximum	400 kg		
14.6. Special precautions for user	Passenger and Cargo	956		
	Passenger and Cargo	400 kg		
	Passenger and Cargo	Y956		
	Passenger and Cargo	Limited Maximum Qty / Pack	30 kg G	

Sea transport (IMDG-Code / GGVSee)

14.1. UN number	3077

14.2. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.		
14.3. Transport hazard class(es)	IMDG Class 9 IMDG Subrisk Not Applicable		
14.4. Packing group	III		
14.5. Environmental hazard	Marine Pollutant		
14.6. Special precautions	EMS Number	F-A, S-F	
for user	Special provisions Limited Quantities	274 335 966 967 969 5 kg	

Inland waterways transport (ADN)

14.1. UN number	3077		
14.2. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.		
14.3. Transport hazard class(es)	9 Not Applicable		
14.4. Packing group	III		
14.5. Environmental hazard	Environmentally hazardous		
	Classification code	M7	
	Special provisions	274; 335; 375; 601	
14.6. Special precautions for user	Limited quantity	5 kg	
	Equipment required	PP, A***	
	Fire cones number	0	

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group

14.7.3. Transport in bulk in accordance with the IGC Code

Product name Ship Type

SECTION 15 Regulatory information

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable - : Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2020/878; Regulation (EC) No 1272/2008 as updated through ATPs.

Information according to 2012/18/EU (Seveso III):

Status

Seveso Category E1

15.2. Chemical safety assessment

For further information please look at the Chemical Safety Assessment and Exposure Scenarios prepared by your Supply Chain if available.

ECHA SUMMARY

Not Applicable

National Inventory Status

National Inventory

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Not Available
Canada - DSL	Not Available
Canada - NDSL	Not Available
China - IECSC	Not Available
Europe - EINEC / ELINCS / NLP	Not Available
Japan - ENCS	Not Available
Korea - KECI	Not Available
New Zealand - NZIoC	Not Available
Philippines - PICCS	Not Available
USA - TSCA	Not Available
Taiwan - TCSI	Not Available
Mexico - INSQ	Not Available
Vietnam - NCI	Not Available
Russia - FBEPH	Not Available
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	16/09/2022
Initial Date	16/09/2022

Full text Risk and Hazard codes

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

- EN 340 Protective clothing
- EN 374 Protective gloves against chemicals and micro-organisms
- EN 13832 Footwear protecting against chemicals
- EN 133 Respiratory protective devices

Definitions and abbreviations

PC - TWA: Permissible Concentration-Time Weighted Average PC - STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit. IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value **BCF: BioConcentration Factors BEI: Biological Exposure Index** AIIC: Australian Inventory of Industrial Chemicals DSL: Domestic Substances List

NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.

