

# Benzene-D6 >99.50 Atom % D 0.03% TMS Apollo Scientific

Part Number: **DE30GT** 

Version No: 1.1

Safety Data Sheet (Conforms to Annex II of REACH (1907/2006) - Regulation 2020/878)

Chemwatch Hazard Alert Code: 4

Issue Date: 16/09/2022 Print Date: 31/07/2023 S.REACH.GBR.EN

# SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### 1.1. Product Identifier

Product name	Benzene-D6 >99.50 Atom % D 0.03% TMS		
Chemical Name	penzene-D6		
Synonyms	lot Available		
Proper shipping name	BENZENE		
Chemical formula	C6-D6		
Other means of identification	Not Available		
CAS number	1076-43-3		
EC number	214-061-8		

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Not Available	
Uses advised against	No specific uses advised against are identified.	

# 1.3. Details of the manufacturer or supplier of the safety data sheet

Registered company name	Apollo Scientific			
Address	Whitefield Road, Bredbury SK62QR United Kingdom			
Telephone	314060505			
Fax	0161 406 0506			
Website	http://www.apolloscientific.co.uk/			
Email	sales@apolloscientific.co.uk			

# 1.4. Emergency telephone number

Association / Organisation	Not Available		
Emergency telephone numbers	Not Available		
Other emergency telephone numbers	Not Available		

# **SECTION 2 Hazards identification**

# 2.1. Classification of the substance or mixture

Classification according to	
regulation (EC) No	

H336 - Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3, H225 - Flammable Liquids Category 2, H340 - Germ Cell Mutagenicity Category 1B, H302 - Acute Toxicity (Oral) Category 4, H315 - Skin Corrosion/Irritation Category

Benzene-D6 >99.50 Atom % D 0.03% TMS

3 Issue Date: 16/09/2022 Print Date: 31/07/2023

1272/2008 [CLP] and amendments [1]

2, H319 - Serious Eye Damage/Eye Irritation Category 2, H350 - Carcinogenicity Category 1A, H372 - Specific Target Organ Toxicity - Repeated Exposure Category 1, H304 - Aspiration Hazard Category 1

Legend:

1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

#### 2.2. Label elements

Version No: 1.1

Hazard pictogram(s)







Signal word

Danger

# Hazard statement(s)

H336	May cause drowsiness or dizziness.			
H225	Highly flammable liquid and vapour.			
H340	ay cause genetic defects.			
H302	Harmful if swallowed.			
H315	Causes skin irritation.			
H319	Causes serious eye irritation.			
H350	May cause cancer.			
H372	Causes damage to organs through prolonged or repeated exposure.			
H304	May be fatal if swallowed and enters airways.			

# Supplementary statement(s)

Not Applicable

# Precautionary statement(s) Prevention

P201	Obtain special instructions before use.			
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.			
P260	Do not breathe mist/vapours/spray.			
P271	Jse only outdoors or in a well-ventilated area.			
P280	Vear protective gloves, protective clothing, eye protection and face protection.			
P240	Ground and bond container and receiving equipment.			
P241	Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment.			
P242	Use non-sparking tools.			
P243	Take action to prevent static discharges.			
P264	Wash all exposed external body areas thoroughly after handling.			
P270	Do not eat, drink or smoke when using this product.			

# Precautionary statement(s) Response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider.			
P331	Do NOT induce vomiting.			
P308+P313	IF exposed or concerned: Get medical advice/ attention.			
P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam to extinguish.			
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.			
P337+P313	If eye irritation persists: Get medical advice/attention.			
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell.			
P302+P352	IF ON SKIN: Wash with plenty of water.			
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].			
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.			
P330	Rinse mouth.			
P332+P313	If skin irritation occurs: Get medical advice/attention.			
P362+P364	Take off contaminated clothing and wash it before reuse.			

Issue Date: **16/09/2022** Print Date: **31/07/2023** 

# Precautionary statement(s) Storage

P403+P235	Store in a well-ventilated place. Keep cool.		
P405	Store locked up.		

### Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

#### 2.3. Other hazards

REACH - Art.57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS print date.

#### **SECTION 3 Composition / information on ingredients**

#### 3.1.Substances

1. CAS No 2.EC No 3.Index No 4.REACH No	%[weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	SCL / M-Factor	Nanoform Particle Characteristics
Not Available	100	Benzene-D6 >99.50 Atom % D 0.03% TMS	Not Applicable	Not Applicable	Not Available

Legend:

1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L; \* EU IOELVs available; [e] Substance identified as having endocrine disrupting properties

#### 3.2.Mixtures

See 'Information on ingredients' in section 3.1

#### **SECTION 4 First aid measures**

# 4.1. Description of first aid measures

Eye Contact	If this product comes in contact with eyes:  • Wash out immediately with water.  • If irritation continues, seek medical attention.  • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs:  Flush skin and hair with running water (and soap if available).  Seek medical attention in event of irritation.
Inhalation	<ul> <li>If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>
Ingestion	<ul> <li>Immediately give a glass of water.</li> <li>First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>

# 4.2 Most important symptoms and effects, both acute and delayed

See Section 11

# 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

#### **SECTION 5 Firefighting measures**

# 5.1. Extinguishing media

# 5.2. Special hazards arising from the substrate or mixture

Fire Incompatibility

 Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

# 5.3. Advice for firefighters

Fire Fi	ghting
---------	--------

Part Number: **DE30GT** Version No: **1.1** 

# Page 4 of 13 Benzene-D6 >99.50 Atom % D 0.03% TMS

Issue Date: **16/09/2022**Print Date: **31/07/2023** 

# Fire/Explosion Hazard

- Liquid and vapour are highly flammable.
- Severe fire hazard when exposed to heat, flame and/or oxidisers.
- Vapour may travel a considerable distance to source of ignition.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- ▶ On combustion, may emit toxic fumes of carbon monoxide (CO).

Combustion products include:

#### **SECTION 6 Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

See section 8

#### 6.2. Environmental precautions

See section 12

# 6.3. Methods and material for containment and cleaning up

Minor Spills

- ► Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact with the substance, by using protective equipment.
   Contain and absorb small quantities with vermiculite or other absorbent material.
- ► Wipe up.
- ▶ Collect residues in a flammable waste container.

Major Spills

#### 6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

#### **SECTION 7 Handling and storage**

#### 7.1. Precautions for safe handling

- ▶ Containers, even those that have been emptied, may contain explosive vapours.
- ▶ Do NOT cut, drill, grind, weld or perform similar operations on or near containers.
- Avoid all personal contact, including inhalation.
- ▶ Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights, heat or ignition sources.
- ► When handling, **DO NOT** eat, drink or smoke
- Vapour may ignite on pumping or pouring due to static electricity.
- Safe handling
  - ► **DO NOT** use plastic buckets.
  - ▶ Earth and secure metal containers when dispensing or pouring product.
  - Use spark-free tools when handling.
  - Avoid contact with incompatible materials.
  - Keep containers securely sealed.
  - Avoid physical damage to containers.
  - Always wash hands with soap and water after handling.
  - Work clothes should be laundered separately.
  - Use good occupational work practice.
  - Observe manufacturer's storage and handling recommendations contained within this SDS.
  - Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.

# Fire and explosion protection

Other information

#### See section 5

#### Store in original containers in approved flame-proof area.

- No smoking, naked lights, heat or ignition sources.
- DO NOT store in pits, depression, basement or areas where vapours may be trapped.
- Keep containers securely sealed.
- Store away from incompatible materials in a cool, dry well ventilated area.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storage and handling recommendations contained within this MSDS.
- Tank storage: Tanks must be specifically designed for use with this product. Bulk storage tanks should be diked (bunded). Locate tanks away from heat and other sources of ignition. Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions.
- ▶ Keep in a cool place. Electrostatic charges will be generated during pumping. Electrostatic discharge may cause fire.

Part Number: **DE30GT** 

Version No: 1.1

Benzene-D6 >99.50 Atom % D 0.03% TMS

Page 5 of 13 Issue Date: 16/09/2022 Print Date: 31/07/2023

Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk. The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.

- For containers, or container linings use mild steel, stainless steel. Examples of suitable materials are: high density polyethylene (HDPE), polypropylene (PP), and Viton (FMK), which have been specifically tested for compatibility with this product.
- For container linings, use amine-adduct cured epoxy paint.
- ► For seals and gaskets use: graphite, PTFE, Viton A, Viton B.
- ▶ Unsuitable material: Some synthetic materials may be unsuitable for containers or container linings depending on the material specification and intended use. Examples of materials to avoid are: natural rubber (NR), nitrile rubber (NBR),  $ethylene\ propylene\ rubber\ (EPDM),\ polymethyl\ methacrylate\ (PMMA),\ polystyrene,\ polyvinyl\ chloride\ (PVC),\ polyisobutylene.$ However, some may be suitable for glove materials.
- Do not cut, drill, grind, weld or perform similar operations on or near containers. Containers, even those that have been emptied, can contain explosive vapours.

#### 7.2. Conditions for safe storage, including any incompatibilities

Packing as supplied by manufacturer. Plastic containers may only be used if approved for flammable liquid. Check that containers are clearly labelled and free from leaks. For low viscosity materials (i): Drums and jerry cans must be of the non-removable head type. (ii): Where a can is to be used as an inner package, the can must have a screwed enclosure. ► For materials with a viscosity of at least 2680 cSt. (23 deg. C) For manufactured product having a viscosity of at least 250 cSt. (23 deg. C) Suitable container Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C): (i) Removable head packaging; (ii) Cans with friction closures and (iii) low pressure tubes and cartridges may be used. Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages In addition, where inner packagings are glass and contain liquids of packing group I there must be sufficient inert absorbent to absorb any spillage, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic. Avoid reaction with oxidising agents Hygroscopic Storage incompatibility ▶ Light sensitive Store under argon Hazard categories in accordance with P5a: Flammable Liquids, P5b: Flammable Liquids, P5c: Flammable Liquids Regulation (EC) No 1272/2008 **Qualifying quantity** (tonnes) of dangerous P5a Lower- / Upper-tier requirements: 10 / 50 substances as referred to P5b Lower- / Upper-tier requirements: 50 / 200 in Article 3(10) for the P5c Lower- / Upper-tier requirements: 5 000 / 50 000 application of

#### 7.3. Specific end use(s)

See section 1.2

#### **SECTION 8 Exposure controls / personal protection**

#### 8.1. Control parameters

Ingredient	DNELs Exposure Pattern Worker	PNECs Compartment
Not Available	Not Available	Not Available

<sup>\*</sup> Values for General Population

#### Occupational Exposure Limits (OEL)

#### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Not Available						

#### Not Applicable

<b>Emergency L</b>	imits
--------------------	-------

Ingredient	TEEL-1	TEEL-2	TEEL-3

# Benzene-D6 >99.50 Atom % D 0.03% TMS

Issue Date: **16/09/2022**Print Date: **31/07/2023** 

Ingredient	TEEL-1	TEEL-2		TEEL-3
Benzene-D6 >99.50 Atom % D 0.03% TMS	Not Available	Not Available		Not Available
Ingredient	Original IDLH		Pavisad INI H	

Page 6 of 13

Ingredient	Original IDLH	Revised IDLH
Benzene-D6 >99.50 Atom % D 0.03% TMS	Not Available	Not Available

#### 8.2. Exposure controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.

For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant.

Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)

# 8.2.1. Appropriate engineering controls

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

- · Adequate ventilation is typically taken to be that which limits the average concentration to no more than 25% of the LEL within the building, room or enclosure containing the dangerous substance.
- · Ventilation for plant and machinery is normally considered adequate if it limits the average concentration of any dangerous substance that might potentially be present to no more than 25% of the LEL. However, an increase up to a maximum 50% LEL can be acceptable where additional safeguards are provided to prevent the formation of a hazardous explosive atmosphere. For example, gas detectors linked to emergency shutdown of the process might be used together with maintaining or increasing the exhaust ventilation on solvent evaporating ovens and gas turbine enclosures.
- Temporary exhaust ventilation systems may be provided for non-routine higher-risk activities, such as cleaning, repair or maintenance in tanks or other confined spaces or in an emergency after a release. The work procedures for such activities should be carefully considered. The atmosphere should be continuously monitored to ensure that ventilation is adequate and the area remains safe. Where workers will enter the space, the ventilation should ensure that the concentration of the dangerous substance does not exceed 10% of the LEL (irrespective of the provision of suitable breathing apparatus)

# 8.2.2. Individual protection measures, such as personal protective equipment









Part Number: **DE30GT** Page 7 of 13 Issue Date: 16/09/2022 Version No: 1.1 Print Date: 31/07/2023

#### Benzene-D6 >99.50 Atom % D 0.03% TMS

Safety glasses with side shields ► Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent] Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should Eye and face protection include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59]. Skin protection See Hand protection below Wear general protective gloves, eg. light weight rubber gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: · frequency and duration of contact, · chemical resistance of glove material, · glove thickness and dexterity Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent). · When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. · When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. · Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for Hands/feet protection long-term use · Contaminated gloves should be replaced. As defined in ASTM F-739-96 in any application, gloves are rated as: · Excellent when breakthrough time > 480 min · Good when breakthrough time > 20 min · Fair when breakthrough time < 20 min · Poor when glove material degrades For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended. It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task. Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example: · Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of. · Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended. **Body protection** See Other protection below Overalls.

- ▶ PVC Apron.
- ▶ PVC protective suit may be required if exposure severe.
- Ensure there is ready access to a safety shower.
- Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may
- For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets).
- Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds. Electrical resistance must range between 0 to 500,000 ohms. Conductive shoes should be stored in lockers close to the room in which they are worn. Personnel who have been issued conductive footwear should not wear them from their place of work to their homes and return.

#### 8.2.3. Environmental exposure controls

Other protection

See section 12

Issue Date: **16/09/2022**Print Date: **31/07/2023** 

# **SECTION 9 Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Appearance	Colourless		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	6.8	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	79.1	Molecular weight (g/mol)	Not Available
Flash point (°C)	-11	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	HIGHLY FLAMMABLE.	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	0.95	VOC g/L	Not Available
Nanoform Solubility	Not Available	Nanoform Particle Characteristics	Not Available
Particle Size	Not Available		

# 9.2. Other information

Not Available

# **SECTION 10 Stability and reactivity**

10.1.Reactivity	See section 7.2
10.2. Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
10.3. Possibility of hazardous reactions	See section 7.2
10.4. Conditions to avoid	See section 7.2
10.5. Incompatible materials	See section 7.2
10.6. Hazardous decomposition products	See section 5.3

# **SECTION 11 Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

Page 9 of 13 Version No: 1.1

Issue Date: 16/09/2022 Print Date: 31/07/2023 Benzene-D6 >99.50 Atom % D 0.03% TMS

Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

Benzene-D6 >99.50 Atom % D 0.03% TMS	TOXICITY	IRRITATION
	Not Available	Eye: adverse effect observed (irritating) <sup>[1]</sup>
		Skin: adverse effect observed (irritating) <sup>[1]</sup>
Legend:	Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS.     Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

Acute Toxicity	<b>~</b>	Carcinogenicity	<b>✓</b>
Skin Irritation/Corrosion	<b>~</b>	Reproductivity	×
Serious Eye Damage/Irritation	<b>~</b>	STOT - Single Exposure	<b>~</b>
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	<b>✓</b>
Mutagenicity	<b>~</b>	Aspiration Hazard	<b>~</b>

★ - Data either not available or does not fill the criteria for classification Legend:

✓ – Data available to make classification

#### 11.2 Information on other hazards

# 11.2.1. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

#### 11.2.2. Other information

See Section 11.1

# **SECTION 12 Ecological information**

# 12.1. Toxicity

D	Endpoint	Test Duration (hr)	Species	Value	Source
Benzene-D6 >99.50 Atom % D 0.03% TMS	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

# 12.2. Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

# 12.3. Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

# 12.4. Mobility in soil

Ingredient	Mobility	
	No Data available for all ingredients	

# 12.5. Results of PBT and vPvB assessment

	P	В	Т
Relevant available data	Not Available	Not Available	Not Available

Part Number: **DE30GT** Page **10** of **13** 

Version No: 1.1

Benzene-D6 >99.50 Atom % D 0.03% TMS Print Date: 31/07/2023

Issue Date: 16/09/2022

	Р	В	Т	
PBT	×	×	×	
vPvB	×	×	×	
PBT Criteria fulfilled	PBT Criteria fulfilled?			
vPvB No			No	

#### 12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

#### 12.7. Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

#### **SECTION 13 Disposal considerations**

# 13.1. Waste treatment methods

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- ▶ Reuse
- ► Recycling
- Disposal (if all else fails)

# Product / Packaging disposal

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- ▶ Where in doubt contact the responsible authority.
- ► Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

Waste treatment options

Not Available

Sewage disposal options

Not Available

# **SECTION 14 Transport information**

### **Labels Required**



Marine Pollutant

NO

HAZCHEM

3WE

#### Land transport (ADR-RID)

14.1. UN number or ID number	1114		
14.2. UN proper shipping name	BENZENE		
14.3. Transport hazard	Class	3	
class(es)	Subsidiary risk	Not Applicable	
14.4. Packing group	П		

Part Number: **DE30GT** Version No: **1.1** 

Benzene-D6 >99.50 Atom % D 0.03% TMS

Issue Date: **16/09/2022**Print Date: **31/07/2023** 

14.5. Environmental hazard	Not Applicable		
	Hazard identification (Kemler)	33	
	Classification code	F1	
14.6. Special precautions	Hazard Label	3	
for user	Special provisions	Not Applicable	
	Limited quantity	1 L	
	Tunnel Restriction Code	2 (D/E)	

# Air transport (ICAO-IATA / DGR)

14.1. UN number	1114				
14.2. UN proper shipping name	Benzene				
	ICAO/IATA Class 3				
14.3. Transport hazard class(es)	ICAO / IATA Subrisk	Not Applicable			
Class(es)	ERG Code 3H				
14.4. Packing group	II				
14.5. Environmental hazard	Not Applicable				
	Special provisions		Not Applicable		
	Cargo Only Packing Instructions		364		
	Cargo Only Maximum Qty / Pack		60 L		
14.6. Special precautions for user	Passenger and Cargo	Packing Instructions	353		
101 4001	Passenger and Cargo Maximum Qty / Pack		5 L		
	Passenger and Cargo	Limited Quantity Packing Instructions	Y341		
	Passenger and Cargo Limited Maximum Qty / Pack		1 L		

# Sea transport (IMDG-Code / GGVSee)

14.1. UN number	1114	1114	
14.2. UN proper shipping name	BENZENE	BENZENE	
14.3. Transport hazard	IMDG Class 3	3	
class(es)	IMDG Subrisk N	Not Applicable	
14.4. Packing group	II.		
14.5. Environmental hazard	Not Applicable		
	EMS Number	F-E, S-D	
14.6. Special precautions for user	Special provisions	Not Applicable	
101 4301	Limited Quantities	1 L	

# Inland waterways transport (ADN)

14.1. UN number	1114
14.2. UN proper shipping name	BENZENE
14.3. Transport hazard class(es)	3 Not Applicable
14.4. Packing group	П
14.5. Environmental hazard	Not Applicable

Part Number: DE30GT Page 12 of 13 Issue Date: 16/09/2022 Version No: 1.1 Print Date: 31/07/2023 Benzene-D6 >99.50 Atom % D 0.03% TMS

14.6. Special precautions for user	Classification code	F1
	Special provisions	Not Applicable
	Limited quantity	1 L
.0. 400	Equipment required	PP, EX, A
	Fire cones number	1

# 14.7. Maritime transport in bulk according to IMO instruments

# 14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

# 14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group

# 14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type

#### **SECTION 15 Regulatory information**

#### 15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable -: Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2020/878; Regulation (EC) No 1272/2008 as updated through ATPs.

#### Information according to 2012/18/EU (Seveso III):

Seveso Category P5a, P5b, P5c

#### 15.2. Chemical safety assessment

For further information please look at the Chemical Safety Assessment and Exposure Scenarios prepared by your Supply Chain if available.

#### **ECHA SUMMARY**

Not Applicable

# **National Inventory Status**

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Not Available
Canada - DSL	Not Available
Canada - NDSL	Not Available
China - IECSC	Not Available
Europe - EINEC / ELINCS / NLP	Not Available
Japan - ENCS	Not Available
Korea - KECI	Not Available
New Zealand - NZIoC	Not Available
Philippines - PICCS	Not Available
USA - TSCA	Not Available
Taiwan - TCSI	Not Available
Mexico - INSQ	Not Available
Vietnam - NCI	Not Available
Russia - FBEPH	Not Available
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

#### **SECTION 16 Other information**

Part Number: DE30GT Page 13 of 13 Issue Date: 16/09/2022 Version No: 1.1 Print Date: 31/07/2023

#### Benzene-D6 >99.50 Atom % D 0.03% TMS

**Revision Date** 16/09/2022 **Initial Date** 16/09/2022

#### Full text Risk and Hazard codes

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eve-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

#### **Definitions and abbreviations**

PC - TWA: Permissible Concentration-Time Weighted Average

PC - STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit,

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value **BCF**: BioConcentration Factors BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

**DSL: Domestic Substances List** NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

**ENCS: Existing and New Chemical Substances Inventory** 

KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.