

# Tantalum(V) chloride, resublimed Apollo Scientific

Part Number: **IN3406** Version No: **1.1** 

Safety Data Sheet (Conforms to Annex II of REACH (1907/2006) - Regulation 2020/878)

Chemwatch Hazard Alert Code: 4

Issue Date: 16/09/2022 Print Date: 31/07/2023 S.REACH.GBR.EN

### SECTION 1 Identification of the substance / mixture and of the company / undertaking

### 1.1. Product Identifier

Product name	Tantalum(V) chloride, resublimed
Chemical Name	tantalum pentachloride
Synonyms	Not Available
Proper shipping name	CORROSIVE SOLID, ACIDIC, INORGANIC, N.O.S.
Chemical formula	CI5Ta
Other means of identification	Not Available
CAS number	7721-01-9
EC number	231-755-6

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Not Available
Uses advised against	No specific uses advised against are identified.

### 1.3. Details of the manufacturer or supplier of the safety data sheet

Registered company name	Apollo Scientific
Address	Whitefield Road, Bredbury SK62QR United Kingdom
Telephone	01614060505
Fax	0161 406 0506
Website	http://www.apolloscientific.co.uk/
Email	sales@apolloscientific.co.uk

### 1.4. Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	Not Available
Other emergency telephone numbers	Not Available

### **SECTION 2 Hazards identification**

# 2.1. Classification of the substance or mixture

Classification according to	
regulation (EC) No	

H314 - Skin Corrosion/Irritation Category 1, H312 - Acute Toxicity (Dermal) Category 4, H318 - Serious Eye Damage/Eye Irritation Category 1, H332 - Acute Toxicity (Inhalation) Category 4, H302 - Acute Toxicity (Oral) Category 4

1272/2008 [CLP] and amendments [1]

Legend: 1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

### 2.2. Label elements

### Hazard pictogram(s)





Signal word

Danger

### Hazard statement(s)

H314	Causes severe skin burns and eye damage.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H302	Harmful if swallowed.

### Supplementary statement(s)

Not Applicable

### Precautionary statement(s) Prevention

P260	Do not breathe dust/fume.
P264	Wash all exposed external body areas thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, protective clothing, eye protection and face protection.
P270	Do not eat, drink or smoke when using this product.

### Precautionary statement(s) Response

P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor/physician/first aider.
P363	Wash contaminated clothing before reuse.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell.
P302+P352	IF ON SKIN: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P362+P364	Take off contaminated clothing and wash it before reuse.

### Precautionary statement(s) Storage

P405 Store locked up.

### Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

### 2.3. Other hazards

REACH - Art.57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS print date.

# **SECTION 3 Composition / information on ingredients**

### 3.1.Substances

1. CAS No 2.EC No 3.Index No	%[weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	SCL / M-Factor	Nanoform Particle Characteristics
------------------------------------	-----------	------	---	-------------------	--------------------------------------

Part Number: IN3406 Page 3 of 13 Issue Date: 16/09/2022 Version No: 1.1 Print Date: 31/07/2023

### Tantalum(V) chloride, resublimed

4.REACH No					
Not Available	100	Tantalum(V) chloride, resublimed	Not Applicable	Not Applicable	Not Available

Legend:

1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L; \* EU IOELVs available; [e] Substance identified as having endocrine disrupting properties

### 3.2.Mixtures

See 'Information on ingredients' in section 3.1

### **SECTION 4 First aid measures**

# 4.1. Description of first aid measures

The Booking Control of the State	
Eye Contact	If this product comes in contact with the eyes:  Immediately hold eyelids apart and flush the eye continuously with running water.  Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.  Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.  Transport to hospital or doctor without delay.  Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs:  Immediately flush body and clothes with large amounts of water, using safety shower if available.  Quickly remove all contaminated clothing, including footwear.  Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.  Transport to hospital, or doctor.
Inhalation	<ul> <li>If fumes or combustion products are inhaled remove from contaminated area.</li> <li>Lay patient down. Keep warm and rested.</li> <li>Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>Transport to hospital, or doctor, without delay.</li> <li>Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema.</li> <li>Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs).</li> <li>As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested.</li> <li>Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered.</li> <li>This must definitely be left to a doctor or person authorised by him/her.</li> <li>(ICSC13719)</li> </ul>
Ingestion	<ul> <li>For advice, contact a Poisons Information Centre or a doctor at once.</li> <li>Urgent hospital treatment is likely to be needed.</li> <li>If swallowed do NOT induce vomiting.</li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>Observe the patient carefully.</li> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>Transport to hospital or doctor without delay.</li> </ul>

### 4.2 Most important symptoms and effects, both acute and delayed

See Section 11

### 4.3. Indication of any immediate medical attention and special treatment needed

For acute or short term repeated exposures to strong acids:

- Airway problems may arise from laryngeal edema and inhalation exposure. Treat with 100% oxygen initially.
- ▶ Respiratory distress may require cricothyroidotomy if endotracheal intubation is contraindicated by excessive swelling
- Intravenous lines should be established immediately in all cases where there is evidence of circulatory compromise.
- Strong acids produce a coagulation necrosis characterised by formation of a coagulum (eschar) as a result of the dessicating action of the acid on proteins in

# INGESTION:

- Immediate dilution (milk or water) within 30 minutes post ingestion is recommended.
- ▶ DO NOT attempt to neutralise the acid since exothermic reaction may extend the corrosive injury.
- ▶ Be careful to avoid further vomit since re-exposure of the mucosa to the acid is harmful. Limit fluids to one or two glasses in an adult.
- ▶ Charcoal has no place in acid management.
- ▶ Some authors suggest the use of lavage within 1 hour of ingestion.

Part Number: IN3406 Version No: 1.1

### Page 4 of 13

### Tantalum(V) chloride, resublimed

Issue Date: **16/09/2022**Print Date: **31/07/2023** 

- Skin lesions require copious saline irrigation. Treat chemical burns as thermal burns with non-adherent gauze and wrapping.
- ▶ Deep second-degree burns may benefit from topical silver sulfadiazine.

#### FYF.

- Eye injuries require retraction of the eyelids to ensure thorough irrigation of the conjuctival cul-de-sacs. Irrigation should last at least 20-30 minutes. DO NOT use neutralising agents or any other additives. Several litres of saline are required.
- Cycloplegic drops, (1% cyclopentolate for short-term use or 5% homatropine for longer term use) antibiotic drops, vasoconstrictive agents or artificial tears may be indicated dependent on the severity of the injury.
- Steroid eye drops should only be administered with the approval of a consulting ophthalmologist).

[Ellenhorn and Barceloux: Medical Toxicology]

# **SECTION 5 Firefighting measures**

### 5.1. Extinguishing media

- ▶ There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

### 5.2. Special hazards arising from the substrate or mixture

Fire Incompatibility

None known.

### 5.3. Advice for firefighters

Fire/Explosion Hazard

Fire		

- Non combustible.
- ▶ Not considered to be a significant fire risk.
- Acids may react with metals to produce hydrogen, a highly flammable and explosive gas.
- ▶ Heating may cause expansion or decomposition leading to violent rupture of containers.
- May emit corrosive, poisonous fumes. May emit acrid smoke.

### **SECTION 6 Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

See section 8

### 6.2. Environmental precautions

See section 12

### 6.3. Methods and material for containment and cleaning up

Minor Spills

- Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material.
- Check regularly for spills and leaks.
- ▶ Remove all ignition sources.
- Clean up all spills immediately.
- Avoid contact with skin and eyes.
- ► Control personal contact with the substance, by using protective equipment.
- Use dry clean up procedures and avoid generating dust.
- Place in a suitable, labelled container for waste disposal.

**Major Spills** 

### 6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

### **SECTION 7 Handling and storage**

### 7.1. Precautions for safe handling

Safe handling

- Avoid all personal contact, including inhalation.
- ▶ Wear protective clothing when risk of exposure occurs.
- ▶ Use in a well-ventilated area.
- ▶ WARNING: To avoid violent reaction, ALWAYS add material to water and NEVER water to material.
- Avoid smoking, naked lights or ignition sources.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.

Part Number: IN3406 Page 5 of 13 Issue Date: 16/09/2022 Version No: 1.1 Print Date: 31/07/2023

### Tantalum(V) chloride, resublimed

Avoid physical damage to containers. Always wash hands with soap and water after handling. ▶ Work clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained. Fire and explosion See section 5 protection ▶ Store in original containers. ► Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Other information Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

### 7.2. Conditions for safe storage, including any incompatibilities

- DO NOT use aluminium or galvanised containers Check regularly for spills and leaks Lined metal can, lined metal pail/ can. Plastic pail. Polyliner drum. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks. For low viscosity materials Drums and jerricans must be of the non-removable head type. Where a can is to be used as an inner package, the can must have a screwed enclosure. Suitable container For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.): Removable head packaging; Cans with friction closures and ▶ low pressure tubes and cartridges may be used. Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient inert cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic. Inorganic acids are generally soluble in water with the release of hydrogen ions. The resulting solutions have pH's of less than 7.0.
  - Storage incompatibility
- Inorganic acids neutralise chemical bases (for example: amines and inorganic hydroxides) to form salts neutralisation can generate dangerously large amounts of heat in small spaces.
- Fig. The dissolution of inorganic acids in water or the dilution of their concentrated solutions with additional water may generate significant heat.
- ▶ The addition of water to inorganic acids often generates sufficient heat in the small region of mixing to cause some of the water to boil explosively. The resulting "bumping" can spatter the acid. Inorganic acids react with active metals, including such structural metals as aluminum and iron, to release hydrogen, a
- flammable gas. Inorganic acids can initiate the polymerisation of certain classes of organic compounds.
- Inorganic acids react with cyanide compounds to release gaseous hydrogen cyanide.
- Inorganic acids generate flammable and/or toxic gases in contact with dithiocarbamates, isocyanates, mercaptans, nitrides, nitriles, sulfides, and strong reducing agents. Additional gas-generating reactions occur with sulfites, nitrites, thiosulfates (to give H2S and SO3), dithionites (SO2), and even carbonates.
- Acids often catalyse (increase the rate of) chemical reactions.
- Moisture sensitive
- ▶ Store under argon

### Hazard categories in accordance with Regulation (EC) No 1272/2008

Not Available

**Qualifying quantity** (tonnes) of dangerous substances as referred to in Article 3(10) for the application of

Not Available

### 7.3. Specific end use(s)

See section 1.2

### **SECTION 8 Exposure controls / personal protection**

### 8.1. Control parameters

Ingredient	DNELs Exposure Pattern Worker	PNECs Compartment
Not Available	Not Available	Not Available

<sup>\*</sup> Values for General Population

### Occupational Exposure Limits (OEL)

### **INGREDIENT DATA**

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Not Available						

### Not Applicable

### Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
Tantalum(V) chloride, resublimed	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
Tantalum(V) chloride, resublimed	Not Available	Not Available

### 8.2. Exposure controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations.

Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

### 8.2.1. Appropriate engineering controls

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the

Version No: 1.1

### Tantalum(V) chloride, resublimed

Issue Date: **16/09/2022**Print Date: **31/07/2023** 

extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

# 8.2.2. Individual protection measures, such as personal protective equipment

Eye and face protection









- Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure.
- Chemical goggles. Whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitted. [AS/NZS 1337.1, EN166 or national equivalent]
- Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection.
- Alternatively a gas mask may replace splash goggles and face shields.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation lens should be removed in a clean environment only after workers have washed hands thoroughly. ICDC NIOSH Current Intelligence Bulletin 591.

	be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].
Skin protection	See Hand protection below
Hands/feet protection	► Elbow length PVC gloves
Body protection	See Other protection below
Other protection	<ul> <li>Overalls.</li> <li>PVC Apron.</li> <li>PVC protective suit may be required if exposure severe.</li> <li>Eyewash unit.</li> <li>Ensure there is ready access to a safety shower.</li> </ul>

### Respiratory protection

Type -P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	P1 Air-line*	-	PAPR-P1
up to 50 x ES	Air-line**	P2	PAPR-P2
up to 100 x ES	-	P3	-
		Air-line*	-
100+ x ES	-	Air-line**	PAPR-P3

<sup>\* -</sup> Negative pressure demand \*\* - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

### 8.2.3. Environmental exposure controls

See section 12

### **SECTION 9 Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Appearance	White		
Physical state	Divided Solid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available

Part Number: IN3406 Page 8 of 13

Not Available

Not Available

Version No: 1.1 Tantalum(V) chloride, resublimed

Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	216	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	242	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Not Available	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	3.68	VOC g/L	Not Available
Nanoform Solubility	Not Available	Nanoform Particle	Not Available

Not Available

Characteristics

### 9.2. Other information

Not Available

# **SECTION 10 Stability and reactivity**

**Nanoform Solubility** 

Particle Size

10.1.Reactivity	See section 7.2
10.2. Chemical stability	Contact with alkaline material liberates heat
10.3. Possibility of hazardous reactions	See section 7.2
10.4. Conditions to avoid	See section 7.2
10.5. Incompatible materials	See section 7.2
10.6. Hazardous decomposition products	See section 5.3

# **SECTION 11 Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Information on toxicological effects

Inhaled	The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.  Corrosive acids can cause irritation of the respiratory tract, with coughing, choking and mucous membrane damage. There may be dizziness, headache, nausea and weakness.
Ingestion	Ingestion of acidic corrosives may produce burns around and in the mouth, the throat and oesophagus. Immediate pain and difficulties in swallowing and speaking may also be evident.  The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	Skin contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue.  Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.  Open cuts, abraded or irritated skin should not be exposed to this material  Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.  Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Еуе	If applied to the eyes, this material causes severe eye damage.  Direct eye contact with acid corrosives may produce pain, tears, sensitivity to light and burns. Mild burns of the epithelia generally recover rapidly and completely.
Chronic	Repeated or prolonged exposure to acids may result in the erosion of teeth, swelling and/or ulceration of mouth lining. Irritation of airways to lung, with cough, and inflammation of lung tissue often occurs.

Issue Date: 16/09/2022

Print Date: 31/07/2023

Version No: 1.1

### Tantalum(V) chloride, resublimed

Issue Date: 16/09/2022 Print Date: 31/07/2023

Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems.

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

Tantalum(V) chloride,	TOXICITY	IRRITATION
resublimed	Oral (Rat) LD50: 1900 mg/kg <sup>[2]</sup>	Not Available
Legend:	Value obtained from Europe ECHA Registered Substances - A     Unless otherwise specified data extracted from RTECS - Regist	

# Tantalum(V) chloride, resublimed

Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.

Acute Toxicity	<b>~</b>	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	<b>~</b>	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

**Legend:** X – Data either not available or does not fill the criteria for classification

✓ – Data available to make classification

# 11.2 Information on other hazards

### 11.2.1. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

### 11.2.2. Other information

See Section 11.1

# **SECTION 12 Ecological information**

### 12.1. Toxicity

Tantalum(V) chloride,	Endpoint	Test Duration (hr)	Species	Value	Source
resublimed	LC50	96h	Fish	>0.002mg/L	2
Legend:	4. US EPA, E	n 1. IUCLID Toxicity Data 2. Europe ECHA F icotox database - Aquatic Toxicity Data 5. EC tion Data 7. METI (Japan) - Bioconcentration	CETOC Aquatic Hazard Assessment Data 6.	•	tic Toxicity

Prevent, by any means available, spillage from entering drains or water courses.

DO NOT discharge into sewer or waterways.

### 12.2. Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air		
	No Data available for all ingredients	No Data available for all ingredients		

### 12.3. Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

### 12.4. Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

### 12.5. Results of PBT and vPvB assessment

	Р	В	Т	
Relevant available data	Not Available	Not Available	Not Av	ailable
PBT	×	×	×	
vPvB	X	X	×	
PBT Criteria fulfilled?				No
vPvB				No

# 12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

### 12.7. Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

Not Available

# **SECTION 13 Disposal considerations**

### 13.1. Waste treatment methods

	Recycle wherever possible.
	► Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable
	treatment or disposal facility can be identified.
Product / Packaging	<ul> <li>Treat and neutralise at an approved treatment plant. Treatment should involve: Mixing or slurrying in water; Neutralisation</li> </ul>
disposal	with soda-lime or soda-ash followed by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical
	wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material)
	▶ Decontaminate empty containers with 5% aqueous sodium hydroxide or soda ash, followed by water. Observe all label
	safeguards until containers are cleaned and destroyed.
Waste treatment options	Not Available

# **SECTION 14 Transport information**

Sewage disposal options

# **Labels Required**



### Land transport (ADR-RID)

• •	•	
14.1. UN number or ID number	3260	
14.2. UN proper shipping name	CORROSIVE SOLI	D, ACIDIC, INORGANIC, N.O.S.
14.3. Transport hazard class(es)	Class Subsidiary risk	8 Not Applicable
14.4. Packing group	II	
14.5. Environmental hazard	Not Applicable	

14.6. Special precautions for user

Hazard identification (Kemler)	80
Classification code	C2
Hazard Label	8
Special provisions	274
Limited quantity	1 kg
Tunnel Restriction Code	2 (E)

# Air transport (ICAO-IATA / DGR)

14.1. UN number	3260		
14.2. UN proper shipping name	Corrosive solid, acidic, i	norganic, n.o.s. *	
	ICAO/IATA Class	8	
14.3. Transport hazard class(es)	ICAO / IATA Subrisk	Not Applicable	
ciass(es)	ERG Code	8L	
14.4. Packing group	II		
14.5. Environmental hazard	Not Applicable		
	Special provisions		A3 A803
	Cargo Only Packing Ir	nstructions	863
	Cargo Only Maximum	Qty / Pack	50 kg
14.6. Special precautions for user	Passenger and Cargo	Packing Instructions	859
101 4001	Passenger and Cargo	Maximum Qty / Pack	15 kg
	Passenger and Cargo	Limited Quantity Packing Instructions	Y844
	Passenger and Cargo	Limited Maximum Qty / Pack	5 kg

# Sea transport (IMDG-Code / GGVSee)

14.1. UN number	3260	
14.2. UN proper shipping name	CORROSIVE SOLID, ACIDIC, INORGANIC, N.O.S.	
14.3. Transport hazard class(es)	IMDG Class 8 IMDG Subrisk N	lot Applicable
14.4. Packing group	II .	
14.5. Environmental hazard	Not Applicable	
14.6. Special precautions for user	EMS Number	F-A, S-B
	Special provisions	274
	Limited Quantities	1 kg

# Inland waterways transport (ADN)

14.1. UN number	3260	
14.2. UN proper shipping name	CORROSIVE SOLID, ACIDIC, INORGANIC, N.O.S.	
14.3. Transport hazard class(es)	8 Not Applicable	
14.4. Packing group	II	
14.5. Environmental hazard	Not Applicable	
14.6. Special precautions for user	Classification code C2	
	Special provisions 274	
	Limited quantity 1 kg	

Tantalum(V) chloride, resublimed

Issue Date: **16/09/2022** Print Date: **31/07/2023** 

Equipment required	PP, EP
Fire cones number	0

### 14.7. Maritime transport in bulk according to IMO instruments

### 14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

### 14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group

### 14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type	
i i dadot i aiii o	Cilip Type	

### **SECTION 15 Regulatory information**

### 15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable -: Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2020/878; Regulation (EC) No 1272/2008 as updated through ATPs.

### Information according to 2012/18/EU (Seveso III):

Seveso Category Not Available

### 15.2. Chemical safety assessment

For further information please look at the Chemical Safety Assessment and Exposure Scenarios prepared by your Supply Chain if available.

### **ECHA SUMMARY**

Not Applicable

### **National Inventory Status**

National Inventory	Status	
Australia - AIIC / Australia Non-Industrial Use	Not Available	
Canada - DSL	Not Available	
Canada - NDSL	Not Available	
China - IECSC	Not Available	
Europe - EINEC / ELINCS / NLP	Not Available	
Japan - ENCS	Not Available	
Korea - KECI	Not Available	
New Zealand - NZIoC	Not Available	
Philippines - PICCS	Not Available	
USA - TSCA	Not Available	
Taiwan - TCSI	Not Available	
Mexico - INSQ	Not Available	
Vietnam - NCI	Not Available	
Russia - FBEPH	Not Available	
Legend:	Yes = All CAS declared ingredients are on the inventory  No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.	

### **SECTION 16 Other information**

Revision Date	16/09/2022
Initial Date	16/09/2022

 Part Number: IN3406
 Page 13 of 13
 Issue Date: 16/09/2022

 Version No: 1.1
 Frint Date: 31/07/2023

### Tantalum(V) chloride, resublimed

### Full text Risk and Hazard codes

### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

### **Definitions and abbreviations**

PC - TWA: Permissible Concentration-Time Weighted Average

PC - STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit,

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard
OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

**ENCS: Existing and New Chemical Substances Inventory** 

KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act
TCSI: Taiwan Chemical Substance Inventory
INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.