

Terbium, chips Apollo Scientific

Part Number: IN3454 Version No: 1.1

Safety Data Sheet (Conforms to Annex II of REACH (1907/2006) - Regulation 2020/878)

Chemwatch Hazard Alert Code: 3

Issue Date: 16/09/2022 Print Date: 31/07/2023 S.REACH.GBR.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

1.1. Product Identifier

| Product name | Terbium, chips | |
|-------------------------------|--------------------------------|--|
| Chemical Name | pium | |
| Synonyms | Available | |
| Proper shipping name | MABLE SOLID, INORGANIC, N.O.S. | |
| Chemical formula | Tb | |
| Other means of identification | Not Available | |
| CAS number | 7440-27-9 | |
| EC number | 231-137-6 | |

1.2. Relevant identified uses of the substance or mixture and uses advised against

| Relevant identified uses | Not Available | |
|--------------------------|--|--|
| Uses advised against | No specific uses advised against are identified. | |

1.3. Details of the manufacturer or supplier of the safety data sheet

| Registered company name | Apollo Scientific | |
|-------------------------|---|--|
| Address | Whitefield Road, Bredbury SK62QR United Kingdom | |
| Telephone | 060505 | |
| Fax | 61 406 0506 | |
| Website | http://www.apolloscientific.co.uk/ | |
| Email | sales@apolloscientific.co.uk | |

1.4. Emergency telephone number

| Association / Organisation | Not Available | |
|-----------------------------------|---------------|--|
| Emergency telephone numbers | Not Available | |
| Other emergency telephone numbers | Not Available | |

SECTION 2 Hazards identification

2.1. Classification of the substance or mixture

| Classification according to | |
|-----------------------------|--|
| regulation (EC) No | |

H228 - Flammable Solids Category 1

Issue Date: **16/09/2022**Print Date: **31/07/2023**

1272/2008 [CLP] and amendments [1]

Legend:

1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

H228

Flammable solid.

Supplementary statement(s)

Not Applicable

Precautionary statement(s) Prevention

| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
|---|--|
| P240 Ground and bond container and receiving equipment. | |
| P241 | Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment. |
| P280 | Wear protective gloves and protective clothing. |

Precautionary statement(s) Response

P370+P378

In case of fire: Use alcohol resistant foam or normal protein foam to extinguish.

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

2.3. Other hazards

REACH - Art.57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS print date.

SECTION 3 Composition / information on ingredients

3.1.Substances

| 1. CAS No 2.EC No 3.Index No 4.REACH No | %[weight] | Name | Classification according to regulation (EC) No 1272/2008 [CLP] and amendments | SCL / M-Factor | Nanoform Particle Characteristics |
|--|-----------|-------------------|---|-------------------|--------------------------------------|
| Not Available | 100 | Terbium, chips | Not Applicable | Not Applicable | Not Available |

Legend:

1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L; * EU IOELVs available; [e] Substance identified as having endocrine disrupting properties

3.2.Mixtures

See 'Information on ingredients' in section 3.1

SECTION 4 First aid measures

4.1. Description of first aid measures

If this product comes in contact with eyes:

Eye Contact

- Wash out immediately with water.If irritation continues, seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

 Part Number: IN3454
 Page 3 of 12
 Issue Date: 16/09/2022

 Version No: 1.1
 Terbium, chips
 Print Date: 31/07/2023

| Skin Contact | If skin or hair contact occurs: Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation. |
|--------------|---|
| Inhalation | If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary. |
| Ingestion | Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. |

4.2 Most important symptoms and effects, both acute and delayed

See Section 11

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

5.1. Extinguishing media

For SMALL FIRES:

Dry chemical, CO2, water spray or foam.

For LARGE FIRES:

Water-spray, fog or foam.

5.2. Special hazards arising from the substrate or mixture

| Fire Incompatibility | None known. |
|----------------------|-------------|
|----------------------|-------------|

5.3. Advice for firefighters

| J.J. Advice for inteliginer | • |
|-----------------------------|--|
| Fire Fighting | Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. Fight fire from a safe distance, with adequate cover. If safe, switch off electrical equipment until vapour fire hazard removed. Use water delivered as a fine spray to control fire and cool adjacent area. Avoid spraying water onto liquid pools. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. |
| Fire/Explosion Hazard | Flammable solid which burns and propagates flame easily, even when partly wetted with water. Any source of ignition, i.e. friction, heat, sparks or flame, may cause fire or explosion. May burn fiercely May form explosive mixtures with air. May REIGNITE after fire is extinguished. Containers may explode on heating. Solids may melt and flow when heated or involved in a fire. Runoff may pollute waterways. Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust may burn rapidly and fiercely if ignited. Dry dust can be charged electrostatically by turbulence, pneumatic transport, pouring, in exhaust ducts and during transport, thereby providing a source of ignition. |

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

See section 8

6.2. Environmental precautions

See section 12

6.3. Methods and material for containment and cleaning up

Minor Spills

- Remove all ignition sources.
- DO NOT touch or walk through spilled material.

▶ Decomposition products may be irritating, poisonous or corrosive.

▶ Clean up all spills immediately.

 Part Number: IN3454
 Page 4 of 12
 Issue Date: 16/09/2022

 Version No: 1.1
 Terbium, chips
 Print Date: 31/07/2023

| | Avoid contact with skin and eyes. Prevent dust cloud. With clean shovel (preferably non-sparking) place material into clean, dry container and cover loosely. Move containers from spill area. Control personal contact with the substance, by using protective equipment. |
|--------------|---|
| Major Spills | Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. DO NOT touch or walk through spilled material. Control personal contact with the substance, by using protective equipment. Prevent, by any means available, spillage from entering drains or water course. No smoking, naked lights or ignition sources. Increase ventilation. Stop leak if safe to do so. Contain or cover with sand, earth or vermiculite. Use only spark-free shovels and explosion proof equipment. Collect recoverable product into labelled containers for recycling. Collect solid residues and seal in labelled drums for disposal. Wash area with water and dike for later disposal; prevent runoff into drains. After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using. If contamination of drains or waterways occurs, advise emergency services. |

6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

7.1. Precautions for safe handling Avoid all personal contact, including inhalation. Wear protective clothing when risk of overexposure occurs. ▶ Use in a well-ventilated area. Prevent concentration in hollows and sumps. ▶ DO NOT enter confined spaces until atmosphere has been checked. ▶ DO NOT allow material to contact humans, exposed food or food utensils. Avoid smoking, naked lights or ignition sources. When handling, **DO NOT** eat, drink or smoke. Safe handling Avoid contact with incompatible materials. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. ▶ Working clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained. Fire and explosion See section 5 protection FOR MINOR QUANTITIES: ▶ Store in an indoor fireproof cabinet or in a room of noncombustible construction. ▶ Provide adequate portable fire-extinguishers in or near the storage area. FOR PACKAGE STORAGE: ▶ Store in original containers in approved flame-proof area. ▶ No smoking, naked lights, heat or ignition sources. ▶ DO NOT store in pits, depressions, basements or areas where vapours may be trapped. ► Keep containers securely sealed. Other information Store away from incompatible materials in a cool, dry, well ventilated area. Protect containers against physical damage and check regularly for leaks. Protect containers from exposure to weather and from direct sunlight unless: (a) the packages are of metal or plastic construction; (b) the packages are securely closed are not opened for any purpose while in the area where they are stored and (c) adequate precautions are taken to ensure that rain water, which might become contaminated by the dangerous goods, is collected and disposed of safely. ▶ Ensure proper stock-control measures are maintained to prevent prolonged storage of dangerous goods. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

7.2. Conditions for safe storage, including any incompatibilities

Suitable container

For low viscosity materials and solids:

Drums and jerricans must be of the non-removable head type.

Where a can is to be used as an inner package, the can must have a screwed enclosure.

Issue Date: 16/09/2022 Print Date: 31/07/2023

| | For materials with a viscosity of at least 2680 cSt. (23 deg. C): Removable head packaging and cans with friction closures may be used. Where combination packages are used, there must be sufficient inert absorbent material to absorb completely any leakage that may occur, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic. All combination packages for Packing group I and II must contain cushioning material. |
|---|---|
| Storage incompatibility | None known • Air Sensitive • Moisture sensitive • Store under argon |
| Hazard categories in accordance with Regulation (EC) No 1272/2008 | Not Available |
| Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of | Not Available |

7.3. Specific end use(s)

See section 1.2

SECTION 8 Exposure controls / personal protection

8.1. Control parameters

| Ingredient | DNELs Exposure Pattern Worker | PNECs Compartment |
|---------------|-------------------------------|----------------------|
| Not Available | Not Available | Not Available |

^{*} Values for General Population

Occupational Exposure Limits (OEL)

INGREDIENT DATA

| Source | Ingredient | Material name | TWA | STEL | Peak | Notes |
|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
| Not Available |

Not Applicable

Emergency Limits

| Ingredient | TEEL-1 | TEEL-2 | | TEEL-3 |
|----------------|---------------|---------------|---------------|---------------|
| Terbium, chips | Not Available | Not Available | | Not Available |
| | | | | |
| Ingredient | Original IDLH | | Revised IDLH | |
| Terbium chips | Not Available | | Not Available | |

8.2. Exposure controls

8.2.1. Appropriate

engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of

fresh circulating air required to effectively remove the contaminant.

Issue Date: 16/09/2022 Print Date: 31/07/2023

| Type of Contaminant: | Air Speed: |
|---|---------------------------------|
| solvent, vapours, degreasing etc., evaporating from tank (in still air) | 0.25-0.5 m/s (50-100 f/min) |
| aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s (100-200 f/min.) |
| direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) | 1-2.5 m/s (200-500 f/min) |
| grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion). | 2.5-10 m/s (500-2000 f/min.) |

Within each range the appropriate value depends on:

| Lower end of the range | Upper end of the range |
|---|------------------------------------|
| 1: Room air currents minimal or favourable to capture | 1: Disturbing room air currents |
| 2: Contaminants of low toxicity or of nuisance value only | 2: Contaminants of high toxicity |
| 3: Intermittent, low production. | 3: High production, heavy use |
| 4: Large hood or large air mass in motion | 4: Small hood - local control only |

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

For large scale or continuous use:

- Spark-free, earthed ventilation system, venting directly to the outside and separate from usual ventilation systems
- ▶ Provide dust collectors with explosion vents

8.2.2. Individual protection measures, such as personal protective equipment







Eye and face protection

- Safety glasses with side shields
- Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eve irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

Skin protection See Hand protection below

Hands/feet protection

- Wear physical protective gloves, e.g. leather.
- Wear safety footwear.

Body protection

See Other protection below

Overalls.

- ► Eyewash unit.
- ▶ Barrier cream.
- Skin cleansing cream.
- Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may

Other protection

- For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets).
- Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds. Electrical resistance must range between 0 to 500,000 ohms. Conductive shoes should be stored in lockers close to the room in which they are worn. Personnel who have been issued conductive footwear should not wear them from their place of work to their homes and return.

Respiratory protection

Type -P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|------------------------------------|----------------------|----------------------|------------------------|

Issue Date: **16/09/2022**Print Date: **31/07/2023**

| up to 10 x ES | P1 Air-line* | - - | PAPR-P1 |
|----------------|-----------------|--------------|---------|
| up to 50 x ES | Air-line** | P2 | PAPR-P2 |
| up to 100 x ES | - | P3 | - |
| | | Air-line* | - |
| 100+ x ES | - | Air-line** | PAPR-P3 |

^{* -} Negative pressure demand ** - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

8.2.3. Environmental exposure controls

See section 12

SECTION 9 Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Appearance | Grey | | |
|--|---------------|--|----------------|
| | | | |
| Physical state | Solid | Relative density (Water = 1) | Not Available |
| Odour | Not Available | Partition coefficient n-octanol / water | Not Available |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | Not Available |
| pH (as supplied) | Not Available | Decomposition temperature (°C) | Not Available |
| Melting point / freezing point (°C) | 1356 | Viscosity (cSt) | Not Available |
| Initial boiling point and boiling range (°C) | 2800 | Molecular weight (g/mol) | Not Available |
| Flash point (°C) | Not Available | Taste | Not Available |
| Evaporation rate | Not Available | Explosive properties | Not Available |
| Flammability | Not Available | Oxidising properties | Not Available |
| Upper Explosive Limit (%) | Not Available | Surface Tension (dyn/cm or mN/m) | Not Applicable |
| Lower Explosive Limit (%) | Not Available | Volatile Component (%vol) | Not Available |
| Vapour pressure (kPa) | Not Available | Gas group | Not Available |
| Solubility in water | Not Available | pH as a solution (1%) | Not Available |
| Vapour density (Air = 1) | 8.234 | VOC g/L | Not Available |
| Nanoform Solubility | Not Available | Nanoform Particle Characteristics | Not Available |
| Particle Size | Not Available | | |

9.2. Other information

Not Available

SECTION 10 Stability and reactivity

| 10.1.Reactivity | See section 7.2 |
|---|--|
| 10.2. Chemical stability | Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur. |
| 10.3. Possibility of hazardous reactions | See section 7.2 |
| 10.4. Conditions to avoid | See section 7.2 |

| Issue Date: 16/09/2022 |
|------------------------|
| Print Date: 31/07/2023 |
| |

| 10.5. Incompatible materials | See section 7.2 |
|--|-----------------|
| 10.6. Hazardous decomposition products | See section 5.3 |

SECTION 11 Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Information on toxicological effects

| Inhaled | The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. |
|--------------|---|
| Ingestion | The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. |
| Skin Contact | The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. |
| Eye | Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may cause transient discomfort characterised by tearing or conjunctival redness (as with windburn). Slight abrasive damage may also result. |
| Chronic | Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course. |

| Toubium obino | TOXICITY | IRRITATION |
|----------------|---|---------------|
| Terbium, chips | Not Available | Not Available |
| Legend: | Value obtained from Europe ECHA Registered Substances - A Unless otherwise specified data extracted from RTECS - Regist | |

| Acute Toxicity | × | Carcinogenicity | × |
|-----------------------------------|---|--------------------------|---|
| Skin Irritation/Corrosion | × | Reproductivity | × |
| Serious Eye Damage/Irritation | × | STOT - Single Exposure | × |
| Respiratory or Skin sensitisation | × | STOT - Repeated Exposure | × |
| Mutagenicity | × | Aspiration Hazard | × |

Legend: X − Data either not available or does not fill the criteria for classification
✓ − Data available to make classification

11.2 Information on other hazards

11.2.1. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

11.2.2. Other information

See Section 11.1

SECTION 12 Ecological information

12.1. Toxicity

| | Endpoint | Test Duration (hr) | Species | Value | Source |
|----------------|------------------|--|--|------------------|------------------|
| Terbium, chips | Not Available | Not Available | Not Available | Not Available | Not Available |
| Legend: | 4. US EPA, E | n 1. IUCLID Toxicity Data 2. Europe ECHA R cotox database - Aquatic Toxicity Data 5. EC tion Data 7. METI (Japan) - Bioconcentration | ETOC Aquatic Hazard Assessment Data 6. | • | - |

12.2. Persistence and degradability

| Ingredient | Persistence: Water/Soil | Persistence: Air |
|------------|---------------------------------------|---------------------------------------|
| | No Data available for all ingredients | No Data available for all ingredients |

Issue Date: **16/09/2022**Print Date: **31/07/2023**

12.3. Bioaccumulative potential

| Ingredient | Bioaccumulation |
|------------|---------------------------------------|
| | No Data available for all ingredients |

12.4. Mobility in soil

| Ingredient | Mobility |
|------------|---------------------------------------|
| | No Data available for all ingredients |

12.5. Results of PBT and vPvB assessment

| | P | В | Т |
|-------------------------|---------------|---------------|---------------|
| Relevant available data | Not Available | Not Available | Not Available |
| PBT | x | × | × |
| vPvB | × | × | x |
| PBT Criteria fulfilled? | | | No |
| vPvB | | | No |

12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

12.7. Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

SECTION 13 Disposal considerations

13.1. Waste treatment methods

| | ▶ Recycle wherever possible. |
|-------------------------|--|
| | Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable |
| Product / Packaging | treatment or disposal facility can be identified. |
| disposal | Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material) Description of the control of the |
| | ▶ Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed. |
| Waste treatment options | Not Available |
| Sewage disposal options | Not Available |
| | |

SECTION 14 Transport information

Labels Required

| Marine Pollutant | NO |
|------------------|----|
| HAZCHEM | 1Z |

Land transport (ADR-RID)

| 14.1. UN number or ID number | 3178 |
|----------------------------------|--|
| 14.2. UN proper shipping name | FLAMMABLE SOLID, INORGANIC, N.O.S. |
| 14.3. Transport hazard class(es) | Class 4.1 Subsidiary risk Not Applicable |
| 14.4. Packing group | II . |

Part Number: **IN3454** Version No: **1.1**

Terbium, chips

Issue Date: **16/09/2022** Print Date: **31/07/2023**

| 14.5. Environmental hazard | Not Applicable | |
|----------------------------|--------------------------------|-------|
| | Hazard identification (Kemler) | 40 |
| | Classification code | F3 |
| 14.6. Special precautions | Hazard Label | 4.1 |
| for user | Special provisions | 274 |
| | Limited quantity | 1 kg |
| | Tunnel Restriction Code | 2 (E) |

Air transport (ICAO-IATA / DGR)

| 14.1. UN number | 3178 | | |
|------------------------------------|---|--|---------|
| 14.2. UN proper shipping name | Flammable solid, inorga | nic, n.o.s. * | |
| | ICAO/IATA Class | 4.1 | |
| 14.3. Transport hazard class(es) | ICAO / IATA Subrisk | Not Applicable | |
| Class(es) | ERG Code | 3L | |
| 14.4. Packing group | II | | |
| 14.5. Environmental hazard | Not Applicable | | |
| | Special provisions | | A3 A803 |
| | Cargo Only Packing Ir | nstructions | 448 |
| | Cargo Only Maximum | Qty / Pack | 50 kg |
| 14.6. Special precautions for user | Passenger and Cargo | Passenger and Cargo Packing Instructions | |
| ioi usei | Passenger and Cargo | Passenger and Cargo Maximum Qty / Pack | |
| | Passenger and Cargo Limited Quantity Packing Instructions | | Y441 |
| | Passenger and Cargo | Limited Maximum Qty / Pack | 5 kg |

Sea transport (IMDG-Code / GGVSee)

| 14.1. UN number | 3178 | | |
|------------------------------------|------------------------------------|----------------|--|
| 14.2. UN proper shipping name | FLAMMABLE SOLID, INORGANIC, N.O.S. | | |
| 14.3. Transport hazard class(es) | IMDG Class 4 | .1 | |
| | IMDG Subrisk N | lot Applicable | |
| 14.4. Packing group | П | | |
| 14.5. Environmental hazard | Not Applicable | | |
| 14.6. Special precautions for user | EMS Number | F-A, S-G | |
| | Special provisions | 274 | |
| | Limited Quantities | 1 kg | |
| | | | |

Inland waterways transport (ADN)

| 14.1. UN number | 3178 | | |
|----------------------------------|------------------------------------|--|--|
| 14.2. UN proper shipping name | FLAMMABLE SOLID, INORGANIC, N.O.S. | | |
| 14.3. Transport hazard class(es) | 4.1 Not Applicable | | |
| 14.4. Packing group | II | | |
| 14.5. Environmental hazard | Not Applicable | | |

Issue Date: **16/09/2022**Print Date: **31/07/2023**

14.6. Special precautions for user

| Classification code | F3 |
|---------------------|------|
| Special provisions | 274 |
| Limited quantity | 1 kg |
| Equipment required | PP |
| Fire cones number | 1 |

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

| Product name |
|--------------|
|--------------|

14.7.3. Transport in bulk in accordance with the IGC Code

| Product name | Ship Type |
|--------------|-----------|
| | |

SECTION 15 Regulatory information

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable -: Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2020/878; Regulation (EC) No 1272/2008 as updated through ATPs.

Information according to 2012/18/EU (Seveso III):

Seveso Category No

Not Available

15.2. Chemical safety assessment

For further information please look at the Chemical Safety Assessment and Exposure Scenarios prepared by your Supply Chain if available.

ECHA SUMMARY

Not Applicable

National Inventory Status

| National Inventory | Status | |
|--|---|--|
| Australia - AIIC / Australia Non-Industrial Use | Not Available | |
| Canada - DSL | Not Available | |
| Canada - NDSL | Not Available | |
| China - IECSC | Not Available | |
| Europe - EINEC / ELINCS / NLP | Not Available | |
| Japan - ENCS | Not Available | |
| Korea - KECI | Not Available | |
| New Zealand - NZIoC | Not Available | |
| Philippines - PICCS | Not Available | |
| USA - TSCA | Not Available | |
| Taiwan - TCSI | Not Available | |
| Mexico - INSQ | Not Available | |
| Vietnam - NCI | Not Available | |
| Russia - FBEPH | Not Available | |
| Legend: | Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration. | |

SECTION 16 Other information

Issue Date: 16/09/2022 Print Date: 31/07/2023

Revision Date 16/09/2022 **Initial Date** 16/09/2022

Full text Risk and Hazard codes

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eve-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

Definitions and abbreviations

PC - TWA: Permissible Concentration-Time Weighted Average PC - STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit,

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value **BCF**: BioConcentration Factors BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.