

Apollo Scientific

Part Number: **OR18285** Version No: **1.1** Safety Data Sheet (Conforms to Annex II of REACH (1907/2006) - Regulation 2020/878) Chemwatch Hazard Alert Code: 2

Issue Date: **16/09/2022** Print Date: **02/08/2023** S.REACH.GBR.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

1.1. Product Identifier

Product name	S-(Chloromethyl)uracil	
Chemical Name	6-(chloromethyl)uracil	
Synonyms	Not Available	
Chemical formula	C5H5CIN2O2	
Other means of identification	Not Available	
CAS number	18592-13-7	
EC number	242-431-9	

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Not Available
Uses advised against	No specific uses advised against are identified.

1.3. Details of the manufacturer or supplier of the safety data sheet

Registered company name	Apollo Scientific	
Address	Nhitefield Road, Bredbury SK62QR United Kingdom	
Telephone	614060505	
Fax	0161 406 0506	
Website	http://www.apolloscientific.co.uk/	
Email	sales@apolloscientific.co.uk	

1.4. Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	Not Available
Other emergency telephone numbers	Not Available

SECTION 2 Hazards identification

2.1. Classification of the substance or mixture

Classification according to regulation (EC) No 1272/2008 [CLP] and amendments ^[1]

H400 - Hazardous to the Aquatic Environment Acute Hazard Category 1, H335 - Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, H302 - Acute Toxicity (Oral) Category 4, H315 - Skin Corrosion/Irritation Category 2, H319 - Serious Eye Damage/Eye Irritation Category 2

Legend: 1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

2.2. Label elements

Hazard pictogram(s)	
Signal word	Warning

Signal word Warning

Hazard statement(s)

H400	Very toxic to aquatic life.
H335	May cause respiratory irritation.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.

Supplementary statement(s)

Not Applicable

Precautionary statement(s) Prevention

P271	Use only outdoors or in a well-ventilated area.	
P261	Avoid breathing dust/fumes.	
P264	Vash all exposed external body areas thoroughly after handling.	
P270	Do not eat, drink or smoke when using this product.	
P273	Avoid release to the environment.	
P280	P280 Wear protective gloves, protective clothing, eye protection and face protection.	

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P391	Collect spillage.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell.
P302+P352	IF ON SKIN: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P330	Rinse mouth.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

Precautionary statement(s) Storage

P405	Store locked up.	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.	

Precautionary statement(s) Disposal

P501

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

2.3. Other hazards

REACH - Art.57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS print date.

SECTION 3 Composition / information on ingredients

3.1.Substances

1. CAS No

2.EC No 3.Index No 4.REACH No			(EC) No 1272/2008 [CLP] and amendments	M-Factor	Characteristics
Not Available	100	6-(Chloromethyl)uracil	Not Applicable	Not Applicable	Not Available

Legend: 1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L; * EU IOELVs available; [e] Substance identified as having endocrine disrupting properties

3.2.Mixtures

See 'Information on ingredients' in section 3.1

SECTION 4 First aid measures

4.1. Description of first aid measures

Eye Contact	 If this product comes in contact with eyes: Wash out immediately with water. If irritation continues, seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	 If skin or hair contact occurs: Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

5.1. Extinguishing media

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

5.2. Special hazards arising from the substrate or mixture

Fire Incompatibility None known.

5.3. Advice for firefighters

Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use.
Fire/Explosion Hazard	 Non combustible. Not considered a significant fire risk, however containers may burn.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

See section 8

6.2. Environmental precautions

See section 12

6.3. Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Avoid contact with skin and eyes. Wear impervious gloves and safety glasses. Use dry clean up procedures and avoid generating dust. Vacuum up (consider explosion-proof machines designed to be grounded during storage and use). Do NOT use air hoses for cleaning Place spilled material in clean, dry, sealable, labelled container.
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Control personal contact with the substance, by using protective equipment and dust respirator. Prevent spillage from entering drains, sewers or water courses. Avoid generating dust. Sweep, shovel up. Recover product wherever possible. Put residues in labelled plastic bags or other containers for disposal. If contamination of drains or waterways occurs, advise emergency services.

6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Safe handling	 Limit all unnecessary personal contact. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
Fire and explosion protection	See section 5
Other information	 Store in original containers. Keep containers securely sealed. Store in a cool, dry area protected from environmental extremes. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS. For major quantities: Consider storage in bunded areas - ensure storage areas are isolated from sources of community water (including stormwater, ground water, lakes and streams). Ensure that accidental discharge to air or water is the subject of a contingency disaster management plan; this may require consultation with local authorities.

7.2. Conditions for safe storage, including any incompatibilities

Suitable container	 Lined metal can, lined metal pail/ can. Plastic pail. Polyliner drum. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	Avoid contamination of water, foodstuffs, feed or seed. None known
Hazard categories in accordance with Regulation (EC) No 1272/2008	E1: Hazardous to the Aquatic Environment in Category Acute 1 or Chronic 1

Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of

E1 Lower- / Upper-tier requirements: 100 / 200

7.3. Specific end use(s)

See section 1.2

SECTION 8 Exposure controls / personal protection

8.1. Control parameters

Ingredient	DNELs Exposure Pattern Worker	PNECs Compartment
Not Available	Not Available	Not Available

* Values for General Population

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Not Available						

Not Applicable

Emergency Limits

Ingredient	TEEL-1	TEEL-2		TEEL-3
6-(Chloromethyl)uracil	Not Available	Not Available		Not Available
In our Paul			Device UDI II	
Ingredient	Original IDLH		Revised IDLH	
6-(Chloromethyl)uracil	Not Available		Not Available	

8.2. Exposure controls

	Engineering controls are used to remove a hazard or place a engineering controls can be highly effective in protecting wo provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activ Enclosure and/or isolation of emission source which keeps a that strategically "adds" and "removes" air in the work enviro designed properly. The design of a ventilation system must a Employers may need to use multiple types of controls to pre	rkers and will typically be independent of ity or process is done to reduce the risk. a selected hazard "physically" away from to onment. Ventilation can remove or dilute a match the particular process and chemica	worker interactions to the worker and ventilation n air contaminant if	
	 Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction. If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. 			
	Such protection might consist of:			
8.2.1. Appropriate (a): particle dust respirators, if necessary, combined with an absorption cartridge;				
engineering controls	(b): filter respirators with absorption cartridge or canister of the right type;			
	(c): fresh-air hoods or masks.			
	Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.			
	Type of Contaminant:		Air Speed:	
			· ·	
	direct spray, spray painting in shallow booths, drum filling, discharge (active generation into zone of rapid air motion)	, .	1-2.5 m/s (200-500 f/min.)	
		porotod ducto (rologood at high initial	2.5-10 m/s	
	grinding, abrasive blasting, tumbling, high speed wheel ge velocity into zone of very high rapid air motion).		(500-2000 f/min.)	
		neraleu uusis (releaseu al nigh iniliai		
	velocity into zone of very high rapid air motion).	Upper end of the range		

2. Contaminants of low toocky or of nuisance value only. 2. Contaminants of high toocky 3. Intermediation 3. High production. 3. High production. 4. Large toock of large and investory that all velocity fast mightly with distance away from the operating of a simple extraction prote. Webody enserves the has extraction protein that and velocity fast might with distance away from the operating of a simple extraction protein that the operate of distance from the extraction protein structure of on-value of data protection. 8.2.2. Individual protection Image interve with side a high on velocities are nutrities of velocities and nutrities. Image interve with side a high on velocities are nutrities of velocities and nutrities of velocities and nutrities. 8.2.2. Individual protection Image interve with side a high on velocities are nutrities of velocities and nutrities of velocities and nutrities. Image interve with side a high on velocities are nutrities of velocities and nutrities of velocities and nutrities. 8.2.2. Individual protection Image interve with side a high on velocities and nutrities of velocities and nutrities of velocities and nutrities of velocities and nutrities. Image interve with nutrities of velocities and nutrities of velocities and nutrities of velocities and nutrities with a side and nutrities with nutrities of velocities and nutrities with a side and nutrities. 8.2.1. Individual protection Image interve with side and operating of velocities and nutrities with a side and velocities and nutrities in velocities and nutrities with a side operating of velocities and nutrities of velocities and nutrities and nutrities and nu	3: High production, 4: High production, how y use 4: Large hood range air mass in motion 4: Small hood-local cottod only 4: Small hood-local cottod hood 4: Small hood-local cottod hood					
4. Large hood or large air mass in motion 4. Small hood-local control only 3. Simple theory shows that air velocity take rapidly with distance away from the opening of a simple excision pion. How well excised at the extraction pion. How all excises in the extraction of the single of distance away from the opening of a simple excised. The extraction pion. How all excises in the extraction of the single of distance away from the opening of a simple excised. There is an extraction pion. How all excises in the distance of route how and the distance away from the opening of a simple excision? The involution is an involution of the involution of the one distance of route how and the distance away from the opening of a simple excision? 8.2.2. Individual protection mass with the base of the opening of th	4: Large locod or large air mass in motion 4: Shall hood-local control only Single Heavy shous that air velocity this cipicity with distance away from the opening of a single extraction pipe. Velocity opening documents of the air species		2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity		
Simple heavy shows that all velocity falls rapidly with distance away from the opening of a single catalon, Therefore and signed at the state of obsained from the stratection point (in single catalon). Therefore data generated 2 meet distance in the two stretches in the state of signed at the stratection (in show beck) at the stratection (in show beck). Therefore data generated 2 meet distance in the two stretches in the stretches	Implementation Simple fragmentations and indications of the sample of the institution and the analysis of the institution and the institution an		3: Intermittent, low production.	3: High production, heavy use		
generative decisions with the square of distance from the oxtanction point (miniple case). Therefore the single of tables protection fan. for example, should be a minimum of 4-10 min (800-2000 fmin) for extraction of mainted is generated 2 meters 8.2.2.1 individual protection generative meters generative meters generative meters 8.2.2.1 individual protection generative meters generative meters generative meters 8.2.2.1 individual protection generative meters generative meters generative meters 8.2.2.1 individual protection generative meters generative meters generative meters 8.2.2.1 individual protection Generative meters generative meters generative meters 8.2.2.1 individual protection Constant departmeters generative meters generative meters 8.2.2.1 individual protection Constant departmeters generative meters generative meters 8.2.2.1 individual protection Constant departmeters generative meters generative meters 8.2.2.1 individual protection Constant departmeters individual protection individual protection 8.2.2.2.1 individual protection Constant departmeters individual protection individual protection 8.2.2.2.1 inditac protection Constant departmeters<	sprenetally decreases with the square of delations from the extendion point (in single-cased). Therefore the survey experiment of the structure of point should be a similarum of 4-10 mills (800-2000 fmin) (in extraction of carbine delices within the extraction appendixes, must leasential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are instance of the structure of		4: Large hood or large air mass in motion	4: Small hood-local control only		
messure such as gruppment Construction Personal protective equipment - Safety glasses with side shields - Contact Insess may pose a special hazard; soft contact lenses may absorb and concentrate initiants. A written policy document, descripting the wearing of there sore restrictions on use, should be created for each work/rate or task. This should include a norwew of lense sore special houses or testicitions on use, should be created for each work/rate or task. This should include a norwew of lense sore special houses or testicitions on use, should be explorement should be prevent soft dependent of the size of there increavel and subletel equipment should be prevent soft dependent on the vert of chemical and first-size of yee refrequent immediately and remove contact lense as son as practicable. Lons should be removed in the first sign of yee refrequency in the soft dependent on the step of the soft as a second to flag yea protection. The selection of sublete gloose does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact brank through time for substances has to be obtained from the manufacturer of the protective gloves and has to be obtained if and chacking in a data care. Cloves must only be worm on clean hands. After using gloves, hands should be washed and diret dorologity. Application of a non-performed missiones in a protection desor of the diret hands? Hands/feet protection - Command diret dorologity. Pay 24: A SNZS 216:1.1 or national equivalent). - When protection below - Contex material, - adstrip?	measures, such as guipment image and the second secon		generally decreases with the square of distance from the ext extraction point should be adjusted, accordingly, after referer extraction fan, for example, should be a minimum of 4-10 m/ distant from the extraction point. Other mechanical considera apparatus, make it essential that theoretical air velocities are	traction point (in simple cases). Therefore the air speed at the nce to distance from the contaminating source. The air velocity at the /s (800-2000 f/min) for extraction of crusher dusts generated 2 metres ations, producing performance deficits within the extraction		
 P Chemical goggles. (ASNZS 1337.1, EN166 or national equivalent) Contact lenses may pose a special hazard; actionated lenses may absomb and concentratic initiants. A written policy document, describing the wearing of lenses or restrictions on use, should be created of reach workplace or task. This should be indexed of reach workplace or task. This should be indexed and first-sid personnel should be trained in their removal and suitable equipment should be readely available. In the event of chemical exposure, begin eye ingianto immediately and remove contact them as soon as practicable. Lens should be removed at the first signs of eye rendeness or initiation - lens should be removed in the first signs of eye rendeness or initiation - lens should be removed in the first signs of eye rendeness or initiation - lens should be removed in the first signs of eye rendeness or initiation - lens should be removed in the first signs of eye rendeness or initiation - lens should be removed in the should be removed in a loss on the readity available. In the avent of protective of a clean environment only after workers have washed hands thorough time for substances have be checked prior to the application. The exact break through time for substances have be checked prior to the application. The exact break through time for substances have to be checked prior to the application. The exact break through time for substances have to be able on the application. Substances have available, and reind are substance do substance have available. The selection of gloves include: - frequency and dried throughly. Application of a non-perfured molecular have available. Substances have available and risk or application of contact. Hends/feet protection be application, gloves with a thickness by cally precterion class of 5 or higher (breakthrough time greater than 20 minutes accordi	 P. Chemical googles, IASN25 1337.1, EN165 or national equivalent] Contact liness may pose a special instant: soft contact liness may aborb and concentrate initiants. A written policy document, descriping the vessing of lenses or restrictions on use, should be created or seak. This is built use a review of lens absorption of the class of chemicals in use and an account of hijury specience. Medical and first-aid personnel should be trained in their removal and sublishe outpress that the restriction of a subsorption of use absorption or use, should be transmost in a class environment only after veska have washed hands thoroughly. (EDC NIOSH Current Intelligence Bulletin 59). Skin protection Skin protection of suitable goves does not only depend on the material, but also on further marks of quality which vary from the selection of suitable goves does not only depend on the material, but also on further marks of quality which vary from The selection of suitable goves does not only depend on the material outprate on substances, the resistance of the glove material can be aclaulated in advance and has therefore to be checked prior to the asplication. The exact break through time for substances has to be dotained from the manufacture or manetis of quality which vary from the second base to be the chemical is a program on give served break and base to be dotained from the manufacture or manetad. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves indust: The exact break through time for substance (e.g. Europe EN 374, US F739, AS/N25 2161.1 or national equivalent). When prolonged or frequently repeated context may court, a glove with a protection leaked is a durability of glove type is dependent on usage. Important factors in the selection of gloves indust: Contemicat as expecified, a glove with a protection class of 3 or higher	measures, such as personal protective				
Hands/feet protection Hands/feet protection <td< th=""><th> Hands/feet protection Add traiting of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advances and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hyginen is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hand should be washed and dred thoroughly. Application of a non-perfumed moisturiser is recommended. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: frequency and duration of contact, chemical resistance of glove material, glove thickness and desterify Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, ASN2S 2161.1 or national equivalent). When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, ASN2S 2161.1.0 ro national equivalent) is recommended. Some glove polymer types are less affected by movement and this should be taken into account when considering gloves to long-term use. Contaminated gloves should be replaced. As defined in ASTM F.739-99 in any application, gloves are rated as: Evallent when breakthrough time > 20 min Fair when breakthrough time > 20 min Fair when breakthrough time > 20 min Fair when breakthrough time > 20 min Foor when glove material degrades For</th><th>Eye and face protection</th><th> Chemical goggles. [AS/NZS 1337.1, EN166 or national e Contact lenses may pose a special hazard; soft contact l document, describing the wearing of lenses or restriction include a review of lens absorption and adsorption for the Medical and first-aid personnel should be trained in their event of chemical exposure, begin eye irrigation immedia be removed at the first signs of eye redness or irritation - </th><th>lenses may absorb and concentrate irritants. A written policy as on use, should be created for each workplace or task. This should e class of chemicals in use and an account of injury experience. removal and suitable equipment should be readily available. In the ately and remove contact lens as soon as practicable. Lens should - lens should be removed in a clean environment only after workers</th></td<>	 Hands/feet protection Add traiting of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advances and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hyginen is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hand should be washed and dred thoroughly. Application of a non-perfumed moisturiser is recommended. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: frequency and duration of contact, chemical resistance of glove material, glove thickness and desterify Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, ASN2S 2161.1 or national equivalent). When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, ASN2S 2161.1.0 ro national equivalent) is recommended. Some glove polymer types are less affected by movement and this should be taken into account when considering gloves to long-term use. Contaminated gloves should be replaced. As defined in ASTM F.739-99 in any application, gloves are rated as: Evallent when breakthrough time > 20 min Fair when breakthrough time > 20 min Fair when breakthrough time > 20 min Fair when breakthrough time > 20 min Foor when glove material degrades For	Eye and face protection	 Chemical goggles. [AS/NZS 1337.1, EN166 or national e Contact lenses may pose a special hazard; soft contact l document, describing the wearing of lenses or restriction include a review of lens absorption and adsorption for the Medical and first-aid personnel should be trained in their event of chemical exposure, begin eye irrigation immedia be removed at the first signs of eye redness or irritation - 	lenses may absorb and concentrate irritants. A written policy as on use, should be created for each workplace or task. This should e class of chemicals in use and an account of injury experience. removal and suitable equipment should be readily available. In the ately and remove contact lens as soon as practicable. Lens should - lens should be removed in a clean environment only after workers		
 Hands/feet protection Hands/feet protection Contaminated gloves should be replaced. As defined in ASTM F-739-96 in any application, gloves are rated as: Contaminated gloves should be replaced. Sond when breakthrough time > 20 min Good when breakthrough time > 20 min For when y depending on the diverse that as the dependent on usage an advector of glove since to a specific chemical, as the permeted of the system and y diverse that be application, gloves and a statistication, gloves and a statistication, gloves and a statistication, gloves are rated as: Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent). When protection advector ty repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.1.0 r national equivalent) is recommended. Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-ferm use. Contaminated gloves should be replaced. As defined in ASTM F-739-96 in any application, gloves are rated as: Sexeelent when breakthrough time > 20 min Fair when breakthrough time > 20 min Fair when breakthrough time > 20 min Fair when breakthrough time > 20 min For when glove material degrades For goven gloves matorial degrades For genenal applications, gloves w	 Handsfret protection Handsfret protection For when the advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal Nygiene is a key alement of effective hand care. Gloves must only be worn on clean hands. After using gloves, hand should be washed and dried thoroughly. Application of a non-perfumed moletuliner is recommended. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: frequency and duration of contact. chemical resistance of glove material, glove thickness and detertity Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent). When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 200 minutes according to EN 374, AS/NZS 2161.10 or national equivalent) is recommended. Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use. Contaminated gloves should be replaced. As defined in ASTM F-733-96 in any application, gloves are rated as: Excellent when breakthrough time > 20 min For when glove material degrades For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended. Ishould be emphasized that glove matherial glove material as appendic to thermical, as permeation efficiency of the glove with a protection advance may also vary depending on the exact composition of the glove material approver the glove thickness is not necessarily	Skin protection	See Hand protection below			
 Hands/feet protection As defined in ASTM F-739-96 in any application, gloves are rated as: Excellent when breakthrough time > 20 min For when breakthrough time > 20 min For when glove material degrades For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended. It should be emphasible that glove with a thickness typically greater than 0.35 mm, are recommended. It should be emphasible that glove with a thickness typically greater than 0.35 mm, are recommended. Fixed point and should be emphasible to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent). When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent). When only brief contact is expected, a glove with a protection class of 5 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent). Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use. Contaminated gloves should be replaced. As defined in ASTM F-739-96 in any application, gloves are rated as: Excellent when breakthrough time > 20 min Poor when glove material degrades For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended. It should be emphasible of that glove thickness is not necessarily a good predictor of glove material. Therefore, glove selection should also be based on consideration of the taks requirements and knowledge of breakthrough time. Glove thickness may also vary depending on the glove matriat and regl	 Hands/feet protection Hands/feet protection Good when breakthrough time > 400 min Good when breakthrough time > 20 min For general applications, gloves with a protection of glove restature to a specific chemical, so thickness in any dependent on the sead composition of a non-perfumed moisturiser is recommended. 		manufacturer to manufacturer. Where the chemical is a prep can not be calculated in advance and has therefore to be che	paration of several substances, the resistance of the glove material necked prior to the application.		
Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present.		Hands/feet protection	Personal hygiene is a key element of effective hand care. Gli should be washed and dried thoroughly. Application of a non Suitability and durability of glove type is dependent on usage - frequency and duration of contact, - chemical resistance of glove material, - glove thickness and - dexterity Select gloves tested to a relevant standard (e.g. Europe EN - When prolonged or frequently repeated contact may occur, greater than 240 minutes according to EN 374, AS/NZS 216 - When only brief contact is expected, a glove with a protecti according to EN 374, AS/NZS 2161.10.1 or national equivale - Some glove polymer types are less affected by movement a long-term use. - Contaminated gloves should be replaced. As defined in ASTM F-739-96 in any application, gloves are - Excellent when breakthrough time > 480 min - Good when breakthrough time > 20 min - Fair when breakthrough time > 20 min - Foor when glove material degrades For general applications, gloves with a thickness typically great It should be emphasised that glove thickness is not necessar permeation efficiency of the glove will be dependent on the effort should also be based on consideration of the task requireme Glove thickness may also vary depending on the glove manu- manufacturers technical data should always be taken into ac Note: Depending on the activity being conducted, gloves of w - Thinner gloves (down to 0.1 mm or less) may be required we gloves are only likely to give short duration protection and wo - Thicker gloves (up to 3 mm or more) may be required wher is abrasion or puncture potential Gloves must only be worn on clean hands. After using gloves non-perfumed moisturiser is recommended. Experience indicates that the following polymers are suitable where abrasive particles are not present.	 apperfumed moisturiser is recommended. Important factors in the selection of gloves include: 374, US F739, AS/NZS 2161.1 or national equivalent). a glove with a protection class of 5 or higher (breakthrough time 51.10.1 or national equivalent) is recommended. ion class of 3 or higher (breakthrough time greater than 60 minutes ent) is recommended. and this should be taken into account when considering gloves for rated as: reater than 0.35 mm, are recommended. trily a good predictor of glove resistance to a specific chemical, as the exact composition of the glove material. Therefore, glove selection ents and knowledge of breakthrough times. ufacturer, the glove type and the glove model. Therefore, the ccount to ensure selection of the most appropriate glove for the task. varying thickness may be required for specific tasks. For example: where a high degree of manual dexterity is needed. However, these ould normally be just for single use applications, then disposed of. re there is a mechanical (as well as a chemical) risk i.e. where there as, hands should be washed and dried thoroughly. Application of a 		

polyvinyl chloride.

	Gloves should be examined for wear and/ or degradation constantly.
Body protection	See Other protection below
Other protection	No special equipment needed when handling small quantities. OTHERWISE: • Overalls. • Barrier cream. • Eyewash unit.

Respiratory protection

Type -P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	P1 Air-line*		PAPR-P1 -
up to 50 x ES	Air-line**	P2	PAPR-P2
up to 100 x ES	-	P3	-
		Air-line*	-
100+ x ES	-	Air-line**	PAPR-P3

* - Negative pressure demand ** - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

· Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.

• The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).

• Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be advernment mandated or vendor recommended.

• Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.

• Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)

· Use approved positive flow mask if significant quantities of dust becomes airborne.

· Try to avoid creating dust conditions.

8.2.3. Environmental exposure controls

See section 12

SECTION 9 Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	White		
Physical state	Divided Solid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	256-258(dec.)	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available

6-(Chloromethyl)ura	acil
---------------------	------

Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Not Available	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available
Nanoform Solubility	Not Available	Nanoform Particle Characteristics	Not Available
Particle Size	Not Available		

9.2. Other information

Not Available

SECTION 10 Stability and reactivity

10.1.Reactivity	See section 7.2
10.2. Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
10.3. Possibility of hazardous reactions	See section 7.2
10.4. Conditions to avoid	See section 7.2
10.5. Incompatible materials	See section 7.2
10.6. Hazardous decomposition products	See section 5.3

SECTION 11 Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled. If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures.
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.
Eye	Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may cause transient discomfort characterised by tearing or conjunctival redness (as with windburn). Slight abrasive damage may also result.
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course. Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis, caused by particles less than 0.5 micron penetrating and remaining in the lung.

6-(Chloromethyl)uracil	TOXICITY Not Available	IRRITATION Not Available
Legend:	1. Value obtained from Europe ECHA Registered Substances - , Unless otherwise specified data extracted from RTECS - Registered	Acute toxicity 2. Value obtained from manufacturer's SDS.

Acute Toxicity	✓	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	*	STOT - Single Exposure	~

Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×
	Le	gend: 🗙 – Data either not ava	ailable or does not fill the criteria for classification

X – Data either not available or does not fill the criteria for classification
 - Data available to make classification

11.2 Information on other hazards

11.2.1. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

11.2.2. Other information

See Section 11.1

SECTION 12 Ecological information

12.1. Toxicity

6-(Chloromethyl)uracil	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

12.2. Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

12.3. Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

12.4. Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

12.5. Results of PBT and vPvB assessment

	Р	В	т
Relevant available data	Not Available	Not Available	Not Available
PBT	×	×	×
vPvB	×	×	×
PBT Criteria fulfilled?			No
vPvB			No

12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

12.7. Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

SECTION 13 Disposal considerations

13.1. Waste treatment methods

	Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate: Reduction
	▶ Reuse
	Recycling
	Disposal (if all else fails) This metanical may be required if unused, as if it has not been contaminated as as to make it unuslitable for its intended use. Shelf
Product / Packaging	This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use,
disposal	and recycling or reuse may not always be appropriate. In most instances the supplier of the material should be consulted.
	 DO NOT allow wash water from cleaning or process equipment to enter drains.
	It may be necessary to collect all wash water for treatment before disposal.
	In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
	Where in doubt contact the responsible authority.
	Recycle wherever possible or consult manufacturer for recycling options.
	Consult State Land Waste Management Authority for disposal.
	Bury residue in an authorised landfill.
	Recycle containers if possible, or dispose of in an authorised landfill.
Waste treatment options	Not Available
Sewage disposal options	Not Available

SECTION 14 Transport information

Labels Required

Marine Pollutant	
HAZCHEM	Not Applicable

Land transport (ADR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number or ID number	Not Applicable					
14.2. UN proper shipping name	Not Applicable	Not Applicable				
14.3. Transport hazard	Class	Not Applicab	le			
class(es)	Subsidiary risk	Subsidiary risk Not Applicable				
14.4. Packing group	Not Applicable					
14.5. Environmental hazard	Not Applicable					
	Hazard identifica	tion (Kemler)	Not Applicable			
	Classification code		Not Applicable			
14.6. Special precautions	Hazard Label		Not Applicable			
for user		IS	Not Applicable			
	Limited quantity		Not Applicable			
	Tunnel Restrictio	on Code	Not Applicable			

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable		
14.2. UN proper shipping name	Not Applicable		
14.3. Transport hazard class(es)	ICAO/IATA Class ICAO / IATA Subrisk ERG Code	Not Applicable Not Applicable	
14.4. Packing group	Not Applicable		

14.5. Environmental hazard	Not Applicable	
	Special provisions	Not Applicable
	Cargo Only Packing Instructions	Not Applicable
	Cargo Only Maximum Qty / Pack	Not Applicable
14.6. Special precautions for user	Passenger and Cargo Packing Instructions	Not Applicable
	Passenger and Cargo Maximum Qty / Pack	Not Applicable
	Passenger and Cargo Limited Quantity Packing Instructions	Not Applicable
	Passenger and Cargo Limited Maximum Qty / Pack	Not Applicable

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable		
14.2. UN proper shipping name	Not Applicable		
14.3. Transport hazard	IMDG Class N	lot Applicable	
class(es)	IMDG Subrisk N	lot Applicable	
14.4. Packing group	Not Applicable		
14.5. Environmental hazard	Not Applicable		
	EMS Number	Not Applicable	
14.6. Special precautions for user	Special provisions	Not Applicable	
	Limited Quantities	Not Applicable	

Inland waterways transport (ADN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable		
14.2. UN proper shipping name	Not Applicable		
14.3. Transport hazard class(es)	Not Applicable Not Applicable		
14.4. Packing group	Not Applicable		
14.5. Environmental hazard	Not Applicable		
14.6. Special precautions for user	Classification code	Not Applicable	
	Special provisions	Not Applicable	
	Limited quantity	Not Applicable	
	Equipment required	Not Applicable	
	Fire cones number	Not Applicable	

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group

14.7.3. Transport in bulk in accordance with the IGC Code

Product name Ship Type

SECTION 15 Regulatory information

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable - : Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2020/878; Regulation (EC) No 1272/2008 as updated through ATPs.

Information according to 2012/18/EU (Seveso III):

Seveso Category	E1
-----------------	----

15.2. Chemical safety assessment

For further information please look at the Chemical Safety Assessment and Exposure Scenarios prepared by your Supply Chain if available.

ECHA SUMMARY

Not Applicable

National Inventory Status

National Inventory	Status		
Australia - AIIC / Australia Non-Industrial Use	Not Available		
Canada - DSL	Not Available		
Canada - NDSL	Not Available		
China - IECSC	Not Available		
Europe - EINEC / ELINCS / NLP	Not Available		
Japan - ENCS	Not Available		
Korea - KECI	Not Available		
New Zealand - NZIoC	Not Available		
Philippines - PICCS	Not Available		
USA - TSCA	Not Available		
Taiwan - TCSI	Not Available		
Mexico - INSQ	Not Available		
Vietnam - NCI	Not Available		
Russia - FBEPH	Not Available		
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.		

SECTION 16 Other information

Revision Date	16/09/2022
Initial Date	16/09/2022

Full text Risk and Hazard codes

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

- EN 166 Personal eye-protection
- EN 340 Protective clothing
- EN 374 Protective gloves against chemicals and micro-organisms
- EN 13832 Footwear protecting against chemicals
- EN 133 Respiratory protective devices

Definitions and abbreviations

- PC TWA: Permissible Concentration-Time Weighted Average
- PC STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit. IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value **BCF: BioConcentration Factors BEI: Biological Exposure Index** AIIC: Australian Inventory of Industrial Chemicals **DSL:** Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances Powered by AuthorITe, from Chemwatch.