

# 2-(Piperidin-1-yl)benzylamine Apollo Scientific

Part Number: **OR23329** Version No: **1.1** 

Safety Data Sheet (Conforms to Annex II of REACH (1907/2006) - Regulation 2020/878)

Chemwatch Hazard Alert Code: 3

Issue Date: **16/05/2022**Print Date: **02/08/2023**S.REACH.GBR.EN

# SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### 1.1. Product Identifier

Product name	-(Piperidin-1-yl)benzylamine		
Chemical Name	Piperidinophenyl)Methylamine		
Synonyms	Not Available		
Proper shipping name	AMINES, SOLID, CORROSIVE, N.O.S. or POLYAMINES, SOLID, CORROSIVE, N.O.S.		
Chemical formula	Not Available		
Other means of identification	Not Available		
CAS number	72752-54-6*		

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Not Available
Uses advised against	No specific uses advised against are identified.

# 1.3. Details of the manufacturer or supplier of the safety data sheet

Registered company name	Apollo Scientific	
Address	hitefield Road, Bredbury SK62QR United Kingdom	
Telephone	14060505	
Fax	161 406 0506	
Website	http://www.apolloscientific.co.uk/	
Email	sales@apolloscientific.co.uk	

# 1.4. Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	Not Available
Other emergency telephone numbers	Not Available

# **SECTION 2 Hazards identification**

# 2.1. Classification of the substance or mixture

Classification according to
regulation (EC) No
1272/2008 [CLP] and
amendments [1]

H314 - Skin Corrosion/Irritation Category 1B, H290 - Corrosive to Metals Category 1, H318 - Serious Eye Damage/Eye Irritation Category 1

Version No: 1.1

#### 2-(Piperidin-1-yl)benzylamine

Issue Date: **16/05/2022**Print Date: **02/08/2023** 

Legend:

1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

### 2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

# Hazard statement(s)

H314	Causes severe skin burns and eye damage.	
H290	May be corrosive to metals.	

# Supplementary statement(s)

Not Applicable

# Precautionary statement(s) Prevention

P260	Do not breathe dust/fume.	
P264	/ash all exposed external body areas thoroughly after handling.	
P280	P280 Wear protective gloves, protective clothing, eye protection and face protection.	
P234	Keep only in original packaging.	

# Precautionary statement(s) Response

P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.		
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].		
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
P310	Immediately call a POISON CENTER/doctor/physician/first aider.		
P363	Wash contaminated clothing before reuse.		
P390	Absorb spillage to prevent material damage.		
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.		

# Precautionary statement(s) Storage

P405 Store locked up.

# Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

# 2.3. Other hazards

REACH - Art.57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS print date.

# **SECTION 3 Composition / information on ingredients**

#### 3.1.Substances

1. CAS No 2.EC No 3.Index No 4.REACH No	%[weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	SCL / M-Factor	Nanoform Particle Characteristics
Not Available	100	2-(Piperidin- 1-yl)benzylamine	Not Applicable	Not Applicable	Not Available

Legend:

1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L; \* EU IOELVs available; [e] Substance identified as having endocrine disrupting properties

# 3.2.Mixtures

Part Number: **OR23329** Page **3** of **14** 

Version No: 1.1 2-(Piperidin-1-yl)benzylamine Print Date: 02/08/2023

See 'Information on ingredients' in section 3.1

#### **SECTION 4 First aid measures**

### 4.1. Description of first aid measures

Eye Contact	If this product comes in contact with the eyes:  Immediately hold eyelids apart and flush the eye continuously with running water.  Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.  Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.  Transport to hospital or doctor without delay.  Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs:  Immediately flush body and clothes with large amounts of water, using safety shower if available.  Quickly remove all contaminated clothing, including footwear.  Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.  Transport to hospital, or doctor.
Inhalation	<ul> <li>If fumes or combustion products are inhaled remove from contaminated area.</li> <li>Lay patient down. Keep warm and rested.</li> <li>Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>Transport to hospital, or doctor, without delay.</li> <li>Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema.</li> <li>Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs).</li> <li>As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested.</li> <li>Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered.</li> <li>This must definitely be left to a doctor or person authorised by him/her.</li> <li>(ICSC13719)</li> </ul>
Ingestion	<ul> <li>For advice, contact a Poisons Information Centre or a doctor at once.</li> <li>Urgent hospital treatment is likely to be needed.</li> <li>If swallowed do NOT induce vomiting.</li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>Observe the patient carefully.</li> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>Transport to hospital or doctor without delay.</li> </ul>

# 4.2 Most important symptoms and effects, both acute and delayed

See Section 11

#### 4.3. Indication of any immediate medical attention and special treatment needed

For acute or short-term repeated exposures to highly alkaline materials:

- ▶ Respiratory stress is uncommon but present occasionally because of soft tissue edema.
- ▶ Unless endotracheal intubation can be accomplished under direct vision, cricothyroidotomy or tracheotomy may be necessary.
- Oxygen is given as indicated.
- ▶ The presence of shock suggests perforation and mandates an intravenous line and fluid administration.
- Damage due to alkaline corrosives occurs by liquefaction necrosis whereby the saponification of fats and solubilisation of proteins allow deep penetration into the tissue.

Alkalis continue to cause damage after exposure.

# INGESTION:

Milk and water are the preferred diluents

No more than 2 glasses of water should be given to an adult.

- Neutralising agents should never be given since exothermic heat reaction may compound injury.
- \* Catharsis and emesis are absolutely contra-indicated.
- \* Activated charcoal does not absorb alkali.
- \* Gastric lavage should not be used.

Supportive care involves the following:

- Withhold oral feedings initially.
- If endoscopy confirms transmucosal injury start steroids only within the first 48 hours.
- ▶ Carefully evaluate the amount of tissue necrosis before assessing the need for surgical intervention.
- Patients should be instructed to seek medical attention whenever they develop difficulty in swallowing (dysphagia).

SKIN AND EYE:

Issue Date: 16/05/2022

Part Number: OR23329 Page 4 of 14

#### 2-(Piperidin-1-yl)benzylamine

Issue Date: **16/05/2022**Print Date: **02/08/2023** 

Injury should be irrigated for 20-30 minutes.

Eye injuries require saline. [Ellenhorn & Barceloux: Medical Toxicology]

#### **SECTION 5 Firefighting measures**

#### 5.1. Extinguishing media

Version No: 1.1

- ▶ There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

#### 5.2. Special hazards arising from the substrate or mixture

Fire Incompatibility

None known.

# 5.3. Advice for firefighters

Fire	Fighting	•

Fire Fighting

- Non combustible.
- Fire/Explosion Hazard

▶ Not considered a significant fire risk, however containers may burn.

May emit corrosive fumes.

#### **SECTION 6 Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

See section 8

#### 6.2. Environmental precautions

See section 12

#### 6.3. Methods and material for containment and cleaning up

<ul> <li>Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before disposal of material.</li> <li>Check regularly for spills and leaks.</li> <li>Remove all ignition sources.</li> <li>Clean up all spills immediately.</li> <li>Avoid contact with skin and eyes.</li> <li>Control personal contact with the substance, by using protective equipment.</li> <li>Use dry clean up procedures and avoid generating dust.</li> <li>Place in a suitable, labelled container for waste disposal.</li> </ul>	discharge or
---	--------------

Major Spills

# 6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# **SECTION 7 Handling and storage**

# 7.1. Precautions for safe handling

Safe handling

Avoid all personal contact, including inhalation.

▶ Wear protective clothing when risk of exposure occurs.

Use in a well-ventilated area.

Avoid contact with moisture.

Avoid contact with incompatible materials.

► When handling, **DO NOT** eat, drink or smoke.

▶ Keep containers securely sealed when not in use.

Avoid physical damage to containers.

Always wash hands with soap and water after handling.

▶ Work clothes should be laundered separately. Launder contaminated clothing before re-use.

Use good occupational work practice.

Observe manufacturer's storage and handling recommendations contained within this SDS.

Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

Fire and explosion protection

See section 5

 Part Number: OR23329
 Page 5 of 14
 Issue Date: 16/05/2022

 Version No: 1.1
 2 (Biopolisis 4 vi) hoperators in a print Date: 02/08/2023
 Print Date: 02/08/2023

# 2-(Piperidin-1-yl)benzylamine

2 (i ipolium i yi)bolizyiummo

Store in original containers.

- Keep containers securely sealed.
- ▶ Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storage and handling recommendations contained within this SDS.
- DO NOT store near acids, or oxidising agents
- ▶ No smoking, naked lights, heat or ignition sources.

#### 7.2. Conditions for safe storage, including any incompatibilities

Other information

- ▶ Lined metal can, lined metal pail/ can.
- Plastic pail.
- Polyliner drum.
- Packing as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

For low viscosity materials

- Drums and jerricans must be of the non-removable head type.
- Where a can is to be used as an inner package, the can must have a screwed enclosure.

Suitable container For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.):

Removable head packaging:

- Cans with friction closures and
- low pressure tubes and cartridges

may be used.

-

Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient inert cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.

Avoid strong acids, acid chlorides, acid anhydrides and chloroformates.

Amines are incompatible with:

- · isocyanates, halogenated organics, peroxides, phenols (acidic), epoxides, anhydrides, and acid halides.
- · strong reducing agents such as hydrides, due to the liberation of flammable gas.

Amines possess a characteristic ammonia smell, liquid amines have a distinctive "fishy" smell. Amines are formally derivatives of ammonia, wherein one or more hydrogen atoms have been replaced by a substituent such as an alkyl or aryl group. Compounds with a nitrogen atom attached to a carbonyl group, thus having the structure R–CO–NR'R?, are called amides and have different chemical properties from amines.

The water solubility of simple amines is enhanced by hydrogen bonding involving these lone electron pairs. Typically salts of ammonium compounds exhibit the following order of solubility in water: primary ammonium (RNH+3) > secondary ammonium (R2NH+2) > tertiary ammonium (R3NH+). Small aliphatic amines display significant solubility in many solvents, whereas those with large substituents are lipophilic. Aromatic amines, such as aniline, have their lone pair electrons conjugated into the benzene ring, thus their tendency to engage in hydrogen bonding is diminished. Their boiling points are high and their solubility in water is low.

Storage incompatibility

Like ammonia, amines are bases. Compared to alkali metal hydroxides, amines are weaker.

- · The basicity of amines depends on:
- · The electronic properties of the substituents (alkyl groups enhance the basicity, aryl groups diminish it).

The degree of solvation of the protonated amine, which includes steric hindrance by the groups on nitrogen.

Owing to inductive effects, the basicity of an amine might be expected to increase with the number of alkyl groups on the amine. Correlations are complicated owing to the effects of solvation which are opposite the trends for inductive effects. Solvation effects also dominate the basicity of aromatic amines.

Solvation significantly affects the basicity of amines. N-H groups strongly interact with water, especially in ammonium ions. Consequently, the basicity of ammonia is enhanced by 10 exp 11 by solvation.

Tertiary amines are more basic than secondary amines, which are more basic than primary amines, and finally ammonia is least basic. The order of pKb's (basicities in water) does not follow this order. Similarly aniline is more basic than ammonia in the gas phase, but ten thousand times less so in aqueous solution.

In aprotic polar solvents such as DMSO, DMF, and acetonitrile the energy of solvation is not as high as in protic polar solvents like water and methanol. For this reason, the basicity of amines in these aprotic solvents is almost solely governed by the electronic effect

- ▶ Air Sensitive
- Store under argon

Hazard categories in accordance with Regulation (EC) No 1272/2008

Not Available

Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of

Not Available

# 7.3. Specific end use(s)

Issue Date: **16/05/2022**Print Date: **02/08/2023** 

See section 1.2

Version No: 1.1

#### **SECTION 8 Exposure controls / personal protection**

# 8.1. Control parameters

Ingredient	DNELs Exposure Pattern Worker	PNECs Compartment	
Not Available	Not Available	Not Available	

<sup>\*</sup> Values for General Population

#### Occupational Exposure Limits (OEL)

#### **INGREDIENT DATA**

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Not Available						

#### Not Applicable

#### **Emergency Limits**

Ingredient	TEEL-1	TEEL-2	TEEL-3
2-(Piperidin- 1-yl)benzylamine	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
2-(Piperidin- 1-yl)benzylamine	Not Available	Not Available

#### 8.2. Exposure controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations.

Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

# 8.2.1. Appropriate engineering controls

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Part Number: OR23329 Page 7 of 14 Version No: 1.1

Issue Date: 16/05/2022 Print Date: 02/08/2023 2-(Piperidin-1-yl)benzylamine

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used

#### 8.2.2. Individual protection measures, such as personal protective equipment

Eye and face protection













- ► Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]
- Full face shield may be required for supplementary but never for primary protection of eyes.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

# Skin protection

#### See Hand protection below

- Wear chemical protective gloves, e.g. PVC.
- ▶ Wear safety footwear or safety gumboots, e.g. Rubber

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

- · frequency and duration of contact,
- · chemical resistance of glove material,
- · glove thickness and
- dexterity

long-term use.

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).

- · When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- · When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes
- according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. · Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for

# Hands/feet protection

- · Contaminated gloves should be replaced.
- As defined in ASTM F-739-96 in any application, gloves are rated as: · Excellent when breakthrough time > 480 min
- · Good when breakthrough time > 20 min
- · Fair when breakthrough time < 20 min
- · Poor when glove material degrades

For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task. Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- · Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
- · Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

# **Body protection**

# See Other protection below

# Other protection

- Overalls. PVC Apron.
- ▶ PVC protective suit may be required if exposure severe.
- Eyewash unit.
- ▶ Ensure there is ready access to a safety shower.

Version No: 1.1

# 2-(Piperidin-1-yl)benzylamine

Issue Date: **16/05/2022**Print Date: **02/08/2023** 

Type -P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	P1 Air-line*	-	PAPR-P1
up to 50 x ES	Air-line**	P2	PAPR-P2
up to 100 x ES	-	P3	-
		Air-line*	-
100+ x ES	-	Air-line**	PAPR-P3

#### \* - Negative pressure demand \*\* - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 deaC)

- · Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- · Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.
- · Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
- · Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)
- · Use approved positive flow mask if significant quantities of dust becomes airborne.
- · Try to avoid creating dust conditions.

#### 8.2.3. Environmental exposure controls

See section 12

# SECTION 9 Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Solid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Not Available	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available
Nanoform Solubility	Not Available	Nanoform Particle Characteristics	Not Available
Particle Size	Not Available		

Issue Date: **16/05/2022** Print Date: **02/08/2023** 

#### 9.2. Other information

Not Available

# **SECTION 10 Stability and reactivity**

10.1.Reactivity	See section 7.2
10.2. Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
10.3. Possibility of hazardous reactions	See section 7.2
10.4. Conditions to avoid	See section 7.2
10.5. Incompatible materials	See section 7.2
10.6. Hazardous decomposition products	See section 5.3

# **SECTION 11 Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Information on toxicological effects

	. ,	S .			
Inhaled	The material can cause respiratory irritation in some persons. The damage.  Inhalation of amine vapours may cause irritation of the mucous respiratory distress and cough. Swelling and inflammation of the nausea, faintness and anxiety.  Persons with impaired respiratory function, airway diseases and further disability if excessive concentrations of particulate are in If prior damage to the circulatory or nervous systems has occurre should be conducted on individuals who may be exposed to furthexposures.	membrane of the nose and throat, and lung irritation with respiratory tract is seen in serious cases; with headache, conditions such as emphysema or chronic bronchitis, may incunated.  ed or if kidney damage has been sustained, proper screenings			
Ingestion	Amines without benzene rings when swallowed are absorbed the throughout the gastrointestinal tract.	The material can produce chemical burns within the oral cavity and gastrointestinal tract following ingestion.  Amines without benzene rings when swallowed are absorbed throughout the gut. Corrosive action may cause damage throughout the gastrointestinal tract.  The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because			
Skin Contact	The material can produce chemical burns following direct contact Skin contact is not thought to have harmful health effects (as cla health damage following entry through wounds, lesions or abras Volatile amine vapours produce irritation and inflammation of the Open cuts, abraded or irritated skin should not be exposed to the Entry into the blood-stream, through, for example, cuts, abrasior Examine the skin prior to the use of the material and ensure that	ssified under EC Directives); the material may still produce ions.  s skin. Direct contact can cause burns. is material is or lesions, may produce systemic injury with harmful effects.			
Eye	The material can produce chemical burns to the eye following direct contact. Vapours or mists may be extremely irritating.  If applied to the eyes, this material causes severe eye damage.				
Chronic	Repeated or prolonged exposure to corrosives may result in the mouth and necrosis (rarely) of the jaw. Bronchial irritation, with c Long-term exposure to respiratory irritants may result in airways problems.  Substance accumulation, in the human body, may occur and ma occupational exposure.	ough, and frequent attacks of bronchial pneumonia may ensue disease, involving difficulty breathing and related whole-body			
2-(Piperidin-	TOXICITY	IRRITATION			
1-yl)benzylamine	Not Available	Not Available			

2-(Piperidin-1-yl)benzylamine Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without

Version No: 1.1

#### 2-(Piperidin-1-yl)benzylamine

Issue Date: **16/05/2022**Print Date: **02/08/2023** 

eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	<b>~</b>	Reproductivity	×
Serious Eye Damage/Irritation	<b>✓</b>	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

**Legend: X** − Data either not available or does not fill the criteria for classification

✓ – Data available to make classification

#### 11.2 Information on other hazards

# 11.2.1. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

#### 11.2.2. Other information

See Section 11.1

# **SECTION 12 Ecological information**

#### 12.1. Toxicity

2-(Piperidin- 1-yl)benzylamine	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	4. US EPA, E	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 8. Vendor Data			

Prevent, by any means available, spillage from entering drains or water courses.

DO NOT discharge into sewer or waterways.

# 12.2. Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

# 12.3. Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

# 12.4. Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

## 12.5. Results of PBT and vPvB assessment

	Р	В	Т
Relevant available data	Not Available	Not Available	Not Available
PBT	×	×	×
vPvB	×	X	×
PBT Criteria fulfilled?			No
vPvB			No

Issue Date: **16/05/2022**Print Date: **02/08/2023** 

# 12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

#### 12.7. Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

# **SECTION 13 Disposal considerations**

# 13.1. Waste treatment methods

Product / Packaging disposal	<ul> <li>Recycle wherever possible.</li> <li>Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</li> <li>Treat and neutralise at an approved treatment plant.</li> <li>Treatment should involve: Mixing or slurrying in water; Neutralisation with suitable dilute acid followed by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).</li> <li>Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.</li> </ul>
Waste treatment options	Not Available
Sewage disposal options	Not Available

# **SECTION 14 Transport information**

# **Labels Required**

	8
Marine Pollutant	NO
HAZCHEM	2X

# Land transport (ADR-RID)

	transport (ABIT IND	,			
	UN number or ID number	3259			
	UN proper shipping name	AMINES, SOLID, (	CORROSIVE, N	N.O.S. or	POLYAMINES, SOLID, CORROSIVE, N.O.S.
	Transport hazard class(es)	Class Subsidiary risk	8 Not Applicab	le	
14.4.	Packing group	III	ı		
	Environmental hazard	Not Applicable			
		Hazard identifica	ation (Kemler)	80	
		Classification co	de	C8	
14.6.	Special precautions	Hazard Label		8	
	for user	Special provision	ns	274	
		Limited quantity		5 kg	
		Tunnel Restriction	on Code	3 (E)	

# Air transport (ICAO-IATA / DGR)

• •	•
14.1. UN number	3259
14.2. UN proper shipping name	Amines, solid, corrosive, n.o.s. *; Polyamines, solid, corrosive, n.o.s. *
14.3. Transport hazard class(es)	ICAO/IATA Class 8 ICAO / IATA Subrisk Not Applicable

Part Number: **OR23329** Page **12** of **14** 

Version No: 1.1 2-(Pineridin-1-vl)

Page 12 of 14 Issue Date: 16/05/2022
2-(Piperidin-1-yl)benzylamine Print Date: 02/08/2023

	ERG Code 8L	
14.4. Packing group	III	
14.5. Environmental hazard	Not Applicable	
	Special provisions	A3 A803
	Cargo Only Packing Instructions	864
	Cargo Only Maximum Qty / Pack	100 kg
14.6. Special precautions for user	Passenger and Cargo Packing Instructions	860
ioi usei	Passenger and Cargo Maximum Qty / Pack	25 kg
	Passenger and Cargo Limited Quantity Packing Instructions	Y845
	Passenger and Cargo Limited Maximum Qty / Pack	5 kg

# Sea transport (IMDG-Code / GGVSee)

14.1. UN number	3259	
14.2. UN proper shipping name	AMINES, SOLID, CO	RROSIVE, N.O.S. or POLYAMINES, SOLID, CORROSIVE, N.O.S.
14.3. Transport hazard	IMDG Class 8	
class(es)	IMDG Subrisk N	lot Applicable
14.4. Packing group	Ш	
14.5. Environmental hazard	Not Applicable	
	EMS Number	F-A, S-B
14.6. Special precautions for user	Special provisions	223 274
ioi usei	Limited Quantities	5 kg

#### Inland waterways transport (ADN)

14.1. UN number	3259	
14.2. UN proper shipping name	AMINES, SOLID, CORR	ROSIVE, N.O.S.; POLYAMINES, SOLID, CORROSIVE, N.O.S.
14.3. Transport hazard class(es)	8 Not Applicable	
14.4. Packing group	III	
14.5. Environmental hazard	Not Applicable	
	Classification code	C8
	Special provisions	274
14.6. Special precautions for user	Limited quantity	5 kg
101 4001	Equipment required	PP, EP
	Fire cones number	0

# 14.7. Maritime transport in bulk according to IMO instruments

# 14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

# 14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
i ioduct name	Oroup

# 14.7.3. Transport in bulk in accordance with the IGC Code

Part Number: OR23329 Page **13** of **14** Issue Date: 16/05/2022 Version No: 1.1 Print Date: 02/08/2023

#### **SECTION 15 Regulatory information**

# 15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable -: Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2020/878; Regulation (EC) No 1272/2008 as updated through ATPs.

#### Information according to 2012/18/EU (Seveso III):

**Seveso Category** 

Not Available

#### 15.2. Chemical safety assessment

For further information please look at the Chemical Safety Assessment and Exposure Scenarios prepared by your Supply Chain if available.

#### **ECHA SUMMARY**

Not Applicable

#### **National Inventory Status**

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Not Available
Canada - DSL	Not Available
Canada - NDSL	Not Available
China - IECSC	Not Available
Europe - EINEC / ELINCS / NLP	Not Available
Japan - ENCS	Not Available
Korea - KECI	Not Available
New Zealand - NZIoC	Not Available
Philippines - PICCS	Not Available
USA - TSCA	Not Available
Taiwan - TCSI	Not Available
Mexico - INSQ	Not Available
Vietnam - NCI	Not Available
Russia - FBEPH	Not Available
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

#### **SECTION 16 Other information**

Revision Date	16/05/2022
Initial Date	16/05/2022

#### Full text Risk and Hazard codes

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

Part Number: OR23329 Page **14** of **14** Issue Date: 16/05/2022 Version No: 1.1 Print Date: 02/08/2023

#### 2-(Piperidin-1-yl)benzylamine

**Definitions and abbreviations** 

PC - TWA: Permissible Concentration-Time Weighted Average

PC - STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit,

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

**DSL: Domestic Substances List** NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.