

# 2-Methylbutyl isothiocyanate Apollo Scientific

Part Number: **OR30206** Version No: **1.1** 

Safety Data Sheet (Conforms to Annex II of REACH (1907/2006) - Regulation 2020/878)

Chemwatch Hazard Alert Code: 3

Issue Date: 16/05/2022 Print Date: 02/08/2023 S.REACH.GBR.EN

# SECTION 1 Identification of the substance / mixture and of the company / undertaking

### 1.1. Product Identifier

| Product name                  | 2-Methylbutyl isothiocyanate             |
|-------------------------------|--|
| Chemical Name                 | 2-Methyl-1-butyl isothiocyanate          |
| Synonyms                      | Not Available                            |
| Proper shipping name          | TOXIC LIQUID, CORROSIVE, ORGANIC, N.O.S. |
| Chemical formula              | Not Available                            |
| Other means of identification | Not Available                            |
| CAS number                    | 4404-51-7*                               |

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

| Relevant identified uses | Not Available                                    |
|--------------------------|--|
| Uses advised against     | No specific uses advised against are identified. |

# 1.3. Details of the manufacturer or supplier of the safety data sheet

| Registered company name | Apollo Scientific                               |
|-------------------------|---|
| Address                 | Whitefield Road, Bredbury SK62QR United Kingdom |
| Telephone               | 01614060505                                     |
| Fax                     | 0161 406 0506                                   |
| Website                 | http://www.apolloscientific.co.uk/              |
| Email                   | sales@apolloscientific.co.uk                    |

# 1.4. Emergency telephone number

| Association / Organisation        | Not Available |
|-----------------------------------|---------------|
| Emergency telephone numbers       | Not Available |
| Other emergency telephone numbers | Not Available |

### **SECTION 2 Hazards identification**

# 2.1. Classification of the substance or mixture

| Classification according to |  |  |
|-----------------------------|--|--|
| regulation (EC) No          |  |  |
| 1272/2008 [CLP] and         |  |  |
| amendments [1]              |  |  |

H311 - Acute Toxicity (Dermal) Category 3, H314 - Skin Corrosion/Irritation Category 1B, H318 - Serious Eye Damage/Eye Irritation Category 1, H331 - Acute Toxicity (Inhalation) Category 3, H301 - Acute Toxicity (Oral) Category 3

Page 2 of 13

# 2-Methylbutyl isothiocyanate

Issue Date: **16/05/2022**Print Date: **02/08/2023** 

Legend:

1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

# 2.2. Label elements

Version No: 1.1

Hazard pictogram(s)





Signal word

Danger

# Hazard statement(s)

| H311 | Toxic in contact with skin.              |
|------|--|
| H314 | Causes severe skin burns and eye damage. |
| H331 | Toxic if inhaled.                        |
| H301 | Toxic if swallowed.                      |

# Supplementary statement(s)

Not Applicable

# Precautionary statement(s) Prevention

| P260 | Do not breathe mist/vapours/spray.   |
|------|--|
| P264 | Wash all exposed external body areas thoroughly after handling.                  |
| P270 | Do not eat, drink or smoke when using this product.                              |
| P271 | Use only outdoors or in a well-ventilated area.                                  |
| P280 | Wear protective gloves, protective clothing, eye protection and face protection. |

# Precautionary statement(s) Response

| P301+P310      | IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider.   |
|----------------|--|
| P301+P330+P331 | IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.   |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].                         |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P302+P352      | IF ON SKIN: Wash with plenty of water.   |
| P363           | Wash contaminated clothing before reuse.   |
| P304+P340      | IF INHALED: Remove person to fresh air and keep comfortable for breathing.   |
| P361+P364      | Take off immediately all contaminated clothing and wash it before reuse.   |

# Precautionary statement(s) Storage

| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. |
|-----------|--|
| P405      | Store locked up.   |

# Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

### 2.3. Other hazards

Inhalation and/or ingestion may produce serious health damage\*.

REACH - Art.57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS print date.

# **SECTION 3 Composition / information on ingredients**

### 3.1.Substances

| 1. CAS No 2.EC No %[weight] 3.Index No | Name | Classification according to regulation (EC) No 1272/2008 [CLP] and amendments | SCL /<br>M-Factor | Nanoform Particle<br>Characteristics |
|--|------|---|-------------------|--------------------------------------|
|--|------|---|-------------------|--------------------------------------|

 Part Number: OR30206
 Page 3 of 13
 Issue Date: 16/05/2022

 Version No: 1.1
 Print Date: 02/08/2023

### 2-Methylbutyl isothiocyanate

| 4.REACH No    |     |                              |                |                   |               |
|---------------|-----|------------------------------|----------------|-------------------|---------------|
| Not Available | 100 | 2-Methylbutyl isothiocyanate | Not Applicable | Not<br>Applicable | Not Available |

Legend:

1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L; \* EU IOELVs available; [e] Substance identified as having endocrine disrupting properties

### 3.2.Mixtures

See 'Information on ingredients' in section 3.1

### **SECTION 4 First aid measures**

### 4.1. Description of first aid measures If this product comes in contact with the eves: Immediately hold eyelids apart and flush the eye continuously with running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally **Eve Contact** lifting the upper and lower lids. ▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. If skin or hair contact occurs: Immediately flush body and clothes with large amounts of water, using safety shower if available. Skin Contact Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. ▶ Transport to hospital, or doctor. If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▶ Transport to hospital, or doctor, without delay. Inhalation Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema. Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs). As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (vet) manifested. ▶ Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered. This must definitely be left to a doctor or person authorised by him/her. (ICSC13719) For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and Ingestion prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.

# 4.2 Most important symptoms and effects, both acute and delayed

See Section 11

### 4.3. Indication of any immediate medical attention and special treatment needed

Transport to hospital or doctor without delay.

As in all cases of suspected poisoning, follow the ABCDEs of emergency medicine (airway, breathing, circulation, disability, exposure), then the ABCDEs of toxicology (antidotes, basics, change absorption, change distribution, change elimination).

Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.

For poisons (where specific treatment regime is absent):

### BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 L/min.
- Monitor and treat, where necessary, for pulmonary oedema.
- Monitor and treat, where necessary, for shock.
- Anticipate seizures.
- ▶ DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to

Part Number: **OR30206** Page **4** of **13** 

### 2-Methylbutyl isothiocyanate

Issue Date: **16/05/2022**Print Date: **02/08/2023** 

swallow, has a strong gag reflex and does not drool.

-----

#### ADVANCED TREATMENT

Version No: 1.1

Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.

- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- ► Treat seizures with diazepam.
- ▶ Proparacaine hydrochloride should be used to assist eye irrigation.

BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

Depending on the degree of exposure, periodic medical examination is indicated. The symptoms of lung oedema often do not manifest until a few hours have passed and they are aggravated by physical effort. Rest and medical observation is therefore essential. Immediate administration of an appropriate spray, by a doctor or a person authorised by him/her should be considered.

(ICSC24419/24421

### **SECTION 5 Firefighting measures**

### 5.1. Extinguishing media

- ▶ Foam
- ► Dry chemical powder.
- ▶ BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog Large fires only.

### 5.2. Special hazards arising from the substrate or mixture

Fire Incompatibility

 Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

### 5.3. Advice for firefighters

# Wear breathing apparatus plus prPrevent, by any means available,

- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves in the event of a fire.
- ▶ Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
- ▶ DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

# F (

Fire Fighting

- Combustible.
- Slight fire hazard when exposed to heat or flame.
- ▶ Heating may cause expansion or decomposition leading to violent rupture of containers.
- ▶ On combustion, may emit toxic fumes of carbon monoxide (CO).
- May emit acrid smoke.
- ▶ Mists containing combustible materials may be explosive.

Fire/Explosion Hazard Combustion products include:

carbon dioxide (CO2)

other pyrolysis products typical of burning organic material.

# **SECTION 6 Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

May emit poisonous fumes.

See section 8

# 6.2. Environmental precautions

See section 12

# 6.3. Methods and material for containment and cleaning up

Minor Spills

▶ Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or

Part Number: OR30206 Page 5 of 13 Issue Date: 16/05/2022 Version No: 1.1 Print Date: 02/08/2023

### 2-Methylbutyl isothiocyanate

disposal of material. Check regularly for spills and leaks. ► Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. • Control personal contact with the substance, by using protective equipment. ▶ Contain and absorb spill with sand, earth, inert material or vermiculite. ▶ Place in a suitable, labelled container for waste disposal. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. ▶ May be violently or explosively reactive. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. ► Consider evacuation (or protect in place). ▶ No smoking, naked lights or ignition sources. ► Increase ventilation. **Major Spills** Stop leak if safe to do so. Water spray or fog may be used to disperse vapour. Contain or absorb spill with sand, earth or vermiculite. Use only spark-free shovels and explosion proof equipment. Collect recoverable product into labelled containers for recycling. ▶ Collect solid residues and seal in labelled drums for disposal. Wash area and prevent runoff into drains. After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using. If contamination of drains or waterways occurs, advise emergency services.

#### 6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

### **SECTION 7 Handling and storage**

### 7.1. Precautions for safe handling

Safe handling

- Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. ▶ Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- ▶ DO NOT enter confined spaces until atmosphere has been checked
- ► DO NOT allow material to contact humans, exposed food or food utensils.
- Avoid contact with incompatible materials.
- ► When handling, **DO NOT** eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- ▶ Work clothes should be laundered separately. Launder contaminated clothing before re-use.
- Use good occupational work practice.
- Observe manufacturer's storage and handling recommendations contained within this SDS.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

### Fire and explosion protection

See section 5

# Other information

Suitable container

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

# 7.2. Conditions for safe storage, including any incompatibilities

- Lined metal can, lined metal pail/ can.
- Plastic pail.
- Polyliner drum.
- - Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.

- For low viscosity materials
- Drums and jerricans must be of the non-removable head type.
- ▶ Where a can is to be used as an inner package, the can must have a screwed enclosure.

Version No: 1.1

### 2-Methylbutyl isothiocyanate

Issue Date: 16/05/2022 Print Date: 02/08/2023

For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.): ► Removable head packaging;

- ► Cans with friction closures and
- low pressure tubes and cartridges

may be used.

Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages \*.

In addition, where inner packagings are glass and contain liquids of packing group I and II there must be sufficient inert absorbent to absorb any spillage \*.

\* unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.

All inner and sole packagings for substances that have been assigned to Packaging Groups I or II on the basis of inhalation toxicity criteria, must be hermetically sealed.

### Storage incompatibility

- ► Avoid reaction with oxidising agents
- Lachrymatory
- ▶ Moisture sensitive
- ► Store under argon

# Hazard categories in accordance with Regulation (EC) No 1272/2008

H2: Acute Toxic

**Qualifying quantity** (tonnes) of dangerous substances as referred to in Article 3(10) for the application of

H2 Lower- / Upper-tier requirements: 50 / 200

### 7.3. Specific end use(s)

See section 1.2

# **SECTION 8 Exposure controls / personal protection**

### 8.1. Control parameters

| Ingredient    | DNELs<br>Exposure Pattern Worker | PNECs<br>Compartment |  |
|---------------|----------------------------------|----------------------|--|
| Not Available | Not Available                    | Not Available        |  |

<sup>\*</sup> Values for General Population

# Occupational Exposure Limits (OEL)

# **INGREDIENT DATA**

| Source        | Ingredient    | Material name | TWA           | STEL          | Peak          | Notes         |
|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
| Not Available |

### Not Applicable

# **Emergency Limits**

| Ingredient                   | TEEL-1        | TEEL-2        | TEEL-3        |
|------------------------------|---------------|---------------|---------------|
| 2-Methylbutyl isothiocyanate | Not Available | Not Available | Not Available |

| Ingredient                   | Original IDLH | Revised IDLH  |
|------------------------------|---------------|---------------|
| 2-Methylbutyl isothiocyanate | Not Available | Not Available |

# 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation

 Part Number: OR30206
 Page 7 of 13
 Issue Date: 16/05/2022

 Version No: 1.1
 Print Date: 02/08/2023

#### 2-Methylbutyl isothiocyanate

that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations.

Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

| Type of Contaminant:  | Air Speed:                      |
|---|---------------------------------|
| solvent, vapours, degreasing etc., evaporating from tank (in still air).  | 0.25-0.5 m/s<br>(50-100 f/min.) |
| aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s<br>(100-200 f/min.)   |
| direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)  | 1-2.5 m/s<br>(200-500 f/min.)   |
| grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).  | 2.5-10 m/s<br>(500-2000 f/min.) |

Within each range the appropriate value depends on:

| Lower end of the range                                     | Upper end of the range           |
|--|----------------------------------|
| 1: Room air currents minimal or favourable to capture      | 1: Disturbing room air currents  |
| 2: Contaminants of low toxicity or of nuisance value only. | 2: Contaminants of high toxicity |
| 3: Intermittent, low production.                           | 3: High production, heavy use    |
| 4: Large hood or large air mass in motion                  | 4: Small hood-local control only |

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

# 8.2.2. Individual protection measures, such as personal protective equipment









### ► C

- ► Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]
- Full face shield may be required for supplementary but never for primary protection of eyes.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

# Eye and face protection

# **Skin protection** See Hand protection below

### Hands/feet protection

- ► Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber
- When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots.

### Body protection

# See Other protection below

# Other protection

- Overalls.
- PVC Apron.PVC protective suit may be required if exposure severe.
- ► Eyewash unit.
- ▶ Ensure there is ready access to a safety shower.

# 8.2.3. Environmental exposure controls

See section 12

Part Number: OR30206 Version No: 1.1

2-Methylbutyl isothiocyanate

Page 8 of 13 Issue Date: 16/05/2022 Print Date: 02/08/2023

# 9.1. Information on basic physical and chemical properties

| Appearance                                   | Not Available |   |               |
|--|---------------|---|---------------|
|  |               |   |               |
| Physical state                               | Liquid        | Relative density (Water = 1)            | Not Available |
| Odour  | Not Available | Partition coefficient n-octanol / water | Not Available |
| Odour threshold                              | Not Available | Auto-ignition temperature (°C)          | Not Available |
| pH (as supplied)                             | Not Available | Decomposition temperature (°C)          | Not Available |
| Melting point / freezing point (°C)          | Not Available | Viscosity (cSt)                         | Not Available |
| Initial boiling point and boiling range (°C) | 84-86/15mm    | Molecular weight (g/mol)                | Not Available |
| Flash point (°C)                             | Not Available | Taste                                   | Not Available |
| Evaporation rate                             | Not Available | Explosive properties                    | Not Available |
| Flammability                                 | Not Available | Oxidising properties                    | Not Available |
| Upper Explosive Limit (%)                    | Not Available | Surface Tension (dyn/cm or mN/m)        | Not Available |
| Lower Explosive Limit (%)                    | Not Available | Volatile Component (%vol)               | Not Available |
| Vapour pressure (kPa)                        | Not Available | Gas group                               | Not Available |
| Solubility in water                          | Not Available | pH as a solution (1%)                   | Not Available |
| Vapour density (Air = 1)                     | Not Available | VOC g/L                                 | Not Available |
| Nanoform Solubility                          | Not Available | Nanoform Particle<br>Characteristics    | Not Available |
| Particle Size                                | Not Available |   |               |

# 9.2. Other information

Not Available

# **SECTION 10 Stability and reactivity**

| 10.1.Reactivity                             | See section 7.2  |
|---|--|
| 10.2. Chemical stability                    | <ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul> |
| 10.3. Possibility of<br>hazardous reactions | See section 7.2  |
| 10.4. Conditions to avoid                   | See section 7.2  |
| 10.5. Incompatible materials                | See section 7.2  |
| 10.6. Hazardous decomposition products      | See section 5.3  |

# **SECTION 11 Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Information on toxicological effects

| Inhaled   | The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.  Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may produce severely damaging effects to the health of the individual. Relatively small amounts absorbed from the lungs may prove fatal.  Inhalation of quantities of liquid mist may be extremely hazardous, even lethal due to spasm, extreme irritation of larynx and bronchi, chemical pneumonitis and pulmonary oedema. |
|-----------|---|
| Ingestion | The material can produce chemical burns within the oral cavity and gastrointestinal tract following ingestion.  Accidental ingestion of the material may be seriously damaging to the health of the individual; animal experiments indicate that ingestion of less than 40 gram may be fatal.   |

Version No: 1.1

### 2-Methylbutyl isothiocyanate

Issue Date: **16/05/2022**Print Date: **02/08/2023** 

| Skin Contact                    | The material can produce chemical burns following direct contact with the skin.  Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.  Open cuts, abraded or irritated skin should not be exposed to this material  Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.  Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. |                           |  |
|---------------------------------|--|---------------------------|--|
| Eye                             | The material can produce chemical burns to the eye following direct contact. Vapours or mists may be extremely irritating. If applied to the eyes, this material causes severe eye damage.   |                           |  |
| Chronic                         | Repeated or prolonged exposure to corrosives may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue. Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems.  Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.  |                           |  |
| 2-Methylbutyl<br>isothiocyanate | TOXICITY  Not Available  | IRRITATION  Not Available |  |
| Legend:                         | Not Available  1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS.  Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances  |                           |  |

# 2-Methylbutyl isothiocyanate

Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.

| Acute Toxicity                    | <b>~</b> | Carcinogenicity          | × |
|-----------------------------------|----------|--------------------------|---|
| Skin Irritation/Corrosion         | <b>~</b> | Reproductivity           | × |
| Serious Eye<br>Damage/Irritation  | <b>~</b> | STOT - Single Exposure   | × |
| Respiratory or Skin sensitisation | ×        | STOT - Repeated Exposure | × |
| Mutagenicity                      | ×        | Aspiration Hazard        | × |

**Legend: X** − Data either not available or does not fill the criteria for classification

✓ – Data available to make classification

### 11.2 Information on other hazards

### 11.2.1. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

### 11.2.2. Other information

See Section 11.1

### **SECTION 12 Ecological information**

### 12.1. Toxicity

| O Matheritheeteel               | Endpoint   | Test Duration (hr) | Species       | Value            | Source           |
|---------------------------------|--|--------------------|---------------|------------------|------------------|
| 2-Methylbutyl<br>isothiocyanate | Not<br>Available   | Not Available      | Not Available | Not<br>Available | Not<br>Available |
| Legend:                         | Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data |                    |               |                  |                  |

Version No: 1.1

# 2-Methylbutyl isothiocyanate

Issue Date: **16/05/2022** Print Date: **02/08/2023** 

# 12.2. Persistence and degradability

| Ingredient | Persistence: Water/Soil               | Persistence: Air                      |  |
|------------|---------------------------------------|---------------------------------------|--|
|            | No Data available for all ingredients | No Data available for all ingredients |  |

# 12.3. Bioaccumulative potential

| Ingredient | Bioaccumulation                       |  |
|------------|---------------------------------------|--|
|            | No Data available for all ingredients |  |

# 12.4. Mobility in soil

| Ingredient | Mobility                              |  |  |
|------------|---------------------------------------|--|--|
|            | No Data available for all ingredients |  |  |

### 12.5. Results of PBT and vPvB assessment

|                         | P             | В             | Т             |  |
|-------------------------|---------------|---------------|---------------|--|
| Relevant available data | Not Available | Not Available | Not Available |  |
| PBT                     | ×             | ×             | ×             |  |
| vPvB                    | ×             | x             | ×             |  |
| PBT Criteria fulfilled? |               |               |               |  |
| vPvB                    |               |               | No            |  |

# 12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

### 12.7. Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

# **SECTION 13 Disposal considerations**

# 13.1. Waste treatment methods

| Product / Packaging<br>disposal | <ul> <li>Recycle wherever possible.</li> <li>Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</li> <li>Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation followed by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus.</li> <li>Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.</li> </ul> |
|---------------------------------|---|
| Waste treatment options         | Not Available   |
| Sewage disposal options         | Not Available   |

# **SECTION 14 Transport information**

# **Labels Required**

|                  | 6   |
|------------------|-----|
| Marine Pollutant | NO  |
| HAZCHEM          | 2XE |

# Land transport (ADR-RID)

| 14.1. UN number or ID number  | 2927                                     |  |
|-------------------------------|--|--|
| 14.2. UN proper shipping name | TOXIC LIQUID, CORROSIVE, ORGANIC, N.O.S. |  |

Part Number: OR30206 Page 11 of 13

Version No: 1.1

# 2-Methylbutyl isothiocyanate

Issue Date: **16/05/2022** Print Date: **02/08/2023** 

| 14.3. | Transport hazard class(es) | Class 6.1 Subsidiary risk 8    |         |  |
|-------|----------------------------|--------------------------------|---------|--|
| 14.4. | Packing group              | II                             |         |  |
| 14.5. | Environmental hazard       | Not Applicable                 |         |  |
|       |                            | Hazard identification (Kemler) | 68      |  |
|       |                            | Classification code            | TC1     |  |
| 14.6. | Special precautions        | Hazard Label                   | 6.1 +8  |  |
|       | for user                   | Special provisions             | 274     |  |
|       |                            | Limited quantity               | 100 ml  |  |
|       |                            | Tunnel Restriction Code        | 2 (D/E) |  |

# Air transport (ICAO-IATA / DGR)

| · ` `                              | ,   |         |  |  |  |
|------------------------------------|---|---------|--|--|--|
| 14.1. UN number                    | 2927  |         |  |  |  |
| 14.2. UN proper shipping name      | Toxic liquid, corrosive, organic, n.o.s. *                |         |  |  |  |
|                                    | ICAO/IATA Class 6.1                                       |         |  |  |  |
| 14.3. Transport hazard class(es)   | ICAO / IATA Subrisk 8                                     |         |  |  |  |
| ciass(es)                          | ERG Code 6C   |         |  |  |  |
| 14.4. Packing group                | II  |         |  |  |  |
| 14.5. Environmental hazard         | Not Applicable  |         |  |  |  |
|                                    | Special provisions  | A4 A137 |  |  |  |
|                                    | Cargo Only Packing Instructions                           | 660     |  |  |  |
|                                    | Cargo Only Maximum Qty / Pack                             | 30 L    |  |  |  |
| 14.6. Special precautions for user | Passenger and Cargo Packing Instructions                  | 653     |  |  |  |
| 101 4001                           | Passenger and Cargo Maximum Qty / Pack                    | 1 L     |  |  |  |
|                                    | Passenger and Cargo Limited Quantity Packing Instructions | Y640    |  |  |  |
|                                    | Passenger and Cargo Limited Maximum Qty / Pack            | 0.5 L   |  |  |  |

# Sea transport (IMDG-Code / GGVSee)

| • •                                      |   |  |  |  |
|--|---|--|--|--|
| 2927                                     |   |  |  |  |
| TOXIC LIQUID, CORROSIVE, ORGANIC, N.O.S. |   |  |  |  |
| IMDG Class 6.                            | 1   |  |  |  |
| IMDG Subrisk 8                           |   |  |  |  |
| II .                                     |   |  |  |  |
| Not Applicable                           |   |  |  |  |
| EMS Number                               | F-A, S-B  |  |  |  |
| Special provisions                       | 274   |  |  |  |
| Limited Quantities                       | 100 mL  |  |  |  |
|  | IMDG Class 6.  IMDG Subrisk 8  II  Not Applicable  EMS Number  Special provisions |  |  |  |

# Inland waterways transport (ADN)

| 14.1. UN number                  | 2927                                     |  |  |  |
|----------------------------------|--|--|--|--|
| 14.2. UN proper shipping name    | TOXIC LIQUID, CORROSIVE, ORGANIC, N.O.S. |  |  |  |
| 14.3. Transport hazard class(es) | 6.1 8                                    |  |  |  |

Part Number: OR30206 Page **12** of **13** Issue Date: 16/05/2022 Version No: 1.1 Print Date: 02/08/2023

### 2-Methylbutyl isothiocyanate

| 14.4. Packing group                | II .                |                |  |
|------------------------------------|---------------------|----------------|--|
| 14.5. Environmental hazard         | Not Applicable      |                |  |
|                                    | Classification code | TC1            |  |
|                                    | Special provisions  | 274; 802       |  |
| 14.6. Special precautions for user | Limited quantity    | 100 ml         |  |
| 101 4001                           | Equipment required  | PP, EP, TOX, A |  |
|                                    | Fire cones number   | 2              |  |

### 14.7. Maritime transport in bulk according to IMO instruments

### 14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

### 14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

| Product name | Group |
|--------------|-------|
|              |       |

# 14.7.3. Transport in bulk in accordance with the IGC Code

# **SECTION 15 Regulatory information**

# 15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable -: Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2020/878; Regulation (EC) No 1272/2008 as updated through ATPs.

# Information according to 2012/18/EU (Seveso III):

|--|

### 15.2. Chemical safety assessment

For further information please look at the Chemical Safety Assessment and Exposure Scenarios prepared by your Supply Chain if available.

### **ECHA SUMMARY**

Not Applicable

### **National Inventory Status**

| tational involvery datase                          |  |  |
|--|--|--|
| National Inventory                                 | Status   |  |
| Australia - AIIC / Australia<br>Non-Industrial Use | Not Available  |  |
| Canada - DSL                                       | Not Available  |  |
| Canada - NDSL                                      | Not Available  |  |
| China - IECSC                                      | Not Available  |  |
| Europe - EINEC / ELINCS /<br>NLP                   | Not Available  |  |
| Japan - ENCS                                       | Not Available  |  |
| Korea - KECI                                       | Not Available  |  |
| New Zealand - NZIoC                                | Not Available  |  |
| Philippines - PICCS                                | Not Available  |  |
| USA - TSCA   | Not Available  |  |
| Taiwan - TCSI                                      | Not Available  |  |
| Mexico - INSQ                                      | Not Available  |  |
| Vietnam - NCI                                      | Not Available  |  |
| Russia - FBEPH                                     | Not Available  |  |
| Legend:  | Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration. |  |

Part Number: OR30206 Page 13 of 13
Version No: 1.1

# 2-Methylbutyl isothiocyanate

**SECTION 16 Other information** 

| Revision Date | 16/05/2022 | | Initial Date | 16/05/2022 |

### Full text Risk and Hazard codes

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

### **Definitions and abbreviations**

PC - TWA: Permissible Concentration-Time Weighted Average

PC - STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit,

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value

BCF: BioConcentration Factors BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act
TCSI: Taiwan Chemical Substance Inventory
INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.

Issue Date: 16/05/2022

Print Date: 02/08/2023