

# Ethyl (pyridin-3-yl)acetate **Apollo Scientific**

Part Number: OR46218 Version No: 2.2 Safety Data Sheet

Chemwatch Hazard Alert Code: 2

Issue Date: 10/07/2023 Print Date: 10/07/2023 S.GHS.GB-NIR.EN

# SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### **Product Identifier**

Product name	hyl (pyridin-3-yl)acetate	
Chemical Name	ethyl 3-pyridylacetate	
Synonyms	Not Available	
Chemical formula	C9-H11-N-O2	
Other means of identification	Not Available	
CAS number	39931-77-6*	

# Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Not Available

# Details of the manufacturer or supplier of the safety data sheet

Registered company name	Apollo Scientific	Apollo Scientific Itd
Address	Whitefield Road, Bredbury SK62QR United Kingdom	Whitefield Road, Bredbury Cheshire SK6 2QR United Kingdom (NI)
Telephone	+44(0) 161 406 0505	
Fax	0161 406 0506 Not Available	
Website	http://www.apolloscientific.co.uk/	apolloscientific.co.uk
Email	sales@apolloscientific.co.uk	sales@apolloscientific.co.uk

# **Emergency telephone number**

Association / Organisation	Not Available
Emergency telephone numbers	Not Available
Other emergency telephone numbers	Not Available

# **SECTION 2 Hazards identification**

# Classification of the substance or mixture

**Classification according to** regulation (EC) No 1272/2008 [CLP] and amendments [1]

H335 - Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, H302 - Acute Toxicity (Oral) Category 4, H315 - Skin Corrosion/Irritation Category 2, H319 - Serious Eye Damage/Eye Irritation Category 2, H317 -Sensitisation (Skin) Category 1

Legend: 1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

# Label elements

Eaber clemento	
Hazard pictogram(s)	
Signal word	Warning

# Hazard statement(s)

H335	May cause respiratory irritation.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.

#### Precautionary statement(s) Prevention

P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, protective clothing, eye protection and face protection.
P261	Avoid breathing mist/vapours/spray.
P264	Wash all exposed external body areas thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P272	Contaminated work clothing should not be allowed out of the workplace.

# Precautionary statement(s) Response

P302+P352	IF ON SKIN: Wash with plenty of water.		
P305+P351+P338	F IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
P333+P313	skin irritation or rash occurs: Get medical advice/attention.		
P337+P313	f eye irritation persists: Get medical advice/attention.		
P362+P364	Take off contaminated clothing and wash it before reuse.		
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell.		
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.		
P330	Rinse mouth.		

#### Precautionary statement(s) Storage

P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

# Precautionary statement(s) Disposal

# **SECTION 3 Composition / information on ingredients**

#### Substances

CAS No	%[weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	SCL / M-Factor
39931-77-6*	100	<u>Ethyl (pyridin-</u> <u>3-yl)acetate</u>	Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3 , Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 2, Sensitisation (Skin) Category 1; H335, H302, H315, H319, H317 <sup>[1]</sup>	Not Available

Legend: 1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L; \* EU IOELVs available; [e] Substance identified as having endocrine disrupting properties

#### Mixtures

See section above for composition of Substances

#### **SECTION 4 First aid measures**

#### Description of first aid measures

Eye Contact	<ul> <li>If this product comes in contact with the eyes:</li> <li>Wash out immediately with fresh running water.</li> <li>Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>				
Skin Contact	<ul> <li>If skin contact occurs:</li> <li>Immediately remove all contaminated clothing, including footwear.</li> <li>Flush skin and hair with running water (and soap if available).</li> <li>Seek medical attention in event of irritation.</li> </ul>				
Inhalation	<ul> <li>If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>				
Ingestion	<ul> <li>IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY.</li> <li>For advice, contact a Poisons Information Centre or a doctor.</li> <li>Urgent hospital treatment is likely to be needed.</li> <li>In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition.</li> <li>If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the SDS should be provided. Further action will be the responsibility of the medical specialist.</li> <li>If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the SDS.</li> <li>Where medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise: <ul> <li>INDUCE vomiting with fingers down the back of the throat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> </ul> </li> <li>NOTE: Wear a protective glove when inducing vomiting by mechanical means.</li> </ul>				

#### Indication of any immediate medical attention and special treatment needed

As in all cases of suspected poisoning, follow the ABCDEs of emergency medicine (airway, breathing, circulation, disability, exposure), then the ABCDEs of toxicology (antidotes, basics, change absorption, change distribution, change elimination). For poisons (where specific treatment regime is absent):

#### BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 L/min.
- Monitor and treat, where necessary, for pulmonary oedema.
- Monitor and treat, where necessary, for shock.
- Anticipate seizures.
- DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.

-----

ADVANCED TREATMENT

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- + Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

# **SECTION 5 Firefighting measures**

#### Extinguishing media

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

# Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.			
Advice for firefighters				
Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves in the event of a fire.</li> <li>Prevent, by any means available, spillage from entering drains or water courses.</li> <li>Use fire fighting procedures suitable for surrounding area.</li> <li>DO NOT approach containers suspected to be hot.</li> <li>Cool fire exposed containers with water spray from a protected location.</li> <li>If safe to do so, remove containers from path of fire.</li> <li>Equipment should be thoroughly decontaminated after use.</li> </ul>			
Fire/Explosion Hazard	<ul> <li>Non combustible.</li> <li>Not considered a significant fire risk, however containers may burn.</li> <li>May emit poisonous fumes.</li> <li>May emit corrosive fumes.</li> </ul>			

# **SECTION 6 Accidental release measures**

#### Personal precautions, protective equipment and emergency procedures

See section 8

#### **Environmental precautions**

See section 12

# Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Clean up all spills immediately.</li> <li>Avoid breathing vapours and contact with skin and eyes.</li> <li>Control personal contact with the substance, by using protective equipment.</li> <li>Contain and absorb spill with sand, earth, inert material or vermiculite.</li> <li>Wipe up.</li> <li>Place in a suitable, labelled container for waste disposal.</li> </ul>
Major Spills	<ul> <li>Moderate hazard.</li> <li>Clear area of personnel and move upwind.</li> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves.</li> <li>Prevent, by any means available, spillage from entering drains or water course.</li> <li>Stop leak if safe to do so.</li> <li>Contain spill with sand, earth or vermiculite.</li> <li>Collect recoverable product into labelled containers for recycling.</li> <li>Neutralise/decontaminate residue (see Section 13 for specific agent).</li> <li>Collect solid residues and seal in labelled drums for disposal.</li> <li>Wash area and prevent runoff into drains.</li> <li>After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.</li> <li>If contamination of drains or waterways occurs, advise emergency services.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# **SECTION 7 Handling and storage**

# Precautions for safe handling Safe handling \* Avoid all personal contact, including inhalation. \* Wear protective clothing when risk of exposure occurs. \* Use in a well-ventilated area.

Avoid contact with moisture.

	Avoid contact with incompatible materials.
	When handling, DO NOT eat, drink or smoke.
	Keep containers securely sealed when not in use.
	Avoid physical damage to containers.
	Always wash hands with soap and water after handling.
	Work clothes should be laundered separately. Launder contaminated clothing before re-use.
	Use good occupational work practice.
	Observe manufacturer's storage and handling recommendations contained within this SDS.
	Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are
	maintained.
	DO NOT allow clothing wet with material to stay in contact with skin
Other information	

# Conditions for safe storage, including any incompatibilities

Suitable container	<ul> <li>Polyethylene or polypropylene container.</li> <li>Packing as recommended by manufacturer.</li> <li>Check all containers are clearly labelled and free from leaks.</li> </ul>
Storage incompatibility	None known <ul> <li>Store under argon</li> </ul>

# **SECTION 8 Exposure controls / personal protection**

# **Control parameters**

# Occupational Exposure Limits (OEL)

# INGREDIENT DATA

Not Available

# Emergency Limits

Ingredient	TEEL-1	TEEL-2		TEEL-3
Ethyl (pyridin-3-yl)acetate	Not Available	Not Available		Not Available
Ingredient	Original IDLH		Revised IDLH	
lingredient	Oliginaliden		Revised IDEIT	
Ethyl (pyridin-3-yl)acetate	Not Available		Not Available	

Occupational Exposure Banding		
Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
Ethyl (pyridin-3-yl)acetate	E	≤ 0.1 ppm
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.	

# Exposure controls

	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designe engineering controls can be highly effective in protecting workers and will typically be independent of worker interaction provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ver that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant designed properly. The design of a ventilation system must match the particular process and chemical or contaminant is Employers may need to use multiple types of controls to prevent employee overexposure.	ns to entilation t if
Appropriate engineering		
controls	General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in specific circumstances. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate prote Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace poss varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effective the contaminant.	ess
	Type of Contaminant: Air Speed	t:
	solvent, vapours, degreasing etc., evaporating from tank (in still air).	

chemical protective gloves, e.g. PVC. safety footwear or safety gumboots, e.g. Rubber	d at low velocity into zone of active generation g, conveyer loading, crusher dusts, gas discl generated dusts (released at high initial veloc 1: Disturbing room air currents 2: Contaminants of high toxicity 3: High production, heavy use 4: Small hood-local control only ance away from the opening of a simple extre extraction point (in simple cases). Therefore rence to distance from the contaminating sc n/s (200-400 f/min) for extraction of solvents il considerations, producing performance def are multiplied by factors of 10 or more when al equivalent] ct lenses may absorb and concentrate irritar ions on use, should be created for each wor the class of chemicals in use and an accoun- eir removal and suitable equipment should be adiately and remove contact lens as soon as on - lens should be removed in a clean enviro	on)       f/min.)         tharge       1-2.5 m/s (200-50 f/min.)         tricity       2.5-10 m/s (500-2000 f/min.)         tricity       the air speed at the ource. The air velocity at the sequence in a tank 2 bificits within the extraction in extraction systems are         nts. A written policy rkplace or task. This should int of injury experience. be readily available. In the spracticable. Lens should	
<ul> <li>generation into zone of rapid air motion)</li> <li>abrasive blasting, tumbling, high speed wheel ge of very high rapid air motion).</li> <li>ach range the appropriate value depends on:</li> <li>Ind of the range</li> <li>air currents minimal or favourable to capture</li> <li>aminants of low toxicity or of nuisance value only.</li> <li>nittent, low production.</li> <li>a hood or large air mass in motion</li> <li>accordingly, after references with the square of distance from the endit of the extraction point. Other mechanical s, make it essential that theoretical air velocities at or used.</li> <li>y glasses with side shields.</li> <li>nical goggles. [AS/NZS 1337.1, EN166 or national act lenses may pose a special hazard; soft contact ment, describing the wearing of lenses or restriction and adsorption for cal and first-aid personnel should be trained in the et of chemical exposure, begin eye irrigation immer moved at the first signs of eye redness or irritation washed hands thoroughly. [CDC NIOSH Current d protection below</li> </ul>	generated dusts (released at high initial velocity         Upper end of the range         1: Disturbing room air currents         2: Contaminants of high toxicity         3: High production, heavy use         4: Small hood-local control only         ance away from the opening of a simple extraction point (in simple cases). Therefore rence to distance from the contaminating sc n/s (200-400 f/min) for extraction of solvents at considerations, producing performance defarer multiplied by factors of 10 or more when         al equivalent]         ct lenses may absorb and concentrate irritarions on use, should be created for each wor the class of chemicals in use and an accounce ir removal and suitable equipment should be adiately and remove contact lens as soon as on - lens should be removed in a clean environment and suitable equipment should be removed in a clean environment and suitable equipment is the clean environment in the clean environment in the clean environment is should be removed in a clean environment in the clean environment is the clean e	f/min.)         acity       2.5-10 m/s (500-2000 f/min.)         acity       3.5-10 m/s (500-200 f/mi	
<ul> <li>e of very high rapid air motion).</li> <li>ach range the appropriate value depends on:</li> <li>and of the range</li> <li>air currents minimal or favourable to capture</li> <li>aminants of low toxicity or of nuisance value only.</li> <li>nittent, low production.</li> <li>e hood or large air mass in motion</li> <li>beory shows that air velocity falls rapidly with distate decreases with the square of distance from the enditor of the extraction point. Other mechanical is, make it essential that theoretical air velocities at or used.</li> <li>Image: A state of the extraction point. Other mechanical is, make it essential that theoretical air velocities at or used.</li> <li>Image: A state of the extraction point. Other mechanical is, make it essential that theoretical air velocities at or used.</li> <li>Image: A state of the extraction point. The extraction point are extracted to point should be adjusted.</li> <li>Image: A state of the extraction point. The extraction point are extracted to point. The extraction point are extracted to a ment, describing the wearing of lenses or restriction and adsorption for cal and first-aid personnel should be trained in the extraction point and adsorption for cal and first-aid personnel should be trained in the extraction point. (CDC NIOSH Current of protection below</li> <li>the chemical protective gloves, e.g. PVC.</li> </ul>	Upper end of the range         1: Disturbing room air currents         2: Contaminants of high toxicity         3: High production, heavy use         4: Small hood-local control only         ance away from the opening of a simple extraction point (in simple cases). Therefore         erence to distance from the contaminating sc         n/s (200-400 f/min) for extraction of solvents         I considerations, producing performance defare multiplied by factors of 10 or more when         al equivalent]         ct lenses may absorb and concentrate irritar         ions on use, should be created for each wor         the class of chemicals in use and an accour         eir removal and suitable equipment should be         adiately and remove contact lens as soon as         on - lens should be removed in a clean enviro	(500-2000 f/min.) arraction pipe. Velocity the air speed at the ource. The air velocity at the sequerated in a tank 2 arraction systems are ficits within the extraction the extraction systems are nextraction systems are nextraction systems are be readily available. In the s practicable. Lens should	
nd of the range a air currents minimal or favourable to capture aminants of low toxicity or of nuisance value only. nittent, low production. e hood or large air mass in motion eory shows that air velocity falls rapidly with dista decreases with the square of distance from the en- point should be adjusted, accordingly, after refer- in fan, for example, should be a minimum of 1-2 m istant from the extraction point. Other mechanical s, make it essential that theoretical air velocities a or used. y glasses with side shields. nical goggles. [AS/NZS 1337.1, EN166 or national act lenses may pose a special hazard; soft contact ment, describing the wearing of lenses or restricti- de a review of lens absorption and adsorption for cal and first-aid personnel should be trained in the et of chemical exposure, begin eye irrigation imme- moved at the first signs of eye redness or irritation washed hands thoroughly. [CDC NIOSH Current d protection below chemical protective gloves, e.g. PVC. safety footwear or safety gumboots, e.g. Rubber	1: Disturbing room air currents         1: Disturbing room air currents         2: Contaminants of high toxicity         3: High production, heavy use         4: Small hood-local control only         ance away from the opening of a simple extraction point (in simple cases). Therefore         extraction point (in simple cases). Therefore         erence to distance from the contaminating sc         n/s (200-400 f/min) for extraction of solvents         I considerations, producing performance defare         are multiplied by factors of 10 or more when         ct lenses may absorb and concentrate irritar         ions on use, should be created for each wor         the class of chemicals in use and an accounce         erine removal and suitable equipment should be         ediately and remove contact lens as soon as         on - lens should be removed in a clean enviro	e the air speed at the ource. The air velocity at the s generated in a tank 2 dificits within the extraction in extraction systems are nextraction sys	
n air currents minimal or favourable to capture aminants of low toxicity or of nuisance value only. nittent, low production. hood or large air mass in motion heory shows that air velocity falls rapidly with dista decreases with the square of distance from the en- point should be adjusted, accordingly, after refe- in fan, for example, should be a minimum of 1-2 m istant from the extraction point. Other mechanical s, make it essential that theoretical air velocities a or used.	1: Disturbing room air currents         1: Disturbing room air currents         2: Contaminants of high toxicity         3: High production, heavy use         4: Small hood-local control only         ance away from the opening of a simple extraction point (in simple cases). Therefore         extraction point (in simple cases). Therefore         erence to distance from the contaminating sc         n/s (200-400 f/min) for extraction of solvents         I considerations, producing performance defare         are multiplied by factors of 10 or more when         ct lenses may absorb and concentrate irritar         ions on use, should be created for each wor         the class of chemicals in use and an accounce         erine removal and suitable equipment should be         ediately and remove contact lens as soon as         on - lens should be removed in a clean enviro	e the air speed at the ource. The air velocity at the s generated in a tank 2 dificits within the extraction in extraction systems are nextraction sys	
aminants of low toxicity or of nuisance value only. nittent, low production. a hood or large air mass in motion teory shows that air velocity falls rapidly with dista decreases with the square of distance from the en- point should be adjusted, accordingly, after refer- in fan, for example, should be a minimum of 1-2 m istant from the extraction point. Other mechanical s, make it essential that theoretical air velocities a or used.	2: Contaminants of high toxicity     3: High production, heavy use     4: Small hood-local control only ance away from the opening of a simple extraction point (in simple cases). Therefore erence to distance from the contaminating sc n/s (200-400 f/min) for extraction of solvents I considerations, producing performance def are multiplied by factors of 10 or more when al equivalent] ct lenses may absorb and concentrate irritar ions on use, should be created for each wor the class of chemicals in use and an accour eir removal and suitable equipment should be adiately and remove contact lens as soon as on - lens should be removed in a clean enviro	e the air speed at the ource. The air velocity at the s generated in a tank 2 dificits within the extraction in extraction systems are nextraction sys	
nittent, low production. e hood or large air mass in motion eeory shows that air velocity falls rapidly with dista decreases with the square of distance from the e in point should be adjusted, accordingly, after refer- in fan, for example, should be a minimum of 1-2 m istant from the extraction point. Other mechanical ist, make it essential that theoretical air velocities a or used. Image: a special that theoretical air velocities a or used. Image: a special hazard; soft contact ment, describing the wearing of lenses or restriction the a review of lens absorption and adsorption for cal and first-aid personnel should be trained in the a of chemical exposure, begin eye irrigation imme moved at the first signs of eye redness or irritation washed hands thoroughly. [CDC NIOSH Current d protection below chemical protective gloves, e.g. PVC. safety footwear or safety gumboots, e.g. Rubber	3: High production, heavy use 4: Small hood-local control only ance away from the opening of a simple extr extraction point (in simple cases). Therefore erence to distance from the contaminating sc n/s (200-400 f/min) for extraction of solvents il considerations, producing performance def are multiplied by factors of 10 or more when al equivalent] ct lenses may absorb and concentrate irritar ions on use, should be created for each wor the class of chemicals in use and an accoun- eir removal and suitable equipment should be adiately and remove contact lens as soon as on - lens should be removed in a clean enviro	e the air speed at the ource. The air velocity at the s generated in a tank 2 dificits within the extraction in extraction systems are nextraction sys	
<ul> <li>a hood or large air mass in motion</li> <li>beory shows that air velocity falls rapidly with distant of decreases with the square of distance from the exponent should be adjusted, accordingly, after reference of a normal should be adjusted, accordingly, after reference of the example, should be a minimum of 1-2 mistant from the extraction point. Other mechanical is, make it essential that theoretical air velocities a for used.</li> <li>Image: the example of the extraction point. Other mechanical is, make it essential that theoretical air velocities a for used.</li> <li>Image: the example of the example of</li></ul>	4: Small hood-local control only ance away from the opening of a simple extr extraction point (in simple cases). Therefore erence to distance from the contaminating sc n/s (200-400 f/min) for extraction of solvents il considerations, producing performance def are multiplied by factors of 10 or more when al equivalent] ct lenses may absorb and concentrate irritar ions on use, should be created for each wor the class of chemicals in use and an account eir removal and suitable equipment should be adiately and remove contact lens as soon as on - lens should be removed in a clean enviro	e the air speed at the ource. The air velocity at the s generated in a tank 2 dificits within the extraction in extraction systems are nextraction sys	
teory shows that air velocity falls rapidly with distance from the experimentation of the square of distance from the experimentation of	ance away from the opening of a simple extr extraction point (in simple cases). Therefore erence to distance from the contaminating sc n/s (200-400 f/min) for extraction of solvents al considerations, producing performance def are multiplied by factors of 10 or more when al equivalent] ct lenses may absorb and concentrate irritar ions on use, should be created for each wor the class of chemicals in use and an accoun- eir removal and suitable equipment should be adiately and remove contact lens as soon as on - lens should be removed in a clean enviro	e the air speed at the ource. The air velocity at the s generated in a tank 2 dificits within the extraction in extraction systems are nextraction sys	
decreases with the square of distance from the en- point should be adjusted, accordingly, after refer- in fan, for example, should be a minimum of 1-2 m istant from the extraction point. Other mechanical s, make it essential that theoretical air velocities a or used.	extraction point (in simple cases). Therefore erence to distance from the contaminating sc n/s (200-400 f/min) for extraction of solvents al considerations, producing performance def are multiplied by factors of 10 or more when al equivalent] ct lenses may absorb and concentrate irritar ions on use, should be created for each wor the class of chemicals in use and an accour eir removal and suitable equipment should be adiately and remove contact lens as soon as on - lens should be removed in a clean enviro	e the air speed at the ource. The air velocity at the s generated in a tank 2 dificits within the extraction in extraction systems are nextraction sys	
inical goggles. [AS/NZS 1337.1, EN166 or national act lenses may pose a special hazard; soft contact ment, describing the wearing of lenses or restricti- de a review of lens absorption and adsorption for cal and first-aid personnel should be trained in the of chemical exposure, begin eye irrigation imme- moved at the first signs of eye redness or irritation washed hands thoroughly. [CDC NIOSH Current d protection below chemical protective gloves, e.g. PVC. safety footwear or safety gumboots, e.g. Rubber	ct lenses may absorb and concentrate irritar ions on use, should be created for each wor the class of chemicals in use and an accour eir removal and suitable equipment should b ediately and remove contact lens as soon as on - lens should be removed in a clean enviro	rkplace or task. This shoul int of injury experience. be readily available. In the s practicable. Lens should	
inical goggles. [AS/NZS 1337.1, EN166 or national act lenses may pose a special hazard; soft contact ment, describing the wearing of lenses or restricti- de a review of lens absorption and adsorption for cal and first-aid personnel should be trained in the of chemical exposure, begin eye irrigation imme- moved at the first signs of eye redness or irritation washed hands thoroughly. [CDC NIOSH Current d protection below chemical protective gloves, e.g. PVC. safety footwear or safety gumboots, e.g. Rubber	ct lenses may absorb and concentrate irritar ions on use, should be created for each wor the class of chemicals in use and an accour eir removal and suitable equipment should b ediately and remove contact lens as soon as on - lens should be removed in a clean enviro	rkplace or task. This shoul int of injury experience. be readily available. In the s practicable. Lens should	
chemical protective gloves, e.g. PVC. safety footwear or safety gumboots, e.g. Rubber			
safety footwear or safety gumboots, e.g. Rubber	See Hand protection below		
<ul> <li>Wear chemical protective gloves, e.g. PVC.</li> <li>Wear safety footwear or safety gumboots, e.g. Rubber</li> <li>NOTE: <ul> <li>The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and or protective equipment, to avoid all possible skin contact.</li> <li>Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.</li> </ul> </li> <li>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove materia can not be calculated in advance and has therefore to be checked prior to the application.</li> <li>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</li> <li>Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hand should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</li> <li>Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: <ul> <li>frequency and duration of contact,</li> <li>chemical resistance of glove material,</li> <li>glove thickness and</li> <li>dexterity</li> </ul> </li> <li>Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</li> <li>When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.</li> <li>Contaminated gloves should be replaced.</li> <li>As defined in ASTM F-73</li></ul>			
n h t l p t h t l p t h t t l o n g g m m e	In hygiene is a key element of effective hand care. be washed and dried thoroughly. Application of a m ty and durability of glove type is dependent on usa ney and duration of contact, cal resistance of glove material, hickness and ty loves tested to a relevant standard (e.g. Europe E prolonged or frequently repeated contact may occ than 240 minutes according to EN 374, AS/NZS 2 only brief contact is expected, a glove with a prote to EN 374, AS/NZS 2161.10.1 or national equiv glove polymer types are less affected by moveme m use.	al hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended. ty and durability of glove type is dependent on usage. Important factors in the selection of glo ney and duration of contact, cal resistance of glove material, hickness and ty loves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or high than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. glove polymer types are less affected by movement and this should be taken into account wh m use. ninated gloves should be replaced.	

	For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended. It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task. Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example: • Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of. • Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.
Body protection	See Other protection below
Other protection	<ul> <li>Overalls.</li> <li>P.V.C apron.</li> <li>Barrier cream.</li> <li>Skin cleansing cream.</li> <li>Eye wash unit.</li> </ul>

# **SECTION 9** Physical and chemical properties

# Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	79-80/0.4mm	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Not Available	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

# **SECTION 10 Stability and reactivity**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7

Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

#### **SECTION 11 Toxicological information**

#### Information on toxicological effects

Inhaled	The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.
Skin Contact	Skin contact is not thought to produce harmful health effects (as classified under EC Directives using animal models). Systemic harm, however, has been identified following exposure of animals by at least one other route and the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	This material can cause eye irritation and damage in some persons.
Chronic	Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.

Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS.
	Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

Ethyl (pyridin-3-yl)acetate	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.		
Acute Toxicity	*	Carcinogenicity	×
Skin Irritation/Corrosion	¥	Reproductivity	×
Serious Eye Damage/Irritation	~	STOT - Single Exposure	~
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	×

Legend:

# SECTION 12 Ecological information

Mutagenicity X

#### Toxicity

Legend: Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) -Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Aspiration Hazard X

Data available to make classification

X – Data either not available or does not fill the criteria for classification

DO NOT discharge into sewer or waterways.

Ingredient	Persistence: Water/Soil	Persistence: Air
Ethyl (pyridin-3-yl)acetate	HIGH	HIGH

# **Bioaccumulative potential**

Ingredient	Bioaccumulation	
Ethyl (pyridin-3-yl)acetate	LOW (LogKOW = 1.3835)	

# Mobility in soil

Ingredient	Mobility
Ethyl (pyridin-3-yl)acetate	LOW (KOC = 258.4)

#### **SECTION 13 Disposal considerations**

Waste treatment methods Product / Packaging disposal	<ul> <li>Containers may still present a chemical hazard/ danger when empty.</li> <li>Return to supplier for reuse/ recycling if possible.</li> <li>Otherwise:</li> <li>If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.</li> <li>Where possible retain label warnings and SDS and observe all notices pertaining to the product.</li> <li>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</li> <li>A Hierarchy of Controls seems to be common - the user should investigate: <ul> <li>Reduction</li> <li>Reuse</li> <li>Recycling</li> <li>Disposal (if all else fails)</li> </ul> </li> <li>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.</li> <li>DO NOT allow wash water from cleaning or process equipment to enter drains.</li> <li>It may be necessary to collect all wash water for treatment before disposal.</li> <li>In all cases disposal to sever may be subject to local laws and regulations and these should be considered first.</li> <li>Where in doubt contact the responsible authority.</li> <li>Recycle wherever possible.</li> <li>Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</li> <li>Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or incin</li></ul>
--	--

# **SECTION 14 Transport information**

#### Labels Required

Marine Pollutant NO

# Land transport (ADR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

# Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

# Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

# Inland waterways transport (ADN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

# Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

#### Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
Ethyl (pyridin-3-yl)acetate	Not Available

#### Transport in bulk in accordance with the IGC Code

Product name	Ship Type
Ethyl (pyridin-3-yl)acetate	Not Available

#### **SECTION 15 Regulatory information**

# Safety, health and environmental regulations / legislation specific for the substance or mixture

Ethyl (pyridin-3-yl)acetate is found on the following regulatory lists

Europe EC Inventory

European Union - European Inventory of Existing Commercial Chemical Substances (EINECS)

#### **National Inventory Status**

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	No (Ethyl (pyridin-3-yl)acetate)
Canada - DSL	No (Ethyl (pyridin-3-yl)acetate)
Canada - NDSL	No (Ethyl (pyridin-3-yl)acetate)
China - IECSC	No (Ethyl (pyridin-3-yl)acetate)
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	No (Ethyl (pyridin-3-yl)acetate)
Korea - KECI	No (Ethyl (pyridin-3-yl)acetate)
New Zealand - NZIoC	No (Ethyl (pyridin-3-yl)acetate)
Philippines - PICCS	No (Ethyl (pyridin-3-yl)acetate)
USA - TSCA	No (Ethyl (pyridin-3-yl)acetate)
Taiwan - TCSI	Yes
Mexico - INSQ	No (Ethyl (pyridin-3-yl)acetate)
Vietnam - NCI	Yes
Russia - FBEPH	No (Ethyl (pyridin-3-yl)acetate)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

#### **SECTION 16 Other information**

Revision Date	10/07/2023
Initial Date	10/07/2023

#### **SDS Version Summary**

Version	Date of Update	Sections Updated
1.2	10/07/2023	Toxicological information - Acute Health (inhaled), Toxicological information - Acute Health (skin), Toxicological information - Acute Health (swallowed), First Aid measures - Advice to Doctor, CAS Number, Toxicological information - Chronic Health, Hazards identification - Classification, Disposal considerations - Disposal, Ecological Information - Environmental, Firefighting measures - Fire Fighter (extinguishing media), Firefighting measures - Fire Fighter (fire fighting), First Aid measures - Fire Fighter (fire fighting), First Aid measures - First Aid (skin), First Aid measures - First Aid (skin), First Aid measures - First Aid (swallowed), Handling and storage - Handling Procedure, Composition / information on ingredients - Ingredients, Korean MSDS Number, Exposure controls / personal protection - Personal Protection (hands/feet), Accidental release measures - Spills (minor), Handling and storage - Storage (storage requirement), Handling and storage - Storage (suitable container), Identification of the substance / mixture and of the company / undertaking - Supplier Information, Identification of the substance / mixture and of the company / undertaking - Synonyms

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

Part Number: OR46218 Version No: 2.2

#### Ethyl (pyridin-3-yl)acetate

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered. For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards: EN 166 Personal eye-protection EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

#### **Definitions and abbreviations**

PC - TWA: Permissible Concentration-Time Weighted Average PC - STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit. IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard **OSF: Odour Safety Factor** NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors **BEI: Biological Exposure Index** AIIC: Australian Inventory of Industrial Chemicals DSL: Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

#### Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	Classification Procedure
Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, H335	Expert judgement
Acute Toxicity (Oral) Category 4, H302	On basis of test data
Skin Corrosion/Irritation Category 2, H315	Expert judgement
Serious Eye Damage/Eye Irritation Category 2, H319	Expert judgement
Sensitisation (Skin) Category 1, H317	Calculation method

Powered by AuthorITe, from Chemwatch.