

Benzyl (4R)-5-amino-4-[[(2S)-2-[(2-methylpropan-2-yl)oxycarbonylamino]propanoyl]amino]-5-oxopentanoa

Apollo Scientific

Part Number: **OR47893** Version No: **2.2** Safety Data Sheet Chemwatch Hazard Alert Code: 2

Issue Date: **10/07/2023** Print Date: **10/07/2023** S.GHS.GB-NIR.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

| Product name | Benzyl (4R)-5-amino-4-[[(2S)-2-[(2-methylpropan-2-yl)oxycarbonylamino]propanoyl]amino]-5-oxopentanoa |
|----------------------------------|--|
| Chemical Name | Boc-Ala-D-Glu(OBzI)-NH2 |
| Synonyms | Not Available |
| Other means of identification | Not Available |
| CAS number | 18814-49-8* |

Relevant identified uses of the substance or mixture and uses advised against

| Relevant identified uses | Not Available |
|--------------------------|---------------|
|--------------------------|---------------|

Details of the manufacturer or supplier of the safety data sheet

| Registered company name | Apollo Scientific | Apollo Scientific Itd |
|-------------------------|---|---|
| Address | Whitefield Road, Bredbury SK62QR United Kingdom | Whitefield Road, Bredbury Cheshire SK6 2QR United Kingdom (NI) |
| Telephone | 01614060505 | +44(0) 161 406 0505 |
| Fax | 0161 406 0506 | Not Available |
| Website | http://www.apolloscientific.co.uk/ | apolloscientific.co.uk |
| Email | sales@apolloscientific.co.uk | sales@apolloscientific.co.uk |

Emergency telephone number

| Association / Organisation | Not Available |
|-----------------------------------|---------------|
| Emergency telephone numbers | Not Available |
| Other emergency telephone numbers | Not Available |

SECTION 2 Hazards identification

Classification of the substance or mixture

Classification according to regulation (EC) No 1272/2008 [CLP] and amendments ^[1]

H312 - Acute Toxicity (Dermal) Category 4, H332 - Acute Toxicity (Inhalation) Category 4, H335 - Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, H302 - Acute Toxicity (Oral) Category 4, H315 - Skin Corrosion/Irritation Category 2, H319 - Serious Eye Damage/Eye Irritation Category 2

Version No: 2.2

Page **2** of **11**

Benzyl (4R)-5-amino-4-[[(2S)-2-[(2-methylpropan-2-yl)oxycarbonylamino]propanoyl]amino]-5-oxopentanoa

Legend: 1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Label elements

| Hazard pictogram(s) | |
|---------------------|---------|
| | |
| Signal word | Warning |

Hazard statement(s)

| H312 | Harmful in contact with skin. |
|------|-----------------------------------|
| H332 | Harmful if inhaled. |
| H335 | May cause respiratory irritation. |
| H302 | Harmful if swallowed. |
| H315 | Causes skin irritation. |
| H319 | Causes serious eye irritation. |

Precautionary statement(s) Prevention

| P271 | Use only outdoors or in a well-ventilated area. |
|------|--|
| P261 | Avoid breathing dust/fumes. |
| P264 | Wash all exposed external body areas thoroughly after handling. |
| P270 | Do not eat, drink or smoke when using this product. |
| P280 | Wear protective gloves, protective clothing, eye protection and face protection. |

Precautionary statement(s) Response

| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
|----------------|--|
| P337+P313 | If eye irritation persists: Get medical advice/attention. |
| P301+P312 | IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell. |
| P302+P352 | IF ON SKIN: Wash with plenty of water. |
| P304+P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |
| P330 | Rinse mouth. |
| P332+P313 | If skin irritation occurs: Get medical advice/attention. |
| P362+P364 | Take off contaminated clothing and wash it before reuse. |

Precautionary statement(s) Storage

| P405 | Store locked up. |
|-----------|--|
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. |

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

| CAS No | %[weight] | Name | Classification according to regulation (EC) No 1272/2008 [CLP] and amendments | SCL / M-Factor |
|-------------|-----------|--|---|-------------------|
| 18814-49-8* | 100 | Benzyl (4R)-5-amino-4-[[(2S)-2-[(2- methylpropan- 2-yl)oxycarbonylamino]propanoyl]amino]- 5-oxopentanoa | Acute Toxicity (Dermal) Category 4, Acute Toxicity (Inhalation) Category 4, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 2; H312, H332, H335, H302, H315, H319 ^[1] | Not Available |

Version No: 2.2

Benzyl (4R)-5-amino-4-[[(2S)-2-[(2-methylpropan-2-yl)oxycarbonylamino]propanoyl]amino]-5-oxopentanoa

Legend: 1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L; * EU IOELVs available; [e] Substance identified as having endocrine disrupting properties

Mixtures

See section above for composition of Substances

SECTION 4 First aid measures

Description of first aid measures

| Eye Contact | If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. |
|--------------|---|
| Skin Contact | If skin or hair contact occurs: Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation. |
| Inhalation | If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary. |
| Ingestion | Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. |

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

There is no restriction on the type of extinguisher which may be used.

Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

| Fire Incompatibility | None known. |
|----------------------|-------------|
| | |

Advice for firefighters

| Fire Fighting | Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. DO NOT approach containers suspected to be hot. |
|-----------------------|--|
| Fire Fighting | Use fire fighting procedures suitable for surrounding area. |
| Fire/Explosion Hazard | Not considered a significant fire risk, however containers may burn. May emit corrosive fumes. |

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

| Version No: 2.2 | Benz | yl (4R)-5-amino-4-[[(2S)-2-[(2-methylpropan-2-yl)oxycarbonylamino]propanoyl]amino]- 5-oxopentanoa |
|-----------------|--------------|---|
| | Minor Spills | Clean up all spills immediately. Avoid breathing dust and contact with skin and eyes. Wear protective clothing, gloves, safety glasses and dust respirator. Use dry clean up procedures and avoid generating dust. Sweep up, shovel up or Vacuum up (consider explosion-proof machines designed to be grounded during storage and use). Place spilled material in clean, dry, sealable, labelled container. |
| | Major Spills | Moderate hazard. CAUTION: Advise personnel in area. Alert Emergency Services and tell them location and nature of hazard. Control personal contact by wearing protective clothing. Prevent, by any means available, spillage from entering drains or water courses. Recover product wherever possible. IF DRY: Use dry clean up procedures and avoid generating dust. Collect residues and place in sealed plastic bags or other containers for disposal. IF WET: Vacuum/shovel up and place in labelled containers for disposal. ALWAYS: Wash area down with large amounts of water and prevent runoff into drains. If contamination of drains or waterways occurs, advise Emergency Services. |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

| Safe handling | Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. DO NOT allow material to contact humans, exposed food or food utensils. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained. |
|-------------------|---|
| Other information | Store in original containers. Keep containers securely sealed. Store in a cool, dry area protected from environmental extremes. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS. For major quantities: Consider storage in bunded areas - ensure storage areas are isolated from sources of community water (including stormwater, ground water, lakes and streams). Ensure that accidental discharge to air or water is the subject of a contingency disaster management plan; this may require consultation with local authorities. |

Conditions for safe storage, including any incompatibilities

| Suitable container | Lined metal can, lined metal pail/ can. Plastic pail. Polyliner drum. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks. |
|-------------------------|--|
| Storage incompatibility | None known |

SECTION 8 Exposure controls / personal protection

Page 5 of 11

Benzyl (4R)-5-amino-4-[[(2S)-2-[(2-methylpropan-2-yl)oxycarbonylamino]propanoyl]amino]-5-oxopentanoa

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

Emergency Limits

| Ingredient | TEEL-1 | TEEL-2 | | TEEL-3 |
|--|---------------|---------------|---------------|---------------|
| Benzyl (4R)-5-amino-4-[[(2S)-2-[(2- methylpropan- 2-yl)oxycarbonylamino]propanoyl]amino]- 5-oxopentanoa | Not Available | Not Available | | Not Available |
| Ingredient | Original IDLH | | Revised IDLH | |
| Benzyl (4R)-5-amino-4-[[(2S)-2-[(2- methylpropan- 2-yl)oxycarbonylamino]propanoyl]amino]- 5-oxopentanoa | Not Available | | Not Available | |

Occupational Exposure Banding

| Ingredient | Occupational Exposure Band Rating | Occupational Exposure Band Limit | |
|--|--|----------------------------------|--|
| Benzyl (4R)-5-amino-4-[[(2S)-2-[(2- methylpropan- 2-yl)oxycarbonylamino]propanoyl]amino]- 5-oxopentanoa | $_{0]-}$ E ≤ 0.01 mg/m ³ | | |
| Notes: | Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health. | | |

Exposure controls

| | Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. | | | | |
|-------------------------------------|---|---|--|--|--|
| | The basic types of engineering controls are: | | | | |
| | Process controls which involve changing the way a job act | ivity or process is done to reduce the risk | | | |
| | Enclosure and/or isolation of emission source which keeps | | | | |
| | that strategically "adds" and "removes" air in the work envi | | | | |
| | designed properly. The design of a ventilation system must Employers may need to use multiple types of controls to provide the system of the s | | al or contaminant in use. | | |
| | Employers may need to use multiple types of controls to pr | event employee overexposure. | | | |
| | Local exhaust ventilation is required where solids are h large, a certain proportion will be powdered by mutual | | n particulates are relatively | | |
| | If in spite of local exhaust an adverse concentration of considered. | the substance in air could occur, respirate | bry protection should be | | |
| | Such protection might consist of: | | | | |
| | (a): particle dust respirators, if necessary, combined with an absorption cartridge; | | | | |
| | | | | | |
| | (b): filter respirators with absorption cartridge or canister of | | | | |
| Appropriate engineering | (b): filter respirators with absorption cartridge or canister of (c): fresh-air hoods or masks. | f the right type; | ormino the "conture | | |
| Appropriate engineering controls | (b): filter respirators with absorption cartridge or canister of (c): fresh-air hoods or masks. | f the right type; ing "escape" velocities which, in turn, det | ermine the "capture | | |
| | (b): filter respirators with absorption cartridge or canister of (c): fresh-air hoods or masks. Air contaminants generated in the workplace possess vary velocities" of fresh circulating air required to effectively rem | f the right type; ing "escape" velocities which, in turn, det | | | |
| | (b): filter respirators with absorption cartridge or canister of (c): fresh-air hoods or masks. Air contaminants generated in the workplace possess vary velocities" of fresh circulating air required to effectively rem Type of Contaminant: | i the right type; ing "escape" velocities which, in turn, det nove the contaminant. | Air Speed: | | |
| | (b): filter respirators with absorption cartridge or canister of (c): fresh-air hoods or masks. Air contaminants generated in the workplace possess vary velocities" of fresh circulating air required to effectively rem Type of Contaminant: direct spray, spray painting in shallow booths, drum filling | i the right type; ing "escape" velocities which, in turn, det nove the contaminant. , conveyer loading, crusher dusts, gas | Air Speed: 1-2.5 m/s (200-500 | | |
| | (b): filter respirators with absorption cartridge or canister of (c): fresh-air hoods or masks. Air contaminants generated in the workplace possess vary velocities" of fresh circulating air required to effectively rem Type of Contaminant: direct spray, spray painting in shallow booths, drum filling discharge (active generation into zone of rapid air motion) | i the right type; ing "escape" velocities which, in turn, det nove the contaminant. , conveyer loading, crusher dusts, gas | Air Speed: 1-2.5 m/s (200-500 f/min.) | | |
| | (b): filter respirators with absorption cartridge or canister of (c): fresh-air hoods or masks. Air contaminants generated in the workplace possess vary velocities" of fresh circulating air required to effectively rem Type of Contaminant: direct spray, spray painting in shallow booths, drum filling discharge (active generation into zone of rapid air motion) grinding, abrasive blasting, tumbling, high speed wheel generation | i the right type; ing "escape" velocities which, in turn, det nove the contaminant. , conveyer loading, crusher dusts, gas | Air Speed: 1-2.5 m/s (200-500 f/min.) 2.5-10 m/s (500-20 | | |
| | (b): filter respirators with absorption cartridge or canister of (c): fresh-air hoods or masks. Air contaminants generated in the workplace possess vary velocities" of fresh circulating air required to effectively rem Type of Contaminant: direct spray, spray painting in shallow booths, drum filling discharge (active generation into zone of rapid air motion) | i the right type; ing "escape" velocities which, in turn, det nove the contaminant. , conveyer loading, crusher dusts, gas | Air Speed: 1-2.5 m/s (200-500 f/min.) | | |
| | (b): filter respirators with absorption cartridge or canister of (c): fresh-air hoods or masks. Air contaminants generated in the workplace possess vary velocities" of fresh circulating air required to effectively rem Type of Contaminant: direct spray, spray painting in shallow booths, drum filling discharge (active generation into zone of rapid air motion) grinding, abrasive blasting, tumbling, high speed wheel generation | i the right type; ing "escape" velocities which, in turn, det nove the contaminant. , conveyer loading, crusher dusts, gas | Air Speed: 1-2.5 m/s (200-500 f/min.) 2.5-10 m/s (500-20 | | |
| | (b): filter respirators with absorption cartridge or canister of (c): fresh-air hoods or masks. Air contaminants generated in the workplace possess vary velocities" of fresh circulating air required to effectively rem Type of Contaminant: direct spray, spray painting in shallow booths, drum filling discharge (active generation into zone of rapid air motion) grinding, abrasive blasting, tumbling, high speed wheel generation into zone of very high rapid air motion). | i the right type; ing "escape" velocities which, in turn, det nove the contaminant. , conveyer loading, crusher dusts, gas | Air Speed: 1-2.5 m/s (200-500 f/min.) 2.5-10 m/s (500-20 | | |
| | (b): filter respirators with absorption cartridge or canister of (c): fresh-air hoods or masks. Air contaminants generated in the workplace possess vary velocities" of fresh circulating air required to effectively rem Type of Contaminant: direct spray, spray painting in shallow booths, drum filling discharge (active generation into zone of rapid air motion) grinding, abrasive blasting, tumbling, high speed wheel generation into zone of very high rapid air motion). Within each range the appropriate value depends on: | i the right type; ing "escape" velocities which, in turn, det nove the contaminant. , conveyer loading, crusher dusts, gas) enerated dusts (released at high initial | Air Speed: 1-2.5 m/s (200-500 f/min.) 2.5-10 m/s (500-20 | | |
| | (b): filter respirators with absorption cartridge or canister of (c): fresh-air hoods or masks. Air contaminants generated in the workplace possess vary velocities" of fresh circulating air required to effectively rem Type of Contaminant: direct spray, spray painting in shallow booths, drum filling discharge (active generation into zone of rapid air motion) grinding, abrasive blasting, tumbling, high speed wheel ge velocity into zone of very high rapid air motion). Within each range the appropriate value depends on: Lower end of the range | f the right type; ing "escape" velocities which, in turn, det nove the contaminant. , conveyer loading, crusher dusts, gas) enerated dusts (released at high initial Upper end of the range | Air Speed: 1-2.5 m/s (200-500 f/min.) 2.5-10 m/s (500-20 | | |
| | (b): filter respirators with absorption cartridge or canister of (c): fresh-air hoods or masks. Air contaminants generated in the workplace possess vary velocities" of fresh circulating air required to effectively rem Type of Contaminant: direct spray, spray painting in shallow booths, drum filling discharge (active generation into zone of rapid air motion) grinding, abrasive blasting, tumbling, high speed wheel ge velocity into zone of very high rapid air motion). Within each range the appropriate value depends on: Lower end of the range 1: Room air currents minimal or favourable to capture | f the right type; ing "escape" velocities which, in turn, det nove the contaminant. , conveyer loading, crusher dusts, gas) enerated dusts (released at high initial Upper end of the range 1: Disturbing room air currents | Air Speed: 1-2.5 m/s (200-500 f/min.) 2.5-10 m/s (500-200 | | |

| Version No: 23 Denzyl (4R)-5-amino-4-[[(28)-2-[(2-methylpropan-2-yl]oxycarbonylamino]propanoyl]amino] 5-cooperationa Denziona Simple hieury about hal air valocky fluid for additiona amap from the opticing of a simple additionation pipe. Molecky parentaly decisions with the space of disersor from the containing source and a space of the extraction piper should be a minimum of 4-10 mis (60)-2000 (min) for estraction or curber dusts generated 2: methers aliant from the stractic piper should be a minimum of 4-10 mis (60)-2000 (min) for estraction or curber dusts generated 2: methers aliant from the stractic piper should be a minimum of 4-10 mis (60)-2000 (min) for estraction or curber dusts generated 2: methers aliant from the stractic piper should be a minimum of 4-10 mis (60)-2000 (min) for estraction or curber dusts generated 2: methers aliant from the stractic piper should be an indicate. Hudividual protective equipment • Safety glasses with idea shields. • Commail depaids have the strate of mass of material should be arealed in advino analy indicate should be arealed in advino analyzed with dusts and anonent, descripting the warming of the safes of relations to minute and advino analyzed be made and material should be arealed in advino analyzed with dusts and the should be arealed in advino and advinoption on use, should be arealed in advino analyzed with the should be arealed in advino and advinoption on use, should be arealed and advinoption of the advinoption of the dusts of the should be arealed in advino and advinoption on the should be arealed in advinoption of a should be arealed in advinoption of the advinoptio | · · | | Issue Date: 10/07/2023 |
|---|-------------------------------------|--|---|
| generally decireases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction class of the contaminating sources. The air velocity at the extraction is not rowardie, should be an informan d +10 mix (800-2000 fmin) for extraction dust generated 2 metres distant from the extraction point. Other mechanical consolventions, producing performance deficits within the extraction apparatuse, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used. Individual protection measures, such as performing the system state installed or used. Suffery glasses with side shinkls. Chemical geographics (ASN22 3137.1, EV166 or national equivalent)! Eye and face protection discusses with side shinkls. Chemical geographics (ASN22 3137.1, EV166 or national equivalent)! Chemical geographics (ASN22 3137.1, EV166 or national equivalent)! Eye and face protection discusses with side shinkls. Chemical geographics (ASN22 3137.1, EV166 or national equivalent)! Chemical geographics (ASN22 3137.1, EV166 or national equivalent)! Madical and first-approxeminal broad dub be tradeed for the mervice and an account of juty sepremect. Madical and first-approxeminal broad dub be tradeed for the mervice in a science approaches or the shifts and account only depend on the material, but also on further marks of quality which vary form manufacture. The should be manufacture on the science shifts and account on in the selection of gloves and has to be observed in | Version No: 2.2 | Benzyl (4R)-5-amino-4-[[(2S)-2-[(2-methylpropan-2-yl)oxycarbonylamino]propanoyl]amino]- | |
| measures, such as personal protection Solid by Bases with aids shields. Even and face protection - Safety glasses with aids shields. Even and face protection - Safety glasses with aids shields. Even and face protection - Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate infrants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a retrieve of lens absorption and adsorption for the class of chemicals in use and an account of injuy experience. Medical and first-aid personnel should be trained in their removal and suitable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. (CDC NIOSH Current Intelligence Bulletin 59]. Skin protection See Hand protection below The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be deserved whem making a final choice. Vertice with increases and the selection of gloves include: increase and duration of orienter. - Herosein Angloves include: increase and basher to be checked prior to the application. The exact break through time of their typresate lease affected in advance with a protection diglo | | generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air sp extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The extraction fan, for example, should be a minimum of 4-10 m/s (800-2000 f/min) for extraction of crusher dusts g distant from the extraction point. Other mechanical considerations, producing performance deficits within the ex apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction | beed at the a air velocity at the generated 2 metres straction |
| Eye and face protection Contail lenses may pose a special hazard; soft contact lenses may packorh and concentrate initiants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and lins: adj personnel should be trained in their mervox all and suitable equipment should be really available. In the event of chemical exposure, begin eye irrigation immediately and removal and suitable equipment should be really available. In the event of chemical exposure, begin eye irrigation immediately and removal in a class on particibable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a class environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59]. Skin protection See Hand protection of suitable gloves does not only depend on the material, but aliso on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Hands/feet protection Suitability of glove type is dependent on usage. Important factors in the selection of gloves include: infequency and duration of contact, ethernical is appressing to exact start than 0. Suitability of glove prive preseted contact may occur, a glove with a protection class of 5 or higher (freakthrough time greater than 240 minutes according to EN 374, ASNZS 2161.1 o | measures, such personal protecti | | |
| Hands/feet protection The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed molisturiser is recommended. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: i frequency and duration of contact, chemical resistance of glove material, glove thickness and i doxteritly Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.10 or national equivalent). When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use. Contaminated gloves should be replaced. As defined in ASTM F739-96 in any applic | Eye and face protecti | Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent] Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A writt document, describing the wearing of lenses or restrictions on use, should be created for each workplace or include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicab be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment or | task. This should y experience. available. In the ble. Lens should |
| Hands/feet protection manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: frequency and duration of contact, chemical resistance of glove material, glove thickness and dexterity Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent). When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.1.0 r national equivalent) is recommended. Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use. Contaminated gloves should be replaced. A defined in ASTM F.739-96 in any application, gloves are rated as: Excellent when breakthrough time > 20 min Fair when breakthrough time > 20 min Fair when breakthrough time > 20 min Foor when glove material degrades | Skin protecti | on See Hand protection below | |
| Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example: Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of. Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended. Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present. polychloroprene. nitrile rubber. butyl rubber. fluorocaoutchouc. | Hands/feet protecti | manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves observed when making a final choice. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After usin should be washed and dired thoroughly. Application of a non-perfumed moisturise is recommended. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves includ . frequency and duration of glove material, chemical resistance of glove material, glove thickness and dexterity Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivale. When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (break through time greater 1 according to EN 374, AS/NZS 2161.10.1 or national equivalen) is recommended. Some glove polymer types are less affected by movement and this should be taken into account when consid long-term use. Contaminated gloves should be replaced. As defined in ASTM F-739-96 in any application, gloves are rated as: Excellent when breakthrough time < 20 min Fair when breakthrough time < 20 min For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended. It should be emphasised that glove thickness typically greater than 0.35 mm, are recommended. It should be emphasised that glove thickness typically greater than 0.45 mm, are recommended. For general applications, gloves with a thickness typically greater than 0.45 mm, are recommended. It should be emphasised that glove thac | e glove material e and has to be g gloves, hands le: ent). ukthrough time than 60 minutes ering gloves for ic chemical, as the glove selection refore, the glove for the task. s. For example: However, these en disposed of. k i.e. where there Application of a |

Page 7 of 11

Benzyl (4R)-5-amino-4-[[(2S)-2-[(2-methylpropan-2-yl)oxycarbonylamino]propanoyl]amino]-5-oxopentanoa

| | Overalls. |
|------------------|-------------------------------|
| | P.V.C apron. |
| Other protection | Barrier cream. |
| | Skin cleansing cream. |
| | Eye wash unit. |
| | |

Respiratory protection

Type -P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|------------------------------------|----------------------|----------------------|------------------------|
| up to 10 x ES | P1 Air-line* | - | PAPR-P1 - |
| up to 50 x ES | Air-line** | P2 | PAPR-P2 |
| up to 100 x ES | - | P3 | - |
| | | Air-line* | - |
| 100+ x ES | - | Air-line** | PAPR-P3 |

* - Negative pressure demand ** - Continuous flow

A(AII classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

· Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.

• The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).

• Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.

Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.

• Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)

· Use approved positive flow mask if significant quantities of dust becomes airborne.

· Try to avoid creating dust conditions.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

| Appearance | Not Available | | | |
|--|---------------|--|----------------|--|
| Physical state | Solid | Relative density (Water = 1) | Not Available | |
| Odour | Not Available | Partition coefficient n-octanol / water | Not Available | |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | Not Available | |
| pH (as supplied) | Not Available | Decomposition temperature (°C) | Not Available | |
| Melting point / freezing point (°C) | Not Available | Viscosity (cSt) | Not Available | |
| Initial boiling point and boiling range (°C) | Not Available | Molecular weight (g/mol) | Not Available | |
| Flash point (°C) | Not Available | Taste | Not Available | |
| Evaporation rate | Not Available | Explosive properties | Not Available | |
| Flammability | Not Available | Oxidising properties | Not Available | |
| Upper Explosive Limit (%) | Not Available | Surface Tension (dyn/cm or mN/m) | Not Applicable | |
| Lower Explosive Limit (%) | Not Available | Volatile Component (%vol) | Not Available | |
| Vapour pressure (kPa) | Not Available | Gas group | Not Available | |

Version No: 2.2 Benzyl (4R)-5-amino-4-[[(2S)-2-[(2-methylpropan-2-yl)oxycarbonylamino]propanoyl]amino]-5-oxopentanoa

| Solubility in water | Not Available | pH as a solution (1%) | Not Available |
|--------------------------|---------------|-----------------------|---------------|
| Vapour density (Air = 1) | Not Available | VOC g/L | Not Available |

SECTION 10 Stability and reactivity

| Reactivity | See section 7 |
|-------------------------------------|---|
| Chemical stability | Product is considered stable and hazardous polymerisation will not occur. |
| Possibility of hazardous reactions | See section 7 |
| Conditions to avoid | See section 7 |
| Incompatible materials | See section 7 |
| Hazardous decomposition products | See section 5 |

SECTION 11 Toxicological information

Information on toxicological effects

| Inhaled | The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. |
|--------------|---|
| Ingestion | The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. |
| Skin Contact | The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. |
| Eye | This material can cause eye irritation and damage in some persons. |
| Chronic | Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course. |

Legend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

| Acute Toxicity | × | Carcinogenicity | × |
|-----------------------------------|---|--------------------------|---|
| Skin Irritation/Corrosion | ✓ | Reproductivity | × |
| Serious Eye Damage/Irritation | × | STOT - Single Exposure | • |
| Respiratory or Skin sensitisation | × | STOT - Repeated Exposure | × |
| Mutagenicity | × | Aspiration Hazard | × |

Legend: X − Data either not available or does not fill the criteria for classification ✓ − Data available to make classification

SECTION 12 Ecological information

Toxicity

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) -Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data Version No: 2.2

Benzyl (4R)-5-amino-4-[[(2S)-2-[(2-methylpropan-2-yl)oxycarbonylamino]propanoyl]amino]-5-oxopentanoa

| Ingredient | Persistence: Water/Soil | Persistence: Air |
|--|-------------------------|------------------|
| Benzyl (4R)-5-amino-4-[[(2S)-2-[(2- methylpropan- 2-yl)oxycarbonylamino]propanoyl]amino]- 5-oxopentanoa | HIGH | HIGH |

Bioaccumulative potential

| Ingredient | Bioaccumulation |
|--|-----------------------|
| Benzyl (4R)-5-amino-4-[[(2S)-2-[(2- methylpropan- 2-yl)oxycarbonylamino]propanoyl]amino]- 5-oxopentanoa | LOW (LogKOW = 1.0693) |

Mobility in soil

| Ingredient | Mobility |
|--|------------------|
| Benzyl (4R)-5-amino-4-[[(2S)-2-[(2- methylpropan- 2-yl)oxycarbonylamino]propanoyl]amino]- 5-oxopentanoa | LOW (KOC = 3834) |

SECTION 13 Disposal considerations

Waste treatment methods

| Product / Packaging disposal Consult State Land Waste Management Authority for disposal. Bury residue in an authorised landfill. Recycle containers if possible, or dispose of in an authorised landfill. |
|--|
|--|

SECTION 14 Transport information

Labels Required

Marine Pollutant NO

Land transport (ADR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Inland waterways transport (ADN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

| Product name | Group |
|--|---------------|
| Benzyl (4R)-5-amino-4-[[(2S)-2-[(2- methylpropan- 2-yl)oxycarbonylamino]propanoyl]amino]- 5-oxopentanoa | Not Available |

Transport in bulk in accordance with the IGC Code

| Product name | Ship Type |
|--|---------------|
| Benzyl (4R)-5-amino-4-[[(2S)-2-[(2- methylpropan- 2-yl)oxycarbonylamino]propanoyl]amino]- 5-oxopentanoa | Not Available |

Benzyl (4R)-5-amino-4-[[(2S)-2-[(2-methylpropan-2-yl)oxycarbonylamino]propanoyl]amino]-5-oxopentanoa

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

Benzyl (4R)-5-amino-4-[[(2S)-2-[(2-methylpropan-2-yl)oxycarbonylamino]propanoyl]amino]-5-oxopentanoa is found on the following regulatory lists
Not Applicable

National Inventory Status

| National Inventory | Status |
|--|--|
| Australia - AIIC / Australia Non-Industrial Use | No (Benzyl (4R)-5-amino-4-[[(2S)-2-[(2-methylpropan-2-yl)oxycarbonylamino]propanoyl]amino]-5-oxopentanoa) |
| Canada - DSL | No (Benzyl (4R)-5-amino-4-[[(2S)-2-[(2-methylpropan-2-yl)oxycarbonylamino]propanoyl]amino]-5-oxopentanoa) |
| Canada - NDSL | No (Benzyl (4R)-5-amino-4-[[(2S)-2-[(2-methylpropan-2-yl)oxycarbonylamino]propanoyl]amino]-5-oxopentanoa) |
| China - IECSC | No (Benzyl (4R)-5-amino-4-[[(2S)-2-[(2-methylpropan-2-yl)oxycarbonylamino]propanoyl]amino]-5-oxopentanoa) |
| Europe - EINEC / ELINCS / NLP | No (Benzyl (4R)-5-amino-4-[[(2S)-2-[(2-methylpropan-2-yl)oxycarbonylamino]propanoyl]amino]-5-oxopentanoa) |
| Japan - ENCS | No (Benzyl (4R)-5-amino-4-[[(2S)-2-[(2-methylpropan-2-yl)oxycarbonylamino]propanoyl]amino]-5-oxopentanoa) |
| Korea - KECI | No (Benzyl (4R)-5-amino-4-[[(2S)-2-[(2-methylpropan-2-yl)oxycarbonylamino]propanoyl]amino]-5-oxopentanoa) |
| New Zealand - NZIoC | No (Benzyl (4R)-5-amino-4-[[(2S)-2-[(2-methylpropan-2-yl)oxycarbonylamino]propanoyl]amino]-5-oxopentanoa) |
| Philippines - PICCS | No (Benzyl (4R)-5-amino-4-[[(2S)-2-[(2-methylpropan-2-yl)oxycarbonylamino]propanoyl]amino]-5-oxopentanoa) |
| USA - TSCA | No (Benzyl (4R)-5-amino-4-[[(2S)-2-[(2-methylpropan-2-yl)oxycarbonylamino]propanoyl]amino]-5-oxopentanoa) |
| Taiwan - TCSI | No (Benzyl (4R)-5-amino-4-[[(2S)-2-[(2-methylpropan-2-yl)oxycarbonylamino]propanoyl]amino]-5-oxopentanoa) |
| Mexico - INSQ | No (Benzyl (4R)-5-amino-4-[[(2S)-2-[(2-methylpropan-2-yl)oxycarbonylamino]propanoyl]amino]-5-oxopentanoa) |
| Vietnam - NCI | No (Benzyl (4R)-5-amino-4-[[(2S)-2-[(2-methylpropan-2-yl)oxycarbonylamino]propanoyl]amino]-5-oxopentanoa) |
| Russia - FBEPH | No (Benzyl (4R)-5-amino-4-[[(2S)-2-[(2-methylpropan-2-yl)oxycarbonylamino]propanoyl]amino]-5-oxopentanoa) |
| Legend: | Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration. |

SECTION 16 Other information

| Revision Date | 10/07/2023 |
|---------------|------------|
| Initial Date | 10/07/2023 |

SDS Version Summary

| Version | Date of Update | Sections Updated |
|---------|-------------------|---|
| 1.2 | 10/07/2023 | CAS Number, Hazards identification - Classification, Composition / information on ingredients - Ingredients, Korean MSDS Number, Identification of the substance / mixture and of the company / undertaking - Supplier Information, Identification of the substance / mixture and of the company / undertaking - Synonyms |

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

Definitions and abbreviations

PC - TWA: Permissible Concentration-Time Weighted Average

PC - STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

Benzyl (4R)-5-amino-4-[[(2S)-2-[(2-methylpropan-2-yl)oxycarbonylamino]propanoyl]amino]-5-oxopentanoa

TEEL: Temporary Emergency Exposure Limit. IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value **BCF: BioConcentration Factors BEI: Biological Exposure Index** AIIC: Australian Inventory of Industrial Chemicals **DSL:** Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

| Classification according to regulation (EC) No 1272/2008 [CLP] and amendments | Classification Procedure |
|---|--------------------------|
| Acute Toxicity (Dermal) Category 4, H312 | Expert judgement |
| Acute Toxicity (Inhalation) Category 4, H332 | Expert judgement |
| Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, H335 | Expert judgement |
| Acute Toxicity (Oral) Category 4, H302 | Expert judgement |
| Skin Corrosion/Irritation Category 2, H315 | Expert judgement |
| Serious Eye Damage/Eye Irritation Category 2, H319 | Expert judgement |

Powered by AuthorITe, from Chemwatch.