

# (2R)-2-Methylpiperazine Apollo Scientific

Part Number: **OR5889** Version No: **2.2** Safety Data Sheet Chemwatch Hazard Alert Code: 3

Issue Date: **18/05/2023** Print Date: **18/05/2023** S.GHS.GB-NIR.EN

#### SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### **Product Identifier**

Product name	(2R)-2-Methylpiperazine
Chemical Name	2-methylpiperazine
Synonyms	Not Available
Proper shipping name	FLAMMABLE SOLID, CORROSIVE, ORGANIC, N.O.S.
Other means of identification	Not Available
CAS number	75336-86-6*

#### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Not

s Not Available

# Details of the manufacturer or supplier of the safety data sheet

Registered company name	Apollo Scientific	Apollo Scientific Itd
Address	Whitefield Road, Bredbury SK62QR United Kingdom	Whitefield Road Not Available SK6 2QR United Kingdom (NI)
Telephone	01614060505	+44(0) 161 406 0505
Fax	0161 406 0506	Not Available
Website	http://www.apolloscientific.co.uk/	apolloscientific.co.uk
Email	sales@apolloscientific.co.uk	sales@apolloscientific.co.uk

# Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	Not Available
Other emergency telephone numbers	Not Available

# **SECTION 2 Hazards identification**

# Classification of the substance or mixture

Classification according to regulation (EC) No 1272/2008 [CLP] and amendments <sup>[1]</sup>	H314 - Skin Corrosion/Irritation Category 1B, H334 - Sensitisation (Respiratory) Category 1, H318 - Serious Eye Damage/Eye Irritation Category 1, H228 - Flammable Solids Category 1
Legend:	1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

#### Label elements



Signal word

#### Hazard statement(s)

H314	Causes severe skin burns and eye damage.	
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
H228	Flammable solid.	

## Precautionary statement(s) Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume.
P264	Wash all exposed external body areas thoroughly after handling.
P280	Wear protective gloves, protective clothing, eye protection and face protection.
P284	[In case of inadequate ventilation] wear respiratory protection.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment.

#### Precautionary statement(s) Response

P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor/physician/first aider.
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor/physician/first aider.
P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam to extinguish.
P363	Wash contaminated clothing before reuse.

# Precautionary statement(s) Storage

P405 Store locked up.

#### Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

# **SECTION 3 Composition / information on ingredients**

#### Substances

CAS No	%[weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	SCL / M-Factor
Not Available	100	(2R)-2- Methylpiperazine	Skin Corrosion/Irritation Category 1B, Sensitisation (Respiratory) Category 1, Serious Eye Damage/Eye Irritation Category 1, Flammable Solids Category 1; H314, H334, H318, H228 <sup>[1]</sup>	Not Available

1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L; \* EU IOELVs Legend: available; [e] Substance identified as having endocrine disrupting properties

#### Mixtures

See section above for composition of Substances

## Description of first aid measures

Eye Contact	<ul> <li>If this product comes in contact with the eyes:</li> <li>Immediately hold eyelids apart and flush the eye continuously with running water.</li> <li>Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.</li> <li>Transport to hospital or doctor without delay.</li> <li>Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
Skin Contact	<ul> <li>If skin or hair contact occurs:</li> <li>Immediately flush body and clothes with large amounts of water, using safety shower if available.</li> <li>Quickly remove all contaminated clothing, including footwear.</li> <li>Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.</li> <li>Transport to hospital, or doctor.</li> </ul>
Inhalation	<ul> <li>If fumes or combustion products are inhaled remove from contaminated area.</li> <li>Lay patient down. Keep warm and rested.</li> <li>Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>Transport to hospital, or doctor, without delay.</li> <li>Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema.</li> <li>Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs).</li> <li>As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested.</li> <li>Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered.</li> <li>This must definitely be left to a doctor or person authorised by him/her. (ICSC13719)</li> </ul>
Ingestion	<ul> <li>For advice, contact a Poisons Information Centre or a doctor at once.</li> <li>Urgent hospital treatment is likely to be needed.</li> <li>If swallowed do NOT induce vomiting.</li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>Observe the patient carefully.</li> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>Transport to hospital or doctor without delay.</li> </ul>

#### Indication of any immediate medical attention and special treatment needed

Depending on the degree of exposure, periodic medical examination is indicated. The symptoms of lung oedema often do not manifest until a few hours have passed and they are aggravated by physical effort. Rest and medical observation is therefore essential. Immediate administration of an appropriate spray, by a doctor or a person authorised by him/her should be considered. (ICSC24419/24421

#### **SECTION 5 Firefighting measures**

#### Extinguishing media

For **SMALL FIRES**: Dry chemical, CO2, water spray or foam. For **LARGE FIRES**: Water-spray, fog or foam.

## Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.
----------------------	-------------

# Advice for firefighters

Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>May be violently or explosively reactive.</li> <li>Wear full body protective clothing with breathing apparatus.</li> <li>Prevent, by any means available, spillage from entering drains or water course.</li> <li>Fight fire from a safe distance, with adequate cover.</li> <li>If safe, switch off electrical equipment until vapour fire hazard removed.</li> </ul>

	<ul> <li>Use water delivered as a fine spray to control the fire and cool adjacent area.</li> <li>Avoid spraying water onto liquid pools.</li> <li>Do not approach containers suspected to be hot.</li> <li>Cool fire exposed containers with water spray from a protected location.</li> <li>If safe to do so, remove containers from path of fire.</li> </ul>
Fire/Explosion Hazard	<ul> <li>Flammable solid which burns and propagates flame easily, even when partly wetted with water.</li> <li>Any source of ignition, i.e. friction, heat, sparks or flame, may cause fire or explosion.</li> <li>May burn fiercely</li> <li>May form explosive mixtures with air.</li> <li>May REIGNITE after fire is extinguished.</li> <li>Containers may explode on heating.</li> <li>Solids may melt and flow when heated or involved in a fire.</li> <li>Runoff may pollute waterways.</li> <li>Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust may burn rapidly and fiercely if ignited.</li> <li>Dry dust can be charged electrostatically by turbulence, pneumatic transport, pouring, in exhaust ducts and during transport, thereby providing a source of ignition.</li> <li>Decomposition products may be irritating, poisonous or corrosive.</li> </ul>

#### **SECTION 6 Accidental release measures**

# Personal precautions, protective equipment and emergency procedures

See section 8

## **Environmental precautions**

See section 12

## Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material.</li> <li>Check regularly for spills and leaks.</li> <li>Remove all ignition sources.</li> <li>DO NOT touch or walk through spilled material.</li> <li>Clean up all spills immediately.</li> <li>Avoid contact with skin and eyes.</li> <li>Prevent dust cloud.</li> <li>With clean shovel (preferably non-sparking) place material into clean, dry container and cover loosely.</li> <li>Move containers from spill area.</li> <li>Control personal contact with the substance, by using protective equipment.</li> </ul>
Major Spills	<ul> <li>Clear area of personnel and move upwind.</li> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>DO NOT touch or walk through spilled material.</li> <li>Wear full protective clothing and breathing apparatus.</li> <li>May be violently or explosively reactive.</li> <li>Prevent, by any means available, spillage from entering drains or water course.</li> <li>No smoking, naked lights or ignition sources.</li> <li>Increase ventilation.</li> <li>Stop leak if safe to do so.</li> <li>Contain or cover with sand, earth or vermiculite.</li> <li>Use only spark-free shovels and explosion proof equipment.</li> <li>Collect recoverable product into labelled containers for recycling.</li> <li>Collect solid residues and seal in labelled drums for disposal.</li> <li>Wash area with water and dike for later disposal; prevent runoff into drains.</li> <li>After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.</li> <li>If contamination of drains or waterways occurs, advise emergency services.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## **SECTION 7 Handling and storage**

## Precautions for safe handling

Safe handling

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of overexposure occurs.

	<ul> <li>Use in a well-ventilated area.</li> <li>Prevent concentration in hollows and sumps.</li> <li>DO NOT enter confined spaces until atmosphere has been checked.</li> <li>DO NOT allow material to contact humans, exposed food or food utensils.</li> <li>Avoid smoking, naked lights or ignition sources.</li> <li>When handling, DO NOT eat, drink or smoke.</li> <li>Avoid contact with incompatible materials.</li> </ul>
	<ul> <li>Keep containers securely sealed when not in use.</li> <li>Avoid physical damage to containers.</li> <li>Always wash hands with soap and water after handling.</li> </ul>
	<ul> <li>Working clothes should be laundered separately. Launder contaminated clothing before re-use.</li> <li>Use good occupational work practice.</li> </ul>
	<ul> <li>Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.</li> </ul>
	FOR MINOR QUANTITIES:
	<ul> <li>Store in an indoor fireproof cabinet or in a room of noncombustible construction.</li> </ul>
	Provide adequate portable fire-extinguishers in or near the storage area. FOR PACKAGE STORAGE:
	<ul> <li>Store in original containers in approved flame-proof area.</li> </ul>
	<ul> <li>No smoking, naked lights, heat or ignition sources.</li> </ul>
	<ul> <li>DO NOT store in pits, depressions, basements or areas where vapours may be trapped.</li> </ul>
	Keep containers securely sealed.
Other information	Store away from incompatible materials in a cool, dry, well ventilated area.
	Protect containers against physical damage and check regularly for leaks.
	Protect containers from exposure to weather and from direct sunlight unless: (a) the packages are of metal or plastic
	construction; (b) the packages are securely closed are not opened for any purpose while in the area where they are stored
	and (c) adequate precautions are taken to ensure that rain water, which might become contaminated by the dangerous
	goods, is collected and disposed of safely.
	Ensure proper stock-control measures are maintained to prevent prolonged storage of dangerous goods.
	Observe manufacturer's storage and handling recommendations contained within this SDS.

# Conditions for safe storage, including any incompatibilities

Suitable container	For low viscosity materials and solids: Drums and jerricans must be of the non-removable head type. Where a can is to be used as an inner package, the can must have a screwed enclosure. For materials with a viscosity of at least 2680 cSt. (23 deg. C): Removable head packaging and cans with friction closures may be used. - Where combination packages are used, there must be sufficient inert absorbent material to absorb completely any leakage that may occur, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.
Storage incompatibility	<ul> <li>Air Sensitive</li> <li>Hygroscopic</li> <li>Store under argon</li> </ul>

# **SECTION 8 Exposure controls / personal protection**

## **Control parameters**

Occupational Exposure Lim	its (OEL)			
INGREDIENT DATA				
Not Available				
Emergency Limits				
Ingredient	TEEL-1	TEEL-2		TEEL-3
(2R)-2-Methylpiperazine	Not Available	Not Available		Not Available
Ingredient	Original IDLH		Revised IDLH	
(2R)-2-Methylpiperazine	Not Available		Not Available	

## **Exposure controls**

Appropriate engineering controls	Engineering controls are used to remove a hazard or place engineering controls can be highly effective in protecting we provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job acti Enclosure and/or isolation of emission source which keeps that strategically "adds" and "removes" air in the work envir designed properly. The design of a ventilation system must Employers may need to use multiple types of controls to pr Local exhaust ventilation usually required. If risk of overexp obtain adequate protection. Supplied-air type respirator ma- ensure adequate protection. Supplied-air type respirator ma- ensure adequate protection. An approved self contained breathing apparatus (SCBA) m Provide adequate ventilation in warehouse or closed storag "escape" velocities which, in turn, determine the "capture ve- contaminant. Type of Contaminant: solvent, vapours, degreasing etc., evaporating from tank ( aerosols, fumes from pouring operations, intermittent cont welding, spray drift, plating acid fumes, pickling (released direct spray, spray painting in shallow booths, drum filling, (active generation into zone of rapid air motion) grinding, abrasive blasting, tumbling, high speed wheel ge into zone of very high rapid air motion). Within each range the appropriate value depends on: Lower end of the range 1: Room air currents minimal or favourable to capture 2: Contaminants of low toxicity or of nuisance value only. 3: Intermittent, low production. 4: Large hood or large air mass in motion Simple theory shows that air velocity falls rapidly with distar generally decreases with the square of distance from the ex- extraction point should be adjusted, accordingly, after refer- extraction point should b	vity or process is done to reduce the risk.         a selected hazard "physically" away from the wo         ronment. Ventilation can remove or dilute an air c         match the particular process and chemical or co         event employee overexposure.         posure exists, wear approved respirator. Correct f         may be required in special circumstances. Correct fing         ge area. Air contaminants generated in the workp         elocities" of fresh circulating air required to effect         in still air).         tainer filling, low speed conveyer transfers,         at low velocity into zone of active generation)         conveyer loading, crusher dusts, gas discharge         enerated dusts (released at high initial velocity         Upper end of the range         1: Disturbing room air currents         2: Contaminants of high toxicity         3: High production, heavy use         4: Small hood-local control only         nce away from the opening of a simple extraction xtraction point (in simple cases). Therefore the ai         ence to distance from the contaminating source. 's (200-400 f/min) for extraction of solvents gener	rinteractions to rker and ventilation ontaminant if intaminant in use. it is essential to t is essential to lace possess varying vely remove the Air Speed: 0.25-0.5 m/s (50-100 f/min.) 0.5-1 m/s (100-200 f/min.) 1-2.5 m/s (200-500 f/min.) 2.5-10 m/s (500-2000 f/min.) pipe. Velocity r speed at the The air velocity at the ated in a tank 2 ithin the extraction
Individual protection measures, such as personal protective	Por large scale or continuous use:     Spark-free, earthed ventilation system, venting directly     Provide dust collectors with explosion vents	to the outside and separate from usual ventilation	n systems
equipment	<ul> <li>Chemical goggles.</li> <li>Full face shield may be required for supplementary but</li> <li>Contact lenses may pose a special hazard; soft contact document, describing the wearing of lenses or restriction include a review of lens absorption and adsorption for th Medical and first-aid personnel should be trained in the event of chemical exposure, begin eye irrigation immed be removed at the first signs of eye redness or irritation have washed hands thoroughly. [CDC NIOSH Current I</li> </ul>	t lenses may absorb and concentrate irritants. A wons on use, should be created for each workplace he class of chemicals in use and an account of in ir removal and suitable equipment should be reactilately and remove contact lens as soon as praction - lens should be removed in a clean environment	or task. This should jury experience. dily available. In the cable. Lens should t only after workers
Skin protection	See Hand protection below		
Hands/feet protection	<ul> <li>Wear physical protective gloves, e.g. leather.</li> <li>Wear safety footwear.</li> </ul>		

See Other protection below

Body protection

Other protection	<ul> <li>Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.</li> <li>For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets).</li> <li>Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds. Electrical resistance must range between 0 to 500,000 ohms. Conductive shoes should be stored in lockers close to the room in which they are worn. Personnel who have been issued conductive footwear should not wear them from their place of work to their homes and return.</li> <li>Overalls.</li> <li>PVC Apron.</li> <li>PVC protective suit may be required if exposure severe.</li> <li>Eyewash unit.</li> <li>Ensure there is ready access to a safety shower.</li> </ul>
------------------	---

#### **Respiratory protection**

Type -P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	P1 Air-line*		PAPR-P1 -
up to 50 x ES	Air-line**	P2	PAPR-P2
up to 100 x ES	-	P3	-
		Air-line*	-
100+ x ES	-	Air-line**	PAPR-P3

\* - Negative pressure demand \*\* - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

## **SECTION 9** Physical and chemical properties

## Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Solid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	86-93	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	155-156	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Not Available	pH as a solution (1%)	Not Available

Vapour density (Air = 1)

Not Available

VOC g/L

Not Available

# **SECTION 10 Stability and reactivity**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

# **SECTION 11 Toxicological information**

# Information on toxicological effects

Inhaled	The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.
Ingestion	The material can produce chemical burns within the oral cavity and gastrointestinal tract following ingestion. The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	The material can produce chemical burns following direct contact with the skin. Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	The material can produce chemical burns to the eye following direct contact. Vapours or mists may be extremely irritating. If applied to the eyes, this material causes severe eye damage.
Chronic	Repeated or prolonged exposure to corrosives may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue. Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS.
	Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

Acute Toxicity	X Carcinogenicity	×
Skin Irritation/Corrosion	✓ Reproductivity	×
Serious Eye Damage/Irritation	✓ STOT - Single Exposure	×
Respiratory or Skin sensitisation	✓ STOT - Repeated Exposure	×
Mutagenicity	X Aspiration Hazard	×

end: X - Data either not available or does not fill the criteria for classification
 - Data available to make classification

# **SECTION 12 Ecological information**

Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity
	4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) -
	Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

DO NOT discharge into sewer or waterways.

# Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air	
	No Data available for all ingredients	No Data available for all ingredients	

## **Bioaccumulative potential**

Ingredient	Bioaccumulation	
	No Data available for all ingredients	

## Mobility in soil

Ingredient	Mobility	
	No Data available for all ingredients	

## **SECTION 13 Disposal considerations**

#### Waste treatment methods

Product / Packaging disposal	<ul> <li>Recycle wherever possible.</li> <li>Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</li> <li>Treat and neutralise at an approved treatment plant. Treatment should involve: Mixing or slurrying in water; Neutralisation followed by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material)</li> <li>Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.</li> </ul>
---------------------------------	---

# **SECTION 14 Transport information**

Marine Pollutant

## Labels Required



# Land transport (ADR-RID)

UN number or ID number	2925		
UN proper shipping name	FLAMMABLE SOLID, O	CORROSIVE, ORGANIC, N.O.S.	
Transport hazard class(es)	Class 4.1 Subsidiary risk 8		
Packing group	III		
Environmental hazard	Not Applicable		
Special precautions for user	Hazard identification Classification code Hazard Label Special provisions Limited quantity Tunnel Restriction Co	FC1       4.1 +8       274       5 kg	

# Air transport (ICAO-IATA / DGR)

UN number	2925			
UN proper shipping name	Flammable solid, corrosive, organic, n.o.s. *			
Transport hazard class(es)	ICAO/IATA Class	4.1		
	ICAO / IATA Subrisk	8		
	ERG Code			
Packing group	111			
Environmental hazard	Not Applicable			
	Special provisions		A3 A803	
	Cargo Only Packing Instructions		449	
	Cargo Only Maximum Qty / Pack		100 kg	
Special precautions for user	Passenger and Cargo Packing Instructions		446	
usei	Passenger and Cargo Maximum Qty / Pack		25 kg	
	Passenger and Cargo Limited Quantity Packing Instructions		Y442	
	Passenger and Cargo Limited Maximum Qty / Pack		5 kg	

## Sea transport (IMDG-Code / GGVSee)

UN number	2925		
UN proper shipping name	FLAMMABLE SOLID	, CORROSIVE, ORGANIC, N.O.S.	
Transport hazard class(es)	IMDG Class 4 IMDG Subrisk 8		
Packing group	II		
Environmental hazard	Not Applicable		
Special precautions for user	EMS Number Special provisions Limited Quantities	F-A, S-G 223 274 5 kg	

# Inland waterways transport (ADN)

UN number	2925		
UN proper shipping name	FLAMMABLE SOLID, CORROSIVE, ORGANIC, N.O.S.		
Transport hazard class(es)	4.1 8		
Packing group	II		
Environmental hazard	Not Applicable		
Special precautions for user	Classification codeFC1Special provisions274Limited quantity5 kgEquipment requiredPP, EPFire cones number0		

# Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

## Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
(2R)-2-Methylpiperazine	Not Available

# Transport in bulk in accordance with the IGC Code

Product name	Ship Type
(2R)-2-Methylpiperazine	Not Available

#### **SECTION 15 Regulatory information**

## Safety, health and environmental regulations / legislation specific for the substance or mixture

#### **National Inventory Status**

National Inventory	Status	
Australia - AIIC / Australia Non-Industrial Use	No ((2R)-2-Methylpiperazine)	
Canada - DSL	No ((2R)-2-Methylpiperazine)	
Canada - NDSL	No ((2R)-2-Methylpiperazine)	
China - IECSC	No ((2R)-2-Methylpiperazine)	
Europe - EINEC / ELINCS / NLP	No ((2R)-2-Methylpiperazine)	
Japan - ENCS	No ((2R)-2-Methylpiperazine)	
Korea - KECI	No ((2R)-2-Methylpiperazine)	
New Zealand - NZIoC	No ((2R)-2-Methylpiperazine)	
Philippines - PICCS	No ((2R)-2-Methylpiperazine)	
USA - TSCA	No ((2R)-2-Methylpiperazine)	
Taiwan - TCSI	Yes	
Mexico - INSQ	No ((2R)-2-Methylpiperazine)	
Vietnam - NCI	Yes	
Russia - FBEPH	No ((2R)-2-Methylpiperazine)	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.	

#### **SECTION 16 Other information**

Revision Date	18/05/2023
Initial Date	18/05/2023

#### **SDS Version Summary**

Version	Date of Update	Sections Updated
1.2	18/05/2023	Toxicological information - Acute Health (eye), Physical and chemical properties - Appearance, CAS Number, Toxicological information - Chronic Health, Hazards identification - Classification, Composition / information on ingredients - Ingredients, Identification of the substance / mixture and of the company / undertaking - Supplier Information, Identification of the substance / mixture and of the company / undertaking - Synonyms

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

- EN 166 Personal eye-protection
- EN 340 Protective clothing
- EN 374 Protective gloves against chemicals and micro-organisms
- EN 13832 Footwear protecting against chemicals
- EN 133 Respiratory protective devices

#### **Definitions and abbreviations**

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit。 IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF<sup>-</sup> BioConcentration Factors **BEI: Biological Exposure Index** AIIC: Australian Inventory of Industrial Chemicals DSL: Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

#### Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	Classification Procedure
Skin Corrosion/Irritation Category 1B, H314	Expert judgement
Sensitisation (Respiratory) Category 1, H334	Expert judgement
Serious Eye Damage/Eye Irritation Category 1, H318	Calculation method
Flammable Solids Category 1, H228	Expert judgement

Powered by AuthorITe, from Chemwatch.