

# Diethyl (methoxycarbonylmethyl)phosphonate **Apollo Scientific**

Part Number: OR59465 Version No: 2.2 Safety Data Sheet

Chemwatch Hazard Alert Code: 2

Issue Date: 10/07/2023 Print Date: 10/07/2023 S.GHS.GB-NIR.EN

### SECTION 1 Identification of the substance / mixture and of the company / undertaking

### **Product Identifier**

Product name	Diethyl (methoxycarbonylmethyl)phosphonate	
Chemical Name	ethyl diethylphosphonoacetate	
Synonyms	Not Available	
Chemical formula	C7-H15-O5-P	
Other means of identification	Not Available	
CAS number	1067-74-9*	

### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Not Available

# Details of the manufacturer or supplier of the safety data sheet

Registered company name	Apollo Scientific	Apollo Scientific Itd
Address	Whitefield Road, Bredbury SK62QR United Kingdom	Whitefield Road, Bredbury Cheshire SK6 2QR United Kingdom (NI)
Telephone	01614060505	+44(0) 161 406 0505
Fax	Fax   0161 406 0506   Not Available	
Website	http://www.apolloscientific.co.uk/	apolloscientific.co.uk
Email	sales@apolloscientific.co.uk	sales@apolloscientific.co.uk

# **Emergency telephone number**

Association / Organisation	Not Available
Emergency telephone numbers	Not Available
Other emergency telephone numbers	Not Available

# **SECTION 2 Hazards identification**

# Classification of the substance or mixture

**Classification according to** regulation (EC) No 1272/2008 [CLP] and amendments [1]

H335 - Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, H315 - Skin Corrosion/Irritation Category 2, H319 - Serious Eye Damage/Eye Irritation Category 2

Legend: 1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

# Label elements

Hazard pictogram(s)	
Signal word	Warning

### Hazard statement(s)

H335	May cause respiratory irritation.	
H315	Causes skin irritation.	
H319	Causes serious eye irritation.	

### Precautionary statement(s) Prevention

P271	P271 Use only outdoors or in a well-ventilated area.	
P261	Avoid breathing mist/vapours/spray.	
P280	Wear protective gloves, protective clothing, eye protection and face protection.	
P264	Wash all exposed external body areas thoroughly after handling.	

# Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P312	Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.	
P337+P313	If eye irritation persists: Get medical advice/attention.	
P302+P352	IF ON SKIN: Wash with plenty of water.	
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
P332+P313	If skin irritation occurs: Get medical advice/attention.	
P362+P364	Take off contaminated clothing and wash it before reuse.	

# Precautionary statement(s) Storage

P405	Store locked up.	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.	

### Precautionary statement(s) Disposal

# **SECTION 3 Composition / information on ingredients**

### Substances

CAS No	%[weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	SCL / M-Factor
1067-74-9*	100	<u>Diethyl</u> (methoxycarbonylmethyl)phosphonate	Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 2; H335, H315, H319 [1]	Not Available

Legend: 1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L; \* EU IOELVs available; [e] Substance identified as having endocrine disrupting properties

### Mixtures

See section above for composition of Substances

# Description of first aid measures

Eye Contact	<ul> <li>If this product comes in contact with the eyes:</li> <li>Wash out immediately with fresh running water.</li> <li>Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
Skin Contact	If skin or hair contact occurs: <ul> <li>Flush skin and hair with running water (and soap if available).</li> <li>Seek medical attention in event of irritation.</li> </ul>
Inhalation	<ul> <li>If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>
Ingestion	<ul> <li>Immediately give a glass of water.</li> <li>First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>

# Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **SECTION 5 Firefighting measures**

# Extinguishing media

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

### Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.

# Advice for firefighters

Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves in the event of a fire.</li> <li>Prevent, by any means available, spillage from entering drains or water courses.</li> <li>Use fire fighting procedures suitable for surrounding area.</li> <li>DO NOT approach containers suspected to be hot.</li> <li>Cool fire exposed containers with water spray from a protected location.</li> <li>If safe to do so, remove containers from path of fire.</li> <li>Equipment should be thoroughly decontaminated after use.</li> </ul>
Fire/Explosion Hazard	<ul> <li>Non combustible.</li> <li>Not considered a significant fire risk, however containers may burn.</li> <li>May emit corrosive fumes.</li> </ul>

### **SECTION 6 Accidental release measures**

# Personal precautions, protective equipment and emergency procedures

See section 8

# **Environmental precautions**

See section 12

# Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Clean up all spills immediately.</li> <li>Avoid breathing vapours and contact with skin and eyes.</li> <li>Control personal contact with the substance, by using protective equipment.</li> <li>Contain and absorb spill with sand, earth, inert material or vermiculite.</li> <li>Wipe up.</li> <li>Place in a suitable, labelled container for waste disposal.</li> </ul>
Major Spills	Moderate hazard. <ul> <li>Clear area of personnel and move upwind.</li> </ul>

<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> </ul>
<ul> <li>Wear breathing apparatus plus protective gloves.</li> </ul>
Prevent, by any means available, spillage from entering drains or water course.
Stop leak if safe to do so.
Contain spill with sand, earth or vermiculite.
<ul> <li>Collect recoverable product into labelled containers for recycling.</li> </ul>
<ul> <li>Neutralise/decontaminate residue (see Section 13 for specific agent).</li> </ul>
<ul> <li>Collect solid residues and seal in labelled drums for disposal.</li> </ul>
<ul> <li>Wash area and prevent runoff into drains.</li> </ul>
After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using
If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# **SECTION 7 Handling and storage**

### Precautions for safe handling

Safe handling	<ul> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Avoid contact with moisture.</li> <li>Avoid contact with incompatible materials.</li> <li>When handling, DO NOT eat, drink or smoke.</li> <li>Keep containers securely sealed when not in use.</li> <li>Avoid physical damage to containers.</li> <li>Always wash hands with soap and water after handling.</li> <li>Work clothes should be laundered separately. Launder contaminated clothing before re-use.</li> <li>Use good occupational work practice.</li> <li>Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.</li> </ul>
Other information	

# Conditions for safe storage, including any incompatibilities

Suitable container	<ul> <li>Polyethylene or polypropylene container.</li> <li>Packing as recommended by manufacturer.</li> <li>Check all containers are clearly labelled and free from leaks.</li> </ul>
Storage incompatibility	None known

# **SECTION 8 Exposure controls / personal protection**

### **Control parameters**

# Occupational Exposure Limits (OEL)

(methoxycarbonylmethyl)phosphonate

#### INGREDIENT DATA

Not Available

#### Emergency Limits

Ingredient	TEEL-1	TEEL-2		TEEL-3
Diethyl (methoxycarbonylmethyl)phosphonate	Not Available	Not Available		Not Available
Ingredient	Original IDLH		Revised IDLH	
	Not Available		Not Available	

Occupational Exposure Banding				
Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit		
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.			

sion No: 2.2		Diethyl (methoxycarbonylmethy	l)phosphonat	е	<b>`</b>	
Ingredient		Occupational Exposure Band Rating	Oco	cupational Expo	sure Band Lin	nit
Diethyl (methoxycarbonylmethyl)phos	phonate	E	≤ 0.	1 ppm		
Notes:		Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.				
xposure controls						
	The ba Proces Enclose that str	this high level of protection. sic types of engineering controls are: s controls which involve changing the way a job acti ure and/or isolation of emission source which keeps ategically "adds" and "removes" air in the work envi ed properly. The design of a ventilation system must	a selected hazar onment. Ventilati	d "physically" aw on can remove o	ray from the wo	ontaminant if
	Employ Genera circums Provide varying	vers may need to use multiple types of controls to pr al exhaust is adequate under normal operating cond stances. If risk of overexposure exists, wear approve e adequate ventilation in warehouse or closed storag gescape" velocities which, in turn, determine the "c taminant.	event employee o itions. Local exha ed respirator. Cor ge areas. Air cont	overexposure. ust ventilation marect fit is essentia aminants genera	ay be required i al to obtain adeo tted in the work	in specific quate protection. place possess
	Employ Genera circums Provide varying the cor	vers may need to use multiple types of controls to pr al exhaust is adequate under normal operating cond stances. If risk of overexposure exists, wear approve e adequate ventilation in warehouse or closed storag g "escape" velocities which, in turn, determine the "c	event employee o itions. Local exha ed respirator. Cor ge areas. Air cont	overexposure. ust ventilation marect fit is essentia aminants genera	ay be required i al to obtain adeo tted in the work	in specific quate protection. place possess
	Employ Genera circums Provide varying the con	vers may need to use multiple types of controls to pr al exhaust is adequate under normal operating cond stances. If risk of overexposure exists, wear approve a adequate ventilation in warehouse or closed storag g "escape" velocities which, in turn, determine the "c ntaminant.	event employee o itions. Local exha ed respirator. Cor ge areas. Air cont apture velocities"	overexposure. ust ventilation marect fit is essentia aminants genera	ay be required i al to obtain adeo tted in the work	in specific quate protection. place possess to effectively remove
Appropriate engineering	Employ Genera circums Provide varying the cor Type solver aeros	vers may need to use multiple types of controls to pr al exhaust is adequate under normal operating cond stances. If risk of overexposure exists, wear approve a adequate ventilation in warehouse or closed storag g "escape" velocities which, in turn, determine the "c intaminant.	event employee o itions. Local exha ed respirator. Cor ge areas. Air cont apture velocities" in still air).	overexposure. ust ventilation m rect fit is essentia aminants genera of fresh circulatir	ay be required i al to obtain adeu ited in the work ng air required t ransfers,	in specific quate protection. place possess to effectively remove Air Speed: 0.25-0.5 m/s
Appropriate engineering controls	Employ Genera circums Provide varying the cor Type solver aeros weldir direct	vers may need to use multiple types of controls to pr al exhaust is adequate under normal operating cond stances. If risk of overexposure exists, wear approve e adequate ventilation in warehouse or closed storag rescape" velocities which, in turn, determine the "c staminant. of Contaminant: nt, vapours, degreasing etc., evaporating from tank of ols, fumes from pouring operations, intermittent con	event employee o itions. Local exha ed respirator. Cor ge areas. Air cont apture velocities" in still air). tainer filling, low s at low velocity in	overexposure. ust ventilation marect fit is essentia aminants genera of fresh circulation speed conveyer to to zone of active	ay be required i al to obtain adec tted in the work ng air required t ransfers, generation)	in specific quate protection. place possess to effectively remove Air Speed: 0.25-0.5 m/s (50-100 f/min) 0.5-1 m/s (100-200
	Employ Genera circums Provide varying the cor Type solver aerose weldir direct (active grindir	vers may need to use multiple types of controls to pre- al exhaust is adequate under normal operating condi- stances. If risk of overexposure exists, wear approve a adequate ventilation in warehouse or closed storage "escape" velocities which, in turn, determine the "c intaminant. of Contaminant: int, vapours, degreasing etc., evaporating from tank of ols, fumes from pouring operations, intermittent con ing, spray drift, plating acid fumes, pickling (released spray, spray painting in shallow booths, drum filling.	event employee o itions. Local exha ed respirator. Cor ge areas. Air cont apture velocities" in still air). tainer filling, low s at low velocity int conveyer loading	overexposure. ust ventilation m rect fit is essentia aminants genera of fresh circulatir speed conveyer t to zone of active g, crusher dusts,	ay be required i al to obtain adec ted in the work ng air required t ransfers, generation) gas discharge	in specific quate protection. place possess to effectively remove Air Speed: 0.25-0.5 m/s (50-100 f/min) 0.5-1 m/s (100-200 f/min.) 1-2.5 m/s (200-500
	Employ Genera circums Provide varying the cor Type solver aeros weldir direct (active grindin into zo	vers may need to use multiple types of controls to pre- al exhaust is adequate under normal operating cond- stances. If risk of overexposure exists, wear approve a adequate ventilation in warehouse or closed storag rescape" velocities which, in turn, determine the "c itaminant. of Contaminant: ht, vapours, degreasing etc., evaporating from tank of ols, fumes from pouring operations, intermittent con ng, spray drift, plating acid fumes, pickling (released spray, spray painting in shallow booths, drum filling, e generation into zone of rapid air motion) ng, abrasive blasting, tumbling, high speed wheel ge	event employee o itions. Local exha ed respirator. Cor ge areas. Air cont apture velocities" in still air). tainer filling, low s at low velocity int conveyer loading	overexposure. ust ventilation m rect fit is essentia aminants genera of fresh circulatir speed conveyer t to zone of active g, crusher dusts,	ay be required i al to obtain adec ted in the work ng air required t ransfers, generation) gas discharge	in specific quate protection. place possess to effectively remove Air Speed: 0.25-0.5 m/s (50-100 f/min) 0.5-1 m/s (100-200 f/min.) 1-2.5 m/s (200-500 f/min.) 2.5-10 m/s
	Employ Genera circums Provide varying the cor Type of solver aerose weldir direct (active grindii into ze	vers may need to use multiple types of controls to pre- al exhaust is adequate under normal operating cond- stances. If risk of overexposure exists, wear approve e adequate ventilation in warehouse or closed storage "escape" velocities which, in turn, determine the "c itaminant. of Contaminant: int, vapours, degreasing etc., evaporating from tank of ols, fumes from pouring operations, intermittent con ing, spray drift, plating acid fumes, pickling (released spray, spray painting in shallow booths, drum filling, e generation into zone of rapid air motion) ing, abrasive blasting, tumbling, high speed wheel geone of very high rapid air motion).	event employee o itions. Local exha ed respirator. Cor ge areas. Air cont apture velocities" in still air). tainer filling, low s at low velocity int conveyer loading	overexposure. ust ventilation management rect fit is essentia aminants genera of fresh circulatin speed conveyer ta to zone of active g, crusher dusts, sleased at high in	ay be required i al to obtain adec ted in the work ng air required t ransfers, generation) gas discharge	in specific quate protection. place possess to effectively remove Air Speed: 0.25-0.5 m/s (50-100 f/min) 0.5-1 m/s (100-200 f/min.) 1-2.5 m/s (200-500 f/min.) 2.5-10 m/s
	Employ Genera circums Provide varying the cor Type solver aerose weldir direct (active grindir into ze Within Lower	vers may need to use multiple types of controls to pre- al exhaust is adequate under normal operating cond- stances. If risk of overexposure exists, wear approve a dequate ventilation in warehouse or closed storage "escape" velocities which, in turn, determine the "c ntaminant. of Contaminant: nt, vapours, degreasing etc., evaporating from tank ( ools, fumes from pouring operations, intermittent con ng, spray drift, plating acid fumes, pickling (released spray, spray painting in shallow booths, drum filling, e generation into zone of rapid air motion) ng, abrasive blasting, tumbling, high speed wheel ge one of very high rapid air motion). each range the appropriate value depends on:	event employee o itions. Local exha ed respirator. Cor ge areas. Air cont apture velocities" in still air). tainer filling, low s at low velocity in conveyer loading enerated dusts (re	overexposure. ust ventilation morect fit is essentia aminants general of fresh circulation speed conveyer to to zone of active g, crusher dusts, eleased at high in e range	ay be required i al to obtain adec ted in the work ng air required t ransfers, generation) gas discharge	in specific quate protection. place possess to effectively remove Air Speed: 0.25-0.5 m/s (50-100 f/min) 0.5-1 m/s (100-200 f/min.) 1-2.5 m/s (200-500 f/min.) 2.5-10 m/s

3: Intermittent, low production. 3: High production, heavy use 4: Large hood or large air mass in motion 4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Individual protection measures, such as personal protective equipment

Eye and face protection



Safety glasses with side shields.

- Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

Hands/feet protection	The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dired thoroughly. Application of a non-perfumed moisturiser is recommended. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:          - frequency and duration of contact,          - othernical resistance of glove material,          - glove thickness and          - deventive second duration of a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).          - When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.          - Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.          - Contaminated gloves should be replaced.          As defined in ASTM F-739-96 in any application, gloves are rated as:          Excellent when breakthrough time < 20 min          - Bor when glove material degrades          For general applications, gloves with a protectior of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material degrades          For owne gloves material degrades          For general applications, gloves will a protection of glove resistance to a specif
Body protection	See Other protection below
Other protection	<ul> <li>Overalls.</li> <li>P.V.C apron.</li> <li>Barrier cream.</li> <li>Skin cleansing cream.</li> <li>Eye wash unit.</li> </ul>

# **SECTION 9** Physical and chemical properties

# Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	127-131/9mm	Molecular weight (g/mol)	Not Available

Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Not Available	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

# **SECTION 10 Stability and reactivity**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

# **SECTION 11 Toxicological information**

# Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.
Eye	This material can cause eye irritation and damage in some persons.
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

Legend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	*	STOT - Single Exposure	*
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend: 🗙 – Data

Data either not available or does not fill the criteria for classification
 Data available to make classification

# **SECTION 12 Ecological information**

# Toxicity

Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity
	4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) -
	Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

# Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
Diethyl (methoxycarbonylmethyl)phosphonate	LOW	LOW

### **Bioaccumulative potential**

Ingredient	Bioaccumulation
Diethyl (methoxycarbonylmethyl)phosphonate	LOW (LogKOW = 0.7374)

### Mobility in soil

Ingredient	Mobility
Diethyl (methoxycarbonylmethyl)phosphonate	LOW (KOC = 143.3)

### **SECTION 13 Disposal considerations**

### Waste treatment methods

Product / Packaging disposal	<ul> <li>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</li> <li>A Hierarchy of Controls seems to be common - the user should investigate: <ul> <li>Reduction</li> <li>Reduction</li> <li>Reuse</li> <li>Recycling</li> <li>Disposal (if all else fails)</li> </ul> </li> <li>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, a recycling or reuse may not always be appropriate.</li> <li><b>DO NOT</b> allow wash water from cleaning or process equipment to enter drains.</li> <li>It may be necessary to collect all wash water for treatment before disposal.</li> <li>In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>Where in doubt contact the responsible authority.</li> <li>Recycle wherever possible.</li> <li>Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suital treatment or disposal facility can be identified.</li> <li>Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or incineration in licensed apparatus (after admixture with suitable combustible material).</li> <li>Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.</li> </ul>
---------------------------------	--

# **SECTION 14 Transport information**

# Labels Required

Marine Pollutant	NO

# Land transport (ADR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

### Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

### Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

# Inland waterways transport (ADN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

### Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

### Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
Diethyl (methoxycarbonylmethyl)phosphonate	Not Available

### Transport in bulk in accordance with the IGC Code

Product name	Ship Type
Diethyl (methoxycarbonylmethyl)phosphonate	Not Available

# **SECTION 15 Regulatory information**

### Safety, health and environmental regulations / legislation specific for the substance or mixture

### Diethyl (methoxycarbonylmethyl)phosphonate is found on the following regulatory lists

Europe EC Inventory	European Union - European Inventory of Existing Commercial Chemical
	Substances (EINECS)

### **National Inventory Status**

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	No (Diethyl (methoxycarbonylmethyl)phosphonate)
Canada - DSL	No (Diethyl (methoxycarbonylmethyl)phosphonate)
Canada - NDSL	No (Diethyl (methoxycarbonylmethyl)phosphonate)
China - IECSC	No (Diethyl (methoxycarbonylmethyl)phosphonate)
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	No (Diethyl (methoxycarbonylmethyl)phosphonate)
Korea - KECI	No (Diethyl (methoxycarbonylmethyl)phosphonate)
New Zealand - NZIoC	Yes
Philippines - PICCS	No (Diethyl (methoxycarbonylmethyl)phosphonate)
USA - TSCA	No (Diethyl (methoxycarbonylmethyl)phosphonate)
Taiwan - TCSI	Yes
Mexico - INSQ	No (Diethyl (methoxycarbonylmethyl)phosphonate)
Vietnam - NCI	Yes
Russia - FBEPH	No (Diethyl (methoxycarbonylmethyl)phosphonate)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

### **SECTION 16 Other information**

Revision Date	10/07/2023
Initial Date	10/07/2023

### SDS Version Summary

Version	Date of Update	Sections Updated
1.2	10/07/2023	Physical and chemical properties - Appearance, CAS Number, Hazards identification - Classification,

Version	Date of Update	Sections Updated
		Composition / information on ingredients - Ingredients, Korean MSDS Number, Identification of the substance / mixture and of the company / undertaking - Supplier Information, Identification of the substance / mixture and of the company / undertaking - Synonyms

### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

### **Definitions and abbreviations**

PC - TWA: Permissible Concentration-Time Weighted Average PC - STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List

NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory

NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act

TCSI: Taiwan Chemical Substance Inventory

INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

### Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	Classification Procedure
Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, H335	Expert judgement
Skin Corrosion/Irritation Category 2, H315	Expert judgement
Serious Eye Damage/Eye Irritation Category 2, H319	Expert judgement

### Issue Date: 10/07/2023 Print Date: 10/07/2023

# Diethyl (methoxycarbonylmethyl)phosphonate

Powered by AuthorITe, from Chemwatch.