

Ethyltriphenylphosphonium lodide Apollo Scientific

Part Number: **OR72634** Version No: **1.1** Safety Data Sheet

Chemwatch Hazard Alert Code: 3

Issue Date: **31/08/2023**Print Date: **31/08/2023**S.GHS.GB-NIR.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	Ethyltriphenylphosphonium lodide
Chemical Name	ethyltriphenylphosphonium iodide
Synonyms	Not Available
Proper shipping name	ORGANOPHOSPHORUS COMPOUND, SOLID, TOXIC, N.O.S.
Chemical formula	C20H20P.I
Other means of identification	Not Available
CAS number	4736-60-1*

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Not Available

Details of the manufacturer or supplier of the safety data sheet

Registered company name	Apollo Scientific	Apollo Scientific Itd		
Address	Whitefield Road, Bredbury SK62QR United Kingdom	Whitefield Road, Bredbury SK6 2QR Northern Ireland (UK)		
Telephone	01614060505	+44(0) 161 406 0505		
Fax	0161 406 0506	Not Available		
Website	http://www.apolloscientific.co.uk/	apolloscientific.co.uk		
Email	Email sales@apolloscientific.co.uk sales@apolloscientific.co.uk			

Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	Not Available
Other emergency telephone numbers	Not Available

SECTION 2 Hazards identification

Classification of the substance or mixture

Classification according to regulation (EC) No 1272/2008 [CLP] and amendments [1]

H301 - Acute Toxicity (Oral) Category 3, H312 - Acute Toxicity (Dermal) Category 4, H315 - Skin Corrosion/Irritation Category 2, H319 - Serious Eye Damage/Eye Irritation Category 2

Page 2 of 12 Version No: 1.1

Ethyltriphenylphosphonium lodide

Issue Date: 31/08/2023 Print Date: 31/08/2023

Legend:

1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

H301	Toxic if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.

Precautionary statement(s) Prevention

P264	Wash all exposed external body areas thoroughly after handling.		
P270	Do not eat, drink or smoke when using this product.		
P280	Wear protective gloves, protective clothing, eye protection and face protection.		

Precautionary statement(s) Response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider.
P330	Rinse mouth.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P302+P352	IF ON SKIN: Wash with plenty of water.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

Precautionary statement(s) Storage

P405 Store locked up.

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

CAS No	%[weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	SCL / M-Factor
--------	-----------	------	---	-------------------

Legend:

1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L; * EU IOELVs available; [e] Substance identified as having endocrine disrupting properties

Mixtures

See section above for composition of Substances

SECTION 4 First aid measures

Description of first aid measures

Eye Contact

If this product comes in contact with the eyes:

▶ Wash out immediately with fresh running water.

Figure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally

Ethyltriphenylphosphonium lodide

	lifting the upper and lower lids. • Seek medical attention without delay; if pain persists or recurs seek medical attention. • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs: Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor.
Ingestion	 If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.

Indication of any immediate medical attention and special treatment needed

- Most organophosphate compounds are rapidly well absorbed from the skin, conjunctiva, gastro-intestinal tract and lungs.
- They are detoxified by Cytochrome P450-mediated monoxygenases in the liver but some metabolites are more toxic than parent compounds.
- Metabolites are usually detected 12-48 hours postexposure.
- Organophosphates phosphorylate acetylcholinesterase with resultant accumulation of large amounts of acetylcholine causing initial stimulation, then
 exhaustion of cholinergic synapse.
- b gamma-aminobutyric acid (GABA)-ergic and dopaminergic pathways provide compensatory inhibition.
- ▶ The clinical manifestation of organophosphate toxicity results from muscarinic, nicotinic and CNS symptoms.
- A garlic-like odour emanating from the patient or involved container may aid the diagnosis.
- Immediate life-threatening symptoms usually are respiratory problems.
- Frequent suction and, if necessary, endotracheal intubation and assisted ventilation may be necessary to maintain adequate oxygenation.
- Theophylline compounds, to treat bronchospasm, should be used cautiously as they may lower the seizure threshold.
- Excessive secretions and bronchospasm should respond to adequate doses of atropine.
- Diazepam is the drug of choice for convulsions.
- Usual methods of decontamination, (activated charcoal and cathartics) should be used when patients present within 4-6 hours postexposure.
- The administration of atropine, as an antidote, does not require confirmation by acetylcholinesterase levels. Severely poisoned patients develop marked resistance to the usual doses of atropine. [Atropine should not be given to a cyanosed patient ICI] NOTE: Hypoxia must be corrected before atropine is given. For adult: 2 mg repeatedly SC or IV until atropinization is achieved and maintained (atropinization is characterised by decreased bronchial secretions, heart rate >100 bpm, dry mouth, diluted pupils).
- Pralidoxime (2-PAM, Protopam) is a specific antidote when given within 24 hours and perhaps up to 36-48 hours postexposure. Although it ameliorates muscle weakness, fasciculations and alterations of consciousness, it does not relieve bronchospasm or bronchorrhea and must be given concurrently with atropine.
 NOTE: Pralidoxime should be given as an adjunct to, NOT a replacement for atropine and should be given in every case where atropine therapy is deemed necessary. Traditional dose: 1 g (or 2 g in severe cases) by slow IV injection over 5-10 minutes. 1-2 g, 4 hourly (maximum dose 12 g in 24 hours) until clinical and analytical recovery is achieved and maintained.
- Avoid parasympathomimetic agents. Phenothiazines and antihistamines may potentiate organophosphate activity. [Ellenhorn and Barceloux: Medical Toxicology]

NOTE: Acute pancreatitis in organophosphate intoxication may be more common than reported. The possible pathogenesis of pancreatic insult are excessive cholinergic stimulation of the pancreas and ductular hypertension. Early recognition and appropriate therapy for acute pancreatitis may lead to an improved prognosis.

Cheng-Tin Hsiao, et al; Clinical Toxicology 34(3), 343-347 (1996)

BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

Determinant Index Sampling Time Comments

1. Cholinesterase activity in red cells 70% of individual's baseline Discretionary NS

B: Background levels occur in specimens collected from subjects NOT exposed

NS:Non-specific determinant; Also observed after exposure to other materials

SQ:Semi-quantitative determinant; Interpretation may be ambiguous. Should be used as a screening test or confirmatory test.

Some jurisdictions require that health surveillance be conducted on occupationally exposed workers. Such surveillance should emphasise

▶ demography, occupational and medical history and health advice

Ethyltriphenylphosphonium lodide

- ▶ physical examination
- baseline estimation of red cell and plasma cholinesterase activity levels by the Ellman method. Estimation of red cell and plasma cholinesterase activity towards the end of the working day

SECTION 5 Firefighting measures

Extinguishing media

- ▶ There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility None known.

Advice for firefighters

Fire Fighting

- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves in the event of a fire.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
 - ▶ DO NOT approach containers suspected to be hot.
 - Cool fire exposed containers with water spray from a protected location.
 - If safe to do so, remove containers from path of fire.
 - Equipment should be thoroughly decontaminated after use.

Fire/Explosion Hazard

- Non combustible.
- Not considered a significant fire risk, however containers may burn.

May emit poisonous fumes.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Remove all ignition sources. Clean up all spills immediately. Avoid contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Use dry clean up procedures and avoid generating dust. Place in a suitable, labelled container for waste disposal. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard.
Major Spills	 Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. Stop leak if safe to do so. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Neutralise/decontaminate residue (see Section 13 for specific agent). Collect solid residues and seal in labelled drums for disposal. Wash area and prevent runoff into drains. After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using. If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling

▶ Avoid all personal contact, including inhalation.

 Part Number: OR72634
 Page 5 of 12
 Issue Date: 31/08/2023

 Version No: 1.1
 Print Date: 31/08/2023

Ethyltriphenylphosphonium lodide

Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. ▶ Prevent concentration in hollows and sumps. ▶ DO NOT enter confined spaces until atmosphere has been checked. ▶ DO NOT allow material to contact humans, exposed food or food utensils. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. ▶ Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. ▶ Work clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. ▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained. Store in original containers. Keep containers securely sealed. ▶ Store in a cool, dry, well-ventilated area. Other information Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2		TEEL-3
Ethyltriphenylphosphonium lodide	Not Available	Not Available		Not Available
Ingredient	Original IDLH		Revised IDLH	
Ethyltriphenylphosphonium lodide	Not Available		Not Available	

Exposure controls

Part Number: OR72634 Page 6 of 12 Issue Date: 31/08/2023 Version No: 1.1 Print Date: 31/08/2023

Ethyltriphenylphosphonium lodide

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations.

Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Appropriate engineering controls

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used

Individual protection measures, such as personal protective equipment





Safety glasses with side shields.







- ► Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]
- Contact lenses may pose a special hazard: soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

Eye and face protection

Skin protection

See Hand protection below

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be

Hands/feet protection

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

· frequency and duration of contact,

observed when making a final choice.

Part Number: OR72634 Page 7 of 12 Issue Date: 31/08/2023 Version No: 1.1

Ethyltriphenylphosphonium lodide

Print Date: 31/08/2023

- · chemical resistance of glove material,
- · glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).

- · When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- · When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- · Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.
- · Contaminated gloves should be replaced.

As defined in ASTM F-739-96 in any application, gloves are rated as:

- · Excellent when breakthrough time > 480 min
- · Good when breakthrough time > 20 min
- · Fair when breakthrough time < 20 min
- · Poor when glove material degrades

For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task. Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- · Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
- · Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

- Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber

Body protection

See Other protection below

Other protection

- Overalls.
- Evewash unit.
- Barrier cream.
- Skin cleansing cream.

Respiratory protection

Type -P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	P1	-	PAPR-P1
	Air-line*	-	-
up to 50 x ES	Air-line**	P2	PAPR-P2
up to 100 x ES	-	P3	-
		Air-line*	-
100+ x ES	-	Air-line**	PAPR-P3

* - Negative pressure demand ** - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- · Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- · The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- · Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.
- · Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory
- · Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)
- · Use approved positive flow mask if significant quantities of dust becomes airborne.
- · Try to avoid creating dust conditions.

Version No: 1.1 Ethyltriphenylphosphonium lodide

Issue Date: 31/08/2023

Print Date: 31/08/2023

Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Solid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	168-172	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Not Available	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	The material is not thought to produce respiratory irritation (as classified by EC Directives using animal models). Nevertheless inhalation of dusts, or fumes, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress. Inhalation of dusts, generated by the material during the course of normal handling, may be damaging to the health of the individual.			
Ingestion	Accidental ingestion of the material may be damaging to the health of the individual.			
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.			

 Part Number: OR72634
 Page 9 of 12
 Issue Date: 31/08/2023

 Version No: 1.1
 Print Date: 31/08/2023

Ethyltriphenylphosphonium lodide

Eye	This material can cause eye irritation and damage in some persons.		
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.		
Ethyltrinhenylphosphonium	TOXICITY	IRRITATION	

lodide	Oral (Rat) LD50: >25<200 mg/kg ^[1]	Eye: adverse effect observed (irreversible damage) ^[1]	
iodide		Skin: no adverse effect observed (not irritating) ^[1]	
Legend:	Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances.		

Acute Toxicity Carcinogenicity × Skin Irritation/Corrosion × Reproductivity Serious Eye STOT - Single Exposure × Damage/Irritation Respiratory or Skin STOT - Repeated Exposure × × sensitisation × × Mutagenicity **Aspiration Hazard**

Legend: X − Data either not available or does not fill the criteria for classification

✓ – Data available to make classification

SECTION 12 Ecological information

Toxicity

	Endpoint	Test Duration (hr)	Species	Value	Source
Ethyltriphenylphosphonium lodide	EC50	48h	Crustacea	0.86mg/l	2
iouide	NOEC(ECx)	NOEC(ECx) 48h Crustacea		0.32mg/l	2
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) -			tic Toxicity	
	Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air	
	No Data available for all ingredients	No Data available for all ingredients	

Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal

- ▶ Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- ▶ Bury residue in an authorised landfill.
- ▶ Recycle containers if possible, or dispose of in an authorised landfill.

Page 10 of 12 Issue Date: 31/08/2023 Version No: 1.1 Print Date: 31/08/2023

Ethyltriphenylphosphonium lodide

SECTION 14 Transport information

Labels Required



Marine Pollutant

Land transport (ADR-RID)

UN number or ID number	3464				
UN proper shipping name	ORGANOPHOSPH	IORUS COMP	OUND, SO	LID, TOXIC, N.O.S.	
Transport hazard class(es)	Class 6.1 Subsidiary risk Not Applicable				
Packing group	III	III			
Environmental hazard	Not Applicable				
	Hazard identificat Classification cod		60 T2		
Special precautions for	Hazard Label		6.1		
user	Special provisions		43 274		
	Limited quantity		5 kg		
	Tunnel Restriction	n Code	2 (E)		

Air transport (ICAO-IATA / DGR)

UN number	3464			
UN proper shipping name	Organophosphorus compound, solid, toxic, n.o.s. *			
Transport hazard class(es)	ICAO/IATA Class	6.1		
	ICAO / IATA Subsidiary Hazard	Not Applicable		
	ERG Code	6L		
Packing group				
Environmental hazard	Not Applicable			
	Special provisions		A3 A5 A6	
Special precautions for user	Cargo Only Packing Instructions		677	
	Cargo Only Maximum Qty / Pack		200 kg	
	Passenger and Cargo Packing Instructions		670	
	Passenger and Cargo Maximum Qty / Pack		100 kg	
	Passenger and Cargo Limited Quantity Packing Instructions		Y645	
	Passenger and Cargo Limited Maximum Qty / Pack		10 kg	

Sea transport (IMDG-Code / GGVSee)

UN number	3464	
UN proper shipping name	ORGANOPHOSPHORUS COMPOUND, SOLID, TOXIC, N.O.S.	
Transport hazard class(es)	IMDG Class 6 IMDG Subrisk N	o.1 Not Applicable
Packing group	III	
Environmental hazard	Not Applicable	
Special precautions for user	EMS Number Special provisions	F-A, S-A 43 223 274

Part Number: **0R72634**Version No: **1.1**

Ethyltriphenylphosphonium lodide

Issue Date: **31/08/2023**Print Date: **31/08/2023**

Limited Quantities 5 kg

Inland waterways transport (ADN)

3464	
ORGANOPHOSPHORU	JS COMPOUND, SOLID, TOXIC, N.O.S.
6.1 Not Applicable	
III	
Not Applicable	
Classification code Special provisions	T2 43; 274; 802
Limited quantity	5 kg
Equipment required	PP, EP
Fire cones number	0
	ORGANOPHOSPHORI 6.1 Not Applicable III Not Applicable Classification code Special provisions Limited quantity Equipment required

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

|--|

Transport in bulk in accordance with the IGC Code

Product name Ship Type

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Not Available
Canada - DSL	Not Available
Canada - NDSL	Not Available
China - IECSC	Not Available
Europe - EINEC / ELINCS / NLP	Not Available
Japan - ENCS	Not Available
Korea - KECI	Not Available
New Zealand - NZIoC	Not Available
Philippines - PICCS	Not Available
USA - TSCA	Not Available
Taiwan - TCSI	Not Available
Mexico - INSQ	Not Available
Vietnam - NCI	Not Available
Russia - FBEPH	Not Available
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	31/08/2023
Initial Date	31/08/2023

Version No: 1.1

Ethyltriphenylphosphonium lodide

Issue Date: **31/08/2023**Print Date: **31/08/2023**

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

Definitions and abbreviations

PC - TWA: Permissible Concentration-Time Weighted Average

PC - STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit,

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act
TCSI: Taiwan Chemical Substance Inventory
INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

•	
Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	Classification Procedure
Acute Toxicity (Oral) Category 3, H301	Expert judgement
Acute Toxicity (Dermal) Category 4, H312	Expert judgement
Skin Corrosion/Irritation Category 2, H315	Expert judgement
Serious Eye Damage/Eye Irritation Category 2, H319	Expert judgement

Powered by AuthorITe, from Chemwatch.