

Bis(tributylstannyl)acetylene Apollo Scientific

Part Number: **OR7761** Version No: **2.2** Safety Data Sheet Chemwatch Hazard Alert Code: 3

Issue Date: **10/07/2023**Print Date: **10/07/2023**S.GHS.GB-NIR.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	Bis(tributylstannyl)acetylene
Chemical Name	bis(tributylstannyl)acetylene
Synonyms	Not Available
Proper shipping name	ORGANOTIN COMPOUND, LIQUID, N.O.S.
Chemical formula	C26H54Sn2
Other means of identification	Not Available
CAS number	994-71-8*

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Not Available

Details of the manufacturer or supplier of the safety data sheet

Registered company name	Apollo Scientific	Apollo Scientific Itd
Address	Whitefield Road, Bredbury SK62QR United Kingdom	Whitefield Road, Bredbury Cheshire SK6 2QR United Kingdom (NI)
Telephone	01614060505	+44(0) 161 406 0505
Fax	0161 406 0506	Not Available
Website	http://www.apolloscientific.co.uk/	apolloscientific.co.uk
Email	sales@apolloscientific.co.uk	sales@apolloscientific.co.uk

Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	Not Available
Other emergency telephone numbers	Not Available

SECTION 2 Hazards identification

Classification of the substance or mixture

Classification according to regulation (EC) No 1272/2008 [CLP] and

H312 - Acute Toxicity (Dermal) Category 4, H400 - Hazardous to the Aquatic Environment Acute Hazard Category 1, H315 - Skin Corrosion/Irritation Category 2, H319 - Serious Eye Damage/Eye Irritation Category 2, H360FD - Reproductive Toxicity Category 1B, H372 - Specific Target Organ Toxicity - Repeated Exposure Category 1, H410 - Hazardous to the Aquatic Environment

Version No: 2.2

Bis(tributyIstannyI)acetylene

amendments [1]	Long-Term Hazard Category 1, H301 - Acute Toxicity (Oral) Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Label elements









Signal	word
Signal	woru

ord Danger

Hazard statement(s)

H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H360FD	May damage fertility. May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H410	Very toxic to aquatic life with long lasting effects.
H301	Toxic if swallowed.

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P260	Do not breathe mist/vapours/spray.
P264	Wash all exposed external body areas thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves, protective clothing, eye protection and face protection.
P273	Avoid release to the environment.

Precautionary statement(s) Response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider.
P308+P313	IF exposed or concerned: Get medical advice/ attention.
P330	Rinse mouth.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P391	Collect spillage.
P302+P352	IF ON SKIN: Wash with plenty of water.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

Precautionary statement(s) Storage

P405 Store locked up.

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

CAS No	%[weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	SCL / M-Factor
994-71-8*	100	Bis(tributylstannyl)acetylene	Acute Toxicity (Dermal) Category 4, Hazardous to the Aquatic Environment Acute Hazard Category 1, Skin	* STOT RE 1; H372: C ≥ 1 % STOT RE

 Part Number: OR7761
 Page 3 of 13
 Issue Date: 10/07/2023

 Version No: 2.2
 Print Date: 10/07/2023

Bis(tributylstannyl)acetylene

CAS No	%[weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	SCL / M-Factor
			Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 2, Reproductive Toxicity Category 1B, Specific Target Organ Toxicity - Repeated Exposure Category 1, Hazardous to the Aquatic Environment Long-Term Hazard Category 1, Acute Toxicity (Oral) Category 3; H312, H315, H319, H360FD, H372, H410, H301 [1]	2; H373: 0,25 % ≤ C < 1 % Skin Irrit. 2; H315: C ≥ 1 % Eye Irrit. 2; H319: C ≥ 1 % M=10

Legend:

1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L; * EU IOELVs available; [e] Substance identified as having endocrine disrupting properties

Mixtures

See section above for composition of Substances

SECTION 4 First aid measures

Eye Contact	If this product comes in contact with the eyes: • Wash out immediately with fresh running water. • Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. • Seek medical attention without delay; if pain persists or recurs seek medical attention. • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs: Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor.
Ingestion	 If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.

Indication of any immediate medical attention and special treatment needed

Scanty animal data indicate that BAL may be useful against dialkyl but not trialkyl organotin compounds. D-penicillamine is thought to be inactive. GOSSELIN, SMITH & HODGE: Clinical Toxicology of Commercial Products, 5th Ed

Dimercaprol is suggested to be an effective antidote for dialkyltin poisoning and has been reported to prevent the accumulation of alpha-keto acids produced by dialkyltin compounds. It does not however appear to protect rats from the general toxic effects of triethyltin compounds. This may be due to the fact that dialkyltin compounds, at least up to dihexyl derivatives, react readily with sulfhydryl groups and trialkyltin compounds do not.

Surgical decompression was considered to be the only treatment that offered any benefit in human cases of cerebral oedema caused by trialkyl compounds. Tin and Organotin Compounds: A Preliminary Review.

ENVIRONMENTAL HEALTH CRITERIA: World Health Organization Geneva 1980.

SECTION 5 Firefighting measures

Extinguishing media

- ▶ There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility	,
----------------------	---

None known.

 Part Number: OR7761
 Page 4 of 13
 Issue Date: 10/07/2023

 Version No: 2.2
 Print Date: 10/07/2023

Bis(tributylstannyl)acetylene

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal.
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. Stop leak if safe to do so. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Neutralise/decontaminate residue (see Section 13 for specific agent). Collect solid residues and seal in labelled drums for disposal. Wash area and prevent runoff into drains. After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using. If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. DO NOT allow material to contact humans, exposed food or food utensils. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
---------------	---

Bis(tributylstannyl)acetylene

Store in original containers.

- ► Keep containers securely sealed.
- ▶ Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Other information

- Lined metal can, lined metal pail/ can.
- Plastic pail.
- Polyliner drum.
- Packing as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

For low viscosity materials

- Drums and ierricans must be of the non-removable head type.
- ▶ Where a can is to be used as an inner package, the can must have a screwed enclosure.

For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.):

- Removable head packaging; Suitable container
 - Cans with friction closures and
 - low pressure tubes and cartridges

may be used.

Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages *.

In addition, where inner packagings are glass and contain liquids of packing group I and II there must be sufficient inert absorbent to absorb any spillage *.

* unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.

Storage incompatibility

- Avoid strong acids, bases.
- ► Store at 2-8°C
- Light sensitive
- Store under argon

SECTION 8 Exposure controls / personal protection

25 mg/m3

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
UK Workplace Exposure Limits (WELs)	Bis(tributylstannyl)acetylene	Tin compounds, organic, except Cyhexatin (ISO), (as Sn)	0.1 mg/m3	0.2 mg/m3	Not Available	Sk

Emergency Limits

Ingredient	TEEL-1	TEEL-2		TEEL-3
Bis(tributylstannyl)acetylene	Not Available	Not Available		Not Available
Ingredient	Original IDLH		Revised IDLH	

Exposure controls

Bis(tributylstannyl)acetylene

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

Not Available

The basic types of engineering controls are:

Appropriate engineering controls

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to

 Part Number: OR7761
 Page 6 of 13
 Issue Date: 10/07/2023

 Version No: 2.2
 Print Date: 10/07/2023

Bis(tributylstannyl)acetylene

obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations.

Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Individual protection measures, such as personal protective equipment









► Co

- Safety glasses with side shields.
- ► Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

Skin protection

Eye and face protection

See Hand protection below

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

- · frequency and duration of contact,
- $\boldsymbol{\cdot}$ chemical resistance of glove material,
- · glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).

- · When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- · When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374. AS/NZS 2161.10.1 or national equivalent) is recommended.
- · Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.
- · Contaminated gloves should be replaced.

Hands/feet protection

 Part Number: OR7761
 Page 7 of 13
 Issue Date: 10/07/2023

 Version No: 2.2
 Print Date: 10/07/2023

Bis(tributyIstannyl)acetylene

As defined in ASTM F-739-96 in any application, gloves are rated as:

- · Excellent when breakthrough time > 480 min
- · Good when breakthrough time > 20 min
- · Fair when breakthrough time < 20 min
- · Poor when glove material degrades

For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task. Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- · Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
- · Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

- ▶ Wear chemical protective gloves, e.g. PVC.
- ▶ Wear safety footwear or safety gumboots, e.g. Rubber

Body protection

See Other protection below

Other protection

- Overalls.
- ▶ Eyewash unit.
- ▶ Barrier cream.
- Skin cleansing cream.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance Not Available

Appearance	Not Available		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Not Available	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reacti	ivitv

See section 7

Version No: 2.2

Issue Date: 10/07/2023 Print Date: 10/07/2023 Bis(tributyIstannyl)acetylene

Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information	on	toxico	logical	ettects

Inhaled	The material is not thought to produce respiratory irritation (as classified by EC Directives using animal models). Nevertheless inhalation of vapours, fumes or aerosols, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress. Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual. The acute toxicity of inhaled organotin compounds resembles that found by other means of exposure.
Ingestion	Accidental ingestion of the material may be damaging to the health of the individual. Subchronic exposures to mono-, di- and tri- and tetra-substituted organotin compounds may elicit toxic response in the central nervous, immune and renal systems, the liver and bile duct and the skin.
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	This material can cause eye irritation and damage in some persons.
Chronic	Ample evidence exists from experimentation that reduced human fertility is directly caused by exposure to the material. Tributyltins and dibutyltins affect hormone function and reproduction. They also damage the nerves and suppress the body s immune system, making one fall ill easily and frequently. They may also cause cancers. Several organotin compounds also cause reproductive and developmental effects. They are classified as persistent, bioaccumulative and toxic.

Legend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

Acute Toxicity	~	Carcinogenicity	×
Skin Irritation/Corrosion	~	Reproductivity	✓
Serious Eye Damage/Irritation	~	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	✓
Mutagenicity	×	Aspiration Hazard	×

Legend:

★ - Data either not available or does not fill the criteria for classification

✓ – Data available to make classification

SECTION 12 Ecological information

Toxicity

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) -Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Bis(tributylstannyl)acetylene

Issue Date: **10/07/2023**Print Date: **10/07/2023**

ligand, with butyltins, octyltins och phenyltins being the most common. A large number of organtin substances are used in society, with some, such as the butyltins, being recognised as environmental pollutants.

Ecotoxicity increases dramatically in the order methylbutyltin (MBT, RSn) < dibutyltin (DBT, R2Sn) < tributyltin (TBT, R3Sn) for certain endpoints. Organotin degrades by UV irradiation or by biological or chemical cleavage, where the tin-carbon bond is broken. This can occur rapidly in water, however adhesion to suspended particles deposited as sedimentation is the key removal process. Organotin compounds are rapidly degraded by light at surfaces, and hence are not released to the air from various surfaces by any significant amounts. The speciation of organotin compounds is pH-dependent, with the cationic form being the primary form at low pHs, and he neutral hydroxide compounds becoming the predominant form with increased pH. In the environmentally relevant pH range (pH 5–9), the neutral hydroxide compounds (i.e., R3SnOH, R2Sn(OH)2, and Rsn(OH)3) predominate. High concentrations of chloride favor the formation of chloro species. The pKa values for trimethyltin, tributyltin, and triphenyltin cations are approximately 6.60, 6.81, 6.25, and 5.2, respectively. Organotin compounds degrate much slower in sediments than in water, with half-lives estimated to be several years. Chemical and/or biological degradration may occur by dealkylation or methylation, which may result in volatile tin compounds. At ambient temperatures, the solubilities of organotin compounds range from 0.0001 to about 50 mg/L. Organotin compounds may be transferred from water to aquatic organisms, and for tributylin and triphenyltin, the more significant route is through the uptake of water rather than what is being channelled through the food chain. BCF values for all organotin compounds show that organotin compounds tends to accumulate in the livers of organisms, with the tributylitin compounds showing the highest BCFs..

The use of tributyltin (TBT) in ship antifouling paints has caused significant harm to the marine environment worldwide. Female molluscs are masculinized by TBT at levels as low as ca 1 ng/l, preventing them from reproducing. Other organotin substances such as dibutyltin (DBT), dioctyltin and monobutyltin (MBT) are commercially used in other applications. Most industrial organotin chemicals (OTCs) are composed of an organotin cation and one or several ligands, and most of these chemicals are reconverted to the organotin cation compounds in natural waters. The cation may form dissolved complexes with e.g. chloride in seawater. Therefore, their environmental partitioning properties such as Kd and Kh depend in part on the balancing anion in the environment.

Organotins are moderately hydrophobic and associate strongly to particles in natural waters. This increases with increasing number of alkyl groups and increased chain length. In harbour sediments MBT exhibits the weakest affinity to particles, and TBT the strongest (MBT < DBT < TBT). In various soils, however, the reverse pattern was observed. In organic soils, log Kd exceeded 4.0, whereas adsorption was less strong in mineral soils. In contrast to hydrophobic pollutants such as PCBs or PAHs (that partition to lipids in organic matter), OTCs are adhere to the functional groups of organic matter, e.g. phenolic and carboxylic groups. Due to their cationic nature, long-range atmospheric transport has not been considered as important. However, TBT forms highly volatile chloride species in seawater and thus has the potential for long-range atmospheric transportation. As organotins are progressively dealkylated in nature, subsequent dealkylation in the atmosphere, may convert TBT to DBT and MBT. This is important to consider when monitoring data are evaluated, since the occurrence of, e.g., DBT may be due to direct release of DBT or to release of TBT that is subsequently dealkylated. Half-lives in soils and sediments usually range from one to a few years, but may be longer under reducing conditions, whereas half-lives in natural waters may range from a few days to several weeks.

Organotin compounds have been detected in various marine organisms, from invertebrates to mammals. In fish and marine mammals, TBT and TPT bioaccumulate more strongly in liver than in muscle. Bioaccumulation is often stronger in bivalves than in fish, a consequence of lower metabolic capacity in bivalves. Trisubstituted OTCs are more strongly bioaccumulated than the less lipophilic disubstituted OTCs. Because TBT is dealkylated in many organisms, DBT may be present in organisms but may not necessarily be the organotin substance that was assimilated. Most studies do not suggest that TBT is biomagnified in aquatic food-chains. However, TPT appears to be biomagnified fairly strongly in the aquatic food chain. The trisubstituted substances, TPT and in particular TBT, are widely considered the most toxic organotin substances. TBT has been demonstrated to cause masculinization (imposex) of female marine molluscs, as well as fish, which consequently compromises their ability to reproduce. While DBT and MBT do not cause imposex, both TBT and DBT have negative effects on the reproductive system of mammals. In line with these facts, TBT and TPT were given the highest category in a European review of endocrine disruption chemicals: "Evidence for endocrine disruption in living organisms". TBT was also classified as "Evidence of potential to cause endocrine disruption in humans".

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
Bis(tributylstannyl)acetylene	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
Bis(tributylstannyl)acetylene	LOW (LogKOW = 14.7394)

Mobility in soil

Version No: 2.2

Ingredient	Mobility
Bis(tributylstannyl)acetylene	LOW (KOC = 69080000)

SECTION 13 Disposal considerations

Waste treatment methods

- ► Containers may still present a chemical hazard/ danger when empty.
- Return to supplier for reuse/ recycling if possible.

Otherwise

Product / Packaging disposal

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- Where possible retain label warnings and SDS and observe all notices pertaining to the product.
 Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

► Reduction

Issue Date: 10/07/2023 Version No: 2.2 Print Date: 10/07/2023

- Bis(tributylstannyl)acetylene
- ► Reuse
- ► Recycling
- ► Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- ▶ It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- ▶ Where in doubt contact the responsible authority.

SECTION 14 Transport information

Labels Required



Marine Pollutant



Land transport (ADR-RID)

and transport (ABIT INB	<i>'</i>			
UN number or ID number	2788			
UN proper shipping name	ORGANOTIN COM	ORGANOTIN COMPOUND, LIQUID, N.O.S.		
	Class	6.1		
Transport hazard class(es)	Subsidiary risk	Not Applicab	le	
Packing group	III			
Environmental hazard	Environmentally ha	azardous		
Special precautions for user	Hazard identification (Kemler)		60	
	Classification code		Т3	
	Hazard Label		6.1	
	Special provisions		43 274	
	Limited quantity		5 L	
	Tunnel Restriction	on Code	2 (E)	

Air transport (ICAO-IATA / DGR)

UN number	2788					
UN proper shipping name	Organotin compound, liquid, n.o.s. *					
Transport hazard class(es)	ICAO/IATA Class	6.1				
	ICAO / IATA Subrisk	Not Applicable				
	ERG Code	6L				
Packing group	III					
Environmental hazard	Environmentally hazard	ous				
	Special provisions	A3 A4 A6				
	Cargo Only Packing Ir	663				
Special precautions for user	Cargo Only Maximum	220 L				
	Passenger and Cargo	655				
	Passenger and Cargo	60 L				
	Passenger and Cargo	Y642				
	Passenger and Cargo	2 L				

Version No: 2.2

Bis(tributyIstannyl)acetylene

Issue Date: **10/07/2023**Print Date: **10/07/2023**

Sea transport (IMDG-Code / GGVSee)

UN number	2788			
UN proper shipping name	ORGANOTIN COMF	ORGANOTIN COMPOUND, LIQUID, N.O.S.		
Transport hazard class(es)		Not Applicable		
Packing group	III			
Environmental hazard	Marine Pollutant			
Special precautions for user	EMS Number Special provisions Limited Quantities			

Inland waterways transport (ADN)

UN number	2788		
UN proper shipping name	ORGANOTIN COMPOUND, LIQUID, N.O.S.		
Transport hazard class(es)	6.1 Not Applicable		
Packing group			
Environmental hazard	Environmentally hazardous		
Special precautions for user	Classification code T3 Special provisions 43; 274; 802 Limited quantity 5 L Equipment required PP, EP, TOX, A Fire cones number 0		

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
Bis(tributylstannyl)acetylene	Not Available

Transport in bulk in accordance with the IGC Code

Product name	Ship Type
Bis(tributylstannyl)acetylene	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

Bis(tributyIstannyl)acetylene is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List EU REACH Regulation (EC) No 1907/2006 - Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

EU REACH Regulation (EC) No 1907/2006 - Annex XVII (Appendix 6) Reproductive toxicants: Category 1 B

European Union (EU) Regulation (EC) No 1272/2008 on Classification,
Labelling and Packaging of Substances and Mixtures - Annex VI
United Nations List of Prior Informed Consent Chemicals
WHO Recommended Classification of Pesticides by Hazard - Table 7.
Pesticides subject to the Rotterdam Convention

National Inventory Status

•	
National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	No (Bis(tributylstannyl)acetylene)
Canada - DSL	No (Bis(tributyIstannyI)acetylene)
Canada - NDSL	No (Bis(tributyIstannyl)acetylene)

Page **12** of **13** Issue Date: 10/07/2023 Version No: 2.2 Print Date: 10/07/2023

Bis(tributyIstannyl)acetylene

National Inventory	Status		
China - IECSC	No (Bis(tributylstannyl)acetylene)		
Europe - EINEC / ELINCS / NLP	No (Bis(tributylstannyl)acetylene)		
Japan - ENCS	No (Bis(tributylstannyl)acetylene)		
Korea - KECI	No (Bis(tributylstannyl)acetylene)		
New Zealand - NZIoC	No (Bis(tributylstannyl)acetylene)		
Philippines - PICCS	No (Bis(tributylstannyl)acetylene)		
USA - TSCA	No (Bis(tributylstannyl)acetylene)		
Taiwan - TCSI	Yes		
Mexico - INSQ	No (Bis(tributylstannyl)acetylene)		
Vietnam - NCI	No (Bis(tributylstannyl)acetylene)		
Russia - FBEPH	No (Bis(tributylstannyl)acetylene)		
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.		

SECTION 16 Other information

Revision Date	10/07/2023
Initial Date	10/07/2023

SDS Version Summary

Version	Date of Update	Sections Updated
1.2	10/07/2023	CAS Number, Firefighting measures - Fire Fighter (extinguishing media), Firefighting measures - Fire Fighter (fire/explosion hazard), Composition / information on ingredients - Ingredients, Korean MSDS Number, Accidental release measures - Spills (minor), Identification of the substance / mixture and of the company / undertaking - Supplier Information, Identification of the substance / mixture and of the company / undertaking - Synonyms

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

Definitions and abbreviations

PC - TWA: Permissible Concentration-Time Weighted Average

PC - STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit,

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

Bis(tributyIstannyl)acetylene

DSL: Domestic Substances List NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act
TCSI: Taiwan Chemical Substance Inventory
INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

онаосиновино и и и риссон	oradomoution and procedure adda to derive the diadomoution for mixtures adder any to regulation (20) 12/2/2000 [02]		
Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	Classification Procedure		
Acute Toxicity (Dermal) Category 4, H312	Expert judgement		
Hazardous to the Aquatic Environment Acute Hazard Category 1, H400	Expert judgement		
Skin Corrosion/Irritation Category 2, H315	Expert judgement		
Serious Eye Damage/Eye Irritation Category 2, H319	Expert judgement		
Reproductive Toxicity Category 1B, H360FD	Calculation method		
Specific Target Organ Toxicity - Repeated Exposure Category 1, H372	Expert judgement		
Hazardous to the Aquatic Environment Long-Term Hazard Category 1, H410	Expert judgement		
Acute Toxicity (Oral) Category 3, H301	Expert judgement		

Powered by AuthorITe, from Chemwatch.