

Cy5.5-se Apollo Scientific

Part Number: OR967425
Version No: 1.1
Safety Data Sheet (Conforms to Annex II of REACH (1907/2006) - Regulation 2020/878)

Chemwatch Hazard Alert Code: 2

Issue Date: 20/07/2023 Print Date: 20/07/2023 S.REACH.GB-NIR.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

1.1. Product Identifier

Product name	Cy5.5-se
Chemical Name	CY5.5-SE
Synonyms	Not Available
Other means of identification	Not Available
CAS number	442912-55-2*

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Use according to manufacturer's directions.
--------------------------	---

Uses advised against No specific uses advised against are identified.

1.3. Details of the manufacturer or supplier of the safety data sheet

Registered company name	Apollo Scientific
Address	Whitefield Road, Bredbury SK62QR United Kingdom
Telephone	01614060505
Fax	0161 406 0506
Website	http://www.apolloscientific.co.uk/
Email	sales@apolloscientific.co.uk

1.4. Emergency telephone number

• • •	
Association / Organisation	Not Available
Emergency telephone numbers	Not Available
Other emergency telephone numbers	Not Available

SECTION 2 Hazards identification

Hazard pictogram(s)

Signal word Warning

Classification according to regulation (EC) No 1272/2008	H302 - Acute Toxicity (Oral) Category 4, H317 - Sensitisation (Skin) Category 1A		
[CLP] and amendments ^[1]			
Legend:	1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI		

Cy5.5-se

H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.

Supplementary statement(s)

Not Applicable

Precautionary statement(s) Prevention		
P280	Wear protective gloves and protective clothing.	
P261	Avoid breathing dust/fumes.	
P264	Wash all exposed external body areas thoroughly after handling.	
P270	Do not eat, drink or smoke when using this product.	
P272	Contaminated work clothing should not be allowed out of the workplace.	

Precautionary statement(s) Response

P302+P352	IF ON SKIN: Wash with plenty of water.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell.
P330	Rinse mouth.

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

2.3. Other hazards

REACH - Art.57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS print date.

SECTION 3 Composition / information on ingredients

3.1.Substances

1. CAS No 2.EC No 3.Index No 4.REACH No	%[weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	SCL / M-Factor	Nanoform Particle Characteristics
1. 442912-55-2* 2.Not Available 3.Not Available 4.Not Available	100	<u>Cy5.5-se</u>	Acute Toxicity (Oral) Category 4, Sensitisation (Skin) Category 1A; H302, H317 ^[1]	Not Available	Not Available

Legend: 1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L; * EU IOELVs available; [e] Substance identified as having endocrine disrupting properties

3.2.Mixtures

See 'Information on ingredients' in section 3.1

SECTION 4 First aid measures

4.1. Description of first aid measures

Eye Contact	 If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY. For advice, contact a Poisons Information Centre or a doctor. Urgent hospital treatment is likely to be needed. In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition. If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the SDS should be provided. Further action will be the responsibility of the medical specialist. If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the SDS.

Cv5.5-se

Where medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:
 INDUCE vomiting with fingers down the back of the throat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

NOTE: Wear a protective glove when inducing vomiting by mechanical means.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11

4.3. Indication of any immediate medical attention and special treatment needed

As in all cases of suspected poisoning, follow the ABCDEs of emergency medicine (airway, breathing, circulation, disability, exposure), then the ABCDEs of toxicology (antidotes, basics, change absorption, change distribution, change elimination).

For poisons (where specific treatment regime is absent):

BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 L/min.
- Monitor and treat, where necessary, for pulmonary oedema.
- Monitor and treat, where necessary, for shock.
- Anticipate seizures.
- DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.

ADVANCED TREATMENT

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- + Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.
 BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

SECTION 5 Firefighting measures

5.1. Extinguishing media

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

5.2. Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.

5.3. Advice for firefighters

Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use.
Fire/Explosion Hazard	 Non combustible. Not considered a significant fire risk, however containers may burn. May emit poisonous fumes. May emit corrosive fumes.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

See section 8

6.2. Environmental precautions

See section 12

6.3. Methods and material for containment and cleaning up

	• •
Minor Spills	 Remove all ignition sources. Clean up all spills immediately. Avoid contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Use dry clean up procedures and avoid generating dust.

	Place in a suitable, labelled container for waste disposal.
Major Spills	 Moderate hazard. CAUTION: Advise personnel in area. Alert Emergency Services and tell them location and nature of hazard. Control personal contact by wearing protective clothing. Prevent, by any means available, spillage from entering drains or water courses. Recover product wherever possible. IF DRY: Use dry clean up procedures and avoid generating dust. Collect residues and place in sealed plastic bags or other containers for disposal. IF WET: Vacuum/shovel up and place in labelled containers for disposal. ALWAYS: Wash area down with large amounts of water and prevent runoff into drains. If contamination of drains or waterways occurs, advise Emergency Services.

6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. DO NOT enter contact humans, exposed food or food utensils. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
Fire and explosion protection	See section 5
Other information	 Store in original containers. Keep containers securely sealed. Store in a cool, dry area protected from environmental extremes. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS. For major quantities: Consider storage in bunded areas - ensure storage areas are isolated from sources of community water (including stormwater, ground water, lakes and streams). Ensure that accidental discharge to air or water is the subject of a contingency disaster management plan; this may require consultation with local authorities.

7.2. Conditions for safe storage, including any incompatibilities

Suitable container	 Polyethylene or polypropylene container. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	► Store at 2-8°C
Hazard categories in accordance with Regulation (EC) No 1272/2008	Not Available
Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of	Not Available

7.3. Specific end use(s)

See section 1.2

SECTION 8 Exposure controls / personal protection

8.1. Control parameters

Ingredient	DNELs Exposure Pattern Worker	PNECs Compartment
Not Available	Not Available	Not Available

* Values for General Population

Occupational Exposure Limits (OEL)

INGREDIENT DATA

rt Number: OR967425			Page 5 of	12			Issue Date: 20/0	
sion No: 1.1			Cy5.5-	se			Print Date: 20/0	
Source	Ingredient	Material name	TWA		STEL	Peak	Notes	
Not Available	Not Available	Not Available	Not Ava	ilable	Not Available	Not Available	Not Available	
Not Applicable								
Emergency Limits								
Ingredient	TEEL-1		TEEL-2			TEEL-3		
Cy5.5-se	Not Available					Not Available		
Ingredient	Original IDLH				Revised IDLH			
Cy5.5-se	Not Available				Not Available			
Occupational Exposure Bandin	ıg							
Ingredient	Occupational Ex	posure Band Rating			Occupational Exp	osure Band Limit		
Cy5.5-se	E				≤ 0.01 mg/m ³			
2. Exposure controls		ols are used to remove a h						
2. Exposure controls	 be highly effective The basic types of Process controls v Enclosure and/or i 'adds' and 'remove ventilation system Employers may ne Local exhaust proportion will If in spite of lo Such protection m (a): particle dust re (b): filter respiration (c): fresh-air hoods 	in protecting workers and f engineering controls are: which involve changing the isolation of emission source es' air in the work environm must match the particular eed to use multiple types of ventilation is required whe be powdered by mutual fri cal exhaust an adverse co ight consist of: espirators, if necessary, coir rs with absorption cartridge	will typically be way a job activ e which keeps a nent. Ventilation process and ch f controls to pre are solids are h iction. Incentration of t mbined with an e or canister of	independen vity or process a selected ha o can remove nemical or co event employ andled as po he substance absorption o the right type	t of worker interactions is is done to reduce the azard 'physically' away to or dilute an air contam intaminant in use. ree overexposure. wders or crystals; even e in air could occur, resp cartridge; 2;	to provide this high leve risk. irom the worker and ve inant if designed prope when particulates are piratory protection shou	el of protection. ntilation that strategically rly. The design of a relatively large, a certair ıld be considered.	
2. Exposure controls	 be highly effective The basic types of Process controls v Enclosure and/or i 'adds' and 'remove ventilation system Employers may ne Local exhaust proportion will If in spite of lo Such protection m (a): particle dust re (b): filter respirator (c): fresh-air hood; Air contaminants g circulating air required 	in protecting workers and f engineering controls are: which involve changing the isolation of emission source set' air in the work environme must match the particular event to use multiple types of the powdered by mutual fri- cal exhaust an adverse co- ight consist of: espirators, if necessary, con- rs with absorption cartridge s or masks. generated in the workplace inter to effectively remove to	will typically be way a job activ e which keeps eent. Ventilatior process and ch f controls to pre- ere solids are h- iction. Incentration of t mbined with an e or canister of e possess varyin	independen vity or process a selected ha o can remove nemical or co event employ andled as po he substance absorption of the right type ng 'escape' v	t of worker interactions is is done to reduce the azard 'physically' away to or dilute an air contam intaminant in use. ree overexposure. wders or crystals; even e in air could occur, resp cartridge; 2;	to provide this high leve risk. irom the worker and ve inant if designed prope when particulates are piratory protection shou	el of protection. ntilation that strategically rly. The design of a relatively large, a certain Id be considered. velocities' of fresh	
2. Exposure controls	 be highly effective The basic types of Process controls w Enclosure and/or i 'adds' and 'remove ventilation system Employers may ne Local exhaust proportion will If in spite of lo Such protection m (a): particle dust re (b): filter respiratori (c): fresh-air hood: Air contaminants g circulating air requ Type of Contamin 	in protecting workers and f engineering controls are: which involve changing the isolation of emission source set air in the work environm must match the particular ed to use multiple types of the ventilation is required whe be powdered by mutual fri cal exhaust an adverse co- light consist of: espirators, if necessary, co- rs with absorption cartridge s or masks. generated in the workplace uired to effectively remove to nant:	will typically be way a job activ e which keeps ent. Ventilatior process and ch f controls to pre- ere solids are h- iction. Incentration of t mbined with an e or canister of the contaminan	independen vity or process a selected ha o can remove hemical or co event employ andled as po he substance absorption of the right type ing 'escape' v it.	t of worker interactions is is done to reduce the azard 'physically' away t e or dilute an air contam intaminant in use. we overexposure. we overexposure. we overexposure. we in air could occur, resp cartridge; e; elocities which, in turn,	to provide this high leve risk. from the worker and ve inant if designed prope when particulates are piratory protection shou determine the 'capture	el of protection. ntilation that strategically rly. The design of a relatively large, a certain ild be considered. velocities' of fresh Air Speed:	
	 be highly effective The basic types of Process controls will Enclosure and/or in 'adds' and 'remove ventilation system Employers may ne Local exhaust proportion will If in spite of lo Such protection m (a): particle dust re (b): filter respiratori (c): fresh-air hood: Air contaminants gioriculating air require Type of Contaminidirect spray, spra 	in protecting workers and f engineering controls are: which involve changing the isolation of emission source set' air in the work environme must match the particular event to use multiple types of the powdered by mutual fri- cal exhaust an adverse co- ight consist of: espirators, if necessary, con- rs with absorption cartridge s or masks. generated in the workplace inter to effectively remove to	will typically be way a job activ e which keeps ent. Ventilatior process and ch f controls to pre- ere solids are h- iction. Incentration of t mbined with an e or canister of the contaminan	independen vity or process a selected ha o can remove hemical or co event employ andled as po he substance absorption of the right type ing 'escape' v it.	t of worker interactions is is done to reduce the azard 'physically' away t e or dilute an air contam intaminant in use. we overexposure. we overexposure. we overexposure. we in air could occur, resp cartridge; e; elocities which, in turn,	to provide this high leve risk. from the worker and ve inant if designed prope when particulates are piratory protection shou determine the 'capture	el of protection. ntilation that strategically rly. The design of a relatively large, a certain Id be considered. velocities' of fresh	
8.2.1. Appropriate engineering	 be highly effective The basic types of Process controls will Enclosure and/or in 'adds' and 'remove ventilation system Employers may ne Local exhaust proportion will If in spite of lo Such protection mitical edust references (c): fresh-air hood: Air contaminants of circulating air required Type of Contamining direct spray, sprageneration into z 	in protecting workers and f engineering controls are: which involve changing the isolation of emission source set air in the work environm must match the particular ede to use multiple types of twentilation is required whe be powdered by mutual fri- cal exhaust an adverse co- ight consist of: espirators, if necessary, co- rs with absorption cartridge s or masks. generated in the workplace lined to effectively remove to nant: ay painting in shallow booth one of rapid air motion) e blasting, tumbling, high s	will typically be way a job activ e which keeps ent. Ventilation process and ch f controls to pre- ere solids are h- iction. Incentration of t mbined with an e or canister of the contaminan	independen vity or process a selected ha o can remove hemical or co avent employ andled as po he substance absorption of the right type ing 'escape' v it.	t of worker interactions is is done to reduce the azard 'physically' away t e or dilute an air contam intaminant in use. we overexposure. we overexposure. we are could occur, resp e in air could occur, resp cartridge; e; elocities which, in turn, ading, crusher dusts, ga	to provide this high leve risk. from the worker and ve inant if designed prope when particulates are piratory protection shou determine the 'capture s discharge (active	el of protection. ntilation that strategically rly. The design of a relatively large, a certain ild be considered. velocities' of fresh Air Speed: 1-2.5 m/s (200-500	
8.2.1. Appropriate engineering	be highly effective The basic types of Process controls w Enclosure and/or i 'adds' and 'remove ventilation system Employers may ne • Local exhaust proportion will • If in spite of lo Such protection m (a): particle dust re (b): filter respirator (c): fresh-air hood: Air contaminants of circulating air requ Type of Contamin direct spray, spra generation into z grinding, abrasiv- very high rapid a	in protecting workers and f engineering controls are: which involve changing the isolation of emission source set air in the work environm must match the particular ede to use multiple types of twentilation is required whe be powdered by mutual fri- cal exhaust an adverse co- ight consist of: espirators, if necessary, co- rs with absorption cartridge s or masks. generated in the workplace lined to effectively remove to nant: ay painting in shallow booth one of rapid air motion) e blasting, tumbling, high s	will typically be way a job activ e which keeps nent. Ventilatior process and cf f controls to pre- ere solids are h- iction. Incentration of t mbined with an e or canister of the contaminant hs, drum filling, speed wheel ge	independen vity or process a selected ha o can remove hemical or co avent employ andled as po he substance absorption of the right type ing 'escape' v it.	t of worker interactions is is done to reduce the azard 'physically' away t e or dilute an air contam intaminant in use. we overexposure. we overexposure. we are could occur, resp e in air could occur, resp cartridge; e; elocities which, in turn, ading, crusher dusts, ga	to provide this high leve risk. from the worker and ve inant if designed prope when particulates are piratory protection shou determine the 'capture s discharge (active	el of protection. ntilation that strategically rly. The design of a relatively large, a certain ild be considered. velocities' of fresh Air Speed: 1-2.5 m/s (200-500 f/min.) 2.5-10 m/s (500-2000	
8.2.1. Appropriate engineering	be highly effective The basic types of Process controls w Enclosure and/or i 'adds' and 'remove ventilation system Employers may ne • Local exhaust proportion will • If in spite of lo Such protection m (a): particle dust re (b): filter respirator (c): fresh-air hood: Air contaminants of circulating air requ Type of Contamin direct spray, spra generation into z grinding, abrasiv- very high rapid a	in protecting workers and f engineering controls are: which involve changing the isolation of emission source set air in the work environm must match the particular ed to use multiple types of the powdered by mutual fri- cal exhaust an adverse co- light consist of: espirators, if necessary, co- rs with absorption cartridge s or masks. generated in the workplace uired to effectively remove to nant: ay painting in shallow booth one of rapid air motion) e blasting, tumbling, high s ir motion).	will typically be way a job activ e which keeps nent. Ventilatior process and cf f controls to pre- ere solids are h- iction. Incentration of t mbined with an e or canister of the contaminant hs, drum filling, speed wheel ge	independen vity or process a selected ha o can remove hemical or co avent employ andled as po he substance absorption of the right type ing 'escape' v it.	t of worker interactions is is done to reduce the azard 'physically' away t e or dilute an air contam intaminant in use. we overexposure. we overexposure. we are could occur, resp e in air could occur, resp cartridge; elocities which, in turn, ading, crusher dusts, ga s (released at high initia	to provide this high leve risk. from the worker and ve inant if designed prope when particulates are piratory protection shou determine the 'capture s discharge (active	el of protection. ntilation that strategically rly. The design of a relatively large, a certain ild be considered. velocities' of fresh Air Speed: 1-2.5 m/s (200-500 f/min.) 2.5-10 m/s (500-2000	
8.2.1. Appropriate engineering	 be highly effective The basic types of Process controls w Enclosure and/or i 'adds' and 'remove ventilation system Employers may ne Local exhaust proportion will If in spite of lo Such protection m (a): particle dust re (b): filter respiratori (c): fresh-air hood Air contaminants g circulating air requ Type of Contamin direct spray, spratigeneration into z grinding, abrasiv very high rapid a Within each range 	in protecting workers and f engineering controls are: which involve changing the isolation of emission source set air in the work environm must match the particular ed to use multiple types of the powdered by mutual fri- cal exhaust an adverse co- light consist of: espirators, if necessary, co- rs with absorption cartridge s or masks. generated in the workplace uired to effectively remove to nant: ay painting in shallow booth one of rapid air motion) e blasting, tumbling, high s ir motion).	will typically be way a job activ e which keeps ent. Ventilation process and ch f controls to pre- ere solids are h- iction. Incentration of t mbined with an e or canister of the contaminant ins, drum filling, speed wheel ge	independen vity or process a selected ha o can remove nemical or co event employ andled as po he substance absorption of the right type ng 'escape' v t. conveyer loa nerated dust	t of worker interactions is is done to reduce the azard 'physically' away t e or dilute an air contam intaminant in use. we overexposure. we overexposure. we are could occur, resp e in air could occur, resp cartridge; elocities which, in turn, ading, crusher dusts, ga s (released at high initia	to provide this high leve risk. from the worker and ve inant if designed prope when particulates are piratory protection shou determine the 'capture s discharge (active	el of protection. ntilation that strategically rly. The design of a relatively large, a certain ild be considered. velocities' of fresh Air Speed: 1-2.5 m/s (200-500 f/min.) 2.5-10 m/s (500-2000	

2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 4-10 m/s (800-2000 f/min) for extraction of crusher dusts generated 2 metres distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

8.2.2. Individual protection measures, such as personal protective equipment	
Eye and face protection	 Safety glasses with side shields. Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent] Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].
Skin protection	See Hand protection below

Hands/feet protection	 NOTE: A material may produce skin sanalisation in produces in an optical space individuals. Care must be taken, when removing gloves and other protective supports to avoid all possible skin contains. Containnated leather items, such as shoes, belts and watch-bands should be removed and destroyed. The seatebraic of suitable gloves does not only depend on the material, but also on further marks of quality which vay from manufacturer to manufacture. Where the chemical is a preparation of several abustances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when maning a final choice. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be waterial and not be calculated in advance and durability of glove type is dependent on usage. Important factors in the selection of gloves include: - requery and duration of contact. - demical messitance of glove material. - glove thickness and - devine the eartic dependent on usage. Important factors in the selection of gloves include: - devine the eartic devine state of a nelevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent). - When only being or totact its were breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.1.0 or national equivalent) is recommended. - When only being contact as expeeded, a glove with a protection class of 5 or higher (breakthrough time equiparity in the AS mini as application, gloves with a protection class of 3 or higher (breakthrough time equiparity in the AS mini as application, gloves whole the replaced. - Sow glove poymer types as reless affected by movoment and this should be taken int
Body protection	See Other protection below
Other protection	 Overalls. P.V.C apron. Barrier cream. Skin cleansing cream. Eye wash unit.

Respiratory protection

Type -P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	P1 Air-line*	-	PAPR-P1 -
up to 50 x ES	Air-line**	P2	PAPR-P2
up to 100 x ES	-	P3	-
		Air-line*	-
100+ x ES	-	Air-line**	PAPR-P3

* - Negative pressure demand ** - Continuous flow

A(AII classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Part Number: OR967425	Page 7 of 12	Issue Date: 20/07/2023
Version No: 1.1	Cv5.5-se	Print Date: 20/07/2023

· Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.

• The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).

Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.

Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
 Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under

appropriate government standards such as NIOSH (US) or CEN (EU) • Use approved positive flow mask if significant quantities of dust becomes airborne.

Try to avoid creating dust conditions.

8.2.3. Environmental exposure controls

See section 12

SECTION 9 Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Solid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Not Available	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available
Nanoform Solubility	Not Available	Nanoform Particle Characteristics	Not Available
Particle Size	Not Available		

9.2. Other information

Not Available

SECTION 10 Stability and reactivity

10.1.Reactivity	See section 7.2	
10.1.Reactivity	See section 7.2	
10.2. Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur. 	
10.3. Possibility of hazardous reactions	See section 7.2	
10.4. Conditions to avoid	See section 7.2	
10.5. Incompatible materials	See section 7.2	
10.6. Hazardous decomposition products	See section 5.3	

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Inhaled	The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.
Skin Contact	Skin contact is not thought to produce harmful health effects (as classified under EC Directives using animal models). Systemic harm, however, has been identified following exposure of animals by at least one other route and the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may cause transient discomfort characterised by tearing or conjunctival redness (as with windburn). Slight abrasive damage may also result.
Chronic	Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

Cy5.5-se	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.		
Acute Toxicity	¥	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend: 🗙

Data either not available or does not fill the criteria for classification
 Data available to make classification

11.2 Information on other hazards

11.2.1. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

11.2.2. Other information

See Section 11.1

SECTION 12 Ecological information

12.1. Toxicity

Legend: Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan - Bioconcentration Data 8. Vendor Data

DO NOT discharge into sewer or waterways.

12.2. Persistence	and	degradability
-------------------	-----	---------------

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients
12.3. Bioaccumulative poter	ntial	
Ingredient	Bioaccumulation	
	No Data available for all ingredients	
12.4. Mobility in soil		
Ingredient	Mobility	
	No Data available for all ingredients	

	Р	В	т
Relevant available data	Not Available	Not Available	Not Available
PBT	×	×	×
vPvB	×	×	×
PBT Criteria fulfilled? No			
vPvB			No

12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

12.7. Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

SECTION 13 Disposal considerations

13.1. Waste treatment methods	
Product / Packaging disposal	 Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible. Otherwise: If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. Where possible retain label warnings and SDS and observe all notices pertaining to the product. Recycle wherever possible or consult manufacturer for recycling options. Consult State Land Waste Management Authority for disposal. Bury residue in an authorised landfill. Recycle containers if possible, or dispose of in an authorised landfill.
Waste treatment options	Not Available
Sewage disposal options	Not Available

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number or ID number	Not Applicable			
14.2. UN proper shipping name	Not Applicable	Not Applicable		
14.3. Transport hazard class(es)	ClassNot ApplicableSubsidiary riskNot Applicable			
14.4. Packing group	Not Applicable			
14.5. Environmental hazard	Not Applicable			
14.6. Special precautions for user	Hazard identification (Kemler) Classification code Hazard Label Special provisions Limited quantity Tunnel Restriction Code	Not Applicable Not Applicable Not Applicable Not Applicable Not Applicable Not Applicable Not Applicable		

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable	
14.2. UN proper shipping name	Not Applicable	
14.3. Transport hazard class(es)	ICAO/IATA Class ICAO / IATA Subrisk ERG Code	Not Applicable Not Applicable
14.4. Packing group	Not Applicable	
14.5. Environmental hazard	Not Applicable	

Cy5.5-se

	Special provisions	Not Applicable
	Cargo Only Packing Instructions	Not Applicable
	Cargo Only Maximum Qty / Pack	Not Applicable
14.6. Special precautions for user	Passenger and Cargo Packing Instructions	Not Applicable
	Passenger and Cargo Maximum Qty / Pack	Not Applicable
	Passenger and Cargo Limited Quantity Packing Instructions	Not Applicable
	Passenger and Cargo Limited Maximum Qty / Pack	Not Applicable

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable		
14.2. UN proper shipping name	Not Applicable		
14.3. Transport hazard class(es)	IMDG Class Not Applicable IMDG Subrisk Not Applicable		
14.4. Packing group	Not Applicable		
14.5. Environmental hazard	Not Applicable		
14.6. Special precautions for user	EMS NumberNot ApplicableSpecial provisionsNot ApplicableLimited QuantitiesNot Applicable		

Inland waterways transport (ADN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable		
14.2. UN proper shipping name	Not Applicable		
14.3. Transport hazard class(es)	Not Applicable Not Applicable		
14.4. Packing group	Not Applicable		
14.5. Environmental hazard	Not Applicable		
14.6. Special precautions for user	Classification codeNot ApplicableSpecial provisionsNot ApplicableLimited quantityNot ApplicableEquipment requiredNot ApplicableFire cones numberNot Applicable		

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
Cy5.5-se	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
Cy5.5-se	Not Available

SECTION 15 Regulatory information

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

Cy5.5-se is found on the following regulatory lists

Not Applicable

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable - : Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2020/878; Regulation (EC) No 1272/2008 as updated through ATPs.

Information according to 2012/18/EU (Seveso III):

Seveso Category	Not Available

15.2. Chemical safety assessment

For further information please look at the Chemical Safety Assessment and Exposure Scenarios prepared by your Supply Chain if available.

Part Number: OR967425	Page 11 of 12	Issue Date: 20/07/2023
Version No: 1.1	Cy5.5-se	Print Date: 20/07/2023

ECHA SUMMARY

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	No (Cy5.5-se)
Canada - DSL	No (Cy5.5-se)
Canada - NDSL	No (Cy5.5-se)
China - IECSC	No (Cy5.5-se)
Europe - EINEC / ELINCS / NLP	No (Cy5.5-se)
Japan - ENCS	No (Cy5.5-se)
Korea - KECI	No (Cy5.5-se)
New Zealand - NZIoC	No (Cy5.5-se)
Philippines - PICCS	No (Cy5.5-se)
USA - TSCA	No (Cy5.5-se)
Taiwan - TCSI	No (Cy5.5-se)
Mexico - INSQ	No (Cy5.5-se)
Vietnam - NCI	No (Cy5.5-se)
Russia - FBEPH	No (Cy5.5-se)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	20/07/2023
Initial Date	20/07/2023

Full text Risk and Hazard codes

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered. For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

Definitions and abbreviations

PC - TWA: Permissible Concentration-Time Weighted Average PC - STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit, IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index AIIC: Australian Inventory of Industrial Chemicals DSL: Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Part Number: OR967425		Page 12 of 12		Issue Date: 20/07/2023	
V	Version No: 1.1		Cy5.5-se		Print Date: 20/07/2023
	Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	Classification Procedure			
	Acute Toxicity (Oral) Category 4, H302	Expert judgement			
	Sensitisation (Skin) Category 1A, H317	Expert judgement			

end of SDS

Powered by AuthorITe, from Chemwatch.