

Apollo Scientific

Part Number: PC302697

Version No: 1.1 Safety Data Sheet (Conforms to Annex II of REACH (1907/2006) - Regulation 2020/878) Chemwatch Hazard Alert Code: 3

Issue Date: **17/04/2023** Print Date: **23/05/2024** S.REACH.GB-NIR.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

1.1. Product Identifier

Product name	-Methyl-5-(pentafluorosulfur)aniline	
Synonyms	Not Available	
Proper shipping name	TOXIC SOLID, ORGANIC, N.O.S.	
Other means of identification	Not Available	
CAS number	623943-52-2*	

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Use according to manufacturer's directions.
Uses advised against	No specific uses advised against are identified.

1.3. Details of the manufacturer or supplier of the safety data sheet

Registered company name	Apollo Scientific
Address	Whitefield Road, Bredbury SK62QR United Kingdom
Telephone	01614060505
Fax	0161 406 0506
Website	http://www.apolloscientific.co.uk/
Email	sales@apolloscientific.co.uk

1.4. Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	Not Available
Other emergency telephone numbers	Not Available

SECTION 2 Hazards identification

2.1. Classification of the substance or mixture

Classification according to regulation (EC) No 1272/2008 [CLP] and amendments ^[1]	H301 - Acute Toxicity (Oral) Category 3, H311 - Acute Toxicity (Dermal) Category 3, H319 - Serious Eye Damage/Eye Irritation Category 2, H335 - Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

2.2. Label elements

Hazard pictogram(s)		
Signal word Danger		
Hazard statement(s)		
H301	Toxic if swallowed.	
H311	Toxic in contact with skin.	

H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
	•

Supplementary statement(s) Not Applicable

Precautionary statement(s) Prevention

P264	Wash all exposed external body areas thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, protective clothing, eye protection and face protection.
P261	Avoid breathing dust/fumes.

Precautionary statement(s) Response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider.
P330	Rinse mouth.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P361+P364	Take off immediately all contaminated clothing and wash it before reuse.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Precautionary statement(s) Storage

P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

Material does not contain any CLP Article 18 substances.

2.3. Other hazards

Inhalation and/or ingestion may produce health damage*.

REACH - Art.57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS print date.

SECTION 3 Composition / information on ingredients

3.1.Substances

1. CAS No 2.EC No 3.Index No 4.REACH No	% [weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	SCL / M- Factor	Nanoform Particle Characteristics
Not Available	100	2-Methyl-5- (pentafluorosulfur)aniline	Not Applicable	Not Applicable	Not Available

Legend: 1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L; * EU IOELVs available; [e] Substance identified as having endocrine disrupting properties

3.2.Mixtures

See 'Information on ingredients' in section 3.1

SECTION 4 First aid measures

4.1. Description of first aid measures

and bescription of mist ald met	
Eye Contact	 If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs: Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor.
Ingestion	If swallowed do NOT induce vomiting.
	Continued

F If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration Observe the patient carefully. • Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. • Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11

4.3. Indication of any immediate medical attention and special treatment needed

As in all cases of suspected poisoning, follow the ABCDEs of emergency medicine (airway, breathing, circulation, disability, exposure), then the ABCDEs of toxicology (antidotes, basics, change absorption, change distribution, change elimination).

For poisons (where specific treatment regime is absent):

BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 L/min.
- Monitor and treat, where necessary, for pulmonary oedema.
- Monitor and treat, where necessary, for shock.
- Anticipate seizures.
- DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.

ADVANCED TREATMENT

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Positive-pressure ventilation using a bag-valve mask might be of use
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- + Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eve irrigation. BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

SECTION 5 Firefighting measures

5.1. Extinguishing media

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

5.2. Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.
5.3. Advice for firefighters	
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use.
Fire/Explosion Hazard	 Non combustible. Not considered a significant fire risk, however containers may burn. May emit poisonous fumes.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures See section 8

6.2. Environmental precautions

See section 12

6.3. Methods and material for containment and cleaning up

Minor Spills	 Remove all ignition sources. Clean up all spills immediately. Avoid contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Use dry clean up procedures and avoid generating dust. Place in a suitable, labelled container for waste disposal. 	
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. Stop leak if safe to do so. Contain spill with sand, earth or vermiculite. 	
		Continued

 Collect recoverable product into labelled containers for recycling. Neutralise/decontaminate residue (see Section 13 for specific agent).
 Collect solid residues and seal in labelled drums for disposal. Wash area and prevent runoff into drains.
 After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using. If contamination of drains or waterways occurs, advise emergency services.

6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

7.1. Precautions for safe handli	ng
Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. DO NOT allow material to contact humans, exposed food or food utensils. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
Fire and explosion protection	See section 5
Other information	 Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS.

7.2. Conditions for safe storage, including any incompatibilities

Suitable container	 Lined metal can, lined metal pail/ can. Plastic pail. Polyliner drum. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks. For low viscosity materials Drums and jerricans must be of the non-removable head type. Where a can is to be used as an inner package, the can must have a screwed enclosure. For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.): Removable head packaging; Cans with friction closures and low pressure tubes and cartridges may be used. Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages *. In addition, where inner packagings are glass and contain liquids of packing group I and II there must be sufficient inert absorbent to absorb any spillage *. * unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.
Storage incompatibility	None known ▶ Store under argon
Hazard categories in accordance with Regulation (EC) No 2012/18/EU (Seveso III)	Not Available
Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of	Not Available

7.3. Specific end use(s) See section 1.2

SECTION 8 Exposure controls / personal protection

8.1. Control parameters

Ingredient	DNELs Exposure Pattern Worker	PNECs Compartment
Not Available	Not Available	Not Available

* Values for General Population

Occupational Exposure Limits (OEL)

	• •					
INGREDIENT DATA						
Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available
Not Applicable Emergency Limits						
Ingredient	TEEL-1		TEEL-2		TEEL-3	
2-Methyl-5- (pentafluorosulfur)aniline	Not Available		Not Available		Not Available	

(pentafluorosulfur)aniline			
Ingredient	Original IDLH	Revised IDLH	
2-Methyl-5- (pentafluorosulfur)aniline	Not Available	Not Available	

8.2. Exposure controls

	Engineering controls are used to remove a hazard or place can be highly effective in protecting workers and will typica The basic types of engineering controls are: Process controls which involve changing the way a job acti Enclosure and/or isolation of emission source which keeps strategically 'adds' and 'removes' air in the work environme design of a ventilation system must match the particular pro Employers may need to use multiple types of controls to pro Local exhaust ventilation usually required. If risk of overexp protection. Supplied-air type respirator may be required in a An approved self contained breathing apparatus (SCBA) m Provide adequate ventilation in warehouse or closed storage velocities which, in turn, determine the 'capture velocities' of	Ily be independent of worker interact vity or process is done to reduce th a selected hazard 'physically' away int. Ventilation can remove or dilute ocess and chemical or contaminant event employee overexposure. posure exists, wear approved respir special circumstances. Correct fit is ay be required in some situations. ge area. Air contaminants generated	ctions to provide this high le risk. y from the worker and ver an air contaminant if des t in use. rator. Correct fit is essentia essential to ensure adeq d in the workplace posses	level of protection. htilation that igned properly. The al to obtain adequate uate protection. ss varying 'escape'	
	Type of Contaminant:			Air Speed:	
	solvent, vapours, degreasing etc., evaporating from tank	(in still air).		0.25-0.5 m/s (50- 100 f/min.)	
8.2.1. Appropriate	aerosols, fumes from pouring operations, intermittent con drift, plating acid fumes, pickling (released at low velocity		ansfers, welding, spray	0.5-1 m/s (100- 200 f/min.)	
engineering controls	direct spray, spray painting in shallow booths, drum filling, generation into zone of rapid air motion)	, conveyer loading, crusher dusts, g	as discharge (active	1-2.5 m/s (200- 500 f/min.)	
	grinding, abrasive blasting, tumbling, high speed wheel ge very high rapid air motion).	enerated dusts (released at high ini	tial velocity into zone of	2.5-10 m/s (500- 2000 f/min.)	
	Within each range the appropriate value depends on:				
	Lower end of the range	Upper end of the range			
	1: Room air currents minimal or favourable to capture	1: Disturbing room air currents			
	2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity			
	3: Intermittent, low production.	3: High production, heavy use			
	4: Large hood or large air mass in motion	4: Small hood-local control only			
	Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.				
	decreases with the square of distance from the extraction p adjusted, accordingly, after reference to distance from the a minimum of 1-2 m/s (200-400 f/min) for extraction of solv mechanical considerations, producing performance deficits	point (in simple cases). Therefore the contaminating source. The air veloc ents generated in a tank 2 meters of within the extraction apparatus, ma	he air speed at the extract bity at the extraction fan, for distant from the extraction	ion point should be or example, should be point. Other	
8.2.2. Individual protection measures, such as personal protective equipment	decreases with the square of distance from the extraction p adjusted, accordingly, after reference to distance from the a minimum of 1-2 m/s (200-400 f/min) for extraction of solv mechanical considerations, producing performance deficits	point (in simple cases). Therefore the contaminating source. The air veloc ents generated in a tank 2 meters of within the extraction apparatus, ma	he air speed at the extract bity at the extraction fan, for distant from the extraction	ion point should be or example, should be point. Other	
measures, such as personal	decreases with the square of distance from the extraction p adjusted, accordingly, after reference to distance from the a minimum of 1-2 m/s (200-400 f/min) for extraction of solv mechanical considerations, producing performance deficits	boint (in simple cases). Therefore the contaminating source. The air veloci- ents generated in a tank 2 meters of within the extraction apparatus, mains are installed or used.	the air speed at the extract ity at the extraction fan, for distant from the extraction ake it essential that theore ate irritants. A written polic ace or task. This should in experience. Medical and fi he event of chemical expore moved at the first signs of	ion point should be or example, should be point. Other etical air velocities are etical air velocities are sy document, nclude a review of irst-aid personnel soure, begin eye eye redness or	
measures, such as personal protective equipment	 decreases with the square of distance from the extraction pradjusted, accordingly, after reference to distance from the e a minimum of 1-2 m/s (200-400 f/min) for extraction of solv mechanical considerations, producing performance deficits multiplied by factors of 10 or more when extraction systems Safety glasses with side shields. Chemical goggles. [AS/NZS 1337.1, EN166 or nationa Contact lenses may pose a special hazard; soft contact describing the wearing of lenses or restrictions on use, lens absorption and adsorption for the class of chemicar should be trained in their removal and suitable equipmirrigation immediately and remove contact lens as soor irritation - lens should be removed in a clean environm 	boint (in simple cases). Therefore the contaminating source. The air veloci- ents generated in a tank 2 meters of within the extraction apparatus, mains are installed or used.	the air speed at the extract ity at the extraction fan, for distant from the extraction ake it essential that theore ate irritants. A written polic ace or task. This should in experience. Medical and fi he event of chemical expore moved at the first signs of	ion point should be or example, should be point. Other etical air velocities are etical air velocities are sy document, nclude a review of irst-aid personnel soure, begin eye eye redness or	
measures, such as personal protective equipment	 decreases with the square of distance from the extraction pradjusted, accordingly, after reference to distance from the era minimum of 1-2 m/s (200-400 f/min) for extraction of solv mechanical considerations, producing performance deficits multiplied by factors of 10 or more when extraction systems Safety glasses with side shields. Chemical goggles. [AS/NZS 1337.1, EN166 or national Contact lenses may pose a special hazard; soft contact describing the wearing of lenses or restrictions on use, lens absorption and adsorption for the class of chemical system intrigation immediately and remove contact lens as soor irritation - lens should be removed in a clean environm Intelligence Bulletin 59]. 	boint (in simple cases). Therefore the contaminating source. The air veloci- ents generated in a tank 2 meters of within the extraction apparatus, ma is are installed or used.	e air speed at the extract ity at the extraction fan, for distant from the extraction ake it essential that theore ate irritants. A written polic ace or task. This should in experience. Medical and f he event of chemical expor moved at the first signs of d hands thoroughly. [CDC ks of quality which vary for e glove material can not b protective gloves and has hands. After using gloves	ion point should be or example, should be point. Other etical air velocities are at cal air velocities are by document, nelude a review of irst-aid personnel osure, begin eye eye redness or NIOSH Current om manufacturer to be calculated in s to be observed	

	chemical resistance of glove material, glove thickness and
	Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).
	· When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than
	240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
	· When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to
	EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
	Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term
	use.
	Contaminated gloves should be replaced.
	As defined in ASTM F-739-96 in any application, gloves are rated as:
	Excellent when breakthrough time > 480 min
	Good when breakthrough time > 20 min
	Fair when breakthrough time < 20 min
	Poor when glove material degrades
	For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.
	It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the
	permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.
	Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers
	technical data should always be taken into account to ensure selection of the most appropriate glove for the task.
	Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:
	Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
	Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion
	or puncture potential
	Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed
	Gioves must only be worn on clear narios. After using gioves, narios should be washed and uned thoroughly. Application of a hor-pertained moisturiser is recommended.
	• Wear chemical protective gloves, e.g. PVC.
	Wear safety footwear or safety gumboots, e.g. Rubber
Body protection	See Other protection below
	▶ Overalls.
	Evewash unit.
Other protection	Barrier cream.
	 Skini deansing cream.

Respiratory protection

Type -P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	P1 Air-line*	-	PAPR-P1 -
up to 50 x ES	Air-line**	P2	PAPR-P2
up to 100 x ES	-	P3	-
		Air-line*	-
100+ x ES	-	Air-line**	PAPR-P3

* - Negative pressure demand ** - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

· Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.

The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).

Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.

Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.

Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)

· Use approved positive flow mask if significant quantities of dust becomes airborne.

· Try to avoid creating dust conditions.

8.2.3. Environmental exposure controls

See section 12

SECTION 9 Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Not Available			
Physical state	Solid	Relative density (Water = 1)	Not Available	
Odour	Not Available	Partition coefficient n-octanol / water	Not Available	
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available	
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available	
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available	

Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Not Available	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available
Nanoform Solubility	Not Available	Nanoform Particle Characteristics	Not Available
Particle Size	Not Available		

9.2. Other information

Not Available

SECTION 10 Stability and reactivity

10.1.Reactivity	See section 7.2
10.2. Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
10.3. Possibility of hazardous reactions	See section 7.2
10.4. Conditions to avoid	See section 7.2
10.5. Incompatible materials	See section 7.2
10.6. Hazardous decomposition products	See section 5.3

SECTION 11 Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhaled	The material is not thought to produce respiratory irr dusts, or fumes, especially for prolonged periods, m Inhalation of dusts, generated by the material during	ay produce respiratory discomfort ar	nd occasionally, distress.
Ingestion	Accidental ingestion of the material may be damagir	ng to the health of the individual.	
Skin Contact	The material is not thought to produce adverse heal models). Nevertheless, good hygiene practice requir occupational setting. Open cuts, abraded or irritated skin should not be ex Entry into the blood-stream, through, for example, co skin prior to the use of the material and ensure that	res that exposure be kept to a minim xposed to this material uts, abrasions or lesions, may produ	um and that suitable gloves be used in an ce systemic injury with harmful effects. Examine the
Eye	This material can cause eye irritation and damage ir	n some persons.	
Chronic	Long-term exposure to the product is not thought to animal models); nevertheless exposure by all routes		
2-Methyl-5-	ΤΟΧΙΟΙΤΥ	IRRITATION	
(pentafluorosulfur)aniline	Not Available	Not Available	
Legend:	 Value obtained from Europe ECHA Registered Su specified data extracted from RTECS - Register of 1 		btained from manufacturer's SDS. Unless otherwise
Acute Toxicity	✓	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	¥	STOT - Single Exposure	✓
•		- .	
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×

Legend:

11.2 Information on other hazards

11.2.1. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

11.2.2. Other information

See Section 11.1

SECTION 12 Ecological information

1. Toxicity					
2-Methyl-5-	Endpoint	Test Duration (hr)	Species	Value	Source
(pentafluorosulfur)aniline	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:		D Toxicity Data 2. Europe ECHA Reg tic Toxicity Data 5. ECETOC Aquatic on Data 8. Vendor Data			

DO NOT discharge into sewer or waterways.

12.2. Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients
12.2 Biogeoumulative potentia	1	

12.3. Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

12.4. Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

12.5. Results of PBT and vPvB assessment

	Р	В	т	
Relevant available data	Not Available	Not Available	Not Available	
PBT	×	×	×	
vPvB	×	×	×	
PBT Criteria fulfilled?			No	
vPvB			No	

12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

12.7. Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

SECTION 13 Disposal considerations

13.1. Waste treatment methods	
Product / Packaging disposal	 Recycle wherever possible or consult manufacturer for recycling options. Consult State Land Waste Management Authority for disposal. Bury residue in an authorised landfill. Recycle containers if possible, or dispose of in an authorised landfill.
Waste treatment options	Not Available
Sewage disposal options	Not Available

SECTION 14 Transport information

Labels Required

	6
Marine Pollutant	NO
HAZCHEM	2X

Land transport (ADR-RID)

14.1. UN number or ID number	2811	
14.2. UN proper shipping name	TOXIC SOLID, ORGANIC, N	N.O.S.
14.3. Transport hazard class(es)	Class 6.1 Subsidiary Hazard Not	1 tApplicable
14.4. Packing group	Ш	
14.5. Environmental hazard	Not Applicable	
	Hazard identification (Kem	nler) 60
	Classification code	T2
14.6. Special precautions for	Hazard Label	6.1
user	Special provisions	274 614
	Limited quantity	5 kg
	Tunnel Restriction Code	E

Air transport (ICAO-IATA / DGR)

14.1. UN number	2811		
14.2. UN proper shipping name	Toxic solid, organic, n.o.s. *		
	ICAO/IATA Class	6.1	
14.3. Transport hazard class(es)	ICAO / IATA Subsidiary Hazard	Not Applicable	
01000(00)	ERG Code	6L	
14.4. Packing group	Ш		
14.5. Environmental hazard	Not Applicable		
	Special provisions		A3 A5
	Cargo Only Packing Instructions		677
	Cargo Only Maximum Qty / Pack		200 kg
14.6. Special precautions for user	Passenger and Cargo Packing Instructions		670
user	Passenger and Cargo Maximum Qty / Pack		100 kg
	Passenger and Cargo Limited Qu	Passenger and Cargo Limited Quantity Packing Instructions	
	Passenger and Cargo Limited Ma	aximum Qty / Pack	10 kg

Sea transport (IMDG-Code / GGVSee)

14.1. UN number	2811		
14.2. UN proper shipping name	TOXIC SOLID, ORGANIC, N.O.S.		
14.3. Transport hazard class(es)	IMDG Class	6.1	
	IMDG Subsidiary Ha	azard Not Applicable	
14.4. Packing group	Ш		
14.5 Environmental hazard	Not Applicable		
14.6. Special precautions for user	EMS Number	F-A, S-A	
	Special provisions	223 274	
	Limited Quantities	5 kg	

Inland waterways transport (ADN)

	,		
14.1. UN number	2811		
14.2. UN proper shipping name	TOXIC SOLID, ORGANIC, N.O.S.		
14.3. Transport hazard class(es)	6.1 Not Applicable		
14.4. Packing group	Ш		
14.5. Environmental hazard	Not Applicable		
14.6. Special precautions for user	Classification code Special provisions Limited quantity Equipment required Fire cones number	T2 274; 614; 802 5 kg PP, EP 0	

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

•			
Product name	Group		
14.7.3. Transport in bulk in	n accordance with the IGC Code		
Product name	Ship Type		

SECTION 15 Regulatory information

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

Additional Regulatory Information

Not Applicable

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable - : Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2020/878; Regulation (EC) No 1272/2008 as updated through ATPs.

Information according to 2012/18/EU (Seveso III):

Seveso Category	Not Available
-----------------	---------------

15.2. Chemical safety assessment

For further information please look at the Chemical Safety Assessment and Exposure Scenarios prepared by your Supply Chain if available.

National Inventory Status	
National Inventory	Status
Australia - AIIC / Australia Non- Industrial Use	Not Available
Canada - DSL	Not Available
Canada - NDSL	Not Available
China - IECSC	Not Available
Europe - EINEC / ELINCS / NLP	Not Available
Japan - ENCS	Not Available
Korea - KECI	Not Available
New Zealand - NZIoC	Not Available
Philippines - PICCS	Not Available
USA - TSCA	Not Available
Taiwan - TCSI	Not Available
Mexico - INSQ	Not Available
Vietnam - NCI	Not Available
Russia - FBEPH	Not Available
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	17/04/2023
Initial Date	06/05/2022

Full text Risk and Hazard codes

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the

workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

- EN 166 Personal eye-protection
- EN 340 Protective clothing
- EN 374 Protective gloves against chemicals and micro-organisms
- EN 13832 Footwear protecting against chemicals
- EN 133 Respiratory protective devices

Definitions and abbreviations

- PC TWA: Permissible Concentration-Time Weighted Average
- PC STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit。
- IDLH: Immediately Dangerous to Life or Health Concentrations

- ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
 OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- BEI: Biological Exposure Index
- DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration
- AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- IECSC: Inventory of Existing Chemical Substance in China
- EINECS: European INventory of Existing Commercial chemical Substances
 ELINCS: European List of Notified Chemical Substances
 NLP: No-Longer Polymers

- ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
 PICCS: Philippine Inventory of Chemicals and Chemical Substances
 TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.