

Apollo Scientific

Part Number: **PC500582** Version No: **1.1** Safety Data Sheet (Conforms to Annex II of REACH (1907/2006) - Regulation 2020/878) Chemwatch Hazard Alert Code: 3

Issue Date: **16/05/2022** Print Date: **01/08/2023** S.REACH.GBR.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

1.1. Product Identifier

Product name	Bromomethyl)-5-fluorobenzenesulphonyl chloride	
Chemical Name	2-(Bromomethyl)-5-fluorobenzenesulphonyl chloride	
Synonyms	Not Available	
Proper shipping name	CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.	
Chemical formula	Not Available	
Other means of identification	Not Available	
CAS number	1820717-41-6*	

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Not Available
Uses advised against	No specific uses advised against are identified.

1.3. Details of the manufacturer or supplier of the safety data sheet

Registered company name	Apollo Scientific
Address	Whitefield Road, Bredbury SK62QR United Kingdom
Telephone	01614060505
Fax	0161 406 0506
Website	http://www.apolloscientific.co.uk/
Email	sales@apolloscientific.co.uk

1.4. Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	Not Available
Other emergency telephone numbers	Not Available

SECTION 2 Hazards identification

2.1. Classification of the substance or mixture

Classification according to regulation (EC) No 1272/2008 [CLP] and amendments ^[1]

H314 - Skin Corrosion/Irritation Category 1B, H318 - Serious Eye Damage/Eye Irritation Category 1

Legend:	1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

2.2. Label elements Hazard pictogram(s) Signal word Danger

Hazard statement(s)

H314

Causes severe skin burns and eye damage.

Supplementary statement(s)

Not Applicable

Precautionary statement(s) Prevention

P260	Do not breathe mist/vapours/spray.	
P264	Wash all exposed external body areas thoroughly after handling.	
P280	Wear protective gloves, protective clothing, eye protection and face protection.	

Precautionary statement(s) Response

P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor/physician/first aider.
P363	Wash contaminated clothing before reuse.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Precautionary statement(s) Storage

P405 Store locked up.

Precautionary statement(s) Disposal

P501

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

2.3. Other hazards

REACH - Art.57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS print date.

SECTION 3 Composition / information on ingredients

3.1.Substances

1. CAS No 2.EC No 3.Index No 4.REACH No	%[weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	SCL / M-Factor	Nanoform Particle Characteristics
Not Available	100	2-(Bromomethyl)- 5-fluorobenzenesulphonyl chloride	Not Applicable	Not Applicable	Not Available

Legend: 1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L; * EU IOELVs available; [e] Substance identified as having endocrine disrupting properties

3.2.Mixtures

See 'Information on ingredients' in section 3.1

4.1. Description of first aid measures

Eye Contact	 If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	 If skin or hair contact occurs: Immediately flush body and clothes with large amounts of water, using safety shower if available. Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to hospital, or doctor.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay. Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema. Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs). As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested. Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered. This must definitely be left to a doctor or person authorised by him/her. (ICSC13719)
Ingestion	 For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Transport to hospital or doctor without delay.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11

4.3. Indication of any immediate medical attention and special treatment needed

For acute or short term repeated exposures to strong acids:

- Airway problems may arise from laryngeal edema and inhalation exposure. Treat with 100% oxygen initially.
- Respiratory distress may require cricothyroidotomy if endotracheal intubation is contraindicated by excessive swelling
- Intravenous lines should be established immediately in all cases where there is evidence of circulatory compromise.
- Strong acids produce a coagulation necrosis characterised by formation of a coagulum (eschar) as a result of the dessicating action of the acid on proteins in specific tissues.

INGESTION:

- Immediate dilution (milk or water) within 30 minutes post ingestion is recommended.
- DO NOT attempt to neutralise the acid since exothermic reaction may extend the corrosive injury.
- Be careful to avoid further vomit since re-exposure of the mucosa to the acid is harmful. Limit fluids to one or two glasses in an adult.
- Charcoal has no place in acid management.
- Some authors suggest the use of lavage within 1 hour of ingestion.
- SKIN:
- Skin lesions require copious saline irrigation. Treat chemical burns as thermal burns with non-adherent gauze and wrapping.
- Deep second-degree burns may benefit from topical silver sulfadiazine.

EYE:

- Eye injuries require retraction of the eyelids to ensure thorough irrigation of the conjuctival cul-de-sacs. Irrigation should last at least 20-30 minutes. DO NOT use neutralising agents or any other additives. Several litres of saline are required.
- Cycloplegic drops, (1% cyclopentolate for short-term use or 5% homatropine for longer term use) antibiotic drops, vasoconstrictive agents or artificial tears may be indicated dependent on the severity of the injury.
- * Steroid eye drops should only be administered with the approval of a consulting ophthalmologist).

[Ellenhorn and Barceloux: Medical Toxicology]

SECTION 5 Firefighting measures

5.1. Extinguishing media

- ▶ Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog Large fires only.

5.2. Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may
	result

5.3. Advice for firefighters

Fire Fighting	
Fire/Explosion Hazard	 Combustible. Slight fire hazard when exposed to heat or flame. Acids may react with metals to produce hydrogen, a highly flammable and explosive gas. Heating may cause expansion or decomposition leading to violent rupture of containers. May emit acrid smoke and corrosive fumes. Combustion products include: carbon monoxide (CO) , carbon dioxide (CO2) , other pyrolysis products typical of burning organic material.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

See section 8

6.2. Environmental precautions

See section 12

6.3. Methods and material for containment and cleaning up

 Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material. Check regularly for spills and leaks. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal.

6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

T.I. Frecautions for sale	nanunng
Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. WARNING: To avoid violent reaction, ALWAYS add material to water and NEVER water to material. Avoid smoking, naked lights or ignition sources. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling.

	 Work clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
Fire and explosion protection	See section 5
Other information	 Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS.

7.2. Conditions for safe storage, including any incompatibilities

Suitable container- Check regularly for spills and leaks - Lined metal can, lined metal pail/ can. - Plastic pail. - Poking as recommended by manufacturer. - Check all containers are clearly labelled and free from leaks. - For tow viscosity materials - Drums and jerricans must be of the non-removable head type. - Drums and jerricans must be of the non-removable head type. - Drums and jerricans must be of the non-removable head type. - Where a can is to be used as an inner package, the can must have a screwed enclosure. For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.): - Removable head packaging; - Cans with friction closures and - low pressure tubes and cartridges may be used. - Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient inert cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.Storage incompatibility& Sister at 2-8°C - Lachrymatory - Light sensitive - Store under argonHazard categories in accordance with Regulation (EC) Not AvailableNot AvailableAudition (ES) of dangerous substances are resti - Store under argonNot AvailableOutigrying quantity (tonnes) of dangerous in Article 3(10) for the application ofNot Available		DO NOT use aluminium or galvanised containers
Plastic pail.Polyliner drum.Polyliner drum.Polyliner drum.Packing as recommended by manufacturer.Check all containers are clearly labelled and free from leaks. For low viscosity materialsSuitable containerWhere a can is to be used as an inner package, the can must have a screwed enclosure.For materialis with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.): * Removable head packaging; Cans with friction closures and low pressure tubes and cartridges may be used.Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient iner cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.Storage incompatibility* Segregate from alkalles, oxidising agents and chemicals readily decomposed by acids, i.e. cyanides, sufficient, acidonal ses. * Store at 2-8°C * Lachymatory Light sensitive * Store under argonHazard categories in substances as referred to in Article 3(10) for theNot AvailableOualifying quantity in Article 3(10) for theNot Available		Check regularly for spills and leaks
Polyliner drum.Packing as recommended by manufacturer. • Check all containers are clearly labelied and free from leaks. For low viscosity materials • Drums and jerricans must be of the non-removable head type. • Where a can is to be used as an inner package, the can must have a screwed enclosure. For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.): • Removable head packaging; • Cans with friction closures and • low pressure tubes and cartridges may be used. • Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient iner cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.Storage incompatibility• Segregate from alkalies, oxidising agents and chemicals readily decomposed by acids, i.e. cyanides, sufficies, carbonates. • Store at 2.ª°C • Lachymatory • Light sensitive • Store under argonHazard categories in accordance with Regulation (EC) No 1272/2008Not AvailableQualifying quantity in Article 3(10) for theNot Available		▶ Lined metal can, lined metal pail/ can.
Suitable containerPacking as recommended by manufacturer. 		▶ Plastic pail.
Suitable containerCheck all containers are clearly labelled and free from leaks. For low viscosity materials • Drums and jericinas must be of the non-removable head type. • Where a can is to be used as an inner package, the can must have a screwed enclosure. For materials with a viscosity of at least 2680 OS1. (23 deg. C) and solids (between 15 C deg. and 40 deg C.): • Removable head backy of at least 2680 OS1. (23 deg. C) and solids (between 15 C deg. and 40 deg C.): • Removable head packy of at least 2680 OS1. (23 deg. C) and solids (between 15 C deg. and 40 deg C.): • Removable head packy of at least 2680 OS1. (23 deg. C) and solids (between 15 C deg. and 40 deg C.): • Removable head packy of at least 2680 OS1. (23 deg. C) and solids (between 15 C deg. and 40 deg C.): • Removable head type. • Iow pressure tubes and cartridges may be used. • low pressure tubes and cartridges may be used. • Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient iner cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic. • Segregate from alkalles, oxidising agents and chemicals readily decomposed by acids, i.e. cyanides, suffices, carbonates. • Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air. • Avoid strong bases. • Store at 2-8°C • Lachtymatory • Light sensitive • Store under argonHazard categories in accordance with n accordance with n accordance with n Article 3(10) for theNot AvailableQualifying quantify in Article 3(10) for theNot Available		▶ Polyliner drum.
Suitable containerFor low viscosity materials 		Packing as recommended by manufacturer.
Suitable container• Drums and jerricans must be of the non-removable head type. • Where a can is to be used as an inner package, the can must have a screwed enclosure. For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.): • Removable head packaging; • Cans with friction closures and • low pressure tubes and cartridges may be used. • Where combination packages are used, and the inner packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.Storage incompatibility• Segregate from alkalies, oxidising agents and chemicals readily decomposed by acids, i.e. cyanides, sulfides, carbonates. • Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air. • Not at 2-8°C • Lachrymatory • Light sensitive • Store argonNot AvailableHazard categories in accordance with (tonnes) of dangerous substances as referred to in Article 3(10) for theNot Available		Check all containers are clearly labelled and free from leaks.
Suitable container• Where a can is to be used as an inner package, the can must have a screwed enclosure.For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.): • Cans with friction closures and • low pressure tubes and cartridges may be used.Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient iner cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.Storage incompatibility• Segregate from alkalies, oxidising agents and chemicals readily decomposed by acids, i.e. cyanides, sufficient timer cushoning material in contact with ingregative acids and the may form an explosive mixture with air. • Avoid strong bases. • Store at 2-8° C • Lachrymatory • Light sensitive • Store at 2-8° C • Lachrymatory • Light sensitive • Store are argonHazard categories in accordance with Regulation (EC) dangerous substances are ferred to in Article 3(10) for theNot AvailableOualifying quantity (tonnes) of dangerous substances are ferred to in Article 3(10) for theNot Available		For low viscosity materials
For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.): * Removable head packaging; * Cans with friction closures and * low pressure tubes and cartridges may be used. * Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient inert cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic. * Segregate from alkalies, oxidising agents and chemicals readily decomposed by acids, i.e. cyanides, sulfides, carbonates. * Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air. * Avoid strong bases. * Store at 2-8°C * Lachrymatory * Light sensitive * Moisture sensitive * Store under argon Mazard categories in accordance with Regulation (EC) No 1272008 Qualifying quantity (tonnes) of dangerous substances as referred. substances as referred. Not Available Not Available		Drums and jerricans must be of the non-removable head type.
• Removable head packaging; • Cans with friction closures and • low pressure tubes and cartridges may be used. • Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient inert cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic. • Segregate from alkalies, oxidising agents and chemicals readily decomposed by acids, i.e. cyanides, sulfides, carbonates. • Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air. • Avoid strong bases. • Store at 2-8°C • Light sensitive • Moisture sensitive • Store under argon Mazard categories in (EC) No 1272/2008 Qualifying quantity (tornes) of dangerous substances are reare used, and the substances are close fitting moulded plastic substances.es are ferefered bin Article 3(10) for the	Suitable container	Where a can is to be used as an inner package, the can must have a screwed enclosure.
• Cans with friction closures and • low pressure tubes and cartridges may be used. • • Where combination packages are used, and the inner packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with here plastic. Where combination packages are used , and the inner packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with here plastic. Storage incompatibility • Segregate from alkalies, oxidising agents and chemicals readily decomposed by acids, i.e. cyanides, sulfides, carbonates. • Store at 2-8°C • Lachrymatory • Light sensitive • Moisture sensitive • Store under argon • Not Available Mazard categorise in (connes) of dangerous substances are refore to in Article 3(10) for the Not Available		For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.):
• Cans with friction closures and • low pressure tubes and cartridges may be used. • • Where combination packages are used, and the inner packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with here plastic. Where combination packages are used , and the inner packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with here plastic. Storage incompatibility • Segregate from alkalies, oxidising agents and chemicals readily decomposed by acids, i.e. cyanides, sulfides, carbonates. • Store at 2-8°C • Lachrymatory • Light sensitive • Moisture sensitive • Store under argon • Not Available Mazard categorise in (connes) of dangerous substances are refore to in Article 3(10) for the Not Available		Removable head packaging;
may be used.Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient iner cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.Storage incompatibility> Segregate from alkalies, oxidising agents and chemicals readily decomposed by acids, i.e. cyanides, sulfides, carbonates. >> Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air. >> Avoid strong bases. >> Store at 2-8°C >>> Lachrymatory >>> Light sensitive >> Store under argonHazard categories in accordance with Regulation (EC) No 12772/2008Not AvailableQualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for theNot Available		Cans with friction closures and
may be used.Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient iner cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.Storage incompatibility> Segregate from alkalies, oxidising agents and chemicals readily decomposed by acids, i.e. cyanides, sulfides, carbonates. >> Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air. >> Avoid strong bases. >> Store at 2-8°C >>> Lachrymatory >>> Light sensitive >> Store under argonHazard categories in accordance with Regulation (EC) No 12772/2008Not AvailableQualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for theNot Available		Iow pressure tubes and cartridges
inert cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic. Storage incompatibility Segregate from alkalies, oxidising agents and chemicals readily decomposed by acids, i.e. cyanides, sulfides, carbonates. Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air. Avoid strong bases. Store at 2-8°C Lachrymatory Light sensitive Moisture sensitive Store under argon Not Available		may be used.
inert cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic. Storage incompatibility Segregate from alkalies, oxidising agents and chemicals readily decomposed by acids, i.e. cyanides, sulfides, carbonates. Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air. Avoid strong bases. Store at 2-8°C Lachrymatory Light sensitive Moisture sensitive Store under argon Not Available		
box and the substances are not incompatible with the plastic. box and the substances are not incompatible with the plastic. storage incompatibility Storage incompatibility Avoid strong bases. Store at 2-8°C Lachrymatory Light sensitive Moisture sensitive Store under argon Not Available Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the		Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient
Storage incompatibility Segregate from alkalies, oxidising agents and chemicals readily decomposed by acids, i.e. cyanides, sulfides, carbonates. Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air. Avoid strong bases. Store at 2-8°C Lachrymatory Light sensitive Moisture sensitive Store under argon Mot Available Not Available		inert cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic
Storage incompatibility Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air. Avoid strong bases. Store at 2-8°C Lachrymatory Light sensitive Moisture sensitive Store under argon Mot Available Not Available Not		box and the substances are not incompatible with the plastic.
Storage incompatibility Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air. Avoid strong bases. Store at 2-8°C Lachrymatory Light sensitive Moisture sensitive Store under argon Mot Available Not Available Not		Segregate from alkalies, oxidising agents and chemicals readily decomposed by acids, i.e. cyanides, sulfides, carbonates
Storage incompatibility Avoid strong bases. Store at 2-8°C Lachrymatory Light sensitive Moisture sensitive Store under argon Hazard categories in accordance with Regulation (EC) No 1272/2008 Not Available Not Available Not Available Not Available Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the Not Available 		
Storage incompatibilityStore at 2-8°C · Lachrymatory · Light sensitive · Moisture sensitive · Store under argonHazard categories in accordance with Regulation (EC) No 		
Storage incompatibility Lachrymatory Light sensitive Moisture sensitive Store under argon Hazard categories in accordance with Regulation (EC) No 1272/2008 Not Available Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the Not Available		5
Light sensitive • Moisture sensitive • Store under argonHazard categories in accordance with Regulation (EC) No 1272/2008Not AvailableQualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for theNot Available	Storage incompatibility	
Image: Provide and Prov		
Image: Provide a state of the state of		5
Hazard categories in accordance with Regulation (EC) No 1272/2008 Not Available Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the Not Available		
accordance with Regulation (EC) No 1272/2008 Not Available Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the Not Available	Herender de verdere la	
Regulation (EC) No Not Available 1272/2008 Qualifying quantity Qualifying quantity Not Available in Article 3(10) for the Not Available		
1272/2008 Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the Not Available		Not Available
Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the		
(tonnes) of dangerous substances as referred to in Article 3(10) for the	12/2/2008	
substances as referred to in Article 3(10) for the Not Available		
in Article 3(10) for the	· · ·	
		Not Available
application of	· · ·	
	application of	

7.3. Specific end use(s)

See section 1.2

SECTION 8 Exposure controls / personal protection

8.1. Control parameters

Ingredient	DNELs Exposure Pattern Worker	PNECs Compartment
Not Available	Not Available	Not Available

* Values for General Population

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Not Available						

Not Applicable

Emergency Limits

Ingredient	TEEL-1	TEEL-2		TEEL-3
2-(Bromomethyl)- 5-fluorobenzenesulphonyl chloride	Not Available	Not Available		Not Available
Ingredient	Original IDLH		Revised IDLH	
2-(Bromomethyl)- 5-fluorobenzenesulphonyl chloride	Not Available		Not Available	

8.2. Exposure controls

	Engineering controls are used to remove a hazard or place a engineering controls can be highly effective in protecting wor provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activi Enclosure and/or isolation of emission source which keeps a that strategically "adds" and "removes" air in the work enviro designed properly. The design of a ventilation system must r Employers may need to use multiple types of controls to pre- Local exhaust ventilation usually required. If risk of overexpo obtain adequate protection. An approved self contained breathing apparatus (SCBA) ma Provide adequate ventilation in warehouse or closed storage	kers and will typically be independent of work ty or process is done to reduce the risk. selected hazard "physically" away from the w nment. Ventilation can remove or dilute an air natch the particular process and chemical or over vent employee overexposure. sure exists, wear approved respirator. Correct be required in special circumstances. Correct y be required in some situations.	vorker and ventilation contaminant if contaminant in use. It fit is essential to t fit is essential to		
	"escape" velocities which, in turn, determine the "capture vel contaminant.	ocities" of fresh circulating air required to effe	ctively remove the		
	Type of Contaminant:		Air Speed:		
	solvent, vapours, degreasing etc., evaporating from tank (i	0.25-0.5 m/s (50-100 f/min.)			
8.2.1. Appropriate engineering controls	aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) 0.5-1 m/s (100-200 f/mi				
	direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)		1-2.5 m/s (200-500 f/min.)		
	grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).		2.5-10 m/s (500-2000 f/min.)		
	Within each range the appropriate value depends on:				
	Lower end of the range	Upper end of the range			
	1: Room air currents minimal or favourable to capture	1: Disturbing room air currents			
	2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity			
	3: Intermittent, low production.	3: High production, heavy use			
	4: Large hood or large air mass in motion	4: Small hood-local control only			
	Simple theory shows that air velocity falls rapidly with distance generally decreases with the square of distance from the ext extraction point should be adjusted, accordingly, after referent extraction fan, for example, should be a minimum of 1-2 m/s meters distant from the extraction point. Other mechanical co apparatus, make it essential that theoretical air velocities are installed or used.	raction point (in simple cases). Therefore the nee to distance from the contaminating source (200-400 f/min) for extraction of solvents gen onsiderations, producing performance deficits	air speed at the e. The air velocity at the erated in a tank 2 within the extraction		

8.2.2. Individual protection measures, such as personal protective equipment



Part Number: PC500582
Version No: 1.1

Eye and face protection	 Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure. Chemical goggles. Whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitted. [AS/NZS 1337.1, EN166 or national equivalent] Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection. Alternatively a gas mask may replace splash goggles and face shields. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].
Skin protection	See Hand protection below
Hands/feet protection	 Elbow length PVC gloves When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots.
Body protection	See Other protection below
Other protection	 Overalls. PVC Apron. PVC protective suit may be required if exposure severe. Eyewash unit. Ensure there is ready access to a safety shower.

Respiratory protection

Type AB Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	AB-AUS / Class1	-
up to 50	1000	-	AB-AUS / Class 1
up to 50	5000	Airline *	-
up to 100	5000	-	AB-2
up to 100	10000	-	AB-3
100+			Airline**

* - Continuous Flow ** - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

+ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.

The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

76ab()

8.2.3. Environmental exposure controls

See section 12

SECTION 9 Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Brown		
		Relative density (Water =	
Physical state	Liquid	Relative density (Water = 1)	Not Available

Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Not Available	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available
Nanoform Solubility	Not Available	Nanoform Particle Characteristics	Not Available
Particle Size	Not Available		

9.2. Other information

Not Available

SECTION 10 Stability and reactivity

10.1.Reactivity	See section 7.2
10.2. Chemical stability	Contact with alkaline material liberates heat
10.3. Possibility of hazardous reactions	See section 7.2
10.4. Conditions to avoid	See section 7.2
10.5. Incompatible materials	See section 7.2
10.6. Hazardous decomposition products	See section 5.3

SECTION 11 Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Information on toxicological effects

Inhaled	The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Corrosive acids can cause irritation of the respiratory tract, with coughing, choking and mucous membrane damage. There may be dizziness, headache, nausea and weakness. The material has NOT been classified by EC Directives or other classification systems as "harmful by inhalation". This is because of the lack of corroborating animal or human evidence.
Ingestion	Ingestion of acidic corrosives may produce burns around and in the mouth, the throat and oesophagus. Immediate pain and difficulties in swallowing and speaking may also be evident. The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	Skin contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue. Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

Eye	If applied to the eyes, this material causes severe eye damage. Direct eye contact with acid corrosives may produce pain, tears, sensitivity to light and burns. Mild burns of the epithelia generally recover rapidly and completely.		
Chronic	airways to lung, with cough, and inflammation Long-term exposure to respiratory irritants ma problems.	y result in the erosion of teeth, swelling and/or ulceration of mouth lining. Irritation of of lung tissue often occurs. y result in airways disease, involving difficulty breathing and related whole-body may occur and may cause some concern following repeated or long-term	
2-(Bromomethyl)- 5-fluorobenzenesulphonyl chloride	TOXICITY Not Available	IRRITATION Not Available	
Legend:		red Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. m RTECS - Register of Toxic Effect of chemical Substances	

2-(Bromomethyl)-5-fluorobenzenesulphonyl chloride

Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend: X – Data either not available or does not fill the criteria for classification

🖌 – Data available to make classification

11.2 Information on other hazards

11.2.1. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

11.2.2. Other information

See Section 11.1

SECTION 12 Ecological information

12.1. Toxicity

2-(Bromomethyl)- 5-fluorobenzenesulphonyl chloride	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

Prevent, by any means available, spillage from entering drains or water courses. **DO NOT** discharge into sewer or waterways.

12.2. Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

12.3. Bioaccumulative potential

Ingredient	Bioaccumulation	
	No Data available for all ingredients	

12.4. Mobility in soil

Ingredient	Mobility	
	No Data available for all ingredients	

12.5. Results of PBT and vPvB assessment

	Р	В	т
Relevant available data	Not Available	Not Available	Not Available
PBT	×	×	×
vPvB	×	×	×
PBT Criteria fulfilled? No			
vPvB			No

12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

12.7. Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

SECTION 13 Disposal considerations

13.1. Waste treatment methods

Product / Packaging disposal	 Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with soda-ash or soda-lime followed by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus Decontaminate empty containers with 5% aqueous sodium hydroxide or soda ash, followed by water. Observe all label safeguards until containers are cleaned and destroyed.
Waste treatment options	Not Available
Sewage disposal options	Not Available

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO
HAZCHEM	2X

Land transport (ADR-RID)

14.1. UN number or ID number	3265		
14.2. UN proper shipping name	CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.		
14.3. Transport hazard	Class	8	
class(es)	Subsidiary risk	Not Applicable	

14.4. Packing group	Ш	
14.5. Environmental hazard	Not Applicable	
	Hazard identification (Kemler)	80
14.6. Special precautions for user	Classification code	C3
	Hazard Label	8
	Special provisions	274
	Limited quantity	1 L
	Tunnel Restriction Code	2 (E)

Air transport (ICAO-IATA / DGR)

	,					
14.1. UN number	3265					
14.2. UN proper shipping name	Corrosive liquid, acidic,	organic, n.o.s. *				
14.3. Transport hazard class(es)	ICAO/IATA Class	8				
	ICAO / IATA Subrisk Not Applicable					
	ERG Code 8L					
14.4. Packing group	I					
14.5. Environmental hazard	Not Applicable					
14.6. Special precautions for user	Special provisions		A3 A803			
	Cargo Only Packing Ir	nstructions	855			
	Cargo Only Maximum	Qty / Pack	30 L			
	Passenger and Cargo	Packing Instructions	851			
	Passenger and Cargo	Maximum Qty / Pack	1 L			
	Passenger and Cargo	Limited Quantity Packing Instructions	Y840			
	Passenger and Cargo	Limited Maximum Qty / Pack	0.5 L			

Sea transport (IMDG-Code / GGVSee)

14.1. UN number	3265		
14.2. UN proper shipping name	CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.		
14.3. Transport hazard	IMDG Class 8		
class(es)	IMDG Subrisk N	ot Applicable	
14.4. Packing group	II		
14.5. Environmental hazard	Not Applicable		
	EMS Number	F-A, S-B	
14.6. Special precautions for user	Special provisions	274	
	Limited Quantities	1 L	

Inland waterways transport (ADN)

14.1. UN number	3265
14.2. UN proper shipping name	CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.
14.3. Transport hazard class(es)	8 Not Applicable
14.4. Packing group	II
14.5. Environmental hazard	Not Applicable

	Classification code	C3
14.6. Special precautions for user	Special provisions	274
	Limited quantity	1 L
	Equipment required	PP, EP
	Fire cones number	0

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
14.7.3. Transport in bulk in accordance with the IGC Code	

	Product name	Ship Type				
--	--------------	-----------	--	--	--	--

SECTION 15 Regulatory information

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable - : Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2020/878; Regulation (EC) No 1272/2008 as updated through ATPs.

Information according to 2012/18/EU (Seveso III):

Seveso Category Not Available

15.2. Chemical safety assessment

For further information please look at the Chemical Safety Assessment and Exposure Scenarios prepared by your Supply Chain if available.

ECHA SUMMARY

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Not Available
Canada - DSL	Not Available
Canada - NDSL	Not Available
China - IECSC	Not Available
Europe - EINEC / ELINCS / NLP	Not Available
Japan - ENCS	Not Available
Korea - KECI	Not Available
New Zealand - NZIoC	Not Available
Philippines - PICCS	Not Available
USA - TSCA	Not Available
Taiwan - TCSI	Not Available
Mexico - INSQ	Not Available
Vietnam - NCI	Not Available
Russia - FBEPH	Not Available
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	16/05/2022
Initial Date	16/05/2022

Full text Risk and Hazard codes

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

Definitions and abbreviations

PC - TWA: Permissible Concentration-Time Weighted Average PC - STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit, IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List

NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory

NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act

TCSI: Taiwan Chemical Substance Inventory

INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.