

# **Apollo Scientific**

Part Number: **PC5581** Version No: **1.1** Safety Data Sheet (Conforms to Annex II of REACH (1907/2006) - Regulation 2020/878) Chemwatch Hazard Alert Code: 2

Issue Date: **16/05/2022** Print Date: **03/08/2023** S.REACH.GBR.EN

# SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### **1.1. Product Identifier**

Product name	1H,3H-Hexafluoropropane
Chemical Name	1,1,2,2,3,3-Hexafluoropropane
Synonyms	Not Available
Proper shipping name	LIQUEFIED GAS, N.O.S.
Chemical formula	C3H2F6
Other means of identification	Not Available
CAS number	27070-61-7*

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Not Available
Uses advised against	No specific uses advised against are identified.

#### 1.3. Details of the manufacturer or supplier of the safety data sheet

Registered company name	Apollo Scientific				
Address	itefield Road, Bredbury SK62QR United Kingdom				
Telephone	1060505				
Fax	0161 406 0506				
Website	ttp://www.apolloscientific.co.uk/				
Email	sales@apolloscientific.co.uk				

# 1.4. Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	Not Available
Other emergency telephone numbers	Not Available

#### **SECTION 2 Hazards identification**

#### 2.1. Classification of the substance or mixture

Classification according to regulation (EC) No 1272/2008 [CLP] and amendments <sup>[1]</sup>

H335 - Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, H315 - Skin Corrosion/Irritation Category 2, H319 - Serious Eye Damage/Eye Irritation Category 2, H280 - Gases Under Pressure (Liquefied Gas)

Legend: 1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

# 2.2. Label elements

Hazard pictogram(s)		
Signal word	Warning	

#### Hazard statement(s)

H335	May cause respiratory irritation.		
H315	Causes skin irritation.		
H319	Causes serious eye irritation.		
H280	Contains gas under pressure; may explode if heated.		

#### Supplementary statement(s)

EUH044	Risk of explosion if heated under confinement.
--------	--

## Precautionary statement(s) Prevention

P271	Use only outdoors or in a well-ventilated area.			
P261	void breathing gas.			
P280	Wear protective gloves, protective clothing, eye protection and face protection.			
P264 Wash all exposed external body areas thoroughly after handling.				

#### Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.					
P312	Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.					
P337+P313	If eye irritation persists: Get medical advice/attention.					
P302+P352	IF ON SKIN: Wash with plenty of water.					
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.					
P332+P313	If skin irritation occurs: Get medical advice/attention.					
P362+P364	Take off contaminated clothing and wash it before reuse.					

## Precautionary statement(s) Storage

P405 Store locked up.			
P410+P403	Protect from sunlight. Store in a well-ventilated place.		
P403+P233	P403+P233         Store in a well-ventilated place. Keep container tightly closed.		

#### Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

# 2.3. Other hazards

REACH - Art.57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS print date.

# **SECTION 3 Composition / information on ingredients**

# 3.1.Substances

1. CAS No 2.EC No 3.Index No 4.REACH No	%[weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	SCL / M-Factor	Nanoform Particle Characteristics
Not Available	100	1H,3H-	Not Applicable	Not	Not Available

1. CAS No 2.EC No 3.Index No 4.REACH No	%[weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	SCL / M-Factor	Nanoform Particle Characteristics
		Hexafluoropropane		Applicable	

Legend: 1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L; \* EU IOELVs available; [e] Substance identified as having endocrine disrupting properties

#### 3.2.Mixtures

See 'Information on ingredients' in section 3.1

#### **SECTION 4 First aid measures**

# 4.1. Description of first aid measures

<ul> <li>If product comes in contact with eyes remove the patient from gas source or contaminated area.</li> <li>Take the patient to the access to an unable of source as the access of allocations.</li> </ul>	
<ul> <li>Take the patient to the nearest eye wash, shower or other source of clean water.</li> <li>Open the eyelid(s) wide to allow the material to evaporate.</li> <li>Gently rinse the affected eye(s) with clean, cool water for at least 15 minutes. Have the patient lie or sit down and t back. Hold the eyelid(s) open and pour water slowly over the eyeball(s) at the inner corners, letting the water run or outer corners.</li> <li>The patient may be in great pain and wish to keep the eyes closed. It is important that the material is rinsed from th prevent further damage.</li> <li>Eye Contact</li> <li>Exer when any be in great pain and wish to keep the eyes closed. It is important that the material is rinsed from the prevent further damage.</li> <li>Exer when no pain persists and vision is good, a doctor should examine the eye as delayed damage may occur.</li> <li>If the patient connot tolerate light, protect the eyes with a clean, loosely tied bandage.</li> <li>Ensure verbal communication and physical contact with the patient.</li> <li>Do NOT allow the patient to tightly shut the eyes</li> <li>Do NOT allow the patient to tightly shut the eyes</li> <li>Do NOT introduce oi</li></ul>	ut of the
<ul> <li>If skin or hair contact occurs:</li> <li>Flush skin and hair with running water (and soap if available).</li> <li>Seek medical attention in event of irritation.</li> <li>In case of cold burns (frost-bite):</li> <li>Move casualty into warmth before thawing the affected part; if feet are affected carry if possible</li> <li>Bathe the affected area immediately in luke-warm water (not more than 35 deg C) for 10 to 15 minutes, immersing and without rubbing</li> <li>DO NOT apply hot water or radiant heat.</li> <li>Apply a clean, dry, light dressing of "fluffed-up" dry gauze bandage</li> <li>If a limb is involved, raise and support this to reduce swelling</li> <li>If an adult is involved and where intense pain occurs provide pain killers such as paracetomol</li> <li>Transport to hospital, or doctor</li> <li>Subsequent blackening of the exposed tissue indicates potential of necrosis, which may require amputation.</li> </ul>	if possible
<ul> <li>Inhalation</li> <li>Following exposure to gas, remove the patient from the gas source or contaminated area.</li> <li>NOTE: Personal Protective Equipment (PPE), including positive pressure self-contained breathing apparatus may la required to assure the safety of the rescuer.</li> <li>Prostheses such as false teeth, which may block the airway, should be removed, where possible, prior to initiating f procedures.</li> <li>If the patient is not breathing spontaneously, administer rescue breathing.</li> <li>If the patient does not have a pulse, administer CPR.</li> <li>If medical oxygen and appropriately trained personnel are available, administer 100% oxygen.</li> <li>Summon an emergency ambulance. If an ambulance is not available, contact a physician, hospital, or Poison Cont for further instruction.</li> <li>Keep the patient warm, comfortable and at rest while awaiting medical care.</li> <li>MONITOR THE BREATHING AND PULSE, CONTINUOUSLY.</li> <li>Administer rescue breathing (preferably with a demand-valve resuscitator, bag-valve mask-device, or pocket mask or CPR if necessary.</li> </ul>	irst aid rol Centre
Ingestion Not considered a normal route of entry.	

# 4.2 Most important symptoms and effects, both acute and delayed

See Section 11

# 4.3. Indication of any immediate medical attention and special treatment needed

For gas exposures:

#### BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- Monitor and treat, where necessary, for pulmonary oedema.
- Monitor and treat, where necessary, for shock.
- Anticipate seizures.

-----

# ADVANCED TREATMENT

• Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.

- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- + Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

# **SECTION 5 Firefighting measures**

#### 5.1. Extinguishing media

**SMALL FIRE:** Use extinguishing agent suitable for type of surrounding fire.

LARGE FIRE: Cool cylinder.

DO NOT direct water at source of leak or venting safety devices as icing may occur.

#### 5.2. Special hazards arising from the substrate or mixture

Fire Incompatibility None known.

#### 5.3. Advice for firefighters

Fire Fighting	GENERAL  Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus and protective gloves. Fight fire from a safe distance, with adequate cover. Use water delivered as a fine spray to control fire and cool adjacent area. DO NOT approach cylinders suspected to be hot. Cool fire exposed cylinders with water spray from a protected location. If safe to do so, remove cylinders from path of fire.  SPECIAL REQUIREMENTS:  Excessive pressures may develop in a gas cylinder exposed in a fire; this may result in explosion. Cylinders with pressure relief devices may release their contents as a result of fire and the released gas may constitute a further source of hazard for the fire-fighter. Cylinders without pressure-relief valves have no provision for controlled release and are therefore more likely to explode if exposed to fire.  FIRE FIGHTING REQUIREMENTS: FIRE FIGHTING REQUIREMENTS: The need for proximity, entry and special protective clothing should be determined for each incident, by a competent fire-fighting safety professional.
Fire/Explosion Hazard	<ul> <li>Containers may explode when heated - Ruptured cylinders may rocket</li> <li>Fire exposed containers may vent contents through pressure relief devices.</li> <li>High concentrations of gas may cause asphyxiation without warning.</li> <li>May decompose explosively when heated or involved in fire.</li> <li>Contact with gas may cause burns, severe injury and/ or frostbite.</li> <li>Decomposition may produce toxic fumes of:</li> <li>Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.</li> </ul>

#### 6.1. Personal precautions, protective equipment and emergency procedures

See section 8

# 6.2. Environmental precautions

See section 12

#### 6.3. Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Avoid breathing vapour and any contact with liquid or gas. Protective equipment including respirator should be used.</li> <li>DO NOT enter confined spaces where gas may have accumulated.</li> <li>Increase ventilation.</li> <li>Clear area of personnel.</li> <li>Stop leak only if safe to so do.</li> <li>Remove leaking cylinders to safe place. Release pressure under safe controlled conditions by opening valve.</li> <li>Do not exert excessive pressure on the valve; do not attempt to operate a damaged valve</li> <li>Orientate cylinder so that the leak is gas, not liquid, to minimise rate of leakage</li> <li>Keep area clear of personnel until gas has dispersed.</li> </ul>
Major Spills	<ul> <li>Clear area of all unprotected personnel and move upwind.</li> <li>Alert Emergency Authority and advise them of the location and nature of hazard.</li> <li>Wear breathing apparatus and protective gloves.</li> <li>Prevent by any means available, spillage from entering drains and water-courses.</li> <li>Consider evacuation.</li> <li>Increase ventilation.</li> <li>No smoking or naked lights within area.</li> <li>Stop leak only if safe to so do.</li> <li>Water spray or fog may be used to disperse vapour.</li> <li>DO NOT enter confined space where gas may have collected.</li> <li>Keep area clear until gas has dispersed.</li> <li>Remove leaking cylinders to a safe place.</li> <li>Fit vent pipes. Release pressure under safe, controlled conditions</li> <li>Burn issuing gas at vent pipes.</li> <li>DO NOT exert excessive pressure on valve; DO NOT attempt to operate damaged valve.</li> </ul>

# 6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# **SECTION 7 Handling and storage**

# 7.1. Precautions for safe handling

Safe handling	<ul> <li>Consider use in closed pressurised systems, fitted with temperature, pressure and safety relief valves which are vented for safe dispersal. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature</li> <li>The tubing network design connecting gas cylinders to the delivery system should include appropriate pressure indicators and vacuum or suction lines.</li> <li>Fully-welded types of pressure gauges, where the bourdon tube sensing element is welded to the gauge body, are recommended.</li> <li>Before connecting gas cylinders, ensure manifold is mechanically secure and does not containing another gas. Before disconnecting or replacing cylinders take care to avoid airborne particulates violently ejected when system pressurises.</li> <li>Consider the use of doubly-contained piping; diaphragm or bellows sealed, soft seat valves; backflow prevention devices; flash arrestors; and flow monitoring or limiting devices. Gas cabinets, with appropriate exhaust treatment, are recommended, as is automatic monitoring of the secondary enclosures and work areas for release.</li> <li>Use a check valve or trap in the discharge line to prevent hazardous back-flow into the cylinder</li> <li>Check regularly for spills or leaks. Keep valves tightly closed but do not apply extra leverage to hand wheels or cylinder keys.</li> <li>Open valve slowly. If valve is resistant to opening then contact your supervisor</li> <li>Valve protection caps must remain in place must remain in place unless container is secured with valve outlet piped to use point.</li> <li>Never insert a pointed object (e.g hooks) into cylinder cap openings as a means to open cap or move cylinder. Such action can inadvertently turn the valve and gas a gas leak. Use an adjustable strap instead of wrench to free an over-tight or rusted cap.</li> <li>A bubble of gas may buildup behind the outlet dust cap during transportation, after prolonged storage, due to defective cylinder valve or if a dust cap is inserted wi</li></ul>

Page 6 of 13

	<ul> <li>Leaking gland nuts may be tightened if necessary.</li> <li>If a cylinder valve will not close completely, remove the cylinder to a well ventilated location (e.g. outside) and, when empty, tag as FAULTY and return to supplier.</li> <li>Obtain a work permit before attempting any repairs.</li> <li>DO NOT attempt repair work on lines, vessels under pressure.</li> <li>Atmospheres must be tested and O.K. before work resumes after leakage.</li> <li>DO NOT transfer gas from one cylinder to another.</li> </ul>
Fire and explosion protection	See section 5
Other information	<ul> <li>Cylinders should be stored in a purpose-built compound with good ventilation, preferably in the open.</li> <li>Such compounds should be sited and built in accordance with statutory requirements.</li> <li>The storage compound should be kept clear and access restricted to authorised personnel only.</li> <li>Cylinders stored in the open should be protected against rust and extremes of weather.</li> <li>Cylinders in storage should be closed when not in use.</li> <li>Where cylinders are fitted with valve protection this should be in place and properly secured.</li> <li>Gas cylinders should be segregated according to the requirements of the Dangerous Goods Act.</li> <li>Preferably store full and empty cylinders separately.</li> <li>Check storage areas for hazardous concentrations of gases prior to entry.</li> <li>Full cylinders in storage should be checked periodically for general condition and leakage.</li> <li>Protect cylinders against physical damage. Move and store cylinders correctly as instructed for their manual handling.</li> <li>NOTE: A 'G' size cylinder is usually too heavy for an inexperienced operator to raise or lower.</li> </ul>

# 7.2. Conditions for safe storage, including any incompatibilities

Suitable container	<ul> <li>Cylinder:</li> <li>Ensure the use of equipment rated for cylinder pressure.</li> <li>Ensure the use of compatible materials of construction.</li> <li>Valve protection cap to be in place until cylinder is secured, connected.</li> <li>Cylinder must be properly secured either in use or in storage.</li> <li>Cylinder valve must be closed when not in use or when empty.</li> <li>Segregate full from empty cylinders.</li> </ul>
Storage incompatibility	Compressed gases may contain a large amount of kinetic energy over and above that potentially available from the energy of reaction produced by the gas in chemical reaction with other substances
Hazard categories in accordance with Regulation (EC) No 1272/2008	Not Available
Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of	Not Available

# 7.3. Specific end use(s)

See section 1.2

# **SECTION 8 Exposure controls / personal protection**

# 8.1. Control parameters

Ingredient	DNELs Exposure Pattern Worker	PNECs Compartment
Not Available	Not Available	Not Available

\* Values for General Population

# Occupational Exposure Limits (OEL)

#### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Not Available						

Not Applicable

# Emergency Limits

Ingredient	TEEL-1	TEEL-2		TEEL-3
1H,3H-Hexafluoropropane	Not Available	Not Available		Not Available
Ingredient	Original IDLH		Revised IDLH	
_	_			
1H,3H-Hexafluoropropane	Not Available		Not Available	

# 8.2. Exposure controls

8.2.1. Appropriate engineering controls	Engineering controls are used to remove a hazard or place a engineering controls can be highly effective in protecting wor provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activit Enclosure and/or isolation of emission source which keeps a that strategically "adds" and "removes" air in the work enviror designed properly. The design of a ventilation system must m Employers may need to use multiple types of controls to prev • Areas where cylinders are stored require good ventilation • Secondary containment and exhaust gas treatment may if • Local exhaust ventilation may be required in work areas. • Consideration should be given to the use of diaphragm or flow-monitoring or limiting devices. • Automated alerting systems with automatic shutdown of g jurisdictions. • Respiratory protection in the form of air-supplied or self-c concentration in the workplace air is less than 19%. • Cartridge respirators do NOT give protection and may res Air contaminants generated in the workplace possess varying velocities" of fresh circulating air required to effectively remove Type of Contaminant: gas discharge (active generation into zone of rapid air moti Within each range the appropriate value depends on: Lower end of the range 1: Room air currents minimal or favourable to capture 2: Contaminants of low toxicity or of nuisance value only. 3: Intermittent, low production. 4: Large hood or large air mass in motion Simple theory shows that air velocity falls rapidly with distance generally decreases with the square of distance from the extra extraction point should be adjusted, accordingly, after referer extraction point should be adjusted, accordingly, after referer extraction fan, for example, should be a minimum of 1-2.5 m/ distant from the extraction point. Other mechanical considera apparatus, make it essential that theoretical air velocities are installed or used.	kers a y or p select ment in atch t rent er and, oe req and, oe req r bello gas-flo ontain g "esca re the 0 0 0 1: D 2: C 3: H 4: S e awa ractior ice to is (2000 tions, s (2000	and will typically be independent process is done to reduce the r ted hazard "physically" away f t. Ventilation can remove or dil the particular process and che mployee overexposure. if enclosed, need discrete/con quired by certain jurisdictions. ows-sealed, soft-seat valves; b tow may be appropriate and ma need breathing equipment must rapid suffocation. ape" velocities which, in turn, of contaminant. Air Speed: 1-2.5 m/s (200-500 f/min.) per end of the range disturbing room air currents contaminants of high toxicity ligh production, heavy use small hood-local control only ay from the opening of a simple n point (in simple cases). There distance from the contaminatio 0-500 f/min.) for extraction of g producing performance deficit	nt of worker interactions to isk. rom the worker and ventilation ute an air contaminant if smical or contaminant in use. trolled exhaust ventilation. ackflow prevention devices and ay in fact be mandatory in certain be worn if the oxygen determine the "capture e extraction pipe. Velocity efore the air speed at the ng source. The air velocity at the gases discharged 2 meters ts within the extraction
8.2.2. Individual protection measures, such as personal protective equipment				
Eye and face protection	<ul> <li>Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]</li> <li>Full face shield may be required for supplementary but never for primary protection of eyes.</li> <li>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].</li> </ul>			
Skin protection	See Hand protection below			
Hands/feet protection	When handling sealed and suitably insulated cylinders wear cloth or leather gloves.			
Body protection	See Other protection below			
	1			

1H,3H-Hexaf	luoropropane
-------------	--------------

	<ul> <li>Protective overalls, closely fitted at neck and wrist.</li> <li>Eye-wash unit.</li> </ul>
Other protection	Ensure availability of lifeline in confined spaces.
	Staff should be trained in all aspects of rescue work.
	Rescue gear: Two sets of SCBA breathing apparatus Rescue Harness, lines etc.

#### **Respiratory protection**

Full face respirator with supplied air.

- Positive pressure, full face, air-supplied breathing apparatus should be used for work in enclosed spaces if a leak is suspected or the primary containment is to be opened (e.g. for a cylinder change)
- + Air-supplied breathing apparatus is required where release of gas from primary containment is either suspected or demonstrated.

# 8.2.3. Environmental exposure controls

See section 12

# **SECTION 9** Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Liquified Gas	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	5	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Not Available	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available
Nanoform Solubility	Not Available	Nanoform Particle Characteristics	Not Available
Particle Size	Not Available		

#### 9.2. Other information

Not Available

#### **SECTION 10 Stability and reactivity**

10.1.Reactivity	See section 7.2	
10.2. Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>	
10.3. Possibility of hazardous reactions	See section 7.2	
10.4. Conditions to avoid	See section 7.2	

# Page 9 of 13 1H,3H-Hexafluoropropane

10.5. Incompatible materials	See section 7.2
10.6. Hazardous decomposition products	See section 5.3

# **SECTION 11 Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directive using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable comeasures be used in an occupational setting. Inhalation of non-toxic gases may cause: • CNS effects: headache, confusion, dizziness, stupor, seizures and coma; • respiratory: shortness of breath and rapid breathing; • cardiovascular: collapse and irregular heart beats; • gastrointestinal: mucous membrane irritation, nausea and vomiting. Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour material is place and replace air in breathing zone, acting as a simple asphyxiant. This may happen with little warning of overexposus The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation.		
Ingestion	Not normally a hazard due to physical form of product. Considered an unlikely route of entry in commercial/industrial environments		
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. Vapourising liquid causes rapid cooling and contact may cause cold burns, frostbite, even through normal gloves. Frozen skin tissues are painless and appear waxy and yellow. Signs and symptoms of frost-bite may include "pins and needles", paleness followed by numbness, a hardening an stiffening of the skin, a progression of colour changes in the affected area, (first white, then mottled and blue and eventually black; on recovery, red, hot, painful and blistered).		
Eye	This material can cause eye irritation and damage in some persons. Not considered to be a risk because of the extreme volatility of the gas.		
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course. Main route of exposure to the gas in the workplace is by inhalation.		
	ΤΟΧΙΟΙΤΥ	IRRITATION	
1H,3H-Hexafluoropropane	Not Available	Not Available	

	TUXICITY	IRRITATION
1H,3H-Hexafluoropropane	Not Available	Not Available
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	¥	Reproductivity	×
Serious Eye Damage/Irritation	~	STOT - Single Exposure	*
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Data entremot available of does not minute criter
 Data available to make classification

# 11.2 Information on other hazards

# 11.2.1. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

#### 11.2.2. Other information

See Section 11.1

# **SECTION 12 Ecological information**

	Endpoint	Test Duration (hr)	Species	Value	Source
1H,3H-Hexafluoropropane	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

# 12.2. Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

# 12.3. Bioaccumulative potential

Ingredient	Bioaccumulation	
	No Data available for all ingredients	

# 12.4. Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

# 12.5. Results of PBT and vPvB assessment

	Р	В	т	
Relevant available data	Not Available	Not Available	Not Available	
PBT	×	×	×	
vPvB	×	×	×	
PBT Criteria fulfilled?	PBT Criteria fulfilled? No			
vPvB			No	

# 12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

## 12.7. Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

# **SECTION 13 Disposal considerations**

# 13.1. Waste treatment methods

Product / Packaging disposal	<ul> <li>Evaporate residue at an approved site.</li> <li>Return empty containers to supplier. If containers are marked non-returnable establish means of disposal with manufacturer prior to purchase.</li> <li>Ensure damaged or non-returnable cylinders are gas-free before disposal.</li> </ul>	
Waste treatment options	Not Available	
Sewage disposal options	Not Available	

# **SECTION 14 Transport information**

# Labels Required

Marine Pollutant	NO
HAZCHEM	2TE

# Land transport (ADR-RID)

14.1. UN number or ID number	3163		
14.2. UN proper shipping name	LIQUEFIED GAS,	N.O.S.	
14.3. Transport hazard	Class	2.2	
class(es)	Subsidiary risk	Not Applicab	le
14.4. Packing group	Not Applicable		
14.5. Environmental hazard	Not Applicable		
	Hazard identifica	ation (Kemler)	20
	Classification co	de	2A
14.6. Special precautions for user	Hazard Label		2.2
	Special provision	าร	274 392 662
	Limited quantity		120 ml
	Tunnel Restrictio	on Code	3 (C/E)

# Air transport (ICAO-IATA / DGR)

14.1. UN number	3163		
14.2. UN proper shipping name	Liquefied gas, n.o.s. *		
14.3. Transport hazard class(es)	ICAO/IATA Class	2.2	
	ICAO / IATA Subrisk	Not Applicable	
	ERG Code	2L	
14.4. Packing group	Not Applicable		
14.5. Environmental hazard	Not Applicable		
14.6. Special precautions for user	Special provisions		Not Applicable
	Cargo Only Packing Ir	200	
	Cargo Only Maximum Qty / Pack		150 kg
	Passenger and Cargo Packing Instructions		200
	Passenger and Cargo Maximum Qty / Pack		75 kg
	Passenger and Cargo Limited Quantity Packing Instructions		Forbidden
	Passenger and Cargo	Limited Maximum Qty / Pack	Forbidden

# Sea transport (IMDG-Code / GGVSee)

14.1. UN number	3163	
14.2. UN proper shipping name	LIQUEFIED GAS, N.C	0.S.
14.3. Transport hazard	IMDG Class 2.	.2
class(es)	IMDG Subrisk N	lot Applicable
14.4. Packing group	Not Applicable	
14.5. Environmental hazard	Not Applicable	
	EMS Number	F-C, S-V
14.6. Special precautions for user	Special provisions	274 392
	Limited Quantities	120 mL

14.1. UN number	3163			
14.2. UN proper shipping name	LIQUEFIED GAS, N.O.S.			
14.3. Transport hazard class(es)	2.2 Not Applicable			
14.4. Packing group	Not Applicable			
14.5. Environmental hazard	Not Applicable			
	Classification code	A		
	Special provisions	74; 392; 662		
14.6. Special precautions for user	Limited quantity	20 ml		
	Equipment required	P		
	Fire cones number			

#### 14.7. Maritime transport in bulk according to IMO instruments

#### 14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

#### 14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group

# 14.7.3. Transport in bulk in accordance with the IGC Code

	Product name	Ship Type
--	--------------	-----------

#### **SECTION 15 Regulatory information**

#### 15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable - : Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2020/878; Regulation (EC) No 1272/2008 as updated through ATPs.

## Information according to 2012/18/EU (Seveso III):

Seveso Category	Not Available
-----------------	---------------

#### 15.2. Chemical safety assessment

For further information please look at the Chemical Safety Assessment and Exposure Scenarios prepared by your Supply Chain if available.

#### ECHA SUMMARY

Not Applicable

## **National Inventory Status**

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Not Available
Canada - DSL	Not Available
Canada - NDSL	Not Available
China - IECSC	Not Available
Europe - EINEC / ELINCS / NLP	Not Available
Japan - ENCS	Not Available
Korea - KECI	Not Available
New Zealand - NZIoC	Not Available
Philippines - PICCS	Not Available
USA - TSCA	Not Available
Taiwan - TCSI	Not Available
Mexico - INSQ	Not Available

National Inventory	Status
Vietnam - NCI	Not Available
Russia - FBEPH	Not Available
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

#### **SECTION 16 Other information**

Revision Date	16/05/2022
Initial Date	16/05/2022

#### Full text Risk and Hazard codes

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

#### Definitions and abbreviations

PC - TWA: Permissible Concentration-Time Weighted Average PC - STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit. IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard **OSF: Odour Safety Factor** NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors **BEI: Biological Exposure Index** AIIC: Australian Inventory of Industrial Chemicals **DSL: Domestic Substances List** NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.