

# Sodium trifluoroacetate **Apollo Scientific**

Part Number: PC6570 Version No: 2.2 Safety Data Sheet

Chemwatch Hazard Alert Code: 4

Issue Date: 06/07/2023 Print Date: 06/07/2023 S.GHS.GB-NIR.EN

### SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### **Product Identifier**

Product name	odium trifluoroacetate	
Chemical Name	trifluoroacetic acid, sodium salt	
Synonyms	Not Available	
Chemical formula	C2HF3O2.Na	
Other means of identification	Not Available	
CAS number	2923-18-4*	

### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Not Available

# Details of the manufacturer or supplier of the safety data sheet

Registered company name	Apollo Scientific	Apollo Scientific Itd
Address	Whitefield Road, Bredbury SK62QR United Kingdom	Whitefield Road, Bredbury Cheshire SK6 2QR United Kingdom (NI)
Telephone	01614060505	+44(0) 161 406 0505
Fax	0161 406 0506	Not Available
Website	http://www.apolloscientific.co.uk/	apolloscientific.co.uk
Email	sales@apolloscientific.co.uk	sales@apolloscientific.co.uk

# **Emergency telephone number**

Association / Organisation	Not Available
Emergency telephone numbers	Not Available
Other emergency telephone numbers	Not Available

# **SECTION 2 Hazards identification**

# Classification of the substance or mixture

**Classification according to** regulation (EC) No 1272/2008 [CLP] and amendments [1]

H300 - Acute Toxicity (Oral) Category 2, H335 - Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, H315 - Skin Corrosion/Irritation Category 2, H319 - Serious Eye Damage/Eye Irritation Category 2

Legend: 1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

# Label elements

Hazard pictogram(s)		
Signal word	Danger	

### Hazard statement(s)

H300	Fatal if swallowed.	
H335	May cause respiratory irritation.	
H315	Causes skin irritation.	
H319	Causes serious eye irritation.	

#### Precautionary statement(s) Prevention

P264	Wash all exposed external body areas thoroughly after handling.	
P270	P270 Do not eat, drink or smoke when using this product.	
P271	Use only outdoors or in a well-ventilated area.	
P261	Avoid breathing dust/fumes.	
P280 Wear protective gloves, protective clothing, eye protection and face protection.		

# Precautionary statement(s) Response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider.		
P330	Rinse mouth.		
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
P312	Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.		
P337+P313	If eye irritation persists: Get medical advice/attention.		
P302+P352	IF ON SKIN: Wash with plenty of water.		
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.		
P332+P313	If skin irritation occurs: Get medical advice/attention.		
P362+P364	Take off contaminated clothing and wash it before reuse.		

### Precautionary statement(s) Storage

P405	Store locked up.	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.	

#### Precautionary statement(s) Disposal

**P501** Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

# **SECTION 3 Composition / information on ingredients**

#### Substances

CAS No	%[weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	SCL / M-Factor
2923-18-4*	100	<u>Sodium</u> trifluoroacetate	Acute Toxicity (Oral) Category 2, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 2; H300, H335, H315, H319 <sup>[1]</sup>	Not Available

Legend: 1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L; \* EU IOELVs available; [e] Substance identified as having endocrine disrupting properties

See section above for composition of Substances

### **SECTION 4 First aid measures**

# Description of first aid measures If this product comes in contact with the eyes: ▶ Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally Eye Contact lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. If skin or hair contact occurs: Skin Contact Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation. If fumes, aerosols or combustion products are inhaled remove from contaminated area. Inhalation Other measures are usually unnecessary. ▶ IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY. ▶ For advice, contact a Poisons Information Centre or a doctor. Urgent hospital treatment is likely to be needed. In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition. If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the SDS should be provided. Further action will be the responsibility of the medical specialist. • If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the Ingestion SDS. Where medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise: INDUCE vomiting with fingers down the back of the throat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. NOTE: Wear a protective glove when inducing vomiting by mechanical means.

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5 Firefighting measures**

#### Extinguishing media

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

#### Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.
----------------------	-------------

#### Advice for firefighters

Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves in the event of a fire.</li> <li>Prevent, by any means available, spillage from entering drains or water courses.</li> <li>Use fire fighting procedures suitable for surrounding area.</li> <li>DO NOT approach containers suspected to be hot.</li> <li>Cool fire exposed containers with water spray from a protected location.</li> <li>If safe to do so, remove containers from path of fire.</li> <li>Equipment should be thoroughly decontaminated after use.</li> </ul>
Fire/Explosion Hazard	<ul> <li>Non combustible.</li> <li>Not considered a significant fire risk, however containers may burn.</li> <li>May emit poisonous fumes.</li> <li>May emit corrosive fumes.</li> </ul>

# **SECTION 6 Accidental release measures**

Personal precautions, protective equipment and emergency procedures

See section 8

### **Environmental precautions**

See section 12

### Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Clean up all spills immediately.</li> <li>Avoid breathing dust and contact with skin and eyes.</li> <li>Wear protective clothing, gloves, safety glasses and dust respirator.</li> <li>Use dry clean up procedures and avoid generating dust.</li> <li>Sweep up, shovel up or</li> <li>Vacuum up (consider explosion-proof machines designed to be grounded during storage and use).</li> <li>Place spilled material in clean, dry, sealable, labelled container.</li> </ul>
Major Spills	<ul> <li>Moderate hazard.</li> <li>CAUTION: Advise personnel in area.</li> <li>Alert Emergency Services and tell them location and nature of hazard.</li> <li>Control personal contact by wearing protective clothing.</li> <li>Prevent, by any means available, spillage from entering drains or water courses.</li> <li>Recover product wherever possible.</li> <li>IF DRY: Use dry clean up procedures and avoid generating dust. Collect residues and place in sealed plastic bags or other containers for disposal. IF WET: Vacuum/shovel up and place in labelled containers for disposal.</li> <li>ALWAYS: Wash area down with large amounts of water and prevent runoff into drains.</li> <li>If contamination of drains or waterways occurs, advise Emergency Services.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# **SECTION 7 Handling and storage**

# Precautions for safe handling

Safe han	<ul> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Prevent concentration in hollows and sumps.</li> <li>DO NOT enter confined spaces until atmosphere has been checked.</li> <li>DO NOT allow material to contact humans, exposed food or food utensils.</li> <li>Avoid contact with incompatible materials.</li> <li>When handling, DO NOT eat, drink or smoke.</li> <li>Keep containers securely sealed when not in use.</li> <li>Avoid physical damage to containers.</li> <li>Always wash hands with soap and water after handling.</li> <li>Work clothes should be laundered separately. Launder contaminated clothing before re-use.</li> <li>Use good occupational work practice.</li> <li>Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.</li> </ul>
Other inform	<ul> <li>Store in original containers.</li> <li>Keep containers securely sealed.</li> <li>Store in a cool, dry area protected from environmental extremes.</li> <li>Store away from incompatible materials and foodstuff containers.</li> <li>Protect containers against physical damage and check regularly for leaks.</li> <li>Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>For major quantities:</li> <li>Consider storage in bunded areas - ensure storage areas are isolated from sources of community water (including stormwater, ground water, lakes and streams).</li> <li>Ensure that accidental discharge to air or water is the subject of a contingency disaster management plan; this may require consultation with local authorities.</li> </ul>

Suitable container	<ul> <li>Polyethylene or polypropylene container.</li> <li>Check all containers are clearly labelled and free from leaks.</li> </ul>
Storage incompatibility	None known

# **SECTION 8 Exposure controls / personal protection**

Not Available

# **Control parameters**

Occupational Exposure Limits (OEL)

### INGREDIENT DATA

Not Available

#### Emergency Limits

Sodium trifluoroacetate

Ingredient	TEEL-1	TEEL-2		TEEL-3
Sodium trifluoroacetate	Not Available	Not Available		Not Available
Ingredient	Original IDLH		Revised IDLH	

Not Available

# Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
Sodium trifluoroacetate	E	≤ 0.01 mg/m³
Notes:	Occupational exposure banding is a process of assigning chemica potency and the adverse health outcomes associated with exposu band (OEB), which corresponds to a range of exposure concentra	ire. The output of this process is an occupational exposure

# **Exposure controls**

	Environmian controls are used to remain a beyond or also		
	<ul> <li>Engineering controls are used to remove a hazard or place engineering controls can be highly effective in protecting we provide this high level of protection.</li> <li>The basic types of engineering controls are:</li> <li>Process controls which involve changing the way a job act Enclosure and/or isolation of emission source which keeps that strategically "adds" and "removes" air in the work envidesigned properly. The design of a ventilation system must Employers may need to use multiple types of controls to p</li> </ul>	vorkers and will typically be independent of tivity or process is done to reduce the risk s a selected hazard "physically" away fror ironment. Ventilation can remove or dilute st match the particular process and chemi	of worker interactions to k. m the worker and ventilations an air contaminant if
	<ul> <li>Local exhaust ventilation is required where solids are l large, a certain proportion will be powdered by mutual</li> <li>If in spite of local exhaust an adverse concentration of considered.</li> <li>Such protection might consist of:         <ul> <li>(a): particle dust respirators, if necessary, combined with a</li> </ul> </li> </ul>	friction. the substance in air could occur, respirat an absorption cartridge;	
	(b): filter respirators with absorption cartridge or canister o (c): fresh-air hoods or masks.		
Appropriate engineering controls		ving "escape" velocities which, in turn, de	termine the "capture
	(c): fresh-air hoods or masks. Air contaminants generated in the workplace possess vary	ving "escape" velocities which, in turn, de	Air Speed:
	(c): fresh-air hoods or masks. Air contaminants generated in the workplace possess vary velocities" of fresh circulating air required to effectively rem	ying "escape" velocities which, in turn, de nove the contaminant. , conveyer loading, crusher dusts, gas	Air Speed:
	<ul> <li>(c): fresh-air hoods or masks.</li> <li>Air contaminants generated in the workplace possess vary velocities" of fresh circulating air required to effectively rem</li> <li>Type of Contaminant:</li> <li>direct spray, spray painting in shallow booths, drum filling</li> </ul>	ying "escape" velocities which, in turn, de nove the contaminant. J, conveyer loading, crusher dusts, gas	Air Speed: 1-2.5 m/s (200-500
	<ul> <li>(c): fresh-air hoods or masks.</li> <li>Air contaminants generated in the workplace possess vary velocities" of fresh circulating air required to effectively rem</li> <li>Type of Contaminant:</li> <li>direct spray, spray painting in shallow booths, drum filling discharge (active generation into zone of rapid air motion grinding, abrasive blasting, tumbling, high speed wheel g</li> </ul>	ying "escape" velocities which, in turn, de nove the contaminant. J, conveyer loading, crusher dusts, gas	Air Speed: 1-2.5 m/s (200-500 f/min.) 2.5-10 m/s (500-20
	<ul> <li>(c): fresh-air hoods or masks.</li> <li>Air contaminants generated in the workplace possess vary velocities" of fresh circulating air required to effectively rem</li> <li>Type of Contaminant:</li> <li>direct spray, spray painting in shallow booths, drum filling discharge (active generation into zone of rapid air motion)</li> <li>grinding, abrasive blasting, tumbling, high speed wheel g velocity into zone of very high rapid air motion).</li> </ul>	ying "escape" velocities which, in turn, de nove the contaminant. J, conveyer loading, crusher dusts, gas	Air Speed: 1-2.5 m/s (200-500 f/min.) 2.5-10 m/s (500-20
	<ul> <li>(c): fresh-air hoods or masks.</li> <li>Air contaminants generated in the workplace possess vary velocities" of fresh circulating air required to effectively rem</li> <li>Type of Contaminant:</li> <li>direct spray, spray painting in shallow booths, drum filling discharge (active generation into zone of rapid air motion grinding, abrasive blasting, tumbling, high speed wheel g velocity into zone of very high rapid air motion).</li> <li>Within each range the appropriate value depends on:</li> </ul>	ving "escape" velocities which, in turn, de nove the contaminant. g, conveyer loading, crusher dusts, gas j) ienerated dusts (released at high initial	Air Speed: 1-2.5 m/s (200-50 f/min.) 2.5-10 m/s (500-2
	<ul> <li>(c): fresh-air hoods or masks.</li> <li>Air contaminants generated in the workplace possess vary velocities" of fresh circulating air required to effectively rem</li> <li>Type of Contaminant:</li> <li>direct spray, spray painting in shallow booths, drum filling discharge (active generation into zone of rapid air motion)</li> <li>grinding, abrasive blasting, tumbling, high speed wheel g velocity into zone of very high rapid air motion).</li> <li>Within each range the appropriate value depends on:</li> <li>Lower end of the range</li> </ul>	ying "escape" velocities which, in turn, denove the contaminant. I, conveyer loading, crusher dusts, gas ) lenerated dusts (released at high initial Upper end of the range 1: Disturbing room air currents	Air Speed: 1-2.5 m/s (200-50 f/min.) 2.5-10 m/s (500-2
	<ul> <li>(c): fresh-air hoods or masks.</li> <li>Air contaminants generated in the workplace possess vary velocities" of fresh circulating air required to effectively rem</li> <li>Type of Contaminant:</li> <li>direct spray, spray painting in shallow booths, drum filling discharge (active generation into zone of rapid air motion grinding, abrasive blasting, tumbling, high speed wheel g velocity into zone of very high rapid air motion).</li> <li>Within each range the appropriate value depends on:</li> <li>Lower end of the range</li> <li>1: Room air currents minimal or favourable to capture</li> </ul>	ying "escape" velocities which, in turn, denove the contaminant. I, conveyer loading, crusher dusts, gas ) lenerated dusts (released at high initial Upper end of the range 1: Disturbing room air currents	Air Speed: 1-2.5 m/s (200-50 f/min.) 2.5-10 m/s (500-2

Image: space and y documents with the space of distance from the extraction point (in sample dised, according y document for the contraction groups. The served of a the extraction for the contraction of custer dised, and the extraction is generated at methods are indicated at velocities are multiplied by texts of 10 or more when extraction systems are smaller of the extraction of custer dised, according y document of the extraction of custer dised, according y document of the extraction of custer dised, according y document of the extraction of the extractin extractin and extractin the extraction of the extraction of the		
messaries, such as guigened         Softey glasses with side shelds.           - The initial gages. [SANXE 1337.]. EN 66 or national capivalent]         - Contact lenses may pose a special hazard, soft contact lenses may about and cancentrate initiants. A written policy durinent, descripting the veeting of lenses or inscitos: on some should be created in a plane policy durine initial and free and poses in plane initiation. The soft and a subted equipation to and a subted equipation to any data special initiation and special policy equipation.           Skin protection         She they glasses with side initiation of a subted equipation to any data special initiation in the second of the initiation of a subted equipation intervention.           Skin protection         She they contact heories in the initiation of a subted equipation intervention in a class environment.           Skin protection         The selection of subta globes does not only depend on the material, but also on further marks of quality which vary from mandacture to manufacture. Where the chrinic is a popuration of several substances, the restatunce of the globes material is an to be calculated in induces to be christed in a subtance with a better to be christed in a subtance of the better weight with a data shift of globes pois 6 dependent on usage. Important factors in the selection of globes include: - Personal hygiene is a key atternet of effective thang clocks. The restatunce of the globes include: - Substability and datability of globes pois 6 dependent on usage. Important factors in the selection of globes include: - Substability and datability of globes pois 6 dependent on usage. Important factors in the selection of globes include: - Restard hysis is a key atternet of a file-scient trans court, a legio the potenamended.           Buinter in		extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 4-10 m/s (800-2000 f/min) for extraction of crusher dusts generated 2 metres distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are
Polencial pagelies, IASN25 1337.1, ENIGE or national equivalent)     Polencial pagelies IASN25 1337.1, ENIGE or national equivalent     Polencial pagelies may be a special haractic soft contract interes may absorb and concentrate infrants. A written policy     document, describing the weaking of lenses or restrictions on use, should be created for each workplace or task. This should     be removed at the first sign of eye redness or instanton - lens should be removed in a clean environment only after workers     we washed hands thoroughly (CDC NIOSH Current Intelligence Bulletin 59).     Skin protection     See Hand protection below     The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from     manufacture to manufacture. Where the chemical is a preparation of several substances, the resultion gloves and has to be     doesence where making a final choice.     Personal hydren is a key element of difficulte hands can. Should be prior to also application.     The sould total throughly (CDC NIOSH Current Intelligence Bulletin 59).     The sould total throughly inter for substances has to be dataset of not the impaction.     The sould total throughly inter for substances has to be dataset in reanufacture.     The sould total throughly of give type is dependent on usage. Important factors in the selection gloves and has to be     doesence where making a final choice.     The sould total the throughly, Application of a non-perfused molecular is incommended.     Substantial of give indicates and the first second mendel.     The sould topic or incountly repeated contact making source and source in higher (treakthrough time     restrictions in the selection and gloves include:     The oward total that streamer and be intered to the choice applies of higher (treakthrough time     restreamer)     Source over the selection of contact.     The oward total that streamer and be applied ton     document, ASN25 2161.1 or national equivalent).     The nonl	measures, such as personal protective	
Hands/feet protection       The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be obtained from the manufacturer of the protective gloves and has to be obtained from the manufacturer of the protective gloves and has to be obtained prior to the application. The exact break through time for substances has to be obtained prior to the application. Subtability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: <ul> <li>frequency and durability of glove type is dependent on usage. Important factors in the selection of gloves include:             <ul> <li>frequency and durability of glove type is dependent on usage. Important factors in the selection of gloves include:             <ul> <li>frequency and durability of glove type is dependent on usage. Important factors in the selection of gloves include:             <ul> <li>frequency and durability of glove types and time application.</li> <li>When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (threatthrough time greater than 240 minutes according to EN 374, ASINZS 2161.10.1 or national equivalent) is recommended.</li> <li>Contemport types are less affected by movement and this should be taken into account when considering gloves for long-farm use.</li> <li>Contemport types are less affected by movement and this should be taken into account when considering gloves for long-farm use.</li> <li>Contemport types are less</li></ul></li></ul></li></ul></li></ul>	Eye and face protection	<ul> <li>Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]</li> <li>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers</li> </ul>
Handsfeet protection <ul> <li>A solution of the several substances, the resistance of the glove material can not be calculated in advances and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be obtained from the manufacturer of the protective gloves and has to be obtained from the manufacturer of the protective gloves and has to be obtained from the manufacturer of the protective gloves and has to be obtained from the manufacturer of the protective gloves, hands should be washed and dired thoroughly. Application of a non-perturned moisturiser is recommended.         Suitability and duration of contact.              - infectorey and duration of contact.             - identical resistance of glove material.             - glove thickness and             - detective             - glove thickness and             - detective             - glove thickness and             - detective             - detective             - glove thickness             and and the protection of glove should be taken into account when considering gloves for             long humbles according to EN 374. ASIX25 2161.10 or national equivalent):             - Contaminate gloves should be replaced.             - Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for             long-term use.             - Contaminate gloves should be replaced.             As defined in ASIM F-7399 bit in any application, gloves are rated as:             - Evaluation the matures in the account when considering gloves for             through the set of onits             - Gord when breakthrough time &lt; 20 min             - Por when glove material degrades             For ownen glove material degrades             Fore orden apglotications, gloves with a thicknesse typic</li></ul>	Skin protection	See Hand protection below
Body protection       See Other protection below		<ul> <li>manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</li> <li>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</li> <li>Personal hygine is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</li> <li>Suitability and duration of contact,</li> <li>chemical resistance of glove material,</li> <li>glove thickness and</li> <li>divet thickness and</li> <li>divet thickness and</li> <li>When protoged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>When protoged or frequently repeated contact may occur, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-tem use.</li> <li>Contaminated gloves should be replaced.</li> <li>As defined in ASTM F-739-96 in any application, gloves are rated as:</li> <li>Excellent when breakthrough time &gt; 20 min</li> <li>Fair when breakthrough time &gt; 20 min</li> <li>Fair when breakthrough time &gt; 20 min</li> <li>Poor when glove moterial degrades</li> <li>Glove thickness may also vary depending on the cast or anyopicitor of glove resistance to a specific chemical, as the permeation efficiency of the glove with a protecting of varying thickness may be required where there is a mechanical (as well as chemical, as the permeation efficiency of the glove with a</li></ul>

#### **Respiratory protection**

Type -P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	P1 Air-line*	-	PAPR-P1 -
up to 50 x ES	Air-line**	P2	PAPR-P2
up to 100 x ES	-	P3	-
		Air-line*	-
100+ x ES	-	Air-line**	PAPR-P3

\* - Negative pressure demand \*\* - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

· Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.

• The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).

• Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.

Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.

• Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)

· Use approved positive flow mask if significant quantities of dust becomes airborne.

· Try to avoid creating dust conditions.

### **SECTION 9 Physical and chemical properties**

#### Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Solid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	205-207(dec.)	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available

Solubility in water	Not Available	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

# **SECTION 10 Stability and reactivity**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

# **SECTION 11 Toxicological information**

# Information on toxicological effects

Inhaled	The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	Severely toxic effects may result from the accidental ingestion of the material; animal experiments indicate that ingestion of less than 5 gram may be fatal or may produce serious damage to the health of the individual.
Skin Contact	Skin contact is not thought to produce harmful health effects (as classified under EC Directives using animal models). Systemic harm, however, has been identified following exposure of animals by at least one other route and the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	This material can cause eye irritation and damage in some persons.
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS.
	Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	~	STOT - Single Exposure	*
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend: X − Data either not available or does not fill the criteria for classification ✓ − Data available to make classification

# **SECTION 12 Ecological information**

Toxicity

4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) -
 Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

**DO NOT** discharge into sewer or waterways.

#### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
Sodium trifluoroacetate	LOW	LOW

#### **Bioaccumulative potential**

Ingredient	Bioaccumulation
Sodium trifluoroacetate	LOW (LogKOW = 0.5025)

# Mobility in soil

Ingredient	Mobility
Sodium trifluoroacetate	MEDIUM (KOC = 2.738)

# **SECTION 13 Disposal considerations**

Waste treatment methods		
	Containers may still present a chemical hazard/ danger when empty.	
	Return to supplier for reuse/ recycling if possible.	
	Otherwise:	
	If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to	
Product / Packaging	store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.	
disposal	Where possible retain label warnings and SDS and observe all notices pertaining to the product.	
-	Recycle wherever possible or consult manufacturer for recycling options.	
	Consult State Land Waste Management Authority for disposal.	
	<ul> <li>Bury residue in an authorised landfill.</li> </ul>	
	<ul> <li>Recycle containers if possible, or dispose of in an authorised landfill.</li> </ul>	

### **SECTION 14 Transport information**

#### Labels Required

Marine Pollutant NO

Land transport (ADR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

# Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Inland waterways transport (ADN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

#### Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

# Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
Sodium trifluoroacetate	Not Available

#### Transport in bulk in accordance with the IGC Code

Product name	Ship Type
Sodium trifluoroacetate	Not Available

#### **SECTION 15 Regulatory information**

#### Safety, health and environmental regulations / legislation specific for the substance or mixture

Sodium trifluoroacetate is found on the following regulatory lists

Europe EC Inventory

European Union - European Inventory of Existing Commercial Chemical Substances (EINECS)

#### **National Inventory Status**

National Inventory	Status		
Australia - AIIC / Australia Non-Industrial Use	No (Sodium trifluoroacetate)		
Canada - DSL	No (Sodium trifluoroacetate)		
Canada - NDSL	Yes		
China - IECSC	No (Sodium trifluoroacetate)		
Europe - EINEC / ELINCS / NLP	/es		
Japan - ENCS	Yes		
Korea - KECI	No (Sodium trifluoroacetate)		
New Zealand - NZIoC	Yes		
Philippines - PICCS	Yes		
USA - TSCA	Yes		
Taiwan - TCSI	Yes		
Mexico - INSQ	No (Sodium trifluoroacetate)		
Vietnam - NCI	Yes		
Russia - FBEPH	Yes		
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.		

# **SECTION 16 Other information**

Revision Date	06/07/2023
Initial Date	06/07/2023

### **SDS Version Summary**

Version	Date of Update	Sections Updated
1.2	06/07/2023	Toxicological information - Acute Health (inhaled), Toxicological information - Acute Health (skin), Toxicological information - Acute Health (swallowed), Physical and chemical properties - Appearance, CAS Number, Toxicological information - Chronic Health, Hazards identification - Classification, Disposal considerations - Disposal, Exposure controls / personal protection - Engineering Control, Ecological Information - Environmental, Firefighting measures - Fire Fighter (extinguishing media), Firefighting measures - Fire Fighter (fire/explosion hazard), Firefighting measures - Fire Fighter (fire fighting), First Aid measures - First Aid (swallowed), Composition / information on ingredients - Ingredients, Stability and reactivity - Instability Condition, Korean MSDS Number, Handling and storage - Storage (suitable container), Identification of the substance / mixture and of the company / undertaking - Supplier Information, Identification of the substance / mixture and of the company / undertaking - Synonyms

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

### **Definitions and abbreviations**

PC - TWA: Permissible Concentration-Time Weighted Average PC - STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit. IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value **BCF: BioConcentration Factors BEI: Biological Exposure Index** AIIC: Australian Inventory of Industrial Chemicals DSL: Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

#### Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	Classification Procedure
Acute Toxicity (Oral) Category 2, H300	On basis of test data
Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, H335	Expert judgement
Skin Corrosion/Irritation Category 2, H315	Expert judgement
Serious Eye Damage/Eye Irritation Category 2, H319	Expert judgement

Powered by AuthorITe, from Chemwatch.