

Apollo Scientific

Part Number: **PC6693** Version No: **2.2** Safety Data Sheet (Conforms to Annex II of REACH (1907/2006) - Regulation 2020/878) Chemwatch Hazard Alert Code: 2

Issue Date: **27/06/2023** Print Date: **03/08/2023** S.REACH.GBR.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

1.1. Product Identifier

| Product name | 2',3',4',5'-Tetrafluoroacetophenone | |
|----------------------------------|-------------------------------------|--|
| Chemical Name | ,3',4',5'-tetrafluoroacetophenone | |
| Synonyms | Available | |
| Proper shipping name | TOXIC LIQUID, ORGANIC, N.O.S. | |
| Chemical formula | C40H78O2 | |
| Other means of identification | Not Available | |
| CAS number | 66286-21-3* | |

1.2. Relevant identified uses of the substance or mixture and uses advised against

| Relevant identified uses | Not Available |
|--------------------------|--|
| Uses advised against | No specific uses advised against are identified. |

1.3. Details of the manufacturer or supplier of the safety data sheet

| Registered company name | Apollo Scientific | Apollo Scientific Itd | |
|-------------------------|---|---|--|
| Address | Whitefield Road, Bredbury SK62QR United Kingdom | Whitefield Road, Bredbury SK6 2QR United Kingdom (NI) | |
| Telephone | 01614060505 | +44(0) 161 406 0505 | |
| Fax | 0161 406 0506 Not Available | | |
| Website | Website http://www.apolloscientific.co.uk/ apolloscientific.co.uk | | |
| Email | sales@apolloscientific.co.uk | sales@apolloscientific.co.uk | |

1.4. Emergency telephone number

| Association / Organisation | Not Available |
|-----------------------------------|---------------|
| Emergency telephone numbers | Not Available |
| Other emergency telephone numbers | Not Available |

SECTION 2 Hazards identification

2.1. Classification of the substance or mixture

Classification according to regulation (EC) No 1272/2008 [CLP] and amendments ^[1]

H312 - Acute Toxicity (Dermal) Category 4, H332 - Acute Toxicity (Inhalation) Category 4, H335 - Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, H302 - Acute Toxicity (Oral) Category 4, H315 - Skin Corrosion/Irritation Category 2, H319 - Serious Eye Damage/Eye Irritation Category 2

Legend: 1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

2.2. Label elements

| Hazard pictogram(s) | |
|---------------------|---------|
| | |
| Signal word | Warning |

Hazard statement(s)

| H312 | Harmful in contact with skin. | |
|------|-----------------------------------|--|
| H332 | Harmful if inhaled. | |
| H335 | May cause respiratory irritation. | |
| H302 | Harmful if swallowed. | |
| H315 | Causes skin irritation. | |
| H319 | Causes serious eye irritation. | |

Supplementary statement(s)

Not Applicable

Precautionary statement(s) Prevention

| P271 | Use only outdoors or in a well-ventilated area. | |
|------|--|--|
| P261 | P261 Avoid breathing mist/vapours/spray. | |
| P264 | Wash all exposed external body areas thoroughly after handling. | |
| P270 | P270 Do not eat, drink or smoke when using this product. | |
| P280 | Wear protective gloves, protective clothing, eye protection and face protection. | |

Precautionary statement(s) Response

| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
|----------------|--|
| P337+P313 | If eye irritation persists: Get medical advice/attention. |
| P301+P312 | IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell. |
| P302+P352 | IF ON SKIN: Wash with plenty of water. |
| P304+P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |
| P330 | Rinse mouth. |
| P332+P313 | If skin irritation occurs: Get medical advice/attention. |
| P362+P364 | Take off contaminated clothing and wash it before reuse. |

Precautionary statement(s) Storage

| P405 | Store locked up. |
|-----------|--|
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. |

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

2.3. Other hazards

Inhalation and/or ingestion may produce health damage*.

REACH - Art.57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS print date.

SECTION 3 Composition / information on ingredients

3.1.Substances

1. CAS No

%[weight] Name

SCL/

| 2.EC No 3.Index No 4.REACH No | | | No 1272/2008 [CLP] and amendments | M-Factor | Particle Characteristics |
|---|-----|--|--|------------------|-----------------------------|
| 1. 66286-21-3* 2.Not Available 3.Not Available 4.Not Available | 100 | <u>2'.3'.4'.5'-</u> Tetrafluoroacetophenone | Acute Toxicity (Dermal) Category 4, Acute Toxicity (Inhalation) Category 4, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 2; H312, H332, H335, H302, H315, H319 ^[1] | Not Available | Not Available |

Legend: 1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L; * EU IOELVs available; [e] Substance identified as having endocrine disrupting properties

3.2.Mixtures

See 'Information on ingredients' in section 3.1

SECTION 4 First aid measures

4.1. Description of first aid measures

| Eye Contact | If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. |
|--------------|--|
| Skin Contact | If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation. |
| Inhalation | If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay. |
| Ingestion | If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice. |

4.2 Most important symptoms and effects, both acute and delayed

See Section 11

4.3. Indication of any immediate medical attention and special treatment needed

As in all cases of suspected poisoning, follow the ABCDEs of emergency medicine (airway, breathing, circulation, disability, exposure), then the ABCDEs of toxicology (antidotes, basics, change absorption, change distribution, change elimination).

For poisons (where specific treatment regime is absent):

BASIC TREATMENT

Establish a patent airway with suction where necessary.

Watch for signs of respiratory insufficiency and assist ventilation as necessary.

Administer oxygen by non-rebreather mask at 10 to 15 L/min.

Monitor and treat, where necessary, for pulmonary oedema.

Monitor and treat, where necessary, for shock.

Anticipate seizures.

DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.

- + Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- + Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- + Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

SECTION 5 Firefighting measures

5.1. Extinguishing media

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog Large fires only.

5.2. Special hazards arising from the substrate or mixture

| Fire Incompatibility | Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result |
|----------------------|---|
|----------------------|---|

5.3. Advice for firefighters

| Fire Fighting | Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use. |
|-----------------------|--|
| Fire/Explosion Hazard | Combustible. Slight fire hazard when exposed to heat or flame. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit toxic fumes of carbon monoxide (CO). May emit acrid smoke. Mists containing combustible materials may be explosive. Combustion products include: , carbon dioxide (CO2) , other pyrolysis products typical of burning organic material. May emit poisonous fumes. |

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

See section 8

6.2. Environmental precautions

See section 12

6.3. Methods and material for containment and cleaning up

| Minor Spills | Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal. |
|--------------|--|
| Major Spills | Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. |

| Wear breathing apparatus plus protective gloves. |
|---|
| Prevent, by any means available, spillage from entering drains or water course. |
| Stop leak if safe to do so. |
| Contain spill with sand, earth or vermiculite. |
| Collect recoverable product into labelled containers for recycling. |
| Neutralise/decontaminate residue (see Section 13 for specific agent). |
| Collect solid residues and seal in labelled drums for disposal. |
| Wash area and prevent runoff into drains. |
| After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using. |
| If contamination of drains or waterways occurs, advise emergency services. |

6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

| Safe handling | Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. DO NOT allow material to contact humans, exposed food or food utensils. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained. DO NOT allow clothing wet with material to stay in contact with skin |
|----------------------------------|---|
| Fire and explosion protection | See section 5 |
| Other information | Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS. |

7.2. Conditions for safe storage, including any incompatibilities

| Suitable container | Lined metal can, lined metal pail/ can. Plastic pail. Polyliner drum. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks. For low viscosity materials Drums and jerricans must be of the non-removable head type. Where a can is to be used as an inner package, the can must have a screwed enclosure. For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.): Removable head packaging; Cans with friction closures and Iow pressure tubes and cartridges may be used. Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packagings are glass and contain liquids of packing group I and II there must be sufficient inert absorbent to absorb any spillage *. * unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic. |
|-------------------------|--|
| Storage incompatibility | Avoid reaction with oxidising agents |
| | |

| Hazard categories in accordance with Regulation (EC) No 1272/2008 | Not Available |
|---|---------------|
| Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of | Not Available |

7.3. Specific end use(s)

See section 1.2

SECTION 8 Exposure controls / personal protection

8.1. Control parameters

| Ingredient | DNELs Exposure Pattern Worker | PNECs Compartment |
|---------------|----------------------------------|----------------------|
| Not Available | Not Available | Not Available |

* Values for General Population

Occupational Exposure Limits (OEL)

INGREDIENT DATA

| Source | Ingredient | Material name | TWA | STEL | Peak | Notes |
|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
| Not Available |

Not Applicable

Emergency Limits

| Ingredient | TEEL-1 | TEEL-2 | | TEEL-3 |
|---|---------------|---------------|---------------|---------------|
| 2',3',4',5'- Tetrafluoroacetophenone | Not Available | Not Available | | Not Available |
| Ingredient | Original IDLH | | Revised IDLH | |
| 2',3',4',5'- Tetrafluoroacetophenone | Not Available | | Not Available | |

Occupational Exposure Banding

| Ingredient | Occupational Exposure Band Rating | Occupational Exposure Band Limit | | |
|---|--|--|--|--|
| 2',3',4',5'- Tetrafluoroacetophenone | E | ≤ 0.1 ppm | | |
| Notes: | potency and the adverse health outcomes associated with exposu | posure banding is a process of assigning chemicals into specific categories or bands based on a chemical's adverse health outcomes associated with exposure. The output of this process is an occupational exposure ch corresponds to a range of exposure concentrations that are expected to protect worker health. | | |

8.2. Exposure controls

| 8.2.1. Appropriate engineering controls | Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. An approved self contained breathing apparatus (SCBA) may be required in some situations. Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying |
|--|--|
| | |

| | "escape" velocities which, in turn, determine the "capture vel contaminant. | ocities" of fresh circulating air required to e | ffectively remove the | | |
|---|--|---|-------------------------|--|--|
| | Type of Contaminant: | Air Speed: | | | |
| | solvent, vapours, degreasing etc., evaporating from tank (in still air). aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | | | | |
| | | | | | |
| | direct spray, spray painting in shallow booths, drum filling, discharge (active generation into zone of rapid air motion) | 1-2.5 m/s (200-500 f/min.) | | | |
| | grinding, abrasive blasting, tumbling, high speed wheel gen velocity into zone of very high rapid air motion). | 2.5-10 m/s (500-2000 f/min.) | | | |
| | Within each range the appropriate value depends on: | | | | |
| | Lower end of the range | Upper end of the range | | | |
| | 1: Room air currents minimal or favourable to capture | 1: Disturbing room air currents | | | |
| | 2: Contaminants of low toxicity or of nuisance value only. | 2: Contaminants of high toxicity | | | |
| | 3: Intermittent, low production. | 3: High production, heavy use | | | |
| | 4: Large hood or large air mass in motion | 4: Small hood-local control only | | | |
| | Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocit extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extra apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems installed or used. | | | | |
| 8.2.2. Individual protection measures, such as personal protective equipment | | | | | |
| Eye and face protection | Safety glasses with side shields. Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent] Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59]. | | | | |
| Skin protection | See Hand protection below | | | | |
| | Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber The selection of suitable gloves does not only depend on the manufacturer to manufacturer. Where the chemical is a prep can not be calculated in advance and has therefore to be che The exact break through time for substances has to be obtai observed when making a final choice. | aration of several substances, the resistance ecked prior to the application. hed from the manufacturer of the protective | e of the glove material | | |
| Hands/feet protection | Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: frequency and duration of contact, chemical resistance of glove material, glove thickness and | | | | |
| | · dexterity Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent). · When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. · When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minute according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. · Some glove polymer types are less affected by movement and this should be taken into account when considering gloves fo long-term use. | | | | |

· Contaminated gloves should be replaced.

- As defined in ASTM F-739-96 in any application, gloves are rated as:
- · Excellent when breakthrough time > 480 min
- · Good when breakthrough time > 20 min
- · Fair when breakthrough time < 20 min

| | Poor when glove material degrades For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended. It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task. Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example: Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of. Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended. |
|------------------|--|
| Body protection | See Other protection below |
| Other protection | Overalls. Eyewash unit. Barrier cream. Skin cleansing cream. |

Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

| Required minimum protection Maximum gas/vapour concentration present in air p.p.m. (by volume) | | Half-face Respirator | Full-Face Respirator |
|--|-------|-------------------------|-------------------------|
| up to 10 | 1000 | A-AUS / Class1 | - |
| up to 50 | 1000 | - | A-AUS / Class 1 |
| up to 50 | 5000 | Airline * | - |
| up to 100 | 5000 | - | A-2 |
| up to 100 | 10000 | - | A-3 |
| 100+ | | | Airline** |

* - Continuous Flow ** - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- + Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

8.2.3. Environmental exposure controls

See section 12

SECTION 9 Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Appearance | Not Available | | |
|------------------|---------------|--|---------------|
| | | | |
| Physical state | Liquid | Relative density (Water = 1) | Not Available |
| Odour | Not Available | Partition coefficient n-octanol / water | Not Available |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | Not Available |
| pH (as supplied) | Not Available | Decomposition temperature (°C) | Not Available |

| Melting point / freezing point (°C) | Not Available | Viscosity (cSt) | Not Available |
|---|---------------|--------------------------------------|---------------|
| Initial boiling point and boiling range (°C) | 83-84/20mm | Molecular weight (g/mol) | Not Available |
| Flash point (°C) | Not Available | Taste | Not Available |
| Evaporation rate | Not Available | Explosive properties | Not Available |
| Flammability | Not Available | Oxidising properties | Not Available |
| Upper Explosive Limit (%) | Not Available | Surface Tension (dyn/cm or mN/m) | Not Available |
| Lower Explosive Limit (%) | Not Available | Volatile Component (%vol) | Not Available |
| Vapour pressure (kPa) | Not Available | Gas group | Not Available |
| Solubility in water | Not Available | pH as a solution (1%) | Not Available |
| Vapour density (Air = 1) | Not Available | VOC g/L | Not Available |
| Nanoform Solubility | Not Available | Nanoform Particle Characteristics | Not Available |
| Particle Size | Not Available | | |

9.2. Other information

Not Available

SECTION 10 Stability and reactivity

| 10.1.Reactivity | See section 7.2 | | |
|---|--|--|--|
| 10.2. Chemical stability | Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur. | | |
| 10.3. Possibility of hazardous reactions | section 7.2 | | |
| 10.4. Conditions to avoid | See section 7.2 | | |
| 10.5. Incompatible materials | See section 7.2 | | |
| 10.6. Hazardous decomposition products | See section 5.3 | | |

SECTION 11 Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Information on toxicological effects

| Inhaled | The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual. |
|---|---|
| Ingestion | Accidental ingestion of the material may be damaging to the health of the individual. |
| This material can cause inflammation of the skin on contact in some persons. The material may accentuate any pre-existing dermatitis condition Skin contact Skin Contact health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with har Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. | |
| Eye | This material can cause eye irritation and damage in some persons. |
| Chronic Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related problems. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long occupational exposure. | |

| Legend: |
|---------|
|---------|

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a

non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the 2',3',4',5'irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe Tetrafluoroacetophenone bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production. Acute Toxicity ~ Carcinogenicity × **Skin Irritation/Corrosion** ~ Reproductivity × Serious Eye ~ STOT - Single Exposure ~ Damage/Irritation **Respiratory or Skin** × STOT - Repeated Exposure × sensitisation × × Mutagenicity **Aspiration Hazard**

Legend:

Data either not available or does not fill the criteria for classification
 Data available to make classification

11.2 Information on other hazards

11.2.1. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

11.2.2. Other information

See Section 11.1

SECTION 12 Ecological information

12.1. Toxicity

| Legend: | Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity |
|---------|---|
| | 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - |
| | Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data |

DO NOT discharge into sewer or waterways.

12.2. Persistence and degradability

| Ingredient | Persistence: Water/Soil | Persistence: Air |
|---|-------------------------|------------------|
| 2',3',4',5'- Tetrafluoroacetophenone | HIGH | HIGH |

12.3. Bioaccumulative potential

| Ingredient | Bioaccumulation | |
|---|-----------------------|--|
| 2',3',4',5'- Tetrafluoroacetophenone | LOW (LogKOW = 2.4752) | |

12.4. Mobility in soil

| Ingredient | Mobility |
|---|-------------------|
| 2',3',4',5'- Tetrafluoroacetophenone | LOW (KOC = 345.2) |

12.5. Results of PBT and vPvB assessment

| | Р | В | т |
|-------------------------|---------------|---------------|---------------|
| Relevant available data | Not Available | Not Available | Not Available |
| PBT | × | × | × |
| vPvB | × | × | × |

Continued...

2',3',4',5'-Tetrafluoroacetophenone

PBT Criteria fulfilled?

vPvB

No

No

12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

12.7. Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

SECTION 13 Disposal considerations

13.1. Waste treatment methods

| Product / Packaging disposal | Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate: Reduction Reuse Recycling Disposal (if all else fails) This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sever may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. Recycle wherever possible or consult manufacturer for recycling options. Consult State Land Waste Authority for disposal. Bury or incinerate residue at an approved site. Recycle containers if possible, or dispose of in an authorised landfill. |
|---------------------------------|--|
| Waste treatment options | Not Available |
| Sewage disposal options | Not Available |

SECTION 14 Transport information

Labels Required

| | 6 |
|------------------|----|
| Marine Pollutant | NO |
| HAZCHEM | 2X |

Land transport (ADR-RID)

| 14.1. UN number or ID number | 2810 | | |
|----------------------------------|---|-------------------------------|--|
| 14.2. UN proper shipping name | TOXIC LIQUID, ORGANIC, N.O.S. | TOXIC LIQUID, ORGANIC, N.O.S. | |
| 14.3. Transport hazard class(es) | Class 6.1 Subsidiary risk Not Applicable | | |
| 14.4. Packing group | III | | |
| 14.5. Environmental hazard | Not Applicable | | |
| 14.6. Special precautions | Hazard identification (Kemler) | 60 | |
| | Classification code | T1 | |
| for user | Hazard Label | 6.1 | |
| | | | |

Air transport (ICAO-IATA / DGR)

| 14.1. UN number | 2810 | | | |
|---------------------------------------|---|----------------------------|------------|--|
| 14.2. UN proper shipping name | Toxic liquid, organic, n.o.s. * | | | |
| | ICAO/IATA Class | 6.1 | | |
| 4.3. Transport hazard class(es) | ICAO / IATA Subrisk | Not Applicable | | |
| class(es) | ERG Code 6L | | | |
| 14.4. Packing group | III | | | |
| 14.5. Environmental hazard | Not Applicable | | | |
| | Special provisions | | A3 A4 A137 | |
| | Cargo Only Packing Ir | 663 | | |
| | Cargo Only Maximum Qty / Pack | | 220 L | |
| 14.6. Special precautions for user | Passenger and Cargo Packing Instructions | | 655 | |
| | Passenger and Cargo Maximum Qty / Pack | | 60 L | |
| | Passenger and Cargo Limited Quantity Packing Instructions | | Y642 | |
| | Passenger and Cargo | Limited Maximum Qty / Pack | 2 L | |

Sea transport (IMDG-Code / GGVSee)

| 14.1. UN number | 2810 | 2810 | |
|------------------------------------|--------------------|-------------------------------|--|
| 14.2. UN proper shipping name | TOXIC LIQUID, OR | TOXIC LIQUID, ORGANIC, N.O.S. | |
| 14.3. Transport hazard | IMDG Class | 6.1 | |
| class(es) | IMDG Subrisk | Not Applicable | |
| 14.4. Packing group | III | | |
| 14.5. Environmental hazard | Not Applicable | | |
| | EMS Number | F-A, S-A | |
| 14.6. Special precautions for user | Special provisions | 3 223 274 | |
| | Limited Quantities | 5 L | |

Inland waterways transport (ADN)

| 444 UN mumber | 2040 | | |
|------------------------------------|-----------------------------------|--|--|
| 14.1. UN number | 2810 | | |
| 14.2. UN proper shipping name | TOXIC LIQUID, ORGANIC, N.O.S. | | |
| 14.3. Transport hazard class(es) | 6.1 Not Applicable | | |
| 14.4. Packing group | III | | |
| 14.5. Environmental hazard | Not Applicable | | |
| | Classification code T1 | | |
| | Special provisions 274; 614; 802 | | |
| 14.6. Special precautions for user | Limited quantity 5 L | | |
| | Equipment required PP, EP, TOX, A | | |
| | Fire cones number 0 | | |

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

| Product name | Group |
|---|---------------|
| 2',3',4',5'- Tetrafluoroacetophenone | Not Available |

14.7.3. Transport in bulk in accordance with the IGC Code

| Product name | Ship Type |
|---|---------------|
| 2',3',4',5'- Tetrafluoroacetophenone | Not Available |

SECTION 15 Regulatory information

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

2',3',4',5'-Tetrafluoroacetophenone is found on the following regulatory lists

Not Applicable

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable - : Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2020/878; Regulation (EC) No 1272/2008 as updated through ATPs.

Information according to 2012/18/EU (Seveso III):

Seveso Category Not Available

15.2. Chemical safety assessment

For further information please look at the Chemical Safety Assessment and Exposure Scenarios prepared by your Supply Chain if available.

ECHA SUMMARY

| CAS number | Index No | ECHA Dossier | |
|--|--|--|--|
| 66286-21-3* | Not Available | Not Available | |
| Hazard Class and Category Code(s) | Pictograms Signal Word Code(s) | Hazard Statement Code(s) | |
| Skin Irrit. 2; Eye Irrit. 2; STOT SE 3 | GHS07; Wng | H315; H319; H335 | |
| Skin Irrit. 2; Eye Irrit. 2; STOT SE 3 | GHS06; Dgr | H315; H319; H335; H301; H311; H331 | |
| | 66286-21-3* Hazard Class and Category Code(s) Skin Irrit. 2; Eye Irrit. 2; STOT SE 3 | 66286-21-3* Not Available Hazard Class and Category Code(s) Pictograms Signal Word Code(s) Skin Irrit. 2; Eye Irrit. 2; STOT SE 3 GHS07; Wng | |

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

National Inventory Status

| National Inventory | Status | |
|--|--|--|
| Australia - AIIC / Australia Non-Industrial Use | No (2',3',4',5'-Tetrafluoroacetophenone) | |
| Canada - DSL | No (2',3',4',5'-Tetrafluoroacetophenone) | |
| Canada - NDSL | No (2',3',4',5'-Tetrafluoroacetophenone) | |
| China - IECSC | No (2',3',4',5'-Tetrafluoroacetophenone) | |
| Europe - EINEC / ELINCS / NLP | No (2',3',4',5'-Tetrafluoroacetophenone) | |
| Japan - ENCS | No (2',3',4',5'-Tetrafluoroacetophenone) | |
| Korea - KECI | No (2',3',4',5'-Tetrafluoroacetophenone) | |
| New Zealand - NZIoC | No (2',3',4',5'-Tetrafluoroacetophenone) | |
| Philippines - PICCS | No (2',3',4',5'-Tetrafluoroacetophenone) | |
| USA - TSCA | No (2',3',4',5'-Tetrafluoroacetophenone) | |
| Taiwan - TCSI | No (2',3',4',5'-Tetrafluoroacetophenone) | |

| National Inventory | Status | | |
|--------------------|--|--|--|
| Mexico - INSQ | No (2',3',4',5'-Tetrafluoroacetophenone) | | |
| Vietnam - NCI | No (2',3',4',5'-Tetrafluoroacetophenone) | | |
| Russia - FBEPH | No (2',3',4',5'-Tetrafluoroacetophenone) | | |
| Legend: | Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration. | | |

SECTION 16 Other information

| Revision Date | 27/06/2023 |
|---------------|------------|
| Initial Date | 28/06/2023 |

Full text Risk and Hazard codes

| H301 | Toxic if swallowed. | |
|------|-----------------------------|--|
| H311 | Toxic in contact with skin. | |
| H331 | Toxic if inhaled. | |

SDS Version Summary

| Version | Date of Update | Sections Updated |
|---------|-------------------|---|
| 1.2 | 27/06/2023 | Toxicological information - Acute Health (inhaled), Toxicological information - Acute Health (skin), CAS Number, Toxicological information - Chronic Health, Hazards identification - Classification, First Aid measures - First Aid (inhaled), First Aid measures - First Aid (skin), Handling and storage - Handling Procedure, Composition / information on ingredients - Ingredients, Exposure controls / personal protection - Personal Protection (hands/feet), Identification of the substance / mixture and of the company / undertaking - Supplier Information, Identification of the substance / mixture and of the company / undertaking - Synonyms |

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

- EN 166 Personal eye-protection
- EN 340 Protective clothing
- EN 374 Protective gloves against chemicals and micro-organisms
- EN 13832 Footwear protecting against chemicals
- EN 133 Respiratory protective devices

Definitions and abbreviations

- PC TWA: Permissible Concentration-Time Weighted Average
- PC STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit,
- IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL :No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- BEI: Biological Exposure Index
- AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List

NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

| Classification according to regulation (EC) No 1272/2008 [CLP] and amendments | Classification Procedure |
|---|--------------------------|
| Acute Toxicity (Dermal) Category 4, H312 | Expert judgement |
| Acute Toxicity (Inhalation) Category 4, H332 | Expert judgement |
| Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, H335 | Calculation method |
| Acute Toxicity (Oral) Category 4, H302 | Expert judgement |
| Skin Corrosion/Irritation Category 2, H315 | Calculation method |
| Serious Eye Damage/Eye Irritation Category 2, H319 | Expert judgement |

Powered by AuthorITe, from Chemwatch.

