

Peptide trifluoroacetic acid Apollo Scientific

Part Number: **PC8841** Version No: **2.2** Safety Data Sheet Chemwatch Hazard Alert Code: 4

Issue Date: **06/07/2023** Print Date: **06/07/2023** S.GHS.GB-NIR.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

| Product name | Peptide trifluoroacetic acid | |
|----------------------------------|------------------------------|--|
| Chemical Name | trifluoroacetic acid | |
| Synonyms | Not Available | |
| Proper shipping name | TRIFLUOROACETIC ACID | |
| Chemical formula | C2HF3O2 | |
| Other means of identification | Not Available | |
| CAS number | 76-05-1* | |

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses N

Not Available

Details of the manufacturer or supplier of the safety data sheet

| Registered company name | Apollo Scientific | Apollo Scientific Itd |
|---|------------------------------------|---|
| Address Whitefield Road, Bredbury SK62QR United Kingdom | | Whitefield Road, Bredbury Cheshire SK6 2QR United Kingdom (NI) |
| Telephone | 01614060505 | +44(0) 161 406 0505 |
| Fax | 0161 406 0506 | Not Available |
| Website | http://www.apolloscientific.co.uk/ | apolloscientific.co.uk |
| Email | sales@apolloscientific.co.uk | sales@apolloscientific.co.uk |

Emergency telephone number

| Association / Organisation | Not Available |
|-----------------------------------|---------------|
| Emergency telephone numbers | Not Available |
| Other emergency telephone numbers | Not Available |

SECTION 2 Hazards identification

Classification of the substance or mixture

Classification according to regulation (EC) No 1272/2008 [CLP] and

H318 - Serious Eye Damage/Eye Irritation Category 1, H332 - Acute Toxicity (Inhalation) Category 4, H314 - Skin Corrosion/Irritation Category 1A, H412 - Hazardous to the Aquatic Environment Long-Term Hazard Category 3

| amendments [1] | |
|----------------|--|
| Legend: | 1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI |

Label elements

| Hazard pictogram(s) | |
|---------------------|--------|
| | |
| Signal word | Danger |

Hazard statement(s)

| H332 Harmful if inhaled. | |
|--------------------------|--|
| H314 | Causes severe skin burns and eye damage. |
| H412 | Harmful to aquatic life with long lasting effects. |

Precautionary statement(s) Prevention

| P260 Do not breathe mist/vapours/spray. | |
|---|--|
| P264 | Wash all exposed external body areas thoroughly after handling. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P280 | Wear protective gloves, protective clothing, eye protection and face protection. |
| P273 | Avoid release to the environment. |

Precautionary statement(s) Response

| P301+P330+P331 | IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. |
|----------------|--|
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P310 | Immediately call a POISON CENTER/doctor/physician/first aider. |
| P363 | Wash contaminated clothing before reuse. |
| P304+P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |

Precautionary statement(s) Storage

P405

Store locked up.

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

| CAS No | %[weight] | Name Classification according to regulation (EC) No 1272/2008 [CLP] and amendments | | SCL / M-Factor |
|----------|-----------|--|--|-------------------|
| 76-05-1* | 100 | Peptide trifluoroacetic acid | Serious Eye Damage/Eye Irritation Category 1, Acute Toxicity (Inhalation) Category 4, Skin Corrosion/Irritation Category 1A, Hazardous to the Aquatic Environment Long-Term Hazard Category 3; H332, H314, H412 ^[1] | * |

Legend: 1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L; * EU IOELVs available; [e] Substance identified as having endocrine disrupting properties

Mixtures

See section above for composition of Substances

SECTION 4 First aid measures

| Eye Contact | If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. |
|--------------|--|
| Skin Contact | If skin or hair contact occurs: Immediately flush body and clothes with large amounts of water, using safety shower if available. Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to hospital, or doctor. |
| Inhalation | If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay. Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema. Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs). As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested. Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered. This must definitely be left to a doctor or person authorised by him/her. (ICSC13719) |
| Ingestion | For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Transport to hospital or doctor without delay. |

Indication of any immediate medical attention and special treatment needed

for corrosives:

BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- Monitor and treat, where necessary, for pulmonary oedema.
- Monitor and treat, where necessary, for shock.
- Anticipate seizures.
- Where eyes have been exposed, flush immediately with water and continue to irrigate with normal saline during transport to hospital.
- DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.
- Skin burns should be covered with dry, sterile bandages, following decontamination.
- **DO NOT** attempt neutralisation as exothermic reaction may occur.

ADVANCED TREATMENT

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

EMERGENCY DEPARTMENT

Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST),

calcium, phosphorus and magnesium, may assist in establishing a treatment regime.

Positive end-expiratory pressure (PEEP)-assisted ventilation may be required for acute parenchymal injury or adult respiratory distress syndrome.

Consider endoscopy to evaluate oral injury.

Consult a toxicologist as necessary.

BRONSTEIN, A.C. and CURRANCE, P.L. EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

SECTION 5 Firefighting measures

Extinguishing media

▶ There is no restriction on the type of extinguisher which may be used.

Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

| Fire Incompatibility | None known. |
|----------------------|-------------|
|----------------------|-------------|

Advice for firefighters

| Fire Fighting | |
|-----------------------|---|
| Fire/Explosion Hazard | Non combustible. Not considered a significant fire risk, however containers may burn. May emit corrosive fumes. |

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

| Minor Spills | Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material. Check regularly for spills and leaks. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal. |
|--------------|---|
| Major Spills | |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

| Safe handling | Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. WARNING: To avoid violent reaction, ALWAYS add material to water and NEVER water to material. Avoid smoking, naked lights or ignition sources. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained. |
|---------------|---|

| | DO NOT allow clothing wet with material to stay in contact with skin |
|-------------------|---|
| Other information | Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS. |

Conditions for safe storage, including any incompatibilities

| Suitable container | Lined metal can, lined metal pail/ can. Plastic pail. Polyliner drum. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks. For low viscosity materials Drums and jerricans must be of the non-removable head type. Where a can is to be used as an inner package, the can must have a screwed enclosure. For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.): Removable head packaging; Cans with friction closures and low pressure tubes and cartridges may be used. Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient inert cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic. |
|-------------------------|--|
| Storage incompatibility | Dangerous goods of other classes. Hygroscopic Store under argon |

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

Emergency Limits

| Ingredient | TEEL-1 | TEEL-2 | | TEEL-3 |
|------------------------------|---------------|---------|---------------|---------|
| Peptide trifluoroacetic acid | 0.13 ppm | 1.4 ppm | | 8.5 ppm |
| Ingredient | Original IDLH | | Revised IDLH | |
| Peptide trifluoroacetic acid | Not Available | | Not Available | |

Occupational Exposure Banding

| Ingredient | Occupational Exposure Band Rating | Occupational Exposure Band Limit |
|------------------------------|--|----------------------------------|
| Peptide trifluoroacetic acid | E | ≤ 0.1 ppm |
| Notes: | Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health. | |

Exposure controls

| Appropriate engineering controls | Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. |
|-------------------------------------|--|
|-------------------------------------|--|

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations.

Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

| Type of Contaminant: | Air Speed: |
|---|---------------------------------|
| solvent, vapours, degreasing etc., evaporating from tank (in still air). | 0.25-0.5 m/s (50-100 f/min.) |
| aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s (100-200 f/min.) |
| direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) | 1-2.5 m/s (200-500 f/min.) |
| grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion). | 2.5-10 m/s (500-2000 f/min.) |

Within each range the appropriate value depends on:

| Lower end of the range | Upper end of the range |
|--|----------------------------------|
| 1: Room air currents minimal or favourable to capture | 1: Disturbing room air currents |
| 2: Contaminants of low toxicity or of nuisance value only. | 2: Contaminants of high toxicity |
| 3: Intermittent, low production. | 3: High production, heavy use |
| 4: Large hood or large air mass in motion | 4: Small hood-local control only |

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

| Individual protection measures, such as personal protective equipment | |
|--|---|
| Eye and face protection | Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure. Chemical goggles. Whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitted. [AS/NZS 1337.1, EN166 or national equivalent] Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection. Alternatively a gas mask may replace splash goggles and face shields. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59]. |
| Skin protection | See Hand protection below |
| Hands/feet protection | Elbow length PVC gloves When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: frequency and duration of contact, chemical resistance of glove material, |

1

Peptide trifluoroacetic acid

| | glove thickness and dexterity Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent). When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use. Contaminated gloves should be replaced. As defined in ASTM F-739-96 in any application, gloves are rated as: Excellent when breakthrough time > 480 min Good when breakthrough time > 20 min Fair when breakthrough time > 20 min Poor when glove material degrades For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended. It should be emphasised that glove thickness is not necessarily a good predictor of glove rasistance to a specific chemical, as the permeation efficiency of the glove mile be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove sof varying thickness may be required for specific tasks. For example: Thinner gloves (down to 0.1 mm or less) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfurmed moisturiser is recommended. |
|------------------|--|
| Body protection | See Other protection below |
| Other protection | Overalls. PVC Apron. PVC protective suit may be required if exposure severe. Eyewash unit. Ensure there is ready access to a safety shower. |

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

| Appearance | Not Available | | |
|---|---------------|--|---------------|
| Physical state | Liquid | Relative density (Water = 1) | Not Available |
| Odour | Not Available | Partition coefficient n-octanol / water | Not Available |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | Not Available |
| pH (as supplied) | Not Available | Decomposition temperature (°C) | Not Available |
| Melting point / freezing point (°C) | 15.4 | Viscosity (cSt) | Not Available |
| Initial boiling point and boiling range (°C) | 72.4 | Molecular weight (g/mol) | Not Available |
| Flash point (°C) | Not Available | Taste | Not Available |
| Evaporation rate | Not Available | Explosive properties | Not Available |
| Flammability | Not Available | Oxidising properties | Not Available |
| Upper Explosive Limit (%) | Not Available | Surface Tension (dyn/cm or mN/m) | Not Available |
| Lower Explosive Limit (%) | Not Available | Volatile Component (%vol) | Not Available |
| Vapour pressure (kPa) | Not Available | Gas group | Not Available |

Solubility in waterNot AvailablepH as a solution (1%)Not AvailableVapour density (Air = 1)Not AvailableVOC g/LNot Available

SECTION 10 Stability and reactivity

| Reactivity | See section 7 | | |
|-------------------------------------|--|--|--|
| Chemical stability | Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur. | | |
| Possibility of hazardous reactions | See section 7 | | |
| Conditions to avoid | See section 7 | | |
| Incompatible materials | See section 7 | | |
| Hazardous decomposition products | See section 5 | | |

SECTION 11 Toxicological information

Information on toxicological effects

| Inhaled | The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. The material has NOT been classified by EC Directives or other classification systems as "harmful by inhalation". This is because of the lack of corroborating animal or human evidence. |
|--------------|--|
| Ingestion | The material can produce severe chemical burns within the oral cavity and gastrointestinal tract following ingestion. The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. |
| Skin Contact | The material can produce severe chemical burns following direct contact with the skin. Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. |
| Eye | The material can produce severe chemical burns to the eye following direct contact. Vapours or mists may be extremely irritating. If applied to the eyes, this material causes severe eye damage. |
| Chronic | Repeated or prolonged exposure to corrosives may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue. Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. |

| Legend: | 1. Value obtained from Europe ECHA Registered Unless otherwise specified data extracted from F | | |
|------------------------------|--|--------------------------------|---|
| | Asthma-like symptoms may continue for months non-allergic condition known as reactive airways highly irritating compound. Main criteria for diagn | dysfunction syndrome (RADS) wh | nich can occur after exposure to high levels of |
| Peptide trifluoroacetic acid | cetic acid individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentra and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a nexposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceating. The disorder is characterized by difficulty breathing, cough and mucus production. | | |
| Acute Toxicity | * | Carcinogenicity | × |

| Skin Irritation/Corrosion | ✓ | Reproductivity | × |
|--------------------------------------|---|--------------------------|---|
| Serious Eye Damage/Irritation | × | STOT - Single Exposure | × |
| Respiratory or Skin sensitisation | × | STOT - Repeated Exposure | × |
| Mutagenicity | × | Aspiration Hazard | × |

Data available to make classification

SECTION 12 Ecological information

Toxicity

| Legend: | Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity |
|---------|---|
| | 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - |
| | Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data |

Prevent, by any means available, spillage from entering drains or water courses. **DO NOT** discharge into sewer or waterways.

Persistence and degradability

| Ingredient | Persistence: Water/Soil | Persistence: Air |
|------------------------------|-------------------------|------------------|
| Peptide trifluoroacetic acid | LOW | LOW |

Bioaccumulative potential

| Ingredient | Bioaccumulation | |
|------------------------------|-----------------------|--|
| Peptide trifluoroacetic acid | LOW (LogKOW = 0.5025) | |

Mobility in soil

| Ingredient | Mobility |
|------------------------------|----------------------|
| Peptide trifluoroacetic acid | MEDIUM (KOC = 2.738) |

SECTION 13 Disposal considerations

Waste treatment methods

| | Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. |
|---------------------|---|
| | A Hierarchy of Controls seems to be common - the user should investigate: |
| | ▶ Reduction |
| | ▶ Reuse |
| | ▶ Recycling |
| | Disposal (if all else fails) |
| | This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it |
| | has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life |
| | considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, ar |
| Product / Packaging | recycling or reuse may not always be appropriate. |
| disposal | DO NOT allow wash water from cleaning or process equipment to enter drains. |
| | It may be necessary to collect all wash water for treatment before disposal. |
| | In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. |
| | Where in doubt contact the responsible authority. |
| | ► Recycle wherever possible. |
| | Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitab |
| | treatment or disposal facility can be identified. |
| | Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation followed by: burial in a land-fi |
| | specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after |
| | admixture with suitable combustible material) |
| | Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed. |

Labels Required

| - | |
|------------------|----|
| | |
| Marine Pollutant | NO |

Land transport (ADR-RID)

| UN number or ID number | 2699 | 2699 | | |
|---------------------------------|--|----------------------|----------------|--|
| UN proper shipping name | TRIFLUOROACET | TRIFLUOROACETIC ACID | | |
| Transport hazard class(es) | Class 8 Subsidiary risk Not Applicable | | | |
| Packing group | I | | | |
| Environmental hazard | Not Applicable | | | |
| Special precautions for user | Hazard identifica | tion (Kemler) | 88 | |
| | Classification code | | C3 | |
| | Hazard Label | | 8 | |
| | Special provisions | | Not Applicable | |
| | Limited quantity | | 0 | |
| | Tunnel Restriction | on Code | 1 (E) | |

Air transport (ICAO-IATA / DGR)

| UN number | 2699 | | | |
|---------------------------------|--|--|----------------|--|
| UN proper shipping name | Trifluoroacetic acid | Trifluoroacetic acid | | |
| | ICAO/IATA Class | 8 | | |
| Transport hazard class(es) | ICAO / IATA Subrisk | Not Applicable | | |
| | ERG Code | 8N | | |
| Packing group | I | | | |
| Environmental hazard | Not Applicable | | | |
| | Special provisions | | Not Applicable | |
| | Cargo Only Packing Instructions | | 854 | |
| | Cargo Only Maximum Qty / Pack | | 2.5 L | |
| Special precautions for user | Passenger and Cargo Packing Instructions | | 850 | |
| usei | Passenger and Cargo Maximum Qty / Pack | | 0.5 L | |
| | Passenger and Cargo | Limited Quantity Packing Instructions | Forbidden | |
| | Passenger and Cargo | Passenger and Cargo Limited Maximum Qty / Pack | | |

Sea transport (IMDG-Code / GGVSee)

| 2699 | 2699 | | |
|--|--|--|--|
| TRIFLUOROACETIC | ACID | | |
| | | | |
| 1 | | | |
| Not Applicable | | | |
| EMS Number Special provisions Limited Quantities | F-A, S-B Not Applicable 0 | | |
| | TRIFLUOROACETIC IMDG Class 8 IMDG Subrisk N I Not Applicable EMS Number Special provisions | | |

Inland waterways transport (ADN)

| UN number | 2699 | | | | |
|---------------------------------|---------------------|----------------|---|--|--|
| UN proper shipping name | TRIFLUOROACETIC A | CID | | | |
| Transport hazard class(es) | 8 Not Applicable | | | | |
| Packing group | 1 | | | | |
| Environmental hazard | Not Applicable | | | | |
| | Classification code | C3 | - | | |
| | Special provisions | Not Applicable | | | |
| Special precautions for user | Limited quantity | 0 | | | |
| 4001 | Equipment required | PP, EP | | | |
| | Fire cones number | 0 | | | |
| | | | | | |

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

| Product name | Group |
|------------------------------|---------------|
| Peptide trifluoroacetic acid | Not Available |

Transport in bulk in accordance with the IGC Code

| Product name | Ship Type |
|------------------------------|---------------|
| Peptide trifluoroacetic acid | Not Available |

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

| Peptide trifluoroacetic acid is found on the following regulatory lists |
|---|
| Europe EC Inventory |
| European Union - European Inventory of Existing Commercial Chemical |
| Substances (EINECS) |

European Union (EU) Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures - Annex VI

National Inventory Status

| National Inventory | Status |
|--|--|
| Australia - AIIC / Australia Non-Industrial Use | Yes |
| Canada - DSL | Yes |
| Canada - NDSL | No (Peptide trifluoroacetic acid) |
| China - IECSC | Yes |
| Europe - EINEC / ELINCS / NLP | Yes |
| Japan - ENCS | Yes |
| Korea - KECI | Yes |
| New Zealand - NZIoC | Yes |
| Philippines - PICCS | Yes |
| USA - TSCA | Yes |
| Taiwan - TCSI | Yes |
| Mexico - INSQ | Yes |
| Vietnam - NCI | Yes |
| Russia - FBEPH | Yes |
| Legend: | Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration. |

SECTION 16 Other information

| Revision Date | 06/07/2023 |
|---------------|------------|
| Initial Date | 06/07/2023 |

SDS Version Summary

| Version | Date of Update | Sections Updated | |
|---------|-------------------|---|--|
| 1.2 | 06/07/2023 | Physical and chemical properties - Appearance, CAS Number, Disposal considerations - Disposal, Firefighting measures - Fire Fighter (extinguishing media), Firefighting measures - Fire Fighter (fire/explosion hazard), Composition / information on ingredients - Ingredients, Korean MSDS Number, Identification of the substance / mixture and of the company / undertaking - Supplier Information, Identification of the substance / mixture and of the company / undertaking - Synonyms | |

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

Definitions and abbreviations

PC - TWA: Permissible Concentration-Time Weighted Average

PC - STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

- TEEL: Temporary Emergency Exposure Limit.
- IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List

NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory

NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act

TCSI: Taiwan Chemical Substance Inventory

INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Classification according to regulation (EC) No 1272/2008 [CLP] and amendments

Classification Procedure

| Peptide | trifluoroacetic | acid |
|---------|-----------------|------|
| | | 4014 |

| Classification according to regulation (EC) No 1272/2008 [CLP] and amendments | Classification Procedure | |
|--|--------------------------|--|
| Serious Eye Damage/Eye Irritation Category 1, H318 | Calculation method | |
| Acute Toxicity (Inhalation) Category 4, H332 | Expert judgement | |
| Skin Corrosion/Irritation Category 1A, H314 | Calculation method | |
| Hazardous to the Aquatic Environment Long-Term Hazard Category 3, H412 | Expert judgement | |

Powered by AuthorITe, from Chemwatch.