

# 6-Chloro-5-fluoro-2,3-dihydro-1H-inden-1-one Apollo Scientific

Part Number: **PC908169**Version No: **2.2**Safety Data Sheet

#### Chemwatch Hazard Alert Code: 2

Issue Date: **05/07/2023**Print Date: **05/07/2023**S.GHS.GB-NIR.EN

#### SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### **Product Identifier**

Product name	6-Chloro-5-fluoro-2,3-dihydro-1H-inden-1-one	
Chemical Name	6-Chloro-5-fluoro-2,3-dihydro-1H-inden-1-one	
Synonyms	Not Available	
Other means of identification	Not Available	
CAS number	881189-75-9*	

#### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Not Available

#### Details of the manufacturer or supplier of the safety data sheet

Registered company name	Apollo Scientific	Apollo Scientific Itd
Address	Whitefield Road, Bredbury SK62QR United Kingdom	Whitefield Road, Bredbury Cheshire SK6 2QR United Kingdom (NI)
Telephone	01614060505	+44(0) 161 406 0505
Fax	0161 406 0506	Not Available
Website	http://www.apolloscientific.co.uk/ apolloscientific.co.uk	
Email	sales@apolloscientific.co.uk sales@apolloscientific.co.uk	

#### **Emergency telephone number**

Association / Organisation	Not Available
Emergency telephone numbers	Not Available
Other emergency telephone numbers	Not Available

#### **SECTION 2 Hazards identification**

#### Classification of the substance or mixture

Classification according to regulation (EC) No 1272/2008 [CLP] and amendments [1]	H335 - Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, H302 - Acute Toxicity (Oral) Category 4, H315 - Skin Corrosion/Irritation Category 2, H319 - Serious Eye Damage/Eye Irritation Category 2
Legend:	1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Version No: 2.2

6-Chloro-5-fluoro-2,3-dihydro-1H-inden-1-one

Issue Date: 05/07/2023

Print Date: 05/07/2023

#### Label elements

#### Hazard pictogram(s)



Signal word

Warning

#### Hazard statement(s)

H335	May cause respiratory irritation.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.

#### Precautionary statement(s) Prevention

	•
P271	Use only outdoors or in a well-ventilated area.
P261	Avoid breathing dust/fumes.
P264	Wash all exposed external body areas thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves, protective clothing, eye protection and face protection.

#### Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell.
P302+P352	IF ON SKIN: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P330	Rinse mouth.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

#### Precautionary statement(s) Storage

P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

#### Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

#### **SECTION 3 Composition / information on ingredients**

#### **Substances**

CAS No	%[weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	SCL / M-Factor
881189-75-9*	100	6-Chloro-5-fluoro- 2,3-dihydro- 1H-inden-1-one	Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3 , Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 2; H335, H302, H315, H319 [1]	Not Available

Legend:

1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L; \* EU IOELVs available; [e] Substance identified as having endocrine disrupting properties

#### **Mixtures**

See section above for composition of Substances

#### **SECTION 4 First aid measures**

Part Number: PC908169 Page 3 of 11

Issue Date: 05/07/2023 Version No: 2.2 Print Date: 05/07/2023

6-Chloro-5-fluoro-2,3-dihydro-1H-inden-1-one

#### Description of first aid measures

Eye Contact	If this product comes in contact with the eyes:  • Wash out immediately with fresh running water.  • Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.  • Seek medical attention without delay; if pain persists or recurs seek medical attention.  • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs:  Flush skin and hair with running water (and soap if available).  Seek medical attention in event of irritation.
Inhalation	<ul> <li>If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>
Ingestion	<ul> <li>Immediately give a glass of water.</li> <li>First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>

#### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

#### **SECTION 5 Firefighting measures**

#### **Extinguishing media**

- ▶ There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

#### Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.
Advice for firefighters	
Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves in the event of a fire.</li> <li>Prevent, by any means available, spillage from entering drains or water courses.</li> <li>Use fire fighting procedures suitable for surrounding area.</li> <li>DO NOT approach containers suspected to be hot.</li> <li>Cool fire exposed containers with water spray from a protected location.</li> <li>If safe to do so, remove containers from path of fire.</li> <li>Equipment should be thoroughly decontaminated after use.</li> </ul>
Fire/Explosion Hazard	<ul> <li>Non combustible.</li> <li>Not considered a significant fire risk, however containers may burn.</li> <li>May emit corrosive fumes.</li> </ul>

#### **SECTION 6 Accidental release measures**

#### Personal precautions, protective equipment and emergency procedures

See section 8

#### **Environmental precautions**

See section 12

Methods and material for	Clean up all spills immediately.     Avoid breathing dust and contact with skin and eyes.     Wear protective clothing, gloves, safety glasses and dust respirator.     Use dry clean up procedures and avoid generating dust.     Sweep up, shovel up or     Vacuum up (consider explosion-proof machines designed to be grounded during storage and use).     Place spilled material in clean, dry, sealable, labelled container.
--------------------------	---

Issue Date: 05/07/2023 Part Number: PC908169 Page 4 of 11 Version No: 2.2

Print Date: 05/07/2023 6-Chloro-5-fluoro-2,3-dihydro-1H-inden-1-one

#### Moderate hazard.

- ► CAUTION: Advise personnel in area.
- ▶ Alert Emergency Services and tell them location and nature of hazard.
- Control personal contact by wearing protective clothing.
- Prevent, by any means available, spillage from entering drains or water courses.
- Recover product wherever possible.
- IF DRY: Use dry clean up procedures and avoid generating dust. Collect residues and place in sealed plastic bags or other containers for disposal. IF WET: Vacuum/shovel up and place in labelled containers for disposal.
- ► ALWAYS: Wash area down with large amounts of water and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise Emergency Services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

#### **SECTION 7 Handling and storage**

**Major Spills** 

#### Precautions for safe handling

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- ▶ DO NOT enter confined spaces until atmosphere has been checked.
- ▶ DO NOT allow material to contact humans, exposed food or food utensils.
- Avoid contact with incompatible materials.
- Safe handling
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- ▶ Work clothes should be laundered separately. Launder contaminated clothing before re-use.
- Use good occupational work practice.
- Observe manufacturer's storage and handling recommendations contained within this SDS.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

## Other information

- ► Store in original containers.
- Keep containers securely sealed.
- ▶ Store in a cool, dry area protected from environmental extremes.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storage and handling recommendations contained within this SDS.

#### For major quantities:

- ▶ Consider storage in bunded areas ensure storage areas are isolated from sources of community water (including stormwater, ground water, lakes and streams).
- Ensure that accidental discharge to air or water is the subject of a contingency disaster management plan; this may require consultation with local authorities.

#### Conditions for safe storage, including any incompatibilities

#### Suitable container

- Lined metal can, lined metal pail/ can.
- Plastic pail.
- Polyliner drum.
- Packing as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

#### Storage incompatibility

None known

► Store at 2-8°C

#### **SECTION 8 Exposure controls / personal protection**

#### **Control parameters**

Occupational Exposure Limits (OEL)

**INGREDIENT DATA** 

Not Available

**Emergency Limits** 

Ingredient TEEL-1 TEEL-2 TEEL-3 Version No: 2.2

## Page 5 of 11 6-Chloro-5-fluoro-2,3-dihydro-1H-inden-1-one

Issue Date: 05/07/2023 Print Date: 05/07/2023

Ingredient	TEEL-1	TEEL-2	TEEL-3
6-Chloro-5-fluoro- 2,3-dihydro-1H-inden-1-one	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
6-Chloro-5-fluoro- 2,3-dihydro-1H-inden-1-one	Not Available	Not Available

#### **Occupational Exposure Banding**

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit	
6-Chloro-5-fluoro- 2,3-dihydro-1H-inden-1-one	E	≤ 0.01 mg/m³	
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.		

#### **Exposure controls**

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.

- Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.
- If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered.

Such protection might consist of:

- (a): particle dust respirators, if necessary, combined with an absorption cartridge;
- (b): filter respirators with absorption cartridge or canister of the right type;

Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

#### Appropriate engineering controls

Type of Contaminant:	Air Speed:
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range	
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents	
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity	
3: Intermittent, low production.	3: High production, heavy use	
4: Large hood or large air mass in motion	4: Small hood-local control only	

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 4-10 m/s (800-2000 f/min) for extraction of crusher dusts generated 2 metres distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Individual protection measures, such as personal protective equipment











 Part Number: PC908169
 Page 6 of 11
 Issue Date: 05/07/2023

 Version No: 2.2
 Print Date: 05/07/2023

#### 6-Chloro-5-fluoro-2,3-dihydro-1H-inden-1-one

► Safety glasses with side shields. ► Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent] Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should Eye and face protection include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59]. Skin protection See Hand protection below The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: · frequency and duration of contact, · chemical resistance of glove material, · glove thickness and · dexterity Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent). · When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. · When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161,10.1 or national equivalent) is recommended. Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use. · Contaminated gloves should be replaced. As defined in ASTM F-739-96 in any application, gloves are rated as: · Excellent when breakthrough time > 480 min - Good when breakthrough time > 20 min Hands/feet protection  $\cdot$  Fair when breakthrough time < 20 min · Poor when glove material degrades For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended. It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task. Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example: · Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of. · Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended. Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present. polychloroprene. nitrile rubber. butyl rubber.

#### **Body protection**

#### See Other protection below

fluorocaoutchouc.polyvinyl chloride.

#### Other protection

see Other protection ber

## P.V.C apron.

Barrier cream.

Overalls.

- Skin cleansing cream.
- ▶ Eye wash unit.

#### Respiratory protection

Type -P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Gloves should be examined for wear and/ or degradation constantly.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator

Version No: 2.2

#### 6-Chloro-5-fluoro-2,3-dihydro-1H-inden-1-one

Issue Date: **05/07/2023**Print Date: **05/07/2023** 

		I.	(
up to 10 v ES	P1	-	PAPR-P1
up to 10 x ES	Air-line*	-	-
up to 50 x ES	Air-line**	P2	PAPR-P2
up to 100 x ES	-	P3	-
		Air-line*	-
100+ x ES	-	Air-line**	PAPR-P3

<sup>\* -</sup> Negative pressure demand \*\* - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- · Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- · Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.
- · Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
- · Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)
- · Use approved positive flow mask if significant quantities of dust becomes airborne.
- $\cdot$  Try to avoid creating dust conditions.

#### **SECTION 9 Physical and chemical properties**

#### Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Solid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Not Available	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

#### **SECTION 10 Stability and reactivity**

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.

 Part Number: PC908169
 Page 8 of 11
 Issue Date: 05/07/2023

 Version No: 2.2
 Print Date: 05/07/2023

#### 6-Chloro-5-fluoro-2,3-dihydro-1H-inden-1-one

Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

#### **SECTION 11 Toxicological information**

#### Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.
Eye	This material can cause eye irritation and damage in some persons.
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

Legend:
1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS.
Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

Acute Toxicity	<b>✓</b>	Carcinogenicity	×
Skin Irritation/Corrosion	<b>✓</b>	Reproductivity	×
Serious Eye Damage/Irritation	<b>✓</b>	STOT - Single Exposure	<b>✓</b>
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend:

★ – Data either not available or does not fill the criteria for classification

✓ – Data available to make classification

#### **SECTION 12 Ecological information**

#### Toxicity

Legend: Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity
4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) -

Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

#### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

#### **Bioaccumulative potential**

Ingredient	Bioaccumulation	
	No Data available for all ingredients	

#### Mobility in soil

<del>-</del>	
Ingredient	Mobility

 Part Number: PC908169
 Page 9 of 11
 Issue Date: 05/07/2023

 Version No: 2.2
 Print Date: 05/07/2023

#### 6-Chloro-5-fluoro-2,3-dihydro-1H-inden-1-one

Ingredient	Mobility
	No Data available for all ingredients

#### **SECTION 13 Disposal considerations**

#### Waste treatment methods

## Product / Packaging disposal

- ▶ Recycle wherever possible or consult manufacturer for recycling options.
- ► Consult State Land Waste Management Authority for disposal.
- ▶ Bury residue in an authorised landfill.
- Recycle containers if possible, or dispose of in an authorised landfill.

#### **SECTION 14 Transport information**

#### **Labels Required**

**Marine Pollutant** 

NO

Land transport (ADR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Inland waterways transport (ADN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

#### Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
6-Chloro-5-fluoro- 2,3-dihydro-1H-inden-1-one	Not Available

### Transport in bulk in accordance with the IGC Code

Product name	Ship Type
6-Chloro-5-fluoro- 2,3-dihydro-1H-inden-1-one	Not Available

#### **SECTION 15 Regulatory information**

#### Safety, health and environmental regulations / legislation specific for the substance or mixture

6-Chloro-5-fluoro-2,3-dihydro-1H-inden-1-one is found on the following regulatory lists

Not Applicable

#### **National Inventory Status**

National Inventory	Status		
Australia - AIIC / Australia Non-Industrial Use	No (6-Chloro-5-fluoro-2,3-dihydro-1H-inden-1-one)		
Canada - DSL	No (6-Chloro-5-fluoro-2,3-dihydro-1H-inden-1-one)		
Canada - NDSL	No (6-Chloro-5-fluoro-2,3-dihydro-1H-inden-1-one)		
China - IECSC	No (6-Chloro-5-fluoro-2,3-dihydro-1H-inden-1-one)		
Europe - EINEC / ELINCS / NLP	No (6-Chloro-5-fluoro-2,3-dihydro-1H-inden-1-one)		
Japan - ENCS	No (6-Chloro-5-fluoro-2,3-dihydro-1H-inden-1-one)		
Korea - KECI	No (6-Chloro-5-fluoro-2,3-dihydro-1H-inden-1-one)		
New Zealand - NZIoC	No (6-Chloro-5-fluoro-2,3-dihydro-1H-inden-1-one)		
Philippines - PICCS	No (6-Chloro-5-fluoro-2,3-dihydro-1H-inden-1-one)		

Page 10 of 11 Issue Date: 05/07/2023 Print Date: 05/07/2023 Version No: 2.2

#### 6-Chloro-5-fluoro-2,3-dihydro-1H-inden-1-one

National Inventory	Status
USA - TSCA	No (6-Chloro-5-fluoro-2,3-dihydro-1H-inden-1-one)
Taiwan - TCSI	No (6-Chloro-5-fluoro-2,3-dihydro-1H-inden-1-one)
Mexico - INSQ	No (6-Chloro-5-fluoro-2,3-dihydro-1H-inden-1-one)
Vietnam - NCI	No (6-Chloro-5-fluoro-2,3-dihydro-1H-inden-1-one)
Russia - FBEPH	No (6-Chloro-5-fluoro-2,3-dihydro-1H-inden-1-one)
	Yes = All CAS declared ingredients are on the inventory
Legend:	No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

#### **SECTION 16 Other information**

Revision Date	05/07/2023
Initial Date	05/07/2023

#### **SDS Version Summary**

Version	Date of Update	Sections Updated
1.2	05/07/2023	Physical and chemical properties - Appearance, CAS Number, Hazards identification - Classification, Composition / information on ingredients - Ingredients, Korean MSDS Number, Identification of the substance / mixture and of the company / undertaking - Supplier Information, Identification of the substance / mixture and of the company / undertaking - Synonyms

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

#### **Definitions and abbreviations**

PC - TWA: Permissible Concentration-Time Weighted Average

PC - STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit,

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSI: Domestic Substances List NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

**ENCS: Existing and New Chemical Substances Inventory** 

KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

Issue Date: 05/07/2023 Version No: 2.2 Print Date: 05/07/2023 6-Chloro-5-fluoro-2,3-dihydro-1H-inden-1-one

TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

#### Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	Classification Procedure	
Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3 , H335	Expert judgement	
Acute Toxicity (Oral) Category 4, H302	Expert judgement	
Skin Corrosion/Irritation Category 2, H315	Expert judgement	
Serious Eye Damage/Eye Irritation Category 2, H319	Expert judgement	

Powered by AuthorITe, from Chemwatch.