

# **Apollo Scientific**

Part Number: **PC99382** Version No: **1.1** Safety Data Sheet (Conforms to Annex II of REACH (1907/2006) - Regulation 2020/878) Chemwatch Hazard Alert Code: 2

Issue Date: **12/03/2023** Print Date: **03/08/2023** S.REACH.GBR.EN

# SECTION 1 Identification of the substance / mixture and of the company / undertaking

# **1.1. Product Identifier**

Product name	4-Bromo-3-fluoro-2-iodobenzonitrile	
Chemical Name	Not Available	
Synonyms	Not Available	
Proper shipping name	NITRILES, SOLID, TOXIC, N.O.S.	
Chemical formula	Not Available	
Other means of identification	Not Available	
CAS number	2167980-85-8*	

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Use according to manufacturer's directions.	
Uses advised against	No specific uses advised against are identified.	

# 1.3. Details of the manufacturer or supplier of the safety data sheet

Registered company name	Apollo Scientific	
Address	Vhitefield Road, Bredbury SK62QR United Kingdom	
Telephone	1614060505	
Fax	0161 406 0506	
Website	http://www.apolloscientific.co.uk/	
Email	sales@apolloscientific.co.uk	

# 1.4. Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	Not Available
Other emergency telephone numbers	Not Available

# **SECTION 2 Hazards identification**

# 2.1. Classification of the substance or mixture

Classification according to regulation (EC) No 1272/2008 [CLP] and amendments <sup>[1]</sup>

H312 - Acute Toxicity (Dermal) Category 4, H332 - Acute Toxicity (Inhalation) Category 4, H335 - Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, H302 - Acute Toxicity (Oral) Category 4, H315 - Skin Corrosion/Irritation Category 2, H319 - Serious Eye Damage/Eye Irritation Category 2

1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI Legend:

# 2.2. Label elements

ElE: Edber ciciliento	
Hazard pictogram(s)	
Signal word	Warning

# Hazard statement(s)

H312	Harmful in contact with skin.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H302	Harmful if swallowed.	
H315	Causes skin irritation.	
H319	Causes serious eye irritation.	

# Supplementary statement(s)

Not Applicable

# Precautionary statement(s) Prevention

P271	Use only outdoors or in a well-ventilated area.	
P261	P261 Avoid breathing dust/fumes.	
P264	4 Wash all exposed external body areas thoroughly after handling.	
P270	70 Do not eat, drink or smoke when using this product.	
P280	Wear protective gloves, protective clothing, eye protection and face protection.	

### Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
P337+P313	If eye irritation persists: Get medical advice/attention.		
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell.		
P302+P352	IF ON SKIN: Wash with plenty of water.		
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.		
P330	Rinse mouth.		
P332+P313	If skin irritation occurs: Get medical advice/attention.		
P362+P364	Take off contaminated clothing and wash it before reuse.		

### Precautionary statement(s) Storage

P405	Store locked up.	
P403+P233 Store in a well-ventilated place. Keep container tightly closed.		

# Precautionary statement(s) Disposal

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

# 2.3. Other hazards

Inhalation and/or ingestion may produce health damage\*.

P501

REACH - Art.57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS print date.

# **SECTION 3 Composition / information on ingredients**

# 3.1.Substances

1. CAS No

%[weight] Name

2.EC No 3.Index No 4.REACH No			(EC) No 1272/2008 [CLP] and amendments	M-Factor	Characteristics
Not Available	100	4-Bromo-3-fluoro- 2-iodobenzonitrile	Not Applicable	Not Applicable	Not Available

Legend: 1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L; \* EU IOELVs available; [e] Substance identified as having endocrine disrupting properties

#### 3.2.Mixtures

See 'Information on ingredients' in section 3.1

### **SECTION 4 First aid measures**

#### 4.1. Description of first aid measures

Eye Contact	<ul> <li>If this product comes in contact with the eyes:</li> <li>Wash out immediately with fresh running water.</li> <li>Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
Skin Contact	<ul> <li>If skin or hair contact occurs:</li> <li>Flush skin and hair with running water (and soap if available).</li> <li>Seek medical attention in event of irritation.</li> </ul>
Inhalation	<ul> <li>If fumes or combustion products are inhaled remove from contaminated area.</li> <li>Lay patient down. Keep warm and rested.</li> <li>Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>Transport to hospital, or doctor.</li> </ul>
Ingestion <ul> <li>If swallowed do NOT induce vomiting.</li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open air prevent aspiration.</li> <li>Observe the patient carefully.</li> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscions</li> <li>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>Seek medical advice.</li> </ul>	

# 4.2 Most important symptoms and effects, both acute and delayed

See Section 11

#### 4.3. Indication of any immediate medical attention and special treatment needed

As in all cases of suspected poisoning, follow the ABCDEs of emergency medicine (airway, breathing, circulation, disability, exposure), then the ABCDEs of toxicology (antidotes, basics, change absorption, change distribution, change elimination).

For poisons (where specific treatment regime is absent):

#### BASIC TREATMENT

-----

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 L/min.
- Monitor and treat, where necessary, for pulmonary oedema.
- Monitor and treat, where necessary, for shock.
- Anticipate seizures.
- DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.

#### ADVANCED TREATMENT

- + Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Positive-pressure ventilation using a bag-valve mask might be of use.

\_\_\_\_\_

- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- + Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.

Treat seizures with diazepam.

Proparacaine hydrochloride should be used to assist eye irrigation.

BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

# **SECTION 5 Firefighting measures**

#### 5.1. Extinguishing media

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

#### 5.2. Special hazards arising from the substrate or mixture

Fire Incompatibility None known.

#### 5.3. Advice for firefighters

Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves in the event of a fire.</li> <li>Prevent, by any means available, spillage from entering drains or water courses.</li> <li>Use fire fighting procedures suitable for surrounding area.</li> <li>DO NOT approach containers suspected to be hot.</li> <li>Cool fire exposed containers with water spray from a protected location.</li> <li>If safe to do so, remove containers from path of fire.</li> <li>Equipment should be thoroughly decontaminated after use.</li> </ul>
Fire/Explosion Hazard	<ul> <li>Non combustible.</li> <li>Not considered a significant fire risk, however containers may burn.</li> <li>May emit poisonous fumes.</li> </ul>

# **SECTION 6 Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

See section 8

#### 6.2. Environmental precautions

See section 12

### 6.3. Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Remove all ignition sources.</li> <li>Clean up all spills immediately.</li> <li>Avoid contact with skin and eyes.</li> </ul>
	<ul> <li>Control personal contact with the substance, by using protective equipment.</li> <li>Use dry clean up procedures and avoid generating dust.</li> <li>Place in a suitable, labelled container for waste disposal.</li> </ul>
Major Spills	<ul> <li>Clear area of personnel and move upwind.</li> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves.</li> <li>Prevent, by any means available, spillage from entering drains or water course.</li> <li>Stop leak if safe to do so.</li> <li>Contain spill with sand, earth or vermiculite.</li> <li>Collect recoverable product into labelled containers for recycling.</li> <li>Neutralise/decontaminate residue (see Section 13 for specific agent).</li> <li>Collect solid residues and seal in labelled drums for disposal.</li> <li>Wash area and prevent runoff into drains.</li> <li>After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.</li> <li>If contamination of drains or waterways occurs, advise emergency services.</li> </ul>

#### 6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# **SECTION 7 Handling and storage**

#### 7.1. Precautions for safe handling

Safe handling

Avoid all personal contact, including inhalation.

Continued...

	Wear protective clothing when risk of exposure occurs.
	▶ Use in a well-ventilated area.
	Prevent concentration in hollows and sumps.
	DO NOT enter confined spaces until atmosphere has been checked.
	DO NOT allow material to contact humans, exposed food or food utensils.
	Avoid contact with incompatible materials.
	When handling, DO NOT eat, drink or smoke.
	Keep containers securely sealed when not in use.
	Avoid physical damage to containers.
	Always wash hands with soap and water after handling.
	Work clothes should be laundered separately. Launder contaminated clothing before re-use.
	Use good occupational work practice.
	Observe manufacturer's storage and handling recommendations contained within this SDS.
	Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are instant.
	maintained.
Fire and explosion protection	See section 5
	Store in original containers.
	Keep containers securely sealed.
Other information	Store in a cool, dry, well-ventilated area.
	Store away from incompatible materials and foodstuff containers.
	Protect containers against physical damage and check regularly for leaks.
	Observe manufacturer's storage and handling recommendations contained within this SDS.

	Lined metal can, lined metal pail/ can.
	<ul> <li>Plastic pail.</li> <li>Polyliner drum.</li> <li>Packing as recommended by manufacturer.</li> </ul>
	Check all containers are clearly labelled and free from leaks.      For low viscosity metaziola
	<ul> <li>For low viscosity materials</li> <li>Drums and jerricans must be of the non-removable head type.</li> </ul>
	<ul> <li>Where a can is to be used as an inner package, the can must have a screwed enclosure.</li> </ul>
	For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.):
Suitable container	<ul> <li>Removable head packaging;</li> <li>Cans with friction closures and</li> </ul>
ounable container	<ul> <li>Iow pressure tubes and cartridges</li> </ul>
	may be used.
	- Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages *.
	In addition, where inner packagings are glass and contain liquids of packing group I and II there must be sufficient inert absorbent to absorb any spillage *.
	* unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.
	<ul> <li>Nitriles may polymerise in the presence of metals and some metal compounds.</li> </ul>
	<ul> <li>They are incompatible with acids; mixing nitriles with strong oxidising acids can lead to extremely violent reactions.</li> <li>Nitriles are generally incompatible with other oxidising agents such as peroxides and epoxides.</li> </ul>
	<ul> <li>The combination of bases and nitriles can produce hydrogen cyanide. Nitriles are hydrolysed exothermally in both aqueous acid and base to give carboxylic acids (or salts of carboxylic acids).</li> </ul>
	<ul> <li>Nitriles can react vigorously with reducing agents.</li> </ul>
Storage incompatibility	The covalent cyano group is endothermic and many organic nitriles are reactive under certain conditions; N-cyano derivatives are reactive or unstable.
	<ul> <li>The majority of endothermic compounds are thermodynamically unstable and may decompose explosively under various</li> </ul>
	circumstances of initiation.
	Many but not all endothermic compounds have been involved in decompositions, reactions and explosions and, in general, compounds with significantly positive values of standard heats of formation, may be considered suspect on stability grounds.
	BRETHERICK L.: Handbook of Reactive Chemical Hazards
	None known <ul> <li>Light sensitive</li> </ul>
Hazard categories in	· Light sensitive
accordance with	Not Available
Regulation (EC) No 1272/2008	
Qualifying quantity	
(tonnes) of dangerous substances as referred to	Not Available
in Article 3(10) for the	

application of

# 7.3. Specific end use(s)

See section 1.2

# **SECTION 8 Exposure controls / personal protection**

# 8.1. Control parameters

Ingredient	DNELs Exposure Pattern Worker	PNECs Compartment
Not Available	Not Available	Not Available

\* Values for General Population

# Occupational Exposure Limits (OEL)

# INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Not Available						

Not Applicable

# Emergency Limits

Ingredient	TEEL-1	TEEL-2		TEEL-3
4-Bromo-3-fluoro- 2-iodobenzonitrile	Not Available	Not Available		Not Available
Ingredient	Original IDLH		Revised IDLH	
4-Bromo-3-fluoro- 2-iodobenzonitrile	Not Available		Not Available	

# 8.2. Exposure controls

	Engineering controls are used to remove a hazard or place	a barrier between the worker and the hazard.	Well-designed	
	engineering controls can be highly effective in protecting wo		•	
	provide this high level of protection.			
	The basic types of engineering controls are:			
	Process controls which involve changing the way a job activ	vity or process is done to reduce the risk.		
	Enclosure and/or isolation of emission source which keeps		worker and ventilation	
	that strategically "adds" and "removes" air in the work envir			
	designed properly. The design of a ventilation system must			
	Employers may need to use multiple types of controls to pre-	event employee overexposure.		
	Local exhaust ventilation usually required. If risk of overexp	osure exists, wear approved respirator. Correc	ct fit is essential to	
	obtain adequate protection. Supplied-air type respirator ma	y be required in special circumstances. Correc	ct fit is essential to	
		ensure adequate protection.		
	An approved self contained breathing apparatus (SCBA) may be required in some situations. Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying			
	Provide adequate ventilation in warehouse or closed storage	a area. Air contaminants generated in the wor	"escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the	
		5	1 1 , 0	
1. Appropriate	"escape" velocities which, in turn, determine the "capture ve	5	1 1 , 0	
•	"escape" velocities which, in turn, determine the "capture ve contaminant.	5	1 1 , 0	
	"escape" velocities which, in turn, determine the "capture ve contaminant.	5	Air Speed:	
•	"escape" velocities which, in turn, determine the "capture ve contaminant.	elocities" of fresh circulating air required to effe	Air Speed: 0.25-0.5 m/s	
•	"escape" velocities which, in turn, determine the "capture ve contaminant. Type of Contaminant: solvent, vapours, degreasing etc., evaporating from tank	(in still air).	Air Speed:	
•	"escape" velocities which, in turn, determine the "capture ve contaminant. Type of Contaminant: solvent, vapours, degreasing etc., evaporating from tank aerosols, fumes from pouring operations, intermittent con	(in still air).	Air Speed: 0.25-0.5 m/s	
-	"escape" velocities which, in turn, determine the "capture ve contaminant. Type of Contaminant: solvent, vapours, degreasing etc., evaporating from tank	(in still air).	Air Speed: 0.25-0.5 m/s (50-100 f/min.)	
	"escape" velocities which, in turn, determine the "capture ve contaminant. Type of Contaminant: solvent, vapours, degreasing etc., evaporating from tank aerosols, fumes from pouring operations, intermittent con welding, spray drift, plating acid fumes, pickling (released	(in still air). tainer filling, low speed conveyer transfers, at low velocity into zone of active	Air Speed: 0.25-0.5 m/s (50-100 f/min.) 0.5-1 m/s	
	"escape" velocities which, in turn, determine the "capture ve contaminant. Type of Contaminant: solvent, vapours, degreasing etc., evaporating from tank aerosols, fumes from pouring operations, intermittent con welding, spray drift, plating acid fumes, pickling (released generation)	(in still air). tainer filling, low speed conveyer transfers, at low velocity into zone of active , conveyer loading, crusher dusts, gas	Air Speed: 0.25-0.5 m/s (50-100 f/min.) 0.5-1 m/s (100-200 f/min.)	
•	<ul> <li>"escape" velocities which, in turn, determine the "capture velocities which, in turn, determine the "capture velocitation of the second seco</li></ul>	(in still air). tainer filling, low speed conveyer transfers, at low velocity into zone of active , conveyer loading, crusher dusts, gas	Air Speed:           0.25-0.5 m/s           (50-100 f/min.)           0.5-1 m/s           (100-200 f/min.)           1-2.5 m/s	
•	"escape" velocities which, in turn, determine the "capture ve contaminant. Type of Contaminant: solvent, vapours, degreasing etc., evaporating from tank aerosols, fumes from pouring operations, intermittent con welding, spray drift, plating acid fumes, pickling (released generation) direct spray, spray painting in shallow booths, drum filling discharge (active generation into zone of rapid air motion)	(in still air). tainer filling, low speed conveyer transfers, at low velocity into zone of active , conveyer loading, crusher dusts, gas	Air Speed:           0.25-0.5 m/s           (50-100 f/min.)           0.5-1 m/s           (100-200 f/min.)           1-2.5 m/s           (200-500 f/min.)	
•	<ul> <li>"escape" velocities which, in turn, determine the "capture velocities which, in turn, determine the "capture velocitation of the second seco</li></ul>	(in still air). tainer filling, low speed conveyer transfers, at low velocity into zone of active , conveyer loading, crusher dusts, gas	Air Speed:           0.25-0.5 m/s           (50-100 f/min.)           0.5-1 m/s           (100-200 f/min.)           1-2.5 m/s           (200-500 f/min.)           2.5-10 m/s	
	<ul> <li>"escape" velocities which, in turn, determine the "capture velocitation of Contaminant.</li> <li>Type of Contaminant:</li> <li>solvent, vapours, degreasing etc., evaporating from tank a aerosols, fumes from pouring operations, intermittent con welding, spray drift, plating acid fumes, pickling (released generation)</li> <li>direct spray, spray painting in shallow booths, drum filling discharge (active generation into zone of rapid air motion)</li> <li>grinding, abrasive blasting, tumbling, high speed wheel generation).</li> </ul>	(in still air). tainer filling, low speed conveyer transfers, at low velocity into zone of active , conveyer loading, crusher dusts, gas	Air Speed:           0.25-0.5 m/s           (50-100 f/min.)           0.5-1 m/s           (100-200 f/min.)           1-2.5 m/s           (200-500 f/min.)           2.5-10 m/s	
Appropriate ing controls	<ul> <li>"escape" velocities which, in turn, determine the "capture velocitation of Contaminant.</li> <li>Type of Contaminant:</li> <li>solvent, vapours, degreasing etc., evaporating from tank a aerosols, fumes from pouring operations, intermittent conwelding, spray drift, plating acid fumes, pickling (released generation)</li> <li>direct spray, spray painting in shallow booths, drum filling discharge (active generation into zone of rapid air motion)</li> <li>grinding, abrasive blasting, tumbling, high speed wheel gevelocity into zone of very high rapid air motion).</li> <li>Within each range the appropriate value depends on:</li> </ul>	(in still air). (in still air). tainer filling, low speed conveyer transfers, at low velocity into zone of active , conveyer loading, crusher dusts, gas ) enerated dusts (released at high initial	Air Speed:           0.25-0.5 m/s           (50-100 f/min.)           0.5-1 m/s           (100-200 f/min.)           1-2.5 m/s           (200-500 f/min.)           2.5-10 m/s	

Continued...

# 4-Bromo-3-fluoro-2-iodobenzonitrile

	2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity		
	3: Intermittent, low production.	3: High production, heavy use		
	4: Large hood or large air mass in motion	4: Small hood-local control only		
	Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.			
8.2.2. Individual protection measures, such as personal protective equipment				
Eye and face protection	document, describing the wearing of lenses or restriction include a review of lens absorption and adsorption for the Medical and first-aid personnel should be trained in their event of chemical exposure, begin eye irrigation immedia	lenses may absorb and concentrate irritants. A written policy as on use, should be created for each workplace or task. This should e class of chemicals in use and an account of injury experience. removal and suitable equipment should be readily available. In the ately and remove contact lens as soon as practicable. Lens should - lens should be removed in a clean environment only after workers		
Skin protection	See Hand protection below			
Hands/feet protection	<ul> <li>manufacturer to manufacturer. Where the chemical is a prep can not be calculated in advance and has therefore to be chemical is exact break through time for substances has to be obtain observed when making a final choice.</li> <li>Personal hygiene is a key element of effective hand care. Glishould be washed and dried thoroughly. Application of a non Suitability and durability of glove type is dependent on usage if requency and duration of contact,</li> <li>chemical resistance of glove material,</li> <li>glove thickness and</li> <li>dexterity</li> <li>Select gloves tested to a relevant standard (e.g. Europe EN.</li> <li>When prolonged or frequently repeated contact may occur, greater than 240 minutes according to EN 374, AS/NZS 2161.</li> <li>When only brief contact is expected, a glove with a protectin according to EN 374, AS/NZS 2161.10.1 or national equivale.</li> <li>Some glove polymer types are less affected by movement long-term use.</li> <li>Contaminated gloves should be replaced.</li> <li>As defined in ASTM F-739-96 in any application, gloves are</li> <li>Excellent when breakthrough time &gt; 20 min</li> <li>Fair when breakthrough time &lt; 20 min</li> <li>Poor when glove material degrades</li> <li>For general applications, gloves with a thickness typically grupt than breakthrough time &lt; 20 min</li> <li>Poor when glove material degrades</li> <li>For general applications, gloves with a thickness typically grupt the should also be based on consideration of the task requirement of efficiency of the glove will be dependent on the deshould also be based on consideration of the task requirement of efficiency of the glove should always be taken into a permeation efficiency of the glove should always be taken into a consideration or the task requirement of thickness may also vary depending on the glove manufacturers technical data should always be taken into a consideration or portection and with thickness may also vary depending on the glove short on the deshould always be taken into a consideration or the t</li></ul>	<ul> <li>ined from the manufacturer of the protective gloves and has to be</li> <li>loves must only be worn on clean hands. After using gloves, hands</li> <li>n-perfumed moisturiser is recommended.</li> <li>e. Important factors in the selection of gloves include:</li> <li>374, US F739, AS/NZS 2161.1 or national equivalent).</li> <li>a glove with a protection class of 5 or higher (breakthrough time</li> <li>11.0.1 or national equivalent) is recommended.</li> <li>ion class of 3 or higher (breakthrough time greater than 60 minutes</li> <li>ent) is recommended.</li> <li>and this should be taken into account when considering gloves for</li> <li>rated as:</li> </ul>		
Body protection	<ul> <li>Wear safety footwear or safety gumboots, e.g. Rubber</li> <li>See Other protection below</li> </ul>			
Other protection	<ul> <li>Overalls.</li> <li>Eyewash unit.</li> <li>Barrier cream.</li> </ul>			

Skin cleansing cream.

# **Respiratory protection**

Type -P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	P1 Air-line*	-	PAPR-P1 -
up to 50 x ES	Air-line**	P2	PAPR-P2
up to 100 x ES	-	P3	-
		Air-line*	-
100+ x ES	-	Air-line**	PAPR-P3

\* - Negative pressure demand \*\* - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

· Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.

• The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).

• Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.

Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.

• Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)

· Use approved positive flow mask if significant quantities of dust becomes airborne.

· Try to avoid creating dust conditions.

#### 8.2.3. Environmental exposure controls

See section 12

#### **SECTION 9** Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Solid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Not Available	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

Nanoform Solul	ility Not Available	Nanoform Particle Characteristics	Not Available
Particle	Size Not Available		

### 9.2. Other information

Not Available

# **SECTION 10 Stability and reactivity**

10.1.Reactivity	See section 7.2
10.2. Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
10.3. Possibility of hazardous reactions	See section 7.2
10.4. Conditions to avoid	See section 7.2
10.5. Incompatible materials	See section 7.2
10.6. Hazardous decomposition products	See section 5.3

# **SECTION 11 Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Information on toxicological effects

Inhaled	The material is not thought to produce respiratory irritation (as classified by EC Directives using animal models). Nevertheless inhalation of dusts, or fumes, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress. Inhalation of dusts, generated by the material during the course of normal handling, may be damaging to the health of the individual.					
Ingestion	Accidental ingestion of the material may be damaging to the health of the individual. Nitrile poisoning exhibits similar symptoms to poisoning due to hydrogen cyanide. The substances irritate the eyes and skin, and are absorbed quickly and completely through the skin.					
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.					
Eye	Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may cause transient discomfort characterised by tearing or conjunctival redness (as with windburn). Slight abrasive damage may also result.					
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.					
4-Bromo-3-fluoro-	ΤΟΧΙCΙΤΥ	IRRITATION				
2-iodobenzonitrile	Not Available	Not Available				
Legend:	<ol> <li>Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS.</li> <li>Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances</li> </ol>					

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	*
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend: X − Data either not available or does not fill the criteria for classification ✓ − Data available to make classification

### 11.2.1. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

#### 11.2.2. Other information

See Section 11.1

# **SECTION 12 Ecological information**

# 12.1. Toxicity

4 Drama 2 fluore	Endpoint	Test Duration (hr)	Species	Value	Source	
4-Bromo-3-fluoro- 2-iodobenzonitrile	Not Available	Not Available	Not Available	Not Available	Not Available	
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data					

#### DO NOT discharge into sewer or waterways.

### 12.2. Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air	
	No Data available for all ingredients	No Data available for all ingredients	

#### 12.3. Bioaccumulative potential

Ingredient	Bioaccumulation			
	No Data available for all ingredients			

### 12.4. Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

# 12.5. Results of PBT and vPvB assessment

	Р	В	Т	
Relevant available data	Not Available	Not Available	Not Available	
PBT	×	×	×	
vPvB	×	×	×	
PBT Criteria fulfilled? No				
vPvB			No	

### 12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

#### 12.7. Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

### **SECTION 13 Disposal considerations**

# 13.1. Waste treatment methods

Product / Packaging disposal	<ul> <li>Recycle wherever possible or consult manufacturer for recycling options.</li> <li>Consult State Land Waste Management Authority for disposal.</li> <li>Bury residue in an authorised landfill.</li> <li>Recycle containers if possible, or dispose of in an authorised landfill.</li> </ul>
Waste treatment options	Not Available
Sewage disposal options	Not Available

# **SECTION 14 Transport information**

# Labels Required

	6 6
Marine Pollutant	NO
HAZCHEM	2X

# Land transport (ADR-RID)

14.1. UN number or ID number	3439				
14.2. UN proper shipping name	NITRILES, SOLID,	NITRILES, SOLID, TOXIC, N.O.S.			
14.3. Transport hazard	Class	6.1			
class(es)	Subsidiary risk	Not Applicab	le		
14.4. Packing group	Ш	III			
14.5. Environmental hazard	Not Applicable				
	Hazard identificat	ion (Kemler)	60		
	Classification code		T2		
14.6. Special precautions for user	Hazard Label		6.1		
	Special provisions		274		
	Limited quantity		5 kg	-	
	Tunnel Restriction	n Code	2 (E)		

# Air transport (ICAO-IATA / DGR)

	-				
14.1. UN number	3439				
14.2. UN proper shipping name	Nitriles, solid, tocix, n.o.s. *				
14.3. Transport hazard class(es)	ICAO/IATA Class 6.1				
	ICAO / IATA Subrisk	Not Applicable			
01033(63)	ERG Code	6L			
14.4. Packing group	Ш				
14.5. Environmental hazard	Not Applicable				
	Special provisions	A3 A5			
	Cargo Only Packing Ir	677			
	Cargo Only Maximum	200 kg			
14.6. Special precautions for user	Passenger and Cargo	670			
	Passenger and Cargo	100 kg			
	Passenger and Cargo	Y645			
	Passenger and Cargo	Limited Maximum Qty / Pack	10 kg		

# Sea transport (IMDG-Code / GGVSee)

14.1. UN number	3439			
14.2. UN proper shipping name	NITRILES, SOLID, TOXIC, N.O.S.			
14.3. Transport hazard class(es)	IMDG Class 6.1			

	IMDG Subrisk No	ot Applicable
14.4. Packing group	III	
14.5. Environmental hazard	Not Applicable	
14.6. Special precautions for user	EMS Number Special provisions Limited Quantities	F-A, S-A 223 274 5 kg

# Inland waterways transport (ADN)

14.1. UN number	3439		
14.2. UN proper shipping name	NITRILES, SOLID, TOXIC, N.O.S.		
14.3. Transport hazard class(es)	6.1 Not Applicable		
14.4. Packing group	III		
14.5. Environmental hazard	Not Applicable		
14.6. Special precautions for user	Classification code	T2	
	Special provisions	274; 802	
	Limited quantity	5 kg	
	Equipment required	PP, EP	
	Fire cones number	0	

### 14.7. Maritime transport in bulk according to IMO instruments

### 14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

# 14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
14.7.3. Transport in bulk in accordance with the IGC Code	

|--|

# **SECTION 15 Regulatory information**

# 15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable - : Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2020/878; Regulation (EC) No 1272/2008 as updated through ATPs.

# Information according to 2012/18/EU (Seveso III):

Seveso Category Not Available

# 15.2. Chemical safety assessment

For further information please look at the Chemical Safety Assessment and Exposure Scenarios prepared by your Supply Chain if available.

### ECHA SUMMARY

Not Applicable

# **National Inventory Status**

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Not Available
Canada - DSL	Not Available
Canada - NDSL	Not Available

National Inventory	Status
China - IECSC	Not Available
Europe - EINEC / ELINCS / NLP	Not Available
Japan - ENCS	Not Available
Korea - KECI	Not Available
New Zealand - NZIoC	Not Available
Philippines - PICCS	Not Available
USA - TSCA	Not Available
Taiwan - TCSI	Not Available
Mexico - INSQ	Not Available
Vietnam - NCI	Not Available
Russia - FBEPH	Not Available
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

### **SECTION 16 Other information**

Revision Date	12/03/2023
Initial Date	23/02/2023

# Full text Risk and Hazard codes

### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

#### Definitions and abbreviations

PC - TWA: Permissible Concentration-Time Weighted Average PC - STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit. IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors **BEI: Biological Exposure Index** AIIC: Australian Inventory of Industrial Chemicals DSL: Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

# Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	Classification Procedure
Acute Toxicity (Dermal) Category 4, H312	Expert judgement
Acute Toxicity (Inhalation) Category 4, H332	Expert judgement
Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, H335	Expert judgement
Acute Toxicity (Oral) Category 4, H302	Expert judgement
Skin Corrosion/Irritation Category 2, H315	Expert judgement
Serious Eye Damage/Eye Irritation Category 2, H319	Expert judgement

Powered by AuthorITe, from Chemwatch.